

**REWORK GROUND SOLID FUSION**
**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : REWORK GROUND SOLID FUSION

Other means of identification : not applicable

Recommended use : Intermediate

Restrictions on use : Reserved for industrial and professional use.

Product dilution information : Product is sold ready to use.

Company : Ecolab Inc.  
370 N. Wabasha Street  
St. Paul, Minnesota USA 55102  
1-800-352-5326

Emergency telephone : 1-800-328-0026 (US/Canada), 1-651-222-5352 (outside US)

Issuing date : 06/30/2014

**SECTION 2. HAZARDS IDENTIFICATION**
**GHS Classification**

Eye irritation : Category 2A

**GHS Label element**

Hazard pictograms :



Signal Word : Warning

Hazard Statements : Causes serious eye irritation.

Precautionary Statements : **Prevention:**  
Wash skin thoroughly after handling. Wear eye protection/ face protection.  
**Response:**  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.

Other hazards : None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Pure substance/mixture : Mixture

Chemical Name	CAS-No.	Concentration (%)
Sodium Carbonate	497-19-8	30 - 60
Phosphonates	67953-76-8	5 - 10
Alcohol ethoxylate	68439-51-0	1 - 5
oxirane, methyl-, polymer with oxirane	9003-11-6	0.1 - 1

## SAFETY DATA SHEET

### REWORK GROUND SOLID FUSION

#### SECTION 4. FIRST AID MEASURES

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.
- In case of skin contact : Rinse with plenty of water.
- If swallowed : Rinse mouth. Get medical attention if symptoms occur.
- If inhaled : Get medical attention if symptoms occur.
- Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal protective equipment.
- Notes to physician : Treat symptomatically.

**See toxicological information (Section 11)**

#### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Not flammable or combustible.
- Hazardous combustion products : Decomposition products may include the following materials:  
Carbon oxides  
nitrogen oxides (NO<sub>x</sub>)  
Sulfur oxides  
Oxides of phosphorus
- Special protective equipment for fire-fighters : Use personal protective equipment.
- Specific extinguishing methods : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Do not allow contact with soil, surface or ground water.
- Methods and materials for containment and cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

## SAFETY DATA SHEET

### REWORK GROUND SOLID FUSION

#### SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid contact with skin and eyes. Wash hands thoroughly after handling.
- Conditions for safe storage : Keep out of reach of children. Store in suitable labeled containers.
- Storage temperature : 0 °C to 50 °C

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

##### Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

- Engineering measures : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

##### Personal protective equipment

- Eye protection : Safety glasses with side-shields
- Hand protection : No special protective equipment required.
- Skin protection : No special protective equipment required.
- Respiratory protection : No personal respiratory protective equipment normally required.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Wash face, hands and any exposed skin thoroughly after handling.

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : powder
- Color : opaque, white
- Odor : odorless
- pH : 10.8 - 11.5, 1 %
- Flash point : not applicable, Does not sustain combustion.
- Odor Threshold : no data available
- Melting point/freezing point : no data available
- Initial boiling point and boiling range : no data available
- Evaporation rate : no data available
- Flammability (solid, gas) : no data available
- Upper explosion limit : no data available
- Lower explosion limit : no data available
- Vapor pressure : no data available
- Relative vapor density : no data available
- Relative density : no data available

## SAFETY DATA SHEET

### REWORK GROUND SOLID FUSION

Water solubility	: soluble
Solubility in other solvents	: no data available
Partition coefficient: n-octanol/water	: no data available
Autoignition temperature	: no data available
Thermal decomposition	: no data available
Viscosity, kinematic	: no data available
Explosive properties	: no data available
Oxidizing properties	: no data available
Molecular weight	: no data available
VOC	: no data available

### SECTION 10. STABILITY AND REACTIVITY

Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reaction known under conditions of normal use.
Conditions to avoid	: None known.
Incompatible materials	: Acids Metals
Hazardous decomposition products	: Decomposition products may include the following materials: Carbon oxides nitrogen oxides (NOx) Sulfur oxides Oxides of phosphorus

### SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure	: Inhalation, Eye contact, Skin contact
--	---

#### Potential Health Effects

Eyes	: Causes serious eye irritation.
Skin	: Health injuries are not known or expected under normal use.
Ingestion	: Health injuries are not known or expected under normal use.
Inhalation	: Health injuries are not known or expected under normal use.
Chronic Exposure	: Health injuries are not known or expected under normal use.

#### Experience with human exposure

Eye contact	: Redness, Pain, Irritation
Skin contact	: No symptoms known or expected.
Ingestion	: No symptoms known or expected.

## SAFETY DATA SHEET

### REWORK GROUND SOLID FUSION

Inhalation : No symptoms known or expected.

#### Toxicity

Acute oral toxicity : Acute toxicity estimate : 2,931 mg/kg  
Acute inhalation toxicity : no data available  
Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Skin corrosion/irritation : no data available  
Serious eye damage/eye irritation : no data available  
Respiratory or skin sensitization : no data available  
Carcinogenicity : no data available  
Reproductive effects : no data available  
Germ cell mutagenicity : no data available  
Teratogenicity : no data available  
STOT-single exposure : no data available  
STOT-repeated exposure : no data available  
Aspiration toxicity : no data available

#### Ingredients

Acute inhalation toxicity : oxirane, methyl-, polymer with oxirane  
4 h LC50 rat: 0.147 mg/l

### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

Environmental Effects : This product has no known ecotoxicological effects.

#### Product

Toxicity to fish : no data available  
Toxicity to daphnia and other aquatic invertebrates : no data available  
Toxicity to algae : no data available

#### Ingredients

Toxicity to fish : Alcohol ethoxylate  
96 h LC50: > 1 mg/l  
  
oxirane, methyl-, polymer with oxirane  
96 h LC50 Fish: > 100 mg/l

#### Ingredients

Toxicity to daphnia and other aquatic invertebrates : Sodium Carbonate  
48 h EC50 Daphnia : 200 mg/l  
  
Phosphonates  
48 h EC50: 167 mg/l

## SAFETY DATA SHEET

### REWORK GROUND SOLID FUSION

#### Persistence and degradability

no data available

#### Bioaccumulative potential

no data available

#### Mobility in soil

no data available

#### Other adverse effects

no data available

### SECTION 13. DISPOSAL CONSIDERATIONS

- Disposal methods : Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.
- Disposal considerations : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

### SECTION 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

#### Land transport (DOT)

Not dangerous goods

#### Sea transport (IMDG/IMO)

Not dangerous goods

### SECTION 15. REGULATORY INFORMATION

#### EPCRA - Emergency Planning and Community Right-to-Know

##### CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

##### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Acute Health Hazard

**SARA 302** : SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### California Prop 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

## SAFETY DATA SHEET

### REWORK GROUND SOLID FUSION

The ingredients of this product are reported in the following inventories:

**1907/2006 (EU) :**

not determined

**Switzerland. New notified substances and declared preparations :**

The mixture contains substances listed on the Swiss Inventory not determined

**United States TSCA Inventory :**

On TSCA Inventory

**Canadian Domestic Substances List (DSL) :**

All components of this product are on the Canadian DSL.

**Australia Inventory of Chemical Substances (AICS) :**

not determined

**New Zealand. Inventory of Chemical Substances :**

On the inventory, or in compliance with the inventory

**Japan. ENCS - Existing and New Chemical Substances Inventory :**

not determined

**Japan. ISHL - Inventory of Chemical Substances (METI) :**

not determined

**Korea. Korean Existing Chemicals Inventory (KECI) :**

not determined

**Philippines Inventory of Chemicals and Chemical Substances (PICCS) :**


not determined

**China. Inventory of Existing Chemical Substances in China (IECSC) :**

not determined

### SECTION 16. OTHER INFORMATION

**NFPA:**



**HMIS III:**

HEALTH	2
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

Issuing date : 06/30/2014  
Version : 1.0  
Prepared by : Regulatory Affairs

## **SAFETY DATA SHEET**

### **REWORK GROUND SOLID FUSION**

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.