

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/02/2015 Reviewed on 04/02/2015

1 Identification

- · Product identifier
- · Trade name: Fumitoxin® Tablets U.S. EPA Reg. No. 72959-1; Fumitoxin® Pellets U.S. EPA Reg. No. 72959-2
- · Relevant identified uses of the substance or mixture and uses advised against
- · Product description Fumigant for Insect & Rodent Control
- · Application of the substance / the mixture

Fumigants used to treat raw agricultural commodities, processed foods, non-food commodities and rodent burrows.

- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

DEGESCH America, Inc.

153 Triangle Dr. P.O. Box 116

Weyers Cave, VA 24486 USA

Telephone: (540) 234-9281 / 800-330-2525

Telefax: (540) 234-8225 www.degeschamerica.com degesch@degeschamerica.com

Emergency telephone number:

For human or animal emergencies: 1-800-308-4856 (Rocky Mountain Poison and Drug Center)

For all other chemical emergencies: 1-800-424-9300 (Chemtrec)

Emergency and Information - DEGESCH America, Inc.: (540) 234-9281 / 800-330-2525

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Water-react. 1 H260 In contact with water releases flammable gases which may ignite spontaneously.



GHS06 Skull and crossbones

Acute Tox. 2 H300 Fatal if swallowed. Acute Tox. 2 H330 Fatal if inhaled.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS09 Environment

Aquatic Acute 1 H400 Very toxic to aquatic life.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/02/2015 Reviewed on 04/02/2015

Trade name: Fumitoxin® Tablets - U.S. EPA Reg. No. 72959-1; Fumitoxin® Pellets - U.S. EPA Reg. No. 72959-2

Skin Irrit. 2 H315 Causes skin irritation.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms









GHS02 GHS05 GHS06 GHS09

- · Signal word Danger
- · Hazard-determining components of labeling:

Aluminum Phosphide

Ammonium Carbamate

· Hazard statements

In contact with water releases flammable gases which may ignite spontaneously.

Fatal if swallowed or if inhaled.

Causes skin irritation.

Causes serious eye damage.

Very toxic to aquatic life.

· Precautionary statements

Keep away from any possible contact with water, because of violent reaction and possible flash fire.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear respiratory protection.

Wear protective gloves/protective clothing/eye protection/face protection.

Avoid release to the environment.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

If swallowed: Immediately call a poison center/doctor.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Specific treatment is urgent (see supplementary first aid instructions on this Safety Data Sheet).

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use for extinction: CO2, sand, extinguishing powder.

If on skin: Wash with plenty of water.

Collect spillage.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a dry place. Store in a closed container.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Unknown acute toxicity:

10.3 percent of the mixture consists of ingredient(s) of unknown toxicity.

(Contd. on page 3)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/02/2015 Reviewed on 04/02/2015

Trade name: Fumitoxin® Tablets - U.S. EPA Reg. No. 72959-1; Fumitoxin® Pellets - U.S. EPA Reg. No. 72959-2

- · Classification system:
- · NFPA ratings (scale 0 4)



The substance demonstrates unusual reactivity with water.

· HMIS-ratings (scale 0 - 4)



· Other hazards None known

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous Compone	ents:	
CAS: 20859-73-8 RTECS: BD 1400000	Aluminum Phosphide Water-react. 1, H260; Acute Tox. 2, H300; Aquatic Acute 1, H400	55%
CAS: 1111-78-0	Ammonium Carbamate Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; Aquatic Acute 3, H402	Proprietary%
RTECS: BD 1200000	Proprietary ♦ STOT SE 3, H335	5-10%
	Proprietary Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320	2-12%

· Additional information:

Fumitoxin Tablets and Fumitoxin Pellets react with water to produce phosphine (hydrogen phosphide, PH3, CAS No. 7803-51-2) as shown in Equation 1. Fumitoxin products are formulated with 55% aluminum phosphide and also contains ammonium carbamate (AC) and inert ingredients. Ammonium carbamate decomposes to liberate ammonia (CAS No. 7664-41-7) and carbon dioxide (CAS No. 124-38-9) as shown in Equation 2.

- 1) AIP + 3H2O ---> AI(OH)3 + PH3
- 2) NH2COONH4 ---> 2NH3 + CO2

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of overexposure are headache, dizziness, nausea, difficult breathing, vomiting, and diarrhea. In ALL cases of overexposure, get medical attention immediately. Take victim to a doctor or emergency treatment facility.

Have product container label or applicator's manual with you when calling a poison control center, doctor, or when going for treatment.

(Contd. on page 4)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/02/2015 Reviewed on 04/02/2015

Trade name: Fumitoxin® Tablets - U.S. EPA Reg. No. 72959-1; Fumitoxin® Pellets - U.S. EPA Reg. No. 72959-2

· After inhalation:

Get exposed person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth to mouth, if possible. Contact a poison control center or doctor for treatment advice.

· After skin contact:

Take off contaminated clothing immediately. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

· After eye contact:

Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eyes. Call a poison control center or doctor for treatment advice.

· After swallowing:

Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not give anything by mouth to an unconscious person. Do not induce vomiting unless told to by a poison control center or doctor.

· Information for doctor:

· Most important symptoms and effects, both acute and delayed

Aluminum phosphide fumigant products react with moisture from the air, acids and many other liquids to release phosphine gas (hydrogen phosphide, PH3). Mild exposure by inhalation causes malaise (indefinite feeling of sickness), headache, ringing in the ears, fatigue, nausea and pressure in the chest which is relieved by removal to fresh aid. Moderate poisoning causes weakness, vomiting, pain just above the stomach, chest pain, diarrhea and dyspnea (difficulty breathing). Symptoms of severe poisoning may occur within a few hours to several days resulting in pulmonary edema and may lead to dizziness, cyanosis, unconsciousness, and death.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water
- · Special hazards arising from the substance or mixture

Phosphine (hydrogen phosphide, PH3)-air mixtures at concentrations above the LEL of 1.8% v/v (18,000 ppm) may ignite spontaneously. Ignition of high concentrations of phosphine gas (hydrogen phosphide, PH3) can product a very energetic reaction. Explosions can occur under these conditions and may cause severe personal injury. Never allow the buildup of phosphine gas (hydrogen phosphide, PH3) to exceed explosive concentrations. Open containers of metal phosphides in open air only and never in a flammable atmosphere. Do not confine spent or partially spent dust from metal phosphide fumigants as the slow release of phosphine gas (hydrogen phosphide, PH3) from these materials may result in the formation of an explosive atmosphere. Spontaneous ignition may occur if large quantities of aluminum phosphide are piled in contact with liquid water. This is particularly true if quantities of these materials are placed in an environment which can provide partial confinement of the hydrogen phosphide gas liberated by hydrolysis.

If incinerated, product will release the following toxic materials: Oxides of aluminum, magnesium, phosphorous, nitrogen (NOx), carbon, phosphine gas (hydrogen phosphide, PH3), ammonia and phosphoric acid.

· Advice for firefighters

Aluminum phosphide is not flammable by itself. However, it reacts readily with water to produce phosphine gas (hydrogen phosphide, PH3) which may ignite spontaneously in air at concentrations above its LEL of 1.8% v/v (18,000 ppm). The UEL of phosphine gas (hydrogen phosphide, PH3) is unknown.

(Contd. on page 5)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/02/2015 Reviewed on 04/02/2015

Trade name: Fumitoxin® Tablets - U.S. EPA Reg. No. 72959-1; Fumitoxin® Pellets - U.S. EPA Reg. No. 72959-2

· Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

Wear a NOISH/MSHA approved full-face gas mask – phosphine gas canister combination may be used at levels up to 15 ppm or following manufacturers' use conditions instructions for escape. Above 15 ppm or in situations where the phosphine gas concentration is unknown, a NIOSH/MSHA approved SCBA must be worn.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Respiratory protection will most likely be required during cleanup of spilled aluminum phosphide fumigants. If the concentration of phosphine (hydrogen phosphide, PH3) is unknown, NIOSH/MSHA approved SCBA or its equivalent must be worn. Full-face gas mask canister combinations may only be worn at concentrations no higher than 15 ppm.

Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

· Methods and material for containment and cleaning up:

If possible, dispose of spilled material by use according to label instructions. Freshly spilled material which has not been contaminated by water or foreign matter may be placed into original or other gas-tight containers. Punctured flasks, pouches or containers may be temporarily repaired using aluminum tape. If the age of the spill is unknown or if the product has been contaminated with soil, debris, water, etc., gather up the spillage in small open buckets having a capacity no larger than about 1 gallon. Do not add more than about 1 to 1.5 kg (2 to 3 lbs.) to a bucket. If on-site wet-deactivation is not feasible, transport the uncovered buckets in open vehicles to a suitable area. Small amounts of spillage, from about 4 to 8 kg (9 to 18 lbs.) may be spread out over the ground in an open area to be deactivated by atmospheric moisture. Alternatively, spilled aluminum phosphide fumigants may be deactivated by the wet method as described in the following:

Wet Deactivation of Spilled Fumitoxin Products:

- 1. Deactivating solution is prepared by adding the appropriate amount of low sudsing detergent to water in a drum or other suitable container. A 2% solution or 4 cups of detergent in 30 gallons is suggested. The container should be filled with deactivating solution to within a few inches of the top.
- 2. The material is added slowly to the deactivating solution and stirred so as to thoroughly wet all of the product. This should be carried out in open air and respiratory protection may be required. At no time should the deactivation drum be covered.
- 3. No more than about 45 to 50 lbs. of Fumitoxin should be added to 15 gallons of water-detergent mixture. Products may ignite during wet deactivation if they are allowed to float to the surface. Add weights or otherwise ensure that products stay submerged until deactivation is completed.
- 4. Allow the mixture to stand, with occasional stirring, for about 36 hours. The resultant slurry of dust or packaged product will then be safe for disposal.
- 5. Dispose of the slurry of deactivated material, with or without preliminary decanting, at a sanitary landfill or other suitable site approved by local authorities. Where permissible, this slurry may be poured into a storm sewer or out onto the ground.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Handling:

· *Precautions for safe handling* Store in a cool, dry place in tightly closed containers.

(Contd. on page 6)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/02/2015 Reviewed on 04/02/2015

Trade name: Fumitoxin® Tablets - U.S. EPA Reg. No. 72959-1; Fumitoxin® Pellets - U.S. EPA Reg. No. 72959-2

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Protect from heat.

Keep protective respiratory device available.

· Conditions for safe storage, including any incompatibilities

Store away from water, acids, bases, strong oxidizing agents and strong reducing agents.

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store products in a locked, dry, well-ventilated area away from heat. Post as a pesticide storage area. Do not store in buildings inhabited by humans or domestic animals.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well-sealed containers.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use local exhaust at filling zones and where leakage and dust formation is probable. Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

· Components with occupational exposure limits:

20859-73-8 Aluminum Phosphide

REL Long-term value: 2 mg/m³

as Al

TLV Long-term value: 1* mg/m³

as Al;*as respirable fraction

Proprietary

PEL Long-term value: 15*; 15** mg/m³

*Total dust; ** Respirable fraction

REL Long-term value: 10* 5** mg/m³

as Al*Total dust**Respirable/pyro powd./welding f.

TLV Long-term value: 1* mg/m³

as AI; *as respirable fraction

Proprietary

TLV Long-term value: 10 mg/m³

7803-51-2 phosphine

PEL Long-term value: 0.4 mg/m³, 0.3 ppm

REL Short-term value: 1 mg/m³, 1 ppm Long-term value: 0.4 mg/m³, 0.3 ppm

TLV Short-term value: (1.4) mg/m³, (1) ppm

Long-term value: (0.42) mg/m³, (0.3) NIC-0.1 ppm

Ceiling limit value: NIC-0.5 ppm

(Contd. on page 7)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/02/2015 Reviewed on 04/02/2015

Trade name: Fumitoxin® Tablets - U.S. EPA Reg. No. 72959-1; Fumitoxin® Pellets - U.S. EPA Reg. No. 72959-2

7664-41-7 ammonia, anhydrous

PEL Long-term value: 35 mg/m³, 50 ppm
REL Short-term value: 27 mg/m³, 35 ppm
Long-term value: 18 mg/m³, 25 ppm
TLV Short-term value: 24 mg/m³, 35 ppm
Long-term value: 17 mg/m³, 25 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Breathing equipment:

Respiratory protection will most likely be required while using aluminum phosphide fumigants. If the concentration of phosphine (hydrogen phosphide, PH3) is unknown, NIOSH/MSHA approved SCBA or its equivalent must be worn. Full-face gas mask canister combinations may only be worn at concentrations no higher than 15 ppm.

· Protection of hands:



Protective gloves

Wear dry gloves of cotton or other material if contact with tablets, pellets, or dust is likely. Gloves should remain dry after use. Aerate gloves and other clothing that may be contaminated in a well-ventilated area prior to laundering.

- · Material of gloves Dry gloves of cotton or other material.
- · Penetration time of glove material

The exact break-through time has to be determined and observed by the manufacturer of the protective aloves.

Eye protection: Not required.

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Solid

Color: Greenish-gray

· *Odor:* Garlic, carbide or decaying fish

Odor threshold: Not determined.pH-value: Not applicable.

· Change in condition

Melting point/Melting range: AIP = $> 1000 \,^{\circ}\text{C}$ (AIP = $> 1832 \,^{\circ}\text{F}$) (PH3 = $-133.5 \,^{\circ}\text{C}$)

Boiling point/Boiling range: AIP = $> 1000 \,^{\circ}\text{C}$ (AIP = $> 1832 \,^{\circ}\text{F}$) (PH3 = $-87.7 \,^{\circ}\text{C}$)

· Flash point: Not determined

(Contd. on page 8)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/02/2015 Reviewed on 04/02/2015

Trade name: Fumitoxin® Tablets - U.S. EPA Reg. No. 72959-1; Fumitoxin® Pellets - U.S. EPA Reg. No. 72959-2

· Flammability (solid, gaseous): Contact with water or acids liberates extremely flammable gases.

· Ignition temperature: Not determined

• Decomposition temperature: Decomposes at ambient conditions when moisture is present.

• Auto igniting: Spontaneously flammable in air.

· Danger of explosion: Not determined.

· Explosion limits:

Lower: 1.8% Vol % (for PH3)

Upper: Not established Vol % (for PH3)

· Vapor pressure: AIP = 0 mm Hg

PH3 = 40 mm Hg @ -129.4 °C AC = 100 mm Hg @ 26.7 °C

• **Density @ 20 °C (68 °F):** AIP = 2.85 g/cm³ (AIP = 23.783 lbs/gal) (PH3 = 1.17 g/cm³)

Relative density
Vapor density
Evaporation rate
Not determined.
Not applicable.
Not applicable.

· Solubility in / Miscibility with

Water: AIP = Insoluble, reacts

PH3 = 26 cc in 100 ml at 17 °C AC = Very soluble, reacts

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not applicable. **Kinematic:** Not applicable.

· Solvent content:

Solids content: 100.0 %

Other information
 No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability

Products are stable to most chemical reactions, except for hydrolysis. Products will react with moist air, liquid water, acids and some other liquids to produce toxic and flammable phosphine (hydrogen phosphide, PH3) gas.

- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions

Contact with water releases flammable gases.

Contact with water releases toxic gases.

- · Conditions to avoid: Avoid prolonged exposure to air.
- · Incompatible materials: Water, acids, bases, strong oxidizing agents and strong reducing agents.
- · Hazardous decomposition products:

Oxides of aluminum, phosphorous, nitrogen (NOx), magnesium, carbon, phosphine gas (hydrogen phosphide, PH3), ammonia and phosphoric acid.

· Additional information:

Phosphine (hydrogen phosphide, PH3) gas may react with certain metals and cause corrosion, especially at higher temperatures and relative humidity. Metals such as copper, brass and other copper alloys, and

(Contd. on page 9)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/02/2015 Reviewed on 04/02/2015

Trade name: Fumitoxin® Tablets - U.S. EPA Reg. No. 72959-1; Fumitoxin® Pellets - U.S. EPA Reg. No. 72959-2

precious metals such as gold and silver are susceptible to corrosion by phosphine. Small electric motors, smoke detectors, brass sprinkler heads, batteries and battery chargers, fork lifts, temperature monitoring systems, switching gears, communication devices, computers, calculators and other electrical equipment may be damaged by this gas. Phosphine (hydrogen phosphide, PH3) will also react with certain metallic salts and, therefore, sensitive items such as photographic film, some inorganic pigments, etc., should not be exposed.

*11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	· LD/LC50 values that are relevant for classification:						
20859-73-	8 Aluminum Ph	osphide					
Oral	LD50	0.4 mg/kg (rat)					
1111-78-0	Ammonium Ca	arbamate					
Oral	LD50	1470 mg/kg (rat)					
Inhalative	LC50/96 hours	37 mg/l (Trout)					
7803-51-2	phosphine						
Inhalative	LC50/1 h	180 ppm (rat)					
7664-41-7 ammonia, anhydrous							
Oral	LD50	350 mg/kg (rat)					
Inhalative	LC50/4 h	2000 mg/l (rat)					

- Primary irritant effect:
- · on the skin:

May be irritating.

Irritant to skin and mucous membranes.

on the eve:

Direct contact may cause eye irritation.

Strong irritant with the danger of severe eye injury.

Causes serious eye irritation.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

Very toxic

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to its carcinogenicity to humans

Group 4 - Probably not carcinogenic to humans

· NTP (National Toxicology Program)

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

(Contd. on page 10)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/02/2015 Reviewed on 04/02/2015

Trade name: Fumitoxin® Tablets - U.S. EPA Reg. No. 72959-1; Fumitoxin® Pellets - U.S. EPA Reg. No. 72959-2

12 Ecological information

- · Toxicity
- · Aquatic toxicity:

Avoid release into the environment. Runoff from fire control or dilution water may cause pollution.

1111-78-0 Ammonium Carbamate

EC50 | 129.1 mg/l (Green algae)

63 mg/l (Water flea)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Very toxic for fish
- Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. When being disposed of, spilled or partially reacted Fumitoxin products are considered hazardous wastes under existing Federal Regulations. If properly exposed, the grayish-white residual dust after a fumigation will not be a hazardous waste and normally contains only a very small amount of unreacted aluminum phosphide. This waste will be safe for disposal. However, the spent residual dust from incompletely exposed Fumitoxin products may require special care.

Triple rinse tablet and pellet flasks and stoppers with water. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities. Rinsate may be disposed of in a storm sewer, sanitary landfill or by other approved procedures. Or, it is permissible to remove lids and expose empty flasks to atmospheric conditions until the residue in the flasks is reacted. Then puncture and dispose of in a sanitary landfill or other approved site, or by other procedures approved by state and local authorities. Some local and state waste disposal regulations may vary from the following recommendations. Disposal procedures should be reviewed with appropriate authorities to ensure compliance with local regulations. Contact your State Pesticide or Environmental Control Agency or Hazardous Waste Specialist at the nearest EPA Regional Office for guidance.

- 1. Confinement of partially spent residual materials, as in a closed container, or collection and storage of large quantities of dust may result in a fire or explosion hazard. Small amounts of phosphine (hydrogen phosphide, PH3) may be given off from unreacted aluminum phosphide, and confinement of the gas may result in a flash.
- 2. In open areas, small amounts of spent residual dust or spent packaged products may be disposed of on site by burial or by spreading over the land surface away from inhabited buildings.
- 3. Residual dust from Fumitoxin products may also be collected and disposed of at a sanitary landfill, or other
 (Contd. on page 11)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/02/2015 Reviewed on 04/02/2015

Trade name: Fumitoxin® Tablets - U.S. EPA Reg. No. 72959-1; Fumitoxin® Pellets - U.S. EPA Reg. No. 72959-2

approved sites or by other procedures approved by Federal, State or Local authorities.

4. From 3 to 5 kg (7 to 10 lbs.) of spent dust from 2 to 3 flasks of Fumitoxin may collected for disposal in a 1-gallon bucket. Larger amounts, up to about one-half case, may be collected in burlap, cotton or other types of porous cloth bags for transportation in an open vehicle to the disposal site. Do not collect dust from more than 7 flasks of tablets, 10 flasks of pellets (about 11 kg or 25 lbs.) in a single bag. Do not pile cloth bags together. Do not use this method for partially spent or "green" dust. Caution: Do not collect dust in large drums, dumpsters, plastic bags or other containers where confinement may occur.

- · Uncleaned packagings:
- · Recommendation:

Triple rinse tablet and pellet flasks and stoppers with water and then offer for recycling or reconditioning; or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

ALUMINIUM PHOSPHIDE

14 Transport information

- · UN-Number
- · DOT, ADR, IMDG, IATA
- · UN proper shipping name
- · DOT
- · ADR
- · IMDG
- · IATA
- · Transport hazard class(es)
- · DOT



· Class

· Label



· Class

· Label

· IMDG



· Class

UN1397

Aluminum phosphide UN1397 Aluminum phosphide, ENVIRONMENTALLY HAZARDOUS ALUMINIUM PHOSPHIDE, MARINE POLLUTANT

4.3 Substances which, in contact with water, emit flammable gases 4.3, 6.1

4.3 (WT2) Substances which, in contact with water, emit flammable gases

4.3. 6.1

4.3 Substances which, in contact with water, emit flammable gases

(Contd. on page 12)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/02/2015 Reviewed on 04/02/2015

Trade name: Fumitoxin® Tablets - U.S. EPA Reg. No. 72959-1; Fumitoxin® Pellets - U.S. EPA Reg. No. 72959-2

· *Label* 4.3/6.1

· IATA



• Class 4.3 Substances which, in contact with water, emit flammable

gases 4 3 (6 1)

· *Label* 4.3 (6.1)

· Packing group

· DOT, ADR, IMDG, IATA

• *Environmental hazards:* Product contains environmentally hazardous substances:

Aluminum Phosphide

• Special marking (ADR): Symbol (fish and tree)

· Special precautions for user Warning: Substances which, in contact with water, emit

flammable gases

Danger code (Kemler): 462EMS Number: F-G,S-N

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· DOT

Quantity limitations
 On passenger aircraft/rail: Forbidden

On cargo aircraft only: 15 kg

· ADR

• Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· IMDG

· Limited quantities (LQ) 0

• Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

• UN "Model Regulation": UN1397, Aluminum phosphide, ENVIRONMENTALLY

HAZARDOUS, 4.3, 6.1, I

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):

20859-73-8 Aluminum Phosphide

· Section 313 (Specific toxic chemical listings):

20859-73-8 Aluminum Phosphide

Proprietary Proprietary

· TSCA (Toxic Substances Control Act):

20859-73-8 Aluminum Phosphide

(Contd. on page 13)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/02/2015 Reviewed on 04/02/2015

Trade name: Fumitoxin® Tablets - U.S. EPA Reg. No. 72959-1; Fumitoxin® Pellets - U.S. EPA Reg. No. 72959-2

Proprietary
Proprietary
Proprietary

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

D, I, II Proprietary

· TLV (Threshold Limit Value established by ACGIH)

A4 **Proprietary**

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms









GHS02 GHS05 GHS06 GHS09

· Signal word Danger

· Hazard-determining components of labeling:

Aluminum Phosphide

Ammonium Carbamate

· Hazard statements

In contact with water releases flammable gases which may ignite spontaneously.

Fatal if swallowed or if inhaled.

Causes skin irritation.

Causes serious eye damage.

Very toxic to aquatic life.

Precautionary statements

Keep away from any possible contact with water, because of violent reaction and possible flash fire.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear respiratory protection.

Wear protective gloves/protective clothing/eye protection/face protection.

Avoid release to the environment.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/02/2015 Reviewed on 04/02/2015

Trade name: Fumitoxin® Tablets - U.S. EPA Reg. No. 72959-1; Fumitoxin® Pellets - U.S. EPA Reg. No. 72959-2

If swallowed: Immediately call a poison center/doctor.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment is urgent (see supplementary first aid instructions on this Safety Data Sheet).

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use for extinction: CO2, sand, extinguishing powder.

If on skin: Wash with plenty of water.

Collect spillage.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a dry place. Store in a closed container.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

State Right to Know		
CAS: 20859-73-8	Aluminum Phosphide	55%
RTECS: BD 1400000	♦ Water-react. 1, H260; ♦ Acute Tox. 2, H300; ♦ Aquatic Acute 1, H400	
CAS: 1111-78-0	Ammonium Carbamate	Proprietary%
	Eye Dam. 1, H318;	
RTECS: BD 1200000	Proprietary	5-10%
	♦ STOT SE 3, H335	
	Proprietary	2-12%
	Proprietary	2-12%
	① Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320	

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

- Date of preparation / last revision 04/02/2015 / -
- · Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 04/02/2015 Reviewed on 04/02/2015

Trade name: Fumitoxin® Tablets - U.S. EPA Reg. No. 72959-1; Fumitoxin® Pellets - U.S. EPA Reg. No. 72959-2

LD50: Lethal dose, 50 percent

Water-react. 1: Substances and Mixtures which, in contact with water, emit flammable gases, Hazard Category 1

Acute Tox. 2: Acute toxicity, Hazard Category 2 Acute Tox. 4: Acute toxicity, Hazard Category 4 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B

STOT SE 3: Serious eye damage/eye irritation, Hazard Category 2B STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1 Aquatic Acute 3: Hazardous to the aquatic environment - AcuteHazard, Category 3

* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com (877) 204-9106