

Filmaxx PRO-200B

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Filmaxx PRO-200B

Other means of identification : Not applicable

Recommended use : Cleaning product

Restrictions on use : Reserved for industrial and professional use.

Product dilution information : No dilution information provided.

Company : Ecolab Inc.

1 Ecolab Place

St. Paul, Minnesota USA 55102

1-800-352-5326

Emergency health

information

1-800-328-0026 (US/Canada), 1-651-222-5352 (outside US)

Issuing date : 09/30/2016

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin corrosion : Category 1A Serious eye damage : Category 1

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : Causes severe skin burns and eye damage.

Precautionary Statements : Prevention:

Wash skin thoroughly after handling. Wear protective gloves/

protective clothing/ eye protection/ face protection.

Response:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep

comfortable for breathing. Immediately call a POISON

CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing. Immediately call a POISON CENTER/doctor. Wash

contaminated clothing before reuse.

Storage:

Store locked up. **Disposal:**

Dispose of contents/ container to an approved waste disposal plant.

Other hazards : None known.

917891-01 1 / 9

Filmaxx PRO-200B

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Pure substance/mixture : Mixture

Chemical name	CAS-No.	Concentration (%)
sodium hydroxide	1310-73-2	10 - 30
Sodium Xylenesulfonate	1300-72-7	1 - 5
1-(2-methoxy-2-methylethoxy)-2-propanol	34590-94-8	1 - 5
ethanol, 2-(2-ethoxyethoxy)-	111-90-0	1 - 5
1-methoxy-2-propanol	107-98-2	1 - 5
Sodium poly(oxyethylene) dodecyl ether sulfate	68585-34-2	1 - 5
potassium hydroxide	1310-58-3	0.1 - 1

SECTION 4. FIRST AID MEASURES

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at

least 15 minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Get medical attention immediately.

In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use

a mild soap if available. Wash clothing before reuse. Thoroughly clean

shoes before reuse. Get medical attention immediately.

If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give

anything by mouth to an unconscious person. Get medical attention

immediately.

If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if

symptoms occur.

Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal

protective equipment.

Notes to physician : Treat symptomatically.

Most important symptoms and effects, both acute and

delayed

: See Section 11 for more detailed information on health effects and

symptoms.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

: None known.

Specific hazards during fire

fighting

: Not flammable or combustible.

Hazardous combustion

products

: Decomposition products may include the following materials:

Carbon oxides

Nitrogen oxides (NOx)

Sulfur oxides

Oxides of phosphorus

Special protective equipment

for fire-fighters

: Use personal protective equipment.

917891-01 2 / 9

Filmaxx PRO-200B

Specific extinguishing methods

: Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Environmental precautions

: Do not allow contact with soil, surface or ground water.

Methods and materials for containment and cleaning up

: Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Do not

breathe dust/ fume/ gas/ mist/ vapors/ spray. Use only with adequate

ventilation. Wash hands thoroughly after handling.

Conditions for safe storage : Do not store near acids. Keep out of reach of children. Store in

suitable labeled containers.

Storage temperature : 0 °C to 50 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Ingredients	CAS-No.	Form of exposure	Permissible concentration	Basis
sodium hydroxide	1310-73-2	Ceiling	2 mg/m3	ACGIH
		Ceiling	2 mg/m3	NIOSH REL
		TWA	2 mg/m3	OSHA Z1
1-(2-methoxy-2-methylethoxy)-2-propanol	34590-94-8	TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		STEL	150 ppm 900 mg/m3	NIOSH REL
		TWA	100 ppm 600 mg/m3	NIOSH REL
		TWA	100 ppm 600 mg/m3	OSHA Z1
ethanol, 2-(2-ethoxyethoxy)-	111-90-0	TWA	25 ppm	AIHA WEEL
1-methoxy-2-propanol	107-98-2	TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH
		STEL	150 ppm	NIOSH REL

917891-01 3 / 9

Filmaxx PRO-200B

			540 mg/m3	
		TWA	100 ppm 360 mg/m3	NIOSH REL
potassium hydroxide	1310-58-3	Ceiling	2 mg/m3	ACGIH
		Ceiling	2 mg/m3	NIOSH REL

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations

below occupational exposure standards.

Personal protective equipment

Eye protection : Wear eye protection/ face protection.

: Wear the following personal protective equipment: Hand protection

Standard glove type.

Gloves should be discarded and replaced if there is any indication of

degradation or chemical breakthrough.

Skin protection : Personal protective equipment comprising: suitable protective gloves,

safety goggles and protective clothing

Respiratory protection : When workers are facing concentrations above the exposure limit they

must use appropriate certified respirators.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

> practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes

and body in case of contact or splash hazard.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid Color : colorless Odor : odorless

13.91, 100 % рΗ Flash point : Not applicable Odor Threshold No data available Melting point/freezing point No data available : No data available Initial boiling point and

boiling range

: No data available Evaporation rate

Flammability (solid, gas) : No data available Upper explosion limit : No data available Lower explosion limit : No data available Vapor pressure : No data available

: No data available Relative vapor density

Relative density : 1.16 Water solubility : soluble

Solubility in other solvents : No data available

917891-01 4/9

Filmaxx PRO-200B

Partition coefficient: n-

octanol/water

: No data available

Autoignition temperature : No data available Thermal decomposition : No data available : No data available Viscosity, kinematic Explosive properties : No data available

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available VOC : No data available

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No dangerous reaction known under conditions of normal use.

Conditions to avoid : None known.

Incompatible materials : Acids

Hazardous decomposition

products

: Decomposition products may include the following materials:

Carbon oxides

Nitrogen oxides (NOx)

Sulfur oxides

Oxides of phosphorus

SECTION 11. TOXICOLOGICAL INFORMATION

exposure

Information on likely routes of : Inhalation, Eye contact, Skin contact

Potential Health Effects

Eyes : Causes serious eye damage.

Skin : Causes severe skin burns.

: Causes digestive tract burns. Ingestion

Inhalation : May cause nose, throat, and lung irritation.

Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Pain, Corrosion

Ingestion : Corrosion, Abdominal pain

Inhalation : Respiratory irritation, Cough

Toxicity

917891-01 5/9

Filmaxx PRO-200B

Product

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Acute inhalation toxicity : No data available

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Skin corrosion/irritation : No data available
Serious eye damage/eye : No data available

irritation

Respiratory or skin

sensitization

: No data available

Carcinogenicity : No data available
Reproductive effects : No data available
Germ cell mutagenicity : No data available
Teratogenicity : No data available
STOT-single exposure : No data available
STOT-repeated exposure : No data available

Aspiration toxicity

: No data available

Ingredients

Acute inhalation toxicity : 1-methoxy-2-propanol

4 h LC50 Rat: 27.3 mg/l

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Environmental Effects : Toxic to aquatic life.

Product

Toxicity to fish : No data available

Toxicity to daphnia and other : No data available

aquatic invertebrates

Toxicity to algae : No data available

Ingredients

Toxicity to fish : 1-(2-methoxy-2-methylethoxy)-2-propanol

96 h LC50 Fish: > 1,000 mg/l

ethanol, 2-(2-ethoxyethoxy)-96 h LC50 Fish: 6,010 mg/l

1-methoxy-2-propanol

96 h LC50 Fish: > 1,000 mg/l

Sodium poly(oxyethylene) dodecyl ether sulfate

96 h LC50 Fish: 28 mg/l

Ingredients

Toxicity to daphnia and other : sodium hydroxide

aquatic invertebrates

sodium hydroxide 48 h EC50: 40 mg/l

917891-01 6 / 9

Filmaxx PRO-200B

Ingredients

Toxicity to algae : Sodium Xylenesulfonate

96 h EC50: 230 mg/l

Persistence and degradability

Biodegradable

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods : Do not contaminate ponds, waterways or ditches with chemical or

used container. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste

disposal facility.

Disposal considerations : Dispose of as unused product. Empty containers should be taken to

an approved waste handling site for recycling or disposal. Do not reuse empty containers. Dispose of in accordance with local, state, and

federal regulations.

RCRA - Resource : D002 (Corrosive)

Conservation and Recovery Authorization Act Hazardous

waste

SECTION 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ
			(lbs)
sodium hydroxide	1310-73-2	1000	8558

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Acute Health Hazard

917891-01 7 / 9

Filmaxx PRO-200B

SARA 302 : No chemicals in this material are subject to the reporting requirements

of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels established

by SARA Title III, Section 313:

ethanol, 2-(2- 111-90-0 2.4915 %

ethoxyethoxy)-

California Prop 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

The ingredients of this product are reported in the following inventories:

United States TSCA Inventory:

On TSCA Inventory

Canadian Domestic Substances List (DSL):

All components of this product are on the Canadian DSL

Australia Inventory of Chemical Substances (AICS):

On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemical Substances:

On the inventory, or in compliance with the inventory

Japan. ENCS - Existing and New Chemical Substances Inventory:

not determined

Japan. ISHL - Inventory of Chemical Substances (METI) :

not determined

Korea. Korean Existing Chemicals Inventory (KECI) :

On the inventory, or in compliance with the inventory

Philippines Inventory of Chemicals and Chemical Substances (PICCS):

On the inventory, or in compliance with the inventory

China. Inventory of Existing Chemical Substances in China (IECSC):


On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

917891-01 8 / 9

Filmaxx PRO-200B

NFPA:



HMIS III:

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

Issuing date 09/30/2016

Version 1.0

Prepared by Regulatory Affairs

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

917891-01 9/9