



SAFETY DATA SHEET

Issuing date 02-Nov-2012

Revision Date 05-Jan-2015

Version 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name Hi-Valu Degreaser

Other means of identification

Product Code 958037
UN/ID No UN3266
Document 958037CGH1-4/ 958037GH0

Recommended use of the chemical and restrictions on use

Recommended use Heavy Duty Alkaline Solvent Degreaser

Details of the supplier of the safety data sheet

Distributor

Hi-Valu, LLC
11434 Moog Dr.
Saint Louis, MO 63146

Emergency telephone number

24 Hour Emergency Phone Number CHEMTREC: 1-800-424-9300 (NORTH AMERICA)
1-703-527-3887 (INTERNATIONAL)
Company Phone Number 314-569-2800

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 1
Serious eye damage/eye irritation	Category 1
Flammable liquids	Category 4

Label elements

Emergency Overview

Danger

Hazard Statements

Causes severe skin burns and eye damage
Combustible liquid



Appearance Transparent

Physical state Liquid

Odor Glycol ether

Precautionary Statements - Prevention

- Do not breathe dust/fume/gas/mist/vapors/spray
- Wash face, hands and any exposed skin thoroughly after handling
- Wear protective gloves/protective clothing/eye protection/face protection
- Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Precautionary Statements - Response

- Immediately call a POISON CENTER or doctor/physician
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- Wash contaminated clothing before reuse
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)**Other information****3. COMPOSITION/INFORMATION ON INGREDIENTS**

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Chemical Name	CAS-No	Weight-%	Trade Secret
2-Butoxyethanol	111-76-2	1% - 10%	*
Potassium hydroxide	1310-58-3	1% - 2%	*
Sodium Metasilicate	6834-92-0	0.5% - 1.5%	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**First aid measures for different exposure routes**

General advice	Show this safety data sheet to the doctor in attendance.
Eye contact	Immediately flush eye with plenty of cool, running water. Remove contact lenses if applicable, and continue flushing for at least 15 minutes, holding eyelids apart to ensure thorough rinsing of the entire eye. GET IMMEDIATE MEDICAL ATTENTION.
Skin contact	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing before re-use. If skin irritation persists, see a physician.
Inhalation	If qualified give oxygen or artificial respiration as needed.

Ingestion Rinse mouth. DO NOT induce vomiting. Give large amounts of water if victim is conscious. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Protection of First-aiders Do not use mouth-to-mouth method if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Most important symptoms/effects, acute and delayed

Main Symptoms The most important known symptoms and effects are described in the labelling in section 2 and/or in section 11.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide (CO₂). Dry chemical. Water spray or fog.

Unsuitable Extinguishing Media This product contains alcohols which will reduce the effectiveness of normal foam. Use alcohol-resistant foam instead.

Specific hazards arising from the chemical

No information available.

Hazardous Combustion Products Carbon monoxide.

Explosion Data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Use personal protective equipment.

Environmental precautions

Environmental precautions Keep out of waterways. Neutralization is normally necessary before waste water is discharged into water treatment plants. See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up

Methods for Containment Dike to contain spill and prevent entry into sewers, waterways, and low areas. Neutralize with dilute acid.

Methods for cleaning up Mop up & flush neutralized material to sewer with plenty of water.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Do not smoke while using or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Avoid prolonged exposure. Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep out of the reach of children. Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible substances.

Incompatible products

Strong oxidizing agents, acids, aluminum and other soft metals.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Review Section 3 & 4 for Exposure Guidelines.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
2-Butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³ Ceiling: 2 mg/m ³
Potassium hydroxide 1310-58-3	-	-	

NIOSH IDLH: Immediately Dangerous to Life or Health

Appropriate engineering controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas Ensure that eyewash stations and safety showers or an equivalent method of decontamination are close to the work location.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Splash-proof chemical goggles or face shield.

Skin and body protection

Impervious rubber, alkali-proof protective gloves. Impervious rubber boots & apron..

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures

Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state

Liquid

Appearance

Transparent

Color

Purple

Odor

Glycol ether

Odor Threshold

No information available

Property

Values

Remarks • Methods

pH

14

Melting/freezing point

No information available

Boiling point/boiling range

~ 100 °C / 212 °F

Flash Point	> 90 °C / > 200 °F	TCC
Evaporation rate	Similar to water	Similar to water
Flammability (solid, gas)	No information available	
Flammability Limits in Air		
Upper flammability limit	No information available	
Lower flammability limit	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Specific Gravity	1.065	
Water solubility	Completely soluble.	Completely soluble.
Solubility in other solvents	No information available	
Partition coefficient: n-octanol/water	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Viscosity, kinematic	No information available	
Viscosity, dynamic	No information available	
Explosive properties	Not explosive	
Oxidizing Properties	No information available	

Other information

Softening point	N/A
Molecular Weight	N/A
VOC Content(%)	< 10 %
Density VALUE	N/A
Bulk Density VALUE	N/A

10. STABILITY AND REACTIVITY**Chemical stability**

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Strong oxidizing agents, acids, aluminum and other soft metals.

Hazardous Decomposition Products

Hydrogen gas by reaction with incompatible metals. May emit toxic fumes under fire conditions. Carbon monoxide (CO).

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Product Information	Causes severe skin burns and eye damage
Inhalation	Irritating to respiratory system.
Eye contact	Corrosive to the eyes and may cause severe damage including blindness.
Skin contact	Contact causes severe skin irritation and possible burns.
Ingestion	Corrosive - causes severe burns to gastrointestinal tract.

Chemical Name	Oral LD50	Dermal LD50	LC50 Inhalation
2-Butoxyethanol 111-76-2	= 470 mg/kg (Rat)	= 99 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h

Potassium hydroxide 1310-58-3	= 284 mg/kg (Rat)	-	-
Sodium Metasilicate 6834-92-0	= 600 mg/kg (Rat)	-	-

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic effects No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
2-Butoxyethanol 111-76-2	A3	Group 3	-	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Chronic toxicity No information available.

Aspiration hazard No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 6638 mg/kg

ATEmix (dermal) 21004 mg/kg

ATEmix (inhalation-dust/mist) 30 mg/l

ATEmix (inhalation-vapor) 9000 mg/l

12. ECOLOGICAL INFORMATION**Ecotoxicity**

1.526% of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
2-Butoxyethanol 111-76-2	-	1490: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 2950: 96 h <i>Lepomis macrochirus</i> mg/L LC50	1698 - 1940: 24 h <i>Daphnia magna</i> mg/L EC50 >1000: 48 h <i>Daphnia magna</i> mg/L EC50
Potassium hydroxide 1310-58-3	-	80: 96 h <i>Gambusia affinis</i> mg/L LC50 static	-
Sodium Metasilicate 6834-92-0	-	210: 96 h <i>Brachydanio rerio</i> mg/L LC50 semi-static 210: 96 h <i>Brachydanio rerio</i> mg/L LC50	-

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
2-Butoxyethanol 111-76-2	0.81
Potassium hydroxide 1310-58-3	0.65 0.83

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging Do not reuse container.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. TRANSPORT INFORMATION

<u>DOT</u>	Regulated
UN/ID No	UN3266
Proper shipping name	Corrosive Liquid, Basic, Inorganic, n.o.s. (Potassium Hydroxide)
Hazard class	8
Packing Group	III
Emergency Response Guide Number	154

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	-
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - All components of this product are listed or are exempt or excluded from listing on the United States Toxic Substances Control Act Section 8(b) Inventory.

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	SARA 313 - Threshold Values %
2-Butoxyethanol - 111-76-2	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	no
Fire Hazard	no
Sudden Release of Pressure Hazard	no
Reactive Hazard	Yes

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Potassium hydroxide 1310-58-3	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

U.S. State Regulations**California Proposition 65**

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

This product contains substances regulated by state right-to-know regulations.

Chemical Name	New Jersey	Massachusetts	Pennsylvania
2-Butoxyethanol 111-76-2	X	X	X
Potassium hydroxide 1310-58-3	X	-	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA	Health Hazards 3	Flammability 1	Instability 0	Physical and chemical hazards COR
HMIS	Health hazard 3	Flammability 1	Physical Hazards 0	Personal protection X

Prepared By

Issuing date

Revision Date

Revision Note

2

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

