

FACILIPRO MAXX DURABLE FLOOR FINISH - PART B

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : FACILIPRO MAXX DURABLE FLOOR FINISH - PART B

Other means of identification : Not applicable

Recommended use : Floor care product

Restrictions on use : Reserved for industrial and professional use.

Product dilution information : 94.7% PART A WITH 5.3% PART B

Company : Ecolab Inc.

1 Ecolab Place

St. Paul, Minnesota USA 55102

1-800-352-5326

Emergency health

information

: 1-800-328-0026 (US/Canada), 1-651-222-5352 (outside US)

Issuing date : 10/17/2019

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Product AS SOLD

Flammable liquids : Category 4
Skin irritation : Category 2
Serious eye damage : Category 1
Skin sensitization : Category 1

Specific target organ toxicity - : Ca

single exposure

: Category 3 (Respiratory system)

Product AT USE DILUTION

Eye irritation : Category 2B

GHS label elements

Product AS SOLD

Hazard pictograms



Signal Word : Danger

Hazard Statements : Combustible liquid.

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation.

Precautionary Statements : Prevention:

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/ eye protection/ face protection.

913652-03 1 / 12

FACILIPRO MAXX DURABLE FLOOR FINISH - PART B

Response:

IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. If skin irritation or rash occurs: Get medical advice/ attention. Take off contaminated clothing and wash before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

Disposal

Dispose of contents/ container to an approved waste disposal plant.

Product AT USE DILUTION

Signal Word : Warning

Hazard Statements : Causes eye irritation.

Precautionary Statements : Prevention:

Wash skin thoroughly after handling.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye

irritation persists: Get medical advice/ attention.

Product AS SOLD

Other hazards : None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Product AS SOLD

Pure substance/mixture : Mixture

Chemical name	CAS-No.	Concentration (%)
hexane, 1,6-diisocyanato-, homopolymer	28182-81-2	60 - 100
Propanol, 1(or 2)-(2-methoxymethylethoxy)-,	88917-22-0	10 - 30
acetate		
poly(oxy-1,2-ethanediyl), .alphatridecylomega	9046-01-9	5 - 10
hydroxy-, phosphate		
cyclohexyldimethylamine	98-94-2	1 - 5
hexamethylene-di-isocyanate	822-06-0	0.1 - 1

Product AT USE DILUTION

Chemical name CAS-No. Concentration (%)

Propanol, 1(or 2)-(2-methoxymethylethoxy)-, 88917-22-0 10 - 20

acetate

SECTION 4. FIRST AID MEASURES

Product AS SOLD

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at

least 15 minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Get medical attention immediately.

In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use

a mild soap if available. Wash clothing before reuse. Thoroughly clean

913652-03 2 / 12

FACILIPRO MAXX DURABLE FLOOR FINISH - PART B

shoes before reuse. Get medical attention.

If swallowed : Rinse mouth. Get medical attention if symptoms occur.

If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention

immediately.

Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal

protective equipment.

Notes to physician : Treat symptomatically.

Most important symptoms and effects, both acute and

delayed

: See Section 11 for more detailed information on health effects and

symptoms.

Product AT USE DILUTION

In case of eye contact : Rinse with plenty of water.

In case of skin contact : Rinse with plenty of water.

If swallowed : Rinse mouth. Get medical attention if symptoms occur.

If inhaled : Get medical attention if symptoms occur.

SECTION 5. FIRE-FIGHTING MEASURES

Product AS SOLD

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during fire

fighting

: Fire Hazard

Keep away from heat and sources of ignition. Flash back possible over considerable distance.

Hazardous combustion

products

: Decomposition products may include the following materials:

Carbon oxides

Nitrogen oxides (NOx) Oxides of phosphorus

Special protective equipment

for fire-fighters

: Use personal protective equipment.

Specific extinguishing

methods

: Fire residues and contaminated fire extinguishing water must be

disposed of in accordance with local regulations. In the event of fire

and/or explosion do not breathe fumes.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Product AS SOLD

Personal precautions, protective equipment and emergency procedures

: Ensure adequate ventilation. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion

and contact with skin and eyes. When workers are facing

concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained

913652-03 3 / 12

FACILIPRO MAXX DURABLE FLOOR FINISH - PART B

personnel only. Refer to protective measures listed in sections 7 and

Environmental precautions : Do not allow contact with soil, surface or ground water.

Methods and materials for containment and cleaning up

: Eliminate all ignition sources if safe to do so. Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

Product AT USE DILUTION

Personal precautions, protective equipment and emergency procedures : Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Do not allow contact with soil, surface or ground water.

Methods and materials for containment and cleaning up

: Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

SECTION 7. HANDLING AND STORAGE

Product AS SOLD

Advice on safe handling : Do not get in eyes, on skin, or on clothing. Do not breathe dust/ fume/

gas/ mist/ vapors/ spray. Use only with adequate ventilation. Keep away from fire, sparks and heated surfaces. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Wash hands thoroughly after handling. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full

Personal Protective Equipment (PPE).

Conditions for safe storage : Keep away from heat and sources of ignition. Keep away from

oxidizing agents. Keep out of reach of children. Store in suitable

labeled containers.

Storage temperature : 10 °C to 40 °C

Product AT USE DILUTION

Advice on safe handling : Wash hands thoroughly after handling. In case of mechanical

malfunction, or if in contact with unknown dilution of product, wear full

Personal Protective Equipment (PPE).

Conditions for safe storage : Keep out of reach of children. Store in suitable labeled containers.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Product AS SOLD

Ingredients with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
hexamethylene-di-isocyanate	822-06-0	TWA	0.005 ppm	ACGIH

913652-03 4 / 12

FACILIPRO MAXX DURABLE FLOOR FINISH - PART B

Ceiling	0.02 ppm 0.14 mg/m3	NIOSH REL
TWA	0.005 ppm 0.035 mg/m3	NIOSH REL

: Effective exhaust ventilation system. Maintain air concentrations Engineering measures

below occupational exposure standards.

Personal protective equipment

Eye protection : Wear eye protection/ face protection.

Hand protection Wear the following personal protective equipment:

Standard glove type.

Gloves should be discarded and replaced if there is any indication of

degradation or chemical breakthrough.

Skin protection : No special protective equipment required.

: When workers are facing concentrations above the exposure limit they Respiratory protection

must use appropriate certified respirators.

: Handle in accordance with good industrial hygiene and safety Hygiene measures

practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes

and body in case of contact or splash hazard.

Product AT USE DILUTION

: Good general ventilation should be sufficient to control worker **Engineering measures**

exposure to airborne contaminants.

Personal protective equipment

Eye protection : No special protective equipment required.

: No special protective equipment required. Hand protection

Skin protection : No special protective equipment required.

Respiratory protection : No personal respiratory protective equipment normally required.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Product AT USE DILUTION Product AS SOLD

Appearance : liquid liquid

Color : clear, light yellow white

Odor : slight ammoniacal : 7, (100 %) 7.0 - 8.5

Flash point : 86 °C closed cup, Sustains combustion

Odor Threshold : No data available Melting point/freezing point : No data available Initial boiling point and : No data available

boiling range

рΗ

913652-03 5/12

FACILIPRO MAXX DURABLE FLOOR FINISH - PART B

Evaporation rate : No data available Flammability (solid, gas) : Not applicable Upper explosion limit : No data available Lower explosion limit : No data available : No data available Vapor pressure Relative vapor density : No data available

Relative density : 1.062 - 1.15

Water solubility : No data available Solubility in other solvents : No data available Partition coefficient: n-: No data available

octanol/water

Autoignition temperature : No data available Thermal decomposition : No data available Viscosity, kinematic : No data available : No data available Explosive properties Oxidizing properties : No data available Molecular weight : No data available VOC : No data available

SECTION 10. STABILITY AND REACTIVITY

Product AS SOLD

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No dangerous reaction known under conditions of normal use.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Bases

Organic materials

Acids

Hazardous decomposition

products

: In case of fire hazardous decomposition products may be produced

such as:

Carbon oxides

Nitrogen oxides (NOx) Oxides of phosphorus

SECTION 11. TOXICOLOGICAL INFORMATION

exposure

Information on likely routes of : Inhalation, Eye contact, Skin contact

Potential Health Effects

Product AS SOLD

Eyes : Causes serious eye damage.

913652-03 6/12

FACILIPRO MAXX DURABLE FLOOR FINISH - PART B

Skin : Causes skin irritation. May cause allergic skin reaction.

Ingestion : Health injuries are not known or expected under normal use.

Inhalation : May cause respiratory tract irritation. May cause nose, throat, and

lung irritation.

Chronic Exposure : Health injuries are not known or expected under normal use.

Product AT USE DILUTION

Eyes : Causes eye irritation.

Skin : Health injuries are not known or expected under normal use.

Ingestion : Health injuries are not known or expected under normal use.

Inhalation : Health injuries are not known or expected under normal use.

Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Product AS SOLD

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Irritation, Allergic reactions

Ingestion : No symptoms known or expected.

Inhalation : No information available.

Product AT USE DILUTION

Eye contact : Redness, Irritation

Skin contact : No symptoms known or expected.

Ingestion : No symptoms known or expected.

Inhalation : No symptoms known or expected.

Toxicity

Product AS SOLD

Product

Acute oral toxicity : No data available
Acute inhalation toxicity : No data available
Acute dermal toxicity : No data available
Skin corrosion/irritation : No data available
Respiratory or skin : No data available

sensitization

Carcinogenicity : No data available
Reproductive effects : No data available
Germ cell mutagenicity : No data available
Teratogenicity : No data available
STOT-single exposure : No data available

913652-03 7 / 12

FACILIPRO MAXX DURABLE FLOOR FINISH - PART B

STOT-repeated exposure : No data available Aspiration toxicity : No data available

Components

Acute oral toxicity : hexamethylene-di-isocyanate

LD50 Rat: 959 mg/kg

Components

Acute inhalation toxicity : hexane, 1,6-diisocyanato-, homopolymer

> 4 h LC50 Rat: 0.462 mg/l Test atmosphere: dust/mist

hexamethylene-di-isocyanate

LC50 Rat: 0.124 mg/l Test atmosphere: vapor

Components

Acute dermal toxicity : hexamethylene-di-isocyanate

LD50 Rat: > 7,000 mg/kg

SECTION 12. ECOLOGICAL INFORMATION

Product AS SOLD

Ecotoxicity

Environmental Effects : Harmful to aquatic life with long lasting effects.

Product

: No data available Toxicity to fish : No data available Toxicity to daphnia and other

aquatic invertebrates

: No data available Toxicity to algae

Components

Toxicity to fish : hexane, 1,6-diisocyanato-, homopolymer

96 h LC50 Danio rerio (zebra fish): > 100 mg/l

Components

aquatic invertebrates

Toxicity to daphnia and other : hexane, 1,6-diisocyanato-, homopolymer

48 h LC50 Daphnia magna (Water flea): 127 mg/l

Components

: hexane, 1,6-diisocyanato-, homopolymer Toxicity to algae

72 h EC50 Desmodesmus subspicatus (green algae): > 1,000 mg/l

Persistence and degradability

Product AS SOLD

Poorly biodegradable

Product AT USE DILUTION

Poorly biodegradable

Bioaccumulative potential

No data available

913652-03 8/12

FACILIPRO MAXX DURABLE FLOOR FINISH - PART B

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Product AS SOLD

Disposal methods : Do not contaminate ponds, waterways or ditches with chemical or

used container. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste

disposal facility.

Disposal considerations : Dispose of as unused product. Empty containers should be taken to

an approved waste handling site for recycling or disposal. Do not reuse empty containers. Dispose of in accordance with local, state, and

federal regulations.

RCRA - Resource

Conservation and Recovery Authorization Act Hazardous

waste

: D001 (Ignitable)

Product AT USE DILUTION

Disposal methods : Do not contaminate ponds, waterways or ditches with chemical or

used container. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste

disposal facility.

Disposal considerations : Dispose of as unused product. Empty containers should be taken to

an approved waste handling site for recycling or disposal. Do not reuse empty containers. Dispose of in accordance with local, state, and

federal regulations.

SECTION 14. TRANSPORT INFORMATION

Product AS SOLD

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (DOT)

Not dangerous goods

Sea transport (IMDG/IMO)

Not dangerous goods

SECTION 15. REGULATORY INFORMATION

Product AS SOLD

EPCRA - Emergency Planning and Community Right-to-Know

913652-03 9 / 12

FACILIPRO MAXX DURABLE FLOOR FINISH - PART B

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
hexamethylene-di-isocyanate	822-06-0	100	58823

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitization

SARA 302 : This material does not contain any components with a section 302

EHS TPQ.

SARA 313 : This material does not contain any chemical components with known

CAS numbers that exceed the threshold (De Minimis) reporting levels

established by SARA Title III, Section 313.

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

California Cleaning Product Right to Know Act of 2017 (SB 258)

This regulation applies to this product.

CAS-No.	Function	List(s)
28182-81-2	Film Former	Not Applicable
88917-22-0	Solvent	Not Applicable
9046-01-9	Film Former	Not Applicable
98-94-2	Film Former	Not Applicable
822-06-0	Film Former	4, 8, 18
	28182-81-2 88917-22-0 9046-01-9 98-94-2	28182-81-2 Film Former 88917-22-0 Solvent 9046-01-9 Film Former 98-94-2 Film Former

^{*}refer to ecolab.com/sds for electronic links to designated lists

The ingredients of this product are reported in the following inventories:

Switzerland. New notified substances and declared preparations :

not determined

United States TSCA Inventory:

All substances listed as active on the TSCA inventory

Canadian Domestic Substances List (DSL) :

All components of this product are on the Canadian DSL

Australia Inventory of Chemical Substances (AICS):

On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemical Substances:

not determined

Japan. ENCS - Existing and New Chemical Substances Inventory :

913652-03 10 / 12

FACILIPRO MAXX DURABLE FLOOR FINISH - PART B

not determined

Korea. Korean Existing Chemicals Inventory (KECI):

On the inventory, or in compliance with the inventory

Philippines Inventory of Chemicals and Chemical Substances (PICCS):

On the inventory, or in compliance with the inventory

China. Inventory of Existing Chemical Substances in China (IECSC):

On the inventory, or in compliance with the inventory


Taiwan Chemical Substance Inventory (TCSI):

On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Product AS SOLD

NFPA:



HMIS III:


HEALTH	3*
FLAMMABILITY	2
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

Product AT USE DILUTION NFPA:



HMIS III:

HEALTH	1
FLAMMABILITY	0
PHYSICAL HAZARD	0
O not significant 1 Clight	

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

Issuing date : 10/17/2019

Version 1.3

Prepared by : Regulatory Affairs

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

913652-03 11/12

FACILIPRO MAXX DURABLE FLOOR FINISH - PART B

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

913652-03 12 / 12