

TURBOMAX

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : TURBOMAX

Other means of identification : Not applicable

Recommended use : Laundry product

Restrictions on use : Reserved for industrial and professional use.

Product dilution information : Product is sold ready to use.

Company : Ecolab Inc.

1 Ecolab Place

St. Paul, Minnesota USA 55102

1-800-352-5326

Emergency health

information

: 1-800-328-0026 (US/Canada), 1-651-222-5352 (outside US)

Issuing date : 05/13/2019

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity (Oral) : Category 4
Skin corrosion : Category 1A
Serious eye damage : Category 1

GHS label elements

Hazard pictograms :





Signal Word : Danger

Hazard Statements : Harmful if swallowed.

Causes severe skin burns and eye damage.

Precautionary Statements : Prevention:

Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep

comfortable for breathing. Immediately call a POISON

CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing. Immediately call a POISON CENTER/doctor. Wash

contaminated clothing before reuse.

Storage:

Store locked up. **Disposal:**

900174-01 1 / 9

TURBOMAX

Dispose of contents/ container to an approved waste disposal plant.

Other hazards : None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Pure substance/mixture Mixture

Chemical name CAS-No. Concentration (%) 10 - 30 potassium hydroxide 1310-58-3 5 - 10 silicic acid (h2sio3), dipotassium salt 10006-28-7 disodium metasilicate 6834-92-0 5 - 10 silica, amorphous, fumed 7631-86-9 1 - 5

SECTION 4. FIRST AID MEASURES

: Rinse immediately with plenty of water, also under the eyelids, for at In case of eye contact

least 15 minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Get medical attention immediately.

In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use

a mild soap if available. Wash clothing before reuse. Thoroughly clean

shoes before reuse. Get medical attention immediately.

If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give

anything by mouth to an unconscious person. Get medical attention

immediately.

If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if

symptoms occur.

Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal

protective equipment.

Notes to physician : Treat symptomatically.

Most important symptoms and effects, both acute and

delayed

: See Section 11 for more detailed information on health effects and

symptoms.

SECTION 5. FIRE-FIGHTING MEASURES

: Use extinguishing measures that are appropriate to local Suitable extinguishing media

circumstances and the surrounding environment.

Unsuitable extinguishing

media

: None known.

Specific hazards during fire

fighting

: Not flammable or combustible.

Hazardous combustion

products

: Decomposition products may include the following materials:

Carbon oxides

for fire-fighters

Special protective equipment : Use personal protective equipment.

Specific extinguishing : Fire residues and contaminated fire extinguishing water must be

900174-01 2/9

TURBOMAX

methods disposed of in accordance with local regulations. In the event of fire

and/or explosion do not breathe fumes.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Do not allow contact with soil, surface or ground water.

Methods and materials for containment and cleaning up

: Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Do not

breathe dust/ fume/ gas/ mist/ vapors/ spray. Use only with adequate ventilation. Wash hands thoroughly after handling. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).

product, wear full Personal Protective Equipment (PPE).

Conditions for safe storage : Do not store near acids. Keep out of reach of children. Store in

suitable labeled containers.

Storage temperature : 0 °C to 50 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
potassium hydroxide	1310-58-3	Ceiling	2 mg/m3	ACGIH
		Ceiling	2 mg/m3	NIOSH REL
silica, amorphous, fumed	7631-86-9	TWA (Dust)	20 millions of particles per cubic foot of air (Silica)	OSHA Z3
		TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z3
		TWA	6 mg/m3 (Silica)	NIOSH REL

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations

below occupational exposure standards.

Personal protective equipment

Eye protection : Wear eye protection/ face protection.

Hand protection : Wear the following personal protective equipment:

900174-01 3 / 9

TURBOMAX

Standard glove type.

Gloves should be discarded and replaced if there is any indication of

degradation or chemical breakthrough.

Skin protection : Personal protective equipment comprising: suitable protective gloves,

safety goggles and protective clothing

Respiratory protection : When workers are facing concentrations above the exposure limit they

must use appropriate certified respirators.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes

and body in case of contact or splash hazard.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : cloudy, colorless

Odor : odorless

pH : 12.5 - 13.5, (100 %)

Flash point : Not applicable, Does not sustain combustion.

Odor Threshold : No data available

Melting point/freezing point : No data available

Initial boiling point and

boiling range

: > 100 °C

Evaporation rate : No data available Flammability (solid, gas) : No data available Upper explosion limit : No data available : No data available Lower explosion limit : No data available Vapor pressure Relative vapor density : No data available Relative density : 1.385 - 1.415 Water solubility : partly soluble

Partition coefficient: n-

Solubility in other solvents

octanol/water

: No data available

: No data available

Autoignition temperature : No data available
Thermal decomposition : No data available
Viscosity, kinematic : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Molecular weight : No data available
VOC : No data available

SECTION 10. STABILITY AND REACTIVITY

900174-01 4 / 9

TURBOMAX

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No dangerous reaction known under conditions of normal use.

Conditions to avoid : None known.

Incompatible materials : Acids

Metals

Hazardous decomposition

products

: In case of fire hazardous decomposition products may be produced

such as:

Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

exposure

Information on likely routes of : Inhalation, Eye contact, Skin contact

Potential Health Effects

Eyes : Causes serious eye damage.

Skin : Causes severe skin burns.

Ingestion : Harmful if swallowed. Causes digestive tract burns.

Inhalation : May cause nose, throat, and lung irritation.

Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Pain, Corrosion

: Corrosion, Abdominal pain Ingestion

Inhalation : Respiratory irritation, Cough

Toxicity

Product

Acute oral toxicity : Acute toxicity estimate : 1,126 mg/kg

Acute inhalation toxicity : No data available Acute dermal toxicity : No data available Skin corrosion/irritation : No data available

Serious eye damage/eye

irritation

: No data available

Respiratory or skin

sensitization

: No data available

: No data available Carcinogenicity

900174-01 5/9

TURBOMAX

Reproductive effects : No data available
Germ cell mutagenicity : No data available
Teratogenicity : No data available
STOT-single exposure : No data available
STOT-repeated exposure : No data available
Aspiration toxicity : No data available

Components

Acute dermal toxicity : silicic acid (h2sio3), dipotassium salt

LD50 Rat: > 5,000 mg/kg

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Environmental Effects : This product has no known ecotoxicological effects.

Product

Toxicity to fish : No data available

Toxicity to daphnia and other aquatic invertebrates : No data available

Toxicity to algae : No data available

Components

Toxicity to fish : silicic acid (h2sio3), dipotassium salt

96 h LC50: 210 mg/l

disodium metasilicate 96 h LC50 Fish: 210 mg/l

silica, amorphous, fumed 96 h LC50: > 10,000 mg/l

Components

Toxicity to daphnia and other : silica, amorphous, fumed

aquatic invertebrates 24 h EC50 Daphnia magna (Water flea): > 1,000 mg/l

Components

Toxicity to algae : silica, amorphous, fumed

72 h EC50: > 10,000 mg/l

Persistence and degradability

Not applicable - inorganic

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

900174-01 6 / 9

TURBOMAX

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods : Where possible recycling is preferred to disposal or incineration. If

recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.

Disposal considerations : Dispose of as unused product. Empty containers should be taken to

an approved waste handling site for recycling or disposal. Do not reuse empty containers. Dispose of in accordance with local, state, and

federal regulations.

RCRA - Resource : D002 (Corrosive)

Conservation and Recovery Authorization Act Hazardous

waste

SECTION 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (DOT)

UN number : 1814

Description of the goods : Potassium hydroxide, solution

Class : 8
Packing group : II
Environmentally hazardous : no

Sea transport (IMDG/IMO)

UN number : 1814

Description of the goods : POTASSIUM HYDROXIDE SOLUTION

Class : 8
Packing group : II
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
potassium hydroxide	1310-58-3	1000	4299

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 302 : This material does not contain any components with a section 302

EHS TPQ.

900174-01 7 / 9

TURBOMAX

SARA 313

: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

California Cleaning Product Right to Know Act of 2017 (SB 258)

This regulation applies to this product.

Chemical Name	CAS-No.	Function	List(s)
water	7732-18-5	Diluent	Not Applicable
potassium hydroxide	1310-58-3	Cleaning Agent	Not Applicable
silicic acid (h2sio3), dipotassium	10006-28-7	Cleaning Agent	Not Applicable
salt			
disodium metasilicate	6834-92-0	Cleaning Agent	Not Applicable
Substituted fatty acid alkyated salt	Withheld	Cleaning Agent	Not Applicable

^{*}refer to ecolab.com/sds for electronic links to designated lists

The ingredients of this product are reported in the following inventories:

United States TSCA Inventory:

All substances listed as active on the TSCA inventory

Canadian Domestic Substances List (DSL):

This product contains one or several components listed in the Canadian NDSL.

Australia Inventory of Chemical Substances (AICS):

On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemical Substances:

not determined

Japan. ENCS - Existing and New Chemical Substances Inventory :

not determined

Korea. Korean Existing Chemicals Inventory (KECI):

On the inventory, or in compliance with the inventory

Philippines Inventory of Chemicals and Chemical Substances (PICCS):

not determined

China. Inventory of Existing Chemical Substances in China (IECSC):

On the inventory, or in compliance with the inventory

Taiwan Chemical Substance Inventory (TCSI):


On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

900174-01 8 / 9

TURBOMAX

NFPA:



HMIS III:

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

Issuing date : 05/13/2019

Version : 1.2

Prepared by : Regulatory Affairs

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

900174-01 9 / 9