

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : QUIK FILL 32 FLOOR STRIPPER

Other means of identification : Not applicable

Recommended use : Floor Stripper

Restrictions on use : For professional and industrial installation and use only.

Product dilution information : 6.25 % - 16.7 %

Company : Ecolab Inc.  
1 Ecolab Place  
St. Paul, Minnesota USA 55102  
1-800-352-5326

Emergency health information : 1-800-328-0026 (US/Canada), 1-651-222-5352 (outside US)

Issuing date : 12/16/2021

**SECTION 2. HAZARDS IDENTIFICATION**
**GHS Classification**
**Product AS SOLD**

Acute toxicity (Inhalation) : Category 4

Skin corrosion : Category 1A

Serious eye damage : Category 1

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

**Product AT USE DILUTION**

Skin corrosion : Category 1A

Serious eye damage : Category 1

**GHS label elements**
**Product AS SOLD**

Hazard pictograms :



Signal Word : Danger

Hazard Statements : Causes severe skin burns and eye damage.  
Harmful if inhaled.  
May cause respiratory irritation.

Precautionary Statements : **Prevention:**  
Avoid breathing mist or vapors. Wash skin thoroughly after handling.  
Use only outdoors or in a well-ventilated area. Wear protective gloves/  
protective clothing/ eye protection/ face protection.  
**Response:**  
IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN  
(or hair): Take off immediately all contaminated clothing. Rinse skin

## SAFETY DATA SHEET

### QUIK FILL 32 FLOOR STRIPPER

with water/ shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. Wash contaminated clothing before reuse.

**Storage:**

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

**Disposal:**

Dispose of contents/ container to an approved waste disposal plant.

#### Product AT USE DILUTION

Hazard pictograms

:



Signal Word

: Danger

Hazard Statements

: Causes severe skin burns and eye damage.

Precautionary Statements

: **Prevention:**

Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. Wash contaminated clothing before reuse.

**Storage:**

Store locked up.

**Disposal:**

Dispose of contents/ container to an approved waste disposal plant.

#### Product AS SOLD

Other hazards

: None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Product AS SOLD

Pure substance/mixture

: Mixture

Chemical name	CAS-No.	Concentration (%)
2-butoxyethanol	111-76-2	10 - 30
Monoethanolamine	141-43-5	5 - 10
Sodium hydroxide	1310-73-2	5 - 10
Sodium Xylenesulfonate	1300-72-7	1 - 5
alcohols, c12-16, ethoxylated >5EO	68551-12-2	1 - 5

#### Product AT USE DILUTION

Chemical name	CAS-No.	Concentration (%)
2-butoxyethanol	111-76-2	1 - 5
Monoethanolamine	141-43-5	1 - 5

# SAFETY DATA SHEET

## QUIK FILL 32 FLOOR STRIPPER

Sodium hydroxide

1310-73-2

0.1 - 1

### SECTION 4. FIRST AID MEASURES

#### Product AS SOLD

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
- If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention.
- Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal protective equipment.
- Notes to physician : Treat symptomatically.
- Most important symptoms and effects, both acute and delayed : See Section 11 for more detailed information on health effects and symptoms.

#### Product AT USE DILUTION

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
- If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

### SECTION 5. FIRE-FIGHTING MEASURES

#### Product AS SOLD

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Not flammable or combustible.
- Hazardous combustion products : Decomposition products may include the following materials:  
Carbon oxides

# SAFETY DATA SHEET

## QUIK FILL 32 FLOOR STRIPPER

Sulfur oxides  
Nitrogen oxides (NOx)

- Special protective equipment for fire-fighters : Use personal protective equipment.
- Specific extinguishing methods : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

#### Product AS SOLD

- Personal precautions, protective equipment and emergency procedures : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Do not allow contact with soil, surface or ground water.
- Methods and materials for containment and cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

#### Product AT USE DILUTION

- Personal precautions, protective equipment and emergency procedures : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Do not allow contact with soil, surface or ground water.
- Methods and materials for containment and cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

### SECTION 7. HANDLING AND STORAGE

#### Product AS SOLD

- Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. Use only with adequate ventilation. Wash hands thoroughly after handling. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).
- Conditions for safe storage : Do not store near acids. Keep out of reach of children. Store in suitable labeled containers.
- Storage temperature : 15 °C to 45 °C

## SAFETY DATA SHEET

### QUIK FILL 32 FLOOR STRIPPER

#### Product AT USE DILUTION

Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. Use only with adequate ventilation. Wash hands thoroughly after handling. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).

Conditions for safe storage : Do not store near acids. Keep out of reach of children. Store in suitable labeled containers.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

##### Product AS SOLD

##### Ingredients with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
2-butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m <sup>3</sup>	NIOSH REL
		TWA	50 ppm 240 mg/m <sup>3</sup>	OSHA Z1
monoethanolamine	141-43-5	TWA	3 ppm	ACGIH
		STEL	6 ppm	ACGIH
		TWA	3 ppm 8 mg/m <sup>3</sup>	NIOSH REL
		STEL	6 ppm 15 mg/m <sup>3</sup>	NIOSH REL
		TWA	3 ppm 6 mg/m <sup>3</sup>	OSHA Z1
sodium hydroxide	1310-73-2	Ceiling	2 mg/m <sup>3</sup>	ACGIH
		Ceiling	2 mg/m <sup>3</sup>	NIOSH REL
		TWA	2 mg/m <sup>3</sup>	OSHA Z1

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

##### Personal protective equipment

Eye protection : Wear eye protection and/or face protection.

Hand protection : Wear the following personal protective equipment:  
Standard glove type.  
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin protection : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing

Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

## SAFETY DATA SHEET

### QUIK FILL 32 FLOOR STRIPPER

#### Product AT USE DILUTION

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

#### Personal protective equipment

Eye protection : Wear eye protection and/or face protection.

Hand protection : Wear the following personal protective equipment:  
Standard glove type.  
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin protection : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing

Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

	Product AS SOLD	Product AT USE DILUTION
Appearance	: liquid	liquid
Color	: red	light pink
Odor	: pungent	pungent
pH	: 13.25, (100 %)	12.7 - 13.4
Flash point	: Not applicable	
Odor Threshold	: No data available	
Melting point/freezing point	: No data available	
Initial boiling point and boiling range	: 100 °C	
Evaporation rate	: No data available	
Flammability (solid, gas)	: Not applicable	
Upper explosion limit	: No data available	
Lower explosion limit	: No data available	
Vapor pressure	: No data available	
Relative vapor density	: No data available	
Relative density	: 1.05	
Water solubility	: No data available	
Solubility in other solvents	: No data available	
Partition coefficient: n-octanol/water	: No data available	
Autoignition temperature	: No data available	
Thermal decomposition	: No data available	
Viscosity, kinematic	: No data available	
Explosive properties	: No data available	

## SAFETY DATA SHEET

### QUIK FILL 32 FLOOR STRIPPER

Oxidizing properties : No data available  
Molecular weight : No data available  
VOC : No data available

#### SECTION 10. STABILITY AND REACTIVITY

##### Product AS SOLD

Reactivity : No dangerous reaction known under conditions of normal use.  
Chemical stability : Stable under normal conditions.  
Possibility of hazardous reactions : No dangerous reaction known under conditions of normal use.  
Conditions to avoid : None known.  
Incompatible materials : Acids  
Metals  
Hazardous decomposition products : In case of fire hazardous decomposition products may be produced such as:  
Carbon oxides  
Sulfur oxides  
Nitrogen oxides (NOx)

#### SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

##### Potential Health Effects

##### Product AS SOLD

Eyes : Causes serious eye damage.  
Skin : Causes severe skin burns.  
Ingestion : Causes digestive tract burns.  
Inhalation : May cause respiratory tract irritation. Harmful if inhaled. May cause nose, throat, and lung irritation.  
Chronic Exposure : Health injuries are not known or expected under normal use.

##### Product AT USE DILUTION

Eyes : Causes serious eye damage.  
Skin : Causes severe skin burns.  
Ingestion : Causes digestive tract burns.  
Inhalation : May cause nose, throat, and lung irritation.  
Chronic Exposure : Health injuries are not known or expected under normal use.

##### Experience with human exposure

##### Product AS SOLD

## SAFETY DATA SHEET

### QUIK FILL 32 FLOOR STRIPPER

Eye contact	: Redness, Pain, Corrosion
Skin contact	: Redness, Pain, Corrosion
Ingestion	: Corrosion, Abdominal pain
Inhalation	: Respiratory irritation, Cough

#### Product AT USE DILUTION

Eye contact	: Redness, Pain, Corrosion
Skin contact	: Redness, Pain, Corrosion
Ingestion	: Corrosion, Abdominal pain
Inhalation	: Respiratory irritation, Cough

#### Toxicity

##### Product AS SOLD

##### Product

Acute oral toxicity	: Acute toxicity estimate : 3,695 mg/kg
Acute inhalation toxicity	: Acute toxicity estimate : > 1 mg/l Test atmosphere: dust/mist
Acute dermal toxicity	: Acute toxicity estimate : > 5,000 mg/kg
Skin corrosion/irritation	: No data available
Serious eye damage/eye irritation	: No data available
Respiratory or skin sensitization	: No data available
Carcinogenicity	: No data available
Reproductive effects	: No data available
Germ cell mutagenicity	: No data available
Teratogenicity	: No data available
STOT-single exposure	: No data available
STOT-repeated exposure	: No data available
Aspiration toxicity	: No data available

### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

##### Product AS SOLD

Environmental Effects	: Harmful to aquatic life.
-----------------------	----------------------------

#### Product AT USE DILUTION

Environmental Effects	: This product has no known ecotoxicological effects.
-----------------------	---

##### Product AS SOLD

##### Product

Toxicity to fish	: No data available
Toxicity to daphnia and other	: No data available



## SAFETY DATA SHEET

### QUIK FILL 32 FLOOR STRIPPER

aquatic invertebrates

Toxicity to algae : No data available

#### Components

Toxicity to fish : 2-butoxyethanol  
96 h LC50 Fish: > 100 mg/l

alcohols, c12-16, ethoxylated >5EO  
LC50: 1.5 mg/l

#### Components

Toxicity to daphnia and other aquatic invertebrates : Monoethanolamine  
48 h LC50 Daphnia magna (Water flea): 65 mg/l

Sodium hydroxide  
48 h EC50: 40 mg/l

#### Components

Toxicity to algae : 2-butoxyethanol  
72 h EC50 Aquatic Plant: 911 mg/l

Sodium Xylenesulfonate  
96 h EC50: 230 mg/l

#### Persistence and degradability

##### Product AT USE DILUTION

Poorly biodegradable

#### Bioaccumulative potential

No data available

#### Mobility in soil

No data available

#### Other adverse effects

No data available

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Product AS SOLD

Disposal methods : Do not contaminate ponds, waterways or ditches with chemical or used container. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.

Disposal considerations : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

RCRA - Resource Conservation and Recovery Authorization Act Hazardous waste : D002 (Corrosive)

##### Product AT USE DILUTION

## SAFETY DATA SHEET

### QUIK FILL 32 FLOOR STRIPPER

Disposal methods	: Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.
Disposal considerations	: Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

### SECTION 14. TRANSPORT INFORMATION

#### Product AS SOLD

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

#### Land transport (DOT)

UN number	: 1719
Description of the goods	: Caustic alkali liquids, n.o.s. (sodium hydroxide, monoethanolamine)
Class	: 8
Packing group	: II
Environmentally hazardous	: no

#### Sea transport (IMDG/IMO)

UN number	: 1719
Proper shipping name	: CAUSTIC ALKALI LIQUID, N.O.S. (sodium hydroxide, monoethanolamine)
Class	: 8
Packing group	: II
Marine pollutant	: no

### SECTION 15. REGULATORY INFORMATION

#### Product AS SOLD

#### EPCRA - Emergency Planning and Community Right-to-Know

#### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Sodium hydroxide	1310-73-2	1000	19980

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

<b>SARA 311/312 Hazards</b>	: Acute toxicity (any route of exposure) Skin corrosion or irritation Serious eye damage or eye irritation Specific target organ toxicity (single or repeated exposure)
-----------------------------	--

<b>SARA 302</b>	: This material does not contain any components with a section 302 EHS TPQ.
-----------------	---

## SAFETY DATA SHEET

### QUIK FILL 32 FLOOR STRIPPER

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:  
2-butoxyethanol 111-76-2 20 - 30 %

#### California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

#### California Cleaning Product Right to Know Act of 2017 (SB 258)

This regulation applies to this product.

Chemical Name	CAS-No.	Function	List(s)
water	7732-18-5	Diluent	Not Applicable
2-butoxyethanol	111-76-2	Solvent	20
Monoethanolamine	141-43-5	Cleaning Agent	Not Applicable
Sodium hydroxide	1310-73-2	Cleaning Agent	20
Sodium Xylenesulfonate	1300-72-7	Stabilizer	Not Applicable
alcohols, c12-16, ethoxylated >5EO	68551-12-2	Cleaning Agent	Not Applicable
Chelating agent	Withheld	Cleaning Agent	Not Applicable
Polycyclic organic acid	Withheld	Dye	Not Applicable
Colorant	Withheld	Dye	Not Applicable
Colorant	Withheld	Dye	Not Applicable

\*refer to ecolab.com/sds for electronic links to designated lists

**The ingredients of this product are reported in the following inventories:**

**Switzerland. New notified substances and declared preparations :**  
not determined

**United States TSCA Inventory :**  
All substances listed as active on the TSCA inventory

**Canadian Domestic Substances List (DSL) :**  
All components of this product are on the Canadian DSL

**Australia. Australian Industrial Chemicals Introduction Scheme (AICIS) :**  
On the inventory, or in compliance with the inventory

**New Zealand. Inventory of Chemical Substances :**  
not determined

**Japan. ENCS - Existing and New Chemical Substances Inventory :**  
not determined

**Korea. Korean Existing Chemicals Inventory (KECI) :**  
On the inventory, or in compliance with the inventory

**Philippines Inventory of Chemicals and Chemical Substances (PICCS) :**  
On the inventory, or in compliance with the inventory

**China. Inventory of Existing Chemical Substances in China (IECSC) :**  
On the inventory, or in compliance with the inventory

**Taiwan Chemical Substance Inventory (TCSI) :**  
not determined


# SAFETY DATA SHEET

## QUIK FILL 32 FLOOR STRIPPER

### SECTION 16. OTHER INFORMATION

#### Product AS SOLD

##### NFPA:




##### HMIS III:

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

#### Product AT USE DILUTION

##### NFPA:



##### HMIS III:

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

Issuing date : 12/16/2021  
Version : 1.3  
Prepared by : Regulatory Affairs

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.