

**Oasis Pro 62 Premium****Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier**

Product name : Oasis Pro 62 Premium

Product code : 113121E

Use of the
Substance/Mixture : Sanitary cleaner

Substance type: : Mixture

For professional users only.

Product dilution information : 1.0 % - 3.0 %

1.2 Relevant identified uses of the substance or mixture and uses advised againstIdentified uses : General purpose cleaner. Spray and wipe manual process
Sanitary cleaner. Spray and wipe manual processRecommended restrictions
on use : Reserved for industrial and professional use.**1.3 Details of the supplier of the safety data sheet**Company : Ecolab Ltd.
PO Box 11; Winnington Avenue
Northwich, Cheshire, United Kingdom CW8 4DX
+353 (0)1 276 3500
ccs@ecolab.com**1.4 Emergency telephone number**Emergency telephone
number : +353 (0)1 276 3500Poison Information Centre
telephone number : For medical professionals only:
+353 (0)1 837 9964 (8am-10pm)

Date of Compilation/Revision : 22.02.2017

Version : 1.1

Section: 2. HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)****Product AS SOLD**

Skin corrosion, Category 1A H314

Serious eye damage, Category 1 H318

Specific target organ toxicity - single exposure, Category 3, H335

Oasis Pro 62 Premium

Respiratory system
Chronic aquatic toxicity, Category 3 H412
The classification of this product is based only on its extreme pH value (in accordance with current European legislation).

Product AT USE DILUTION

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Product AS SOLD

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H314 Causes severe skin burns and eye damage.
H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH071 Corrosive to the respiratory tract.

Precautionary Statements : **Prevention:**
P273 Avoid release to the environment.
P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label:

Isotridecanol, ethoxylated
monoethanolamine

Product AT USE DILUTION

Not a hazardous substance or mixture.

Additional Labelling:

Product AS SOLD

Special labelling of certain mixtures : Contains: hexyl salicylate May produce an allergic reaction.

2.3 Other hazards

Product AS SOLD

None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

Oasis Pro 62 Premium

3.2 Mixtures

Product AS SOLD

Hazardous components

Chemical Name	CAS-No. EC-No. REACH No.	ClassificationREGULATION (EC) No 1272/2008	Concentration: [%]
Isotridecanol, ethoxylated	69011-36-5 500-241-6	Acute toxicity Category 4; H302 Skin irritation Category 2; H315 Serious eye damage Category 1; H318	>= 10 - < 20
fatty alcohol alkoxylate		Skin irritation Category 2; H315	>= 10 - < 20
monoethanolamine	141-43-5 205-483-3 01-2119486455-28	Acute toxicity Category 4; H302 Acute toxicity Category 4; H332 Acute toxicity Category 4; H312 Skin corrosion Category 1B; H314 Serious eye damage Category 1; H318	>= 5 - < 10
propan-2-ol	67-63-0 200-661-7 01-2119457558-25	Flammable liquids Category 2; H225 Eye irritation Category 2; H319 Specific target organ toxicity - single exposure Category 3; H336	>= 3 - < 5
alanine, n,n-bis(carboxymethyl)-, trisodium salt	164462-16-2 01-0000016977-53	Skin irritation Category 2; H315 Eye irritation Category 2; H319	>= 1 - < 2.5
Benzalkonium chloride	68424-85-1 270-325-2 01-2119965180-41	Acute toxicity Category 4; H302 Skin corrosion Category 1B; H314 Serious eye damage Category 1; H318 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 1; H410	>= 0.5 - < 1
hexyl salicylate	6259-76-3 228-408-6 01-2119638275-36	Skin sensitization Sub-category 1A; H317 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 1; H410	< 0.1

Product AT USE DILUTION

Hazardous components

Chemical Name	CAS-No. EC-No. REACH No.	ClassificationREGULATION (EC) No 1272/2008	Concentration: [%]
Benzalkonium chloride	68424-85-1 270-325-2 01-2119965180-41	Acute toxicityCategory 4; H302 Skin corrosionCategory 1B; H314 Serious eye damageCategory 1; H318 Acute aquatic toxicityCategory 1; H400 Chronic aquatic toxicityCategory 1; H410	< 0.1
Substances with a workplace exposure limit :			
monoethanolamine	141-43-5 205-483-3 01-2119486455-28	Acute toxicityCategory 4; H302 Acute toxicityCategory 4; H332 Acute toxicityCategory 4; H312 Skin corrosionCategory 1B; H314 Serious eye damageCategory 1; H318	>= 0.25 - < 0.5
propan-2-ol	67-63-0 200-661-7	Flammable liquidsCategory 2; H225 Eye irritationCategory 2; H319	>= 0.1 - < 0.25

Oasis Pro 62 Premium

	01-2119457558-25	Specific target organ toxicity - single exposure Category 3; H336	
--	------------------	---	--

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section: 4. FIRST AID MEASURES**4.1 Description of first aid measures****Product AS SOLD**

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
- If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

Product AT USE DILUTION

- In case of eye contact : Rinse with plenty of water.
- In case of skin contact : Rinse with plenty of water.
- If swallowed : Rinse mouth. Get medical attention if symptoms occur.
- If inhaled : Get medical attention if symptoms occur.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

Section: 5. FIREFIGHTING MEASURES**Product AS SOLD****5.1 Extinguishing media**

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Fire Hazard
Keep away from heat and sources of ignition.

Oasis Pro 62 Premium

Flash back possible over considerable distance.
Beware of vapours accumulating to form explosive concentrations.
Vapours can accumulate in low areas.

Hazardous combustion products : Decomposition products may include the following materials:
Carbon oxides
nitrogen oxides (NOx)
Sulphur oxides
Oxides of phosphorus

5.3 Advice for firefighters

Special protective equipment for firefighters : Use personal protective equipment.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Product AS SOLD

Advice for non-emergency personnel : Ensure adequate ventilation. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

Product AT USE DILUTION

Advice for non-emergency personnel : Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

6.2 Environmental precautions

Product AS SOLD

Environmental precautions : Do not allow contact with soil, surface or ground water.

Product AT USE DILUTION

Environmental precautions : No special environmental precautions required.

6.3 Methods and materials for containment and cleaning up

Product AS SOLD

Methods for cleaning up : Eliminate all ignition sources if safe to do so. Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with

Oasis Pro 62 Premium

water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

Product AT USE DILUTION

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

6.4 Reference to other sections

See Section 1 for emergency contact information.

For personal protection see section 8.

See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Product AS SOLD

Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Do not breathe dust/fume/gas/mist/vapours/spray. Use only with adequate ventilation. Keep away from fire, sparks and heated surfaces. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Wash hands thoroughly after handling.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Product AT USE DILUTION

Advice on safe handling : Wash hands after handling. For personal protection see section 8.

Hygiene measures : Wash hands before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

Product AS SOLD

Requirements for storage areas and containers : Keep away from heat and sources of ignition. Keep away from oxidizing agents. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

Storage temperature : -5 °C to 40 °C

Product AT USE DILUTION

Requirements for storage areas and containers : Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

7.3 Specific end uses

Product AS SOLD

Oasis Pro 62 Premium

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Product AS SOLD

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
monoethanolamine	141-43-5	OELV - 15 min (STEL)	3 ppm 7.6 mg/m ³	IR_OEL
Further information	Sk	Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body		
	IOEL V	Indicative Occupational Exposure Limit Value		
		OELV - 8 hrs (TWA)	1 ppm 2.5 mg/m ³	IR_OEL
Further information	Sk	Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body		
	IOEL V	Indicative Occupational Exposure Limit Value		
propan-2-ol	67-63-0	OELV - 8 hrs (TWA)	200 ppm	IR_OEL
Further information	Sk	Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body		
		OELV - 15 min (STEL)	400 ppm	IR_OEL
Further information	Sk	Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body		

DNEL

propan-2-ol	:	End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 888 mg/cm ²
		End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 500 mg/m ³
		End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 319 mg/cm ²
		End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 89 mg/m ³
		End Use: Consumers Exposure routes: Ingestion Potential health effects: Long-term systemic effects Value: 26 ppm

PNEC

propan-2-ol	:	Fresh water Value: 140.9 mg/l
-------------	---	----------------------------------

Oasis Pro 62 Premium

	Marine water Value: 140.9 mg/l	
	Intermittent use/release Value: 140.9 mg/l	
	Fresh water Value: 552 mg/kg	
	Marine sediment Value: 552 mg/kg	
	Soil Value: 28 mg/kg	
	Sewage treatment plant Value: 2251 mg/l	
	Oral Value: 160 mg/kg	

8.2 Exposure controls

Product AS SOLD

Appropriate engineering controls

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

Individual protection measures

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Eye/face protection (EN 166) : Safety goggles
Face-shield

Hand protection (EN 374) : Recommended preventive skin protection
Gloves
Nitrile rubber
butyl-rubber
Breakthrough time: 1 – 4 hours
Minimum thickness for butyl-rubber 0.7 mm for nitrile rubber 0.4 mm or equivalent (please refer to the gloves manufacturer/distributor for advise).
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin and body protection (EN 14605) : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing

Respiratory protection (EN 143, 14387) : None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU

Oasis Pro 62 Premium

requirements(89/656/EEC, 89/686/EEC), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

Product AT USE DILUTION**Appropriate engineering controls**

Engineering measures : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands before breaks and immediately after handling the product.

Eye/face protection (EN 166) : No special protective equipment required.

Hand protection (EN 374) : No special protective equipment required.

Skin and body protection (EN 14605) : No special protective equipment required.

Respiratory protection (EN 143, 14387) : None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, 89/686/EEC), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

Environmental exposure controls

General advice : Consider the provision of containment around storage vessels.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES**9.1 Information on basic physical and chemical properties**

	Product AS SOLD	Product AT USE DILUTION
Appearance	: liquid	liquid
Colour	: orange	light orange
Odour	: slight	pleasant
pH	: 11.4 - 12.4, 100 %	10.4 - 10.9
Flash point	: 45 °C closed cup, Does not sustain combustion.	
Odour Threshold	: Not applicable and/or not determined for the mixture	
Melting point/freezing point	: Not applicable and/or not determined for the mixture	
Initial boiling point and boiling range	: Not applicable and/or not determined for the mixture	
Evaporation rate	: Not applicable and/or not determined for the mixture	
Flammability (solid, gas)	: Not applicable and/or not determined for the mixture	

Oasis Pro 62 Premium

Upper explosion limit	: Not applicable and/or not determined for the mixture
Lower explosion limit	: Not applicable and/or not determined for the mixture
Vapour pressure	: Not applicable and/or not determined for the mixture
Relative vapour density	: Not applicable and/or not determined for the mixture
Relative density	: 1.015 - 1.02
Water solubility	: soluble
Solubility in other solvents	: Not applicable and/or not determined for the mixture
Partition coefficient: n-octanol/water	: Not applicable and/or not determined for the mixture
Auto-ignition temperature	: Not applicable and/or not determined for the mixture
Thermal decomposition	: Not applicable and/or not determined for the mixture
Viscosity, kinematic	: Not applicable and/or not determined for the mixture
Explosive properties	: Not applicable and/or not determined for the mixture
Oxidizing properties	: The substance or mixture is not classified as oxidizing.

9.2 Other information

Not applicable and/or not determined for the mixture

Section: 10. STABILITY AND REACTIVITY

Product AS SOLD

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Acids

10.6 Hazardous decomposition products

Decomposition products may include the following materials:

Carbon oxides
nitrogen oxides (NO_x)
Sulphur oxides
Oxides of phosphorus

Section: 11. TOXICOLOGICAL INFORMATION

Oasis Pro 62 Premium

11.1 Information on toxicological effects

Product AS SOLD

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Product

Acute oral toxicity : Acute toxicity estimate : > 2,000 mg/kg

Acute inhalation toxicity : 4 h Acute toxicity estimate : > 5 mg/l

Acute dermal toxicity : Acute toxicity estimate : > 2,000 mg/kg

Skin corrosion/irritation : There is no data available for this product.

Serious eye damage/eye irritation : There is no data available for this product.

Respiratory or skin sensitization : There is no data available for this product.

Carcinogenicity : There is no data available for this product.

Reproductive effects : There is no data available for this product.

Germ cell mutagenicity : There is no data available for this product.

Teratogenicity : There is no data available for this product.

STOT - single exposure : There is no data available for this product.

STOT - repeated exposure : There is no data available for this product.

Aspiration toxicity : There is no data available for this product.

Components

Acute oral toxicity : Isotridecanol, ethoxylated
LD50 rat: 1,250 mg/kg

monoethanolamine
LD50 rat: 1,089 mg/kg

propan-2-ol
LD50 rat: 5,840 mg/kg

alanine, n,n-bis(carboxymethyl)-, trisodium salt
LD50 rat: > 2,000 mg/kg

Benzalkonium chloride
LD50 rat: 344 mg/kg

hexyl salicylate
LD50 rat: > 5,000 mg/kg

Components

Oasis Pro 62 Premium

Acute inhalation toxicity : monoethanolamine
4 h LC50 rat: > 1.6 mg/l

propan-2-ol
4 h LC50 rat: > 30 mg/l

Components

Acute dermal toxicity : Isotridecanol, ethoxylated
LD50 : 2,150 mg/kg

monoethanolamine
LD50 rabbit: 1,025 mg/kg

propan-2-ol
LD50 rabbit: 12,870 mg/kg

alanine, n,n-bis(carboxymethyl)-, trisodium salt
LD50 rat: > 4,000 mg/kg

Benzalkonium chloride
LD50 rabbit: 3,340 mg/kg

hexyl salicylate
LD50 rabbit: > 5,000 mg/kg

Potential Health Effects

Product AS SOLD

Eyes : Causes serious eye damage.

Skin : Causes severe skin burns.

Ingestion : Causes digestive tract burns.

Inhalation : May cause nose, throat, and lung irritation.

Chronic Exposure : Health injuries are not known or expected under normal use.

Product AT USE DILUTION

Eyes : Health injuries are not known or expected under normal use.

Skin : Health injuries are not known or expected under normal use.

Ingestion : Health injuries are not known or expected under normal use.

Inhalation : Health injuries are not known or expected under normal use.

Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Product AS SOLD

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Pain, Corrosion

Ingestion : Corrosion, Abdominal pain

Inhalation : Respiratory irritation, Cough

Oasis Pro 62 Premium

Product AT USE DILUTION

Eye contact	: No symptoms known or expected.
Skin contact	: No symptoms known or expected.
Ingestion	: No symptoms known or expected.
Inhalation	: No symptoms known or expected.

Section: 12. ECOLOGICAL INFORMATION

Product AS SOLD

12.1 Ecotoxicity

Environmental Effects	: Harmful to aquatic life with long lasting effects.
-----------------------	--

Product

Toxicity to fish	: no data available
Toxicity to daphnia and other aquatic invertebrates	: no data available
Toxicity to algae	: no data available

Components

Toxicity to fish	: Isotridecanol, ethoxylated LC50: 5.33 mg/l
	propan-2-ol 96 h LC50 Pimephales promelas (fathead minnow): 9,640 mg/l
	alanine, n,n-bis(carboxymethyl)-, trisodium salt 96 h LC50 Fish: > 200 mg/l
	hexyl salicylate 96 h LC50 Danio rerio (zebra fish): 1.34 mg/l

Components

Toxicity to daphnia and other aquatic invertebrates	: monoethanolamine 48 h EC50 Daphnia: 65 mg/l
	propan-2-ol LC50 Daphnia magna (Water flea): > 10,000 mg/l
	Benzalkonium chloride 48 h EC50 Daphnia magna (Water flea): 0.016 mg/l
	hexyl salicylate 48 h EC50 Daphnia magna (Water flea): 0.357 mg/l

Components

Toxicity to algae	: hexyl salicylate 72 h EC50 Desmodesmus subspicatus (green algae): 0.28 mg/l
-------------------	--

12.2 Persistence and degradability

Oasis Pro 62 Premium

Product

Biodegradability : The surfactants contained in the product are biodegradable according to the requirements of the detergent regulation 648/2004/EC

Components

Biodegradability : Isotridecanol, ethoxylated
Result: Readily biodegradable.

fatty alcohol alkoxylate
Result: Readily biodegradable.

monoethanolamine
Result: Readily biodegradable.

propan-2-ol
Result: Readily biodegradable.

alanine, n,n-bis(carboxymethyl)-, trisodium salt
Result: Readily biodegradable.

Benzalkonium chloride
Result: Biodegradable

hexyl salicylate
Result: Readily biodegradable.

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods

Product AS SOLD

Product : The product should not be allowed to enter drains, water courses

Oasis Pro 62 Premium

or the soil. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.

Contaminated packaging : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

Guidance for Waste Code selection : Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations.

Product AT USE DILUTION

Product : Diluted product can be flushed to sanitary sewer.

Contaminated packaging : Dispose of in accordance with local, state, and federal regulations.

Section: 14. TRANSPORT INFORMATION

Product AS SOLD

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

14.1 UN number : 2491
 14.2 UN proper shipping name : ETHANOLAMINE, SOLUTION
 14.3 Transport hazard class(es) : 8
 14.4 Packing group : III
 14.5 Environmental hazards : No
 14.6 Special precautions for user : None

Air transport (IATA)

14.1 UN number : 2491
 14.2 UN proper shipping name : Ethanolamine solution
 14.3 Transport hazard class(es) : 8
 14.4 Packing group : III
 14.5 Environmental hazards : No
 14.6 Special precautions for user : None

Sea transport (IMDG/IMO)

14.1 UN number : 2491
 14.2 UN proper shipping name : ETHANOLAMINE SOLUTION

Oasis Pro 62 Premium

14.3 Transport hazard : 8
 class(es)
 14.4 Packing group : III
 14.5 Environmental hazards : No
 14.6 Special precautions for user : None
 14.7 Transport in bulk : Not applicable.
 according to Annex II of
 MARPOL 73/78 and the IBC
 Code

Section: 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Detergents : 15 % or over but less than 30 %: Non-ionic surfactants
 Regulation EC 648/2004 less than 5 %: Anionic surfactants, Cationic surfactants
 Other constituents: Perfumes

National Regulations

Take note of Dir 94/33/EC on the protection of young people at work.

Other regulations : Safety, Health and Welfare at Work Act, 2005
 European Communities (Classification, Packaging, Labelling and
 Notification of Dangerous Preparations) Regulations 1995. (S.I.
 272 of 1995) as amended

15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

Section: 16. OTHER INFORMATION

Procedure used to derive the classification according to REGULATION (EC) No 1272/2008

Classification	Justification
Skin corrosion 1A, H314	Calculation method
Serious eye damage 1, H318	Calculation method
Specific target organ toxicity - single exposure 3, H335	Calculation method
Chronic aquatic toxicity 3, H412	Calculation method

Full text of H-Statements

H225 Highly flammable liquid and vapour.
 H302 Harmful if swallowed.
 H312 Harmful in contact with skin.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H336 May cause drowsiness or dizziness.
 H400 Very toxic to aquatic life.

Oasis Pro 62 Premium

H410

Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

ANNEX: EXPOSURE SCENARIOS**DPD+ Substances:**

The following substances are the lead substances that contribute to the mixture Exposure Scenario according to the DPD+ Rule:

Oasis Pro 62 Premium

Route	Substance	CAS-No.	EINECS-No.
Ingestion	monoethanolamine	141-43-5	205-483-3
Inhalation	propan-2-ol	67-63-0	200-661-7
Dermal	monoethanolamine	141-43-5	205-483-3
Eyes	Isotridecanol, ethoxylated monoethanolamine	69011-36-5 141-43-5	500-241-6 205-483-3
aquatic environment	Benzalkonium chloride	68424-85-1	270-325-2

Physical properties DPD+ Substances:

Substance	Vapour pressure	Water solubility	Pow	Molar Mass
monoethanolamine	0.488 hPa	> 1,000 g/l	0.117	
propan-2-ol	6,020 Pa			60.10 g/mol
monoethanolamine	0.488 hPa	> 1,000 g/l	0.117	
Benzalkonium chloride	< 0.0000001 hPa	403 g/l		

To calculate if your downstream Operating Conditions and Risk management Measures are safe, please calculate your risk factor at the website below:

www.ecetoc.org/tra

Short title of Exposure Scenario : **General purpose cleaner. Spray and wipe manual process**

Use descriptors

Main User Groups : Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Sectors of end-use : **SU22:** Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Process categories : **PROC10:** Roller application or brushing
PROC11: Non industrial spraying
PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities

Product categories : **PC35:** Washing and cleaning products (including solvent based products)

Environmental Release Categories : **ERC8a:** Wide dispersive indoor use of processing aids in open systems

Oasis Pro 62 Premium

Short title of Exposure Scenario : **Sanitary cleaner. Spray and wipe manual process**

Use descriptors

Main User Groups : Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Sectors of end-use : **SU22:** Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Process categories : **PROC10:** Roller application or brushing
PROC11: Non industrial spraying
PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities

Product categories : **PC35:** Washing and cleaning products (including solvent based products)

Environmental Release Categories : **ERC8a:** Wide dispersive indoor use of processing aids in open systems