

Derclean Spray Quick**Section: 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : Derclean Spray Quick

Other means of identification : Not applicable.

Recommended use : Disinfectant

Restrictions on use : Reserved for industrial and professional use.

Product dilution information : No dilution information provided.

Company : Ecolab (PTY) LTD
1 Ampere Street
Chloorkop, Johannesburg South Africa 1620
+2711578 5000

Nalco Angola Limitada
Rua Tipografia Mama Tita, 22B Predio Soliel
Luanda, Angola
Tel: 244-222-395120
Fax: 244-222-394855

Ecolab Kenya
Tulip House, Mombasa Road
Next to Sameer Business Park
PO Box 63497-00619
Nairobi, Kenya
+254-20-354-0624/189/191
kenya.info@ecolab.com

Emergency telephone number : +32-(0)3-575-5555 Trans-European

Issuing date : 28.09.2021

Section: 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 2

Eye irritation : Category 2A

Specific target organ toxicity - single exposure : Category 3 (Central Nervous System)

Acute aquatic toxicity : Category 3

GHS Label element

Hazard pictograms :



Signal Word : Danger

Hazard Statements : Highly flammable liquid and vapour.
Causes serious eye irritation.

SAFETY DATA SHEET

Derclean Spray Quick

May cause drowsiness or dizziness.
Harmful to aquatic life.

Precautionary Statements : **Prevention:**
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed. Avoid breathing mist or vapours. Avoid release to the environment. Wear protective gloves/ eye protection/ face protection.
Response:
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. If eye irritation persists: Get medical advice/ attention. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:
Store in a well-ventilated place. Keep container tightly closed.

Other hazards : None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

Pure substance/mixture : Mixture

Chemical Name	CAS-No.	Concentration: (%)
ethanol	64-17-5	30 - 60
Isopropyl Alcohol	67-63-0	1 - 5
benzalkonium chloride	68424-85-1	0,1 - 1

Section: 4. FIRST AID MEASURES

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.

In case of skin contact : Rinse with plenty of water.

If swallowed : Rinse mouth. Get medical attention if symptoms occur.

If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Notes to physician : Treat symptomatically.

Most important symptoms and effects, both acute and delayed : See Section 11 for more detailed information on health effects and symptoms.

Section: 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : High volume water jet

SAFETY DATA SHEET

Derclean Spray Quick

- Specific hazards during firefighting : Fire Hazard
Keep away from heat and sources of ignition.
Flash back possible over considerable distance.
Beware of vapours accumulating to form explosive concentrations.
Vapours can accumulate in low areas.
- Hazardous combustion products : Decomposition products may include the following materials:
Carbon oxides
- Special protective equipment for firefighters : Use personal protective equipment.
- Specific extinguishing methods : Use water spray to cool unopened containers. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Section: 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed.
- Environmental precautions : Do not allow contact with soil, surface or ground water.
- Methods and materials for containment and cleaning up : Eliminate all ignition sources if safe to do so. Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

Section: 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray. Use only with adequate ventilation. Keep away from fire, sparks and heated surfaces. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Wash hands thoroughly after handling. Open drum carefully as content may be under pressure. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).
- Conditions for safe storage : Keep away from heat and sources of ignition. Keep in a cool, well-ventilated place. Keep away from oxidizing agents. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.
- Storage temperature : 5 °C to 25 °C

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis

SAFETY DATA SHEET

Derclean Spray Quick

ethanol	64-17-5	TWA OEL-RL	1.000 ppm 1.900 mg/m ³	ZA OEL
ethanol	64-17-5	TWA	1.000 ppm 1.900 mg/m ³	KE OEL
ethanol	64-17-5	TWA	1.000 ppm 1.900 mg/m ³	NIOSH REL
		TWA	1.000 ppm 1.900 mg/m ³	OSHA Z1
Isopropyl Alcohol	67-63-0	STEL OEL-RL	500 ppm 1.225 mg/m ³	ZA OEL
		TWA OEL-RL	400 ppm 960 mg/m ³	ZA OEL
Isopropyl Alcohol	67-63-0	TWA	400 ppm 980 mg/m ³	KE OEL
		STEL	500 ppm 1.225 mg/m ³	KE OEL
Isopropyl Alcohol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m ³	NIOSH REL
		STEL	500 ppm 1.225 mg/m ³	NIOSH REL
		TWA	400 ppm 980 mg/m ³	OSHA Z1

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

Personal protective equipment

Eye protection : Safety goggles
Face-shield

Hand protection : Recommended preventive skin protection
Gloves
Nitrile rubber
butyl-rubber
Breakthrough time: 1 – 4 hours
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin protection : No special protective equipment required.

Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Wash face, hands and any exposed skin thoroughly after handling.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid
Colour : clear, colourless
Odour : characteristic

SAFETY DATA SHEET

Derclean Spray Quick

pH	: 5,0 - 6,5, (100 %)
Flash point	: 21 °C closed cup
Odour Threshold	: no data available
Melting point/freezing point	: no data available
Initial boiling point and boiling range	: > 35 °C
Evaporation rate	: no data available
Flammability (solid, gas)	: Not applicable.
Upper explosion limit	: no data available
Lower explosion limit	: no data available
Vapour pressure	: no data available
Relative vapour density	: no data available
Relative density	: 0,88 - 0,92
Water solubility	: soluble
Solubility in other solvents	: no data available
Partition coefficient: n-octanol/water	: no data available
Auto-ignition temperature	: no data available
Thermal decomposition	: no data available
Viscosity, kinematic	: no data available
Explosive properties	: no data available
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Molecular weight	: no data available
VOC	: no data available

Section: 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reaction known under conditions of normal use.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: None known.
Hazardous decomposition products	: In case of fire hazardous decomposition products may be produced such as: Carbon oxides

Section: 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Potential Health Effects

SAFETY DATA SHEET

Derclean Spray Quick

Eyes	: Causes serious eye irritation.
Skin	: Health injuries are not known or expected under normal use.
Ingestion	: Health injuries are not known or expected under normal use.
Inhalation	: Inhalation may cause central nervous system effects.
Chronic Exposure	: Health injuries are not known or expected under normal use.

Experience with human exposure

Eye contact	: Redness, Pain, Irritation
Skin contact	: No symptoms known or expected.
Ingestion	: No symptoms known or expected.
Inhalation	: Dizziness, Drowsiness

Toxicity

Product

Acute oral toxicity	: no data available
Acute inhalation toxicity	: 4 h Acute toxicity estimate : > 40 mg/l Test atmosphere: vapour
Acute dermal toxicity	: no data available
Skin corrosion/irritation	: no data available
Serious eye damage/eye irritation	: no data available
Respiratory or skin sensitization	: no data available
Carcinogenicity	: no data available
Reproductive effects	: no data available
Germ cell mutagenicity	: no data available
Teratogenicity	: no data available
STOT - single exposure	: no data available
STOT - repeated exposure	: no data available
Aspiration toxicity	: no data available

Components

Acute oral toxicity	: ethanol LD50 rat: 10.470 mg/kg
	Isopropyl Alcohol LD50 rat: 5.840 mg/kg
	benzalkonium chloride LD50 rat: 344 mg/kg

Components

SAFETY DATA SHEET

Derclean Spray Quick

Acute dermal toxicity : ethanol
LD50 rabbit: 15.800 mg/kg

Isopropyl Alcohol
LD50 rabbit: 12.870 mg/kg

benzalkonium chloride
LD50 rabbit: 3.340 mg/kg

Section: 12. ECOLOGICAL INFORMATION

Toxicity

Environmental Effects : Harmful to aquatic life.

Product

Toxicity to fish : no data available

Toxicity to daphnia and other aquatic invertebrates : no data available

Toxicity to algae : no data available

Components

Toxicity to fish : ethanol
96 h LC50 Pimephales promelas (fathead minnow): > 100 mg/l

Isopropyl Alcohol
96 h LC50 Pimephales promelas (fathead minnow): 9.640 mg/l

Components

Toxicity to daphnia and other aquatic invertebrates : ethanol
48 h EC50 Aquatic Invertebrate: 857 mg/l

Isopropyl Alcohol
LC50 Daphnia magna (Water flea): > 10.000 mg/l

benzalkonium chloride
48 h EC50 Daphnia magna (Water flea): 0,016 mg/l

Persistence and degradability

Readily biodegradable.

Bioaccumulative potential

no data available

Mobility in soil

no data available

Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Disposal methods : The product should not be allowed to enter drains, water courses or the soil. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance

SAFETY DATA SHEET

Derclean Spray Quick

with local regulations. Dispose of wastes in an approved waste disposal facility.

Disposal considerations : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

Section: 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ZA DG)

UN number : 1170
Description of the goods : ETHANOL SOLUTION
Class : 3
Packing group : II
Environmentally hazardous : No

Air transport (IATA)

UN number : 1170
Proper shipping name : Ethanol solution
Class : 3
Packing group : II
Environmentally hazardous : No

Sea transport (IMDG/IMO)

UN number : 1170
Proper shipping name : ETHANOL SOLUTION
Class : 3
Packing group : II
Marine pollutant : No

Section: 15. REGULATORY INFORMATION

The components of this product are reported in the following inventories:

United States TSCA Inventory :

All substances listed as active on the TSCA inventory

Canadian Domestic Substances List (DSL) :

All components of this product are on the Canadian DSL.

Australia. Australian Industrial Chemicals Introduction Scheme (AICIS) :

On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand :
not determined

Japan. ENCS - Existing and New Chemical Substances Inventory :

On the inventory, or in compliance with the inventory

Korea. Korean Existing Chemicals Inventory (KECI) :

On the inventory, or in compliance with the inventory

SAFETY DATA SHEET

Derclean Spray Quick

Philippines Inventory of Chemicals and Chemical Substances (PICCS) :

On the inventory, or in compliance with the inventory

China Inventory of Existing Chemical Substances :

On the inventory, or in compliance with the inventory

Taiwan Chemical Substance Inventory :

On the inventory, or in compliance with the inventory

Section: 16. OTHER INFORMATION

Issuing date : 28.09.2021
version : 1.1
Prepared by : Regulatory Affairs

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.