

CHAMELEON® UPLIGHT

Comprehensive unit specification

Part No.	CHAUPL004 (014) / CHAUPL024 (034) / CHAUPL044 (054)
Description	Chameleon® Uplight White / Magnolia / Silver
Unit Class	I
Guarantee	3 years
Area of Coverage	40 m ²
Voltage Range	220-240V
Frequency Range	50-60Hz
IP Rating	20
Ambient operating temperatures	0 to +40°C *
Power Consumption	25W
Glueboard (Quantity/Reference)	1 / BOACHA850
Tube (Quantity/Reference/Description)	1 / TUB15W490 / 15 Watt 45cm long T8 Quantum® shatterproof
Mains Cable	Hard Wired / HO5RN-F
Unit Dimensions mm	H210 x W470 x D170
Carton Dimensions	H265 x W515 x D265 (supplied in quantity of 2)
Unit Weight	3,7 kg
Carton Weight	8,2 kg

* recommended operating temperature range, should they be exceeded in either way it may affect the working of the unit.

The Chameleon® Uplight is compliant with the essential requirements of the EMC Directive 2014/30/EU and the Low Voltage Directive 2006/95/EC. The unit is CE marked.

Additionally, the Chameleon® Uplight unit is compliant with the following International Standards:

- EN 55014-1:2001 Electromagnetic compatibility. Requirements for household appliances, electric tools and similar apparatus. Emission.
- EN 61000-3-2:2001 Electromagnetic compatibility (EMC) -- Part 3-2: Limits – Limits for harmonic current emissions.
- EN 61000-3-3:1995 Electromagnetic compatibility (EMC) - Part 3: Limits - Section 3: Limitation of voltage fluctuations and flicker in low-voltage supply systems for equipment with rated current <= 16 A.
- IEC 60335-1:2010 Safety of household and similar electrical appliances – Part 1: General requirements.
- IEC 60335-2-59:2002 Household and similar electrical appliances – Safety – Part 2-59: Particular requirements for insect killers.

Engineering and Technical Manager Signature:



Dated: 25th April 2018