

Section: 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : INSPEXX 150

Other means of identification : Not applicable.

Recommended use : Sanitizer

Restrictions on use : Reserved for industrial and professional use.

Product dilution information : No dilution information provided.

Company

Ecolab Gulf FZE
P.O. Box 17063
Jebel Ali Free Zone Area, Near Container Terminal 3 - North Zone
Dubai
UAE
00971 4 8014444 Customer Services, 00971 48146800 00971 4
8014000 Reception phone numbers

Nalco Egypt Trading
5th Settlement, South 90th St.
The Address Building No 67th – 1st floor
New Cairo, Cairo, Egypt11835
0020 2 25 37 1195,

Ecolab Maroc S.A.R.L.
Batiment, Lot. Mounir 1, Parc Industriel
Attawfik
Route 1029
Sidi Maarouf, Casablanca, Morocco
00212 22 58 25 30 - 35,

Emergency telephone : +32-(0)3-575-5555 Trans-European
number

Issuing date : 29.06.2021

Section: 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 4

Oxidizing liquids : Category 3

Acute toxicity (Oral) : Category 4

Skin corrosion : Category 1

Serious eye damage : Category 1

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

GHS Label element

SAFETY DATA SHEET

INSPEXX 150

Hazard pictograms



Signal Word

: Danger

Hazard Statements

: Combustible liquid
May intensify fire; oxidiser.
Harmful if swallowed.
Causes severe skin burns and eye damage.
May cause respiratory irritation.

Precautionary Statements

: **Prevention:**
Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep/Store away from clothing and other combustible materials. Take any precaution to avoid mixing with combustibles. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician. Wash contaminated clothing before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:
Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal:
Dispose of contents/ container to an approved waste disposal plant.

Other hazards

: Do not mix with bleach or other chlorinated products – will cause chlorine gas.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

Pure substance/mixture

: Mixture

Chemical Name

CAS-No.

Concentration: (%)

Acetic acid

64-19-7

10 - 30

Hydrogen peroxide

7722-84-1

10 - 30

Peracetic acid

79-21-0

10 - 30

Section: 4. FIRST AID MEASURES

In case of eye contact

: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

In case of skin contact

: Wash off immediately with plenty of water for at least 15 minutes. Use

SAFETY DATA SHEET

INSPEXX 150

a mild soap if available. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.

- | | |
|---|---|
| If swallowed | : Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately. |
| If inhaled | : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur. |
| Protection of first-aiders | : If potential for exposure exists refer to Section 8 for specific personal protective equipment. |
| Notes to physician | : Treat symptomatically. |
| Most important symptoms and effects, both acute and delayed | : See Section 11 for more detailed information on health effects and symptoms. |

Section: 5. FIREFIGHTING MEASURES

- | | |
|---|--|
| Suitable extinguishing media | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Unsuitable extinguishing media | : High volume water jet |
| Specific hazards during firefighting | : Fire Hazard
Keep away from heat and sources of ignition.
Flash back possible over considerable distance.
Special protective equipment for firefighters
Oxidizer. Contact with other material may cause fire.
Oxidizer; material is an oxidizer which may readily react with other materials, especially upon heating. |
| Hazardous combustion products | : Decomposition products may include the following materials:
Carbon oxides |
| Special protective equipment for firefighters | : In case of fire, wear a full face positive-pressure self contained breathing apparatus and protective suit. |
| Specific extinguishing methods | : Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes. |

Section: 6. ACCIDENTAL RELEASE MEASURES

- | | |
|---|--|
| Personal precautions, protective equipment and emergency procedures | : Ensure adequate ventilation. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8. |
| Environmental precautions | : Do not allow contact with soil, surface or ground water. |

SAFETY DATA SHEET

INSPEXX 150

Methods and materials for containment and cleaning up : Eliminate all ignition sources if safe to do so. Stop leak if safe to do so. Isolate the waste do not allow it to come into contact with incompatible materials. For small spills contain with sand or vermiculite and dilute the contained product at least 10 times with water. Transfer to an open topped container and remove to a safe place for neutralization* / disposal. For large spills contain spill and evacuate the area, leave until the reaction subsides, then collect up for disposal. Obtain consent from the local water company / authority if considering discharge to sewer. *NEUTRALIZATION : once diluted, neutralize with a suitable alkali such as sodium bicarbonate. Combustible materials exposed to this product should be rinsed immediately with large amounts of water to ensure that all product is removed. Residual product which is allowed to dry on organic materials such as rags, cloths, paper, fabrics, cotton, leather, wood, or other combustibles may spontaneously ignite and result in a fire.

Section: 7. HANDLING AND STORAGE

Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Do not breathe dust/fume/gas/mist/vapours/spray. Use only with adequate ventilation. Keep away from fire, sparks and heated surfaces. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Wash hands thoroughly after handling. Do not mix with bleach or other chlorinated products – will cause chlorine gas. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).

Conditions for safe storage : Keep away from heat and sources of ignition. Keep in a cool, well-ventilated place. Keep away from reducing agents. Keep away from strong bases. Keep away from combustible material. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers. Pressure bursts may occur due to gas evolution if the container is not adequately vented. May be stored with other similar strong oxidizing agents, provided they are compatible.

Storage temperature : -20 °C to 30 °C

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
Acetic acid	64-19-7	TWA	10 ppm 25 mg/m ³	BH OEL
		STEL	15 ppm 37 mg/m ³	BH OEL
Acetic acid	64-19-7	TWA	10 ppm 25 mg/m ³	ARE OEL
		STEL	15 ppm 37 mg/m ³	ARE OEL
Acetic acid	64-19-7	TWA	10 ppm	ACGIH
		STEL	15 ppm	ACGIH
		STEL	15 ppm 37 mg/m ³	NIOSH REL

SAFETY DATA SHEET

INSPEXX 150

		TWA	10 ppm 25 mg/m ³	NIOSH REL
		TWA	10 ppm 25 mg/m ³	OSHA Z1
Hydrogen peroxide	7722-84-1	TWA	1 ppm 1.4 mg/m ³	BH OEL
Hydrogen peroxide	7722-84-1	TWA	1 ppm 1.4 mg/m ³	ARE OEL
Hydrogen peroxide	7722-84-1	TWA	1 ppm	ACGIH
		TWA	1 ppm 1.4 mg/m ³	NIOSH REL
		TWA	1 ppm 1.4 mg/m ³	OSHA Z1
Peracetic acid	79-21-0	STEL	0.4 ppm	ACGIH

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

Personal protective equipment

Eye protection : Wear eye protection/face protection.

Hand protection : Recommended preventive skin protection
Gloves
Nitrile rubber
butyl-rubber
Breakthrough time: 1 – 4 hours
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin protection : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing

Respiratory protection : When respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization, consider the use of certified respiratory protection equipment meeting EU requirements (89/656/EEC, (EU) 2016/425), or equivalent, with filter type:

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid
Colour : colourless
Odour : pungent
pH : 0.5 - 1.5, (100 %)
Flash point : 72 °C closed cup
Odour Threshold : no data available
Melting point/freezing point : no data available

SAFETY DATA SHEET

INSPEXX 150

Initial boiling point and boiling range	: > 100 °C
Evaporation rate	: no data available
Flammability (solid, gas)	: Not applicable.
Upper explosion limit	: no data available
Lower explosion limit	: no data available
Vapour pressure	: no data available
Relative vapour density	: no data available
Relative density	: 1.13 - 1.15
Water solubility	: soluble
Solubility in other solvents	: no data available
Partition coefficient: n-octanol/water	: no data available
Auto-ignition temperature	: no data available
Thermal decomposition	: no data available
Viscosity, kinematic	: no data available
Explosive properties	: no data available
Oxidizing properties	: Yes
Molecular weight	: no data available
VOC	: no data available

Section: 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Contamination may result in dangerous pressure increases - closed containers may rupture.
Possibility of hazardous reactions	: Do not mix with bleach or other chlorinated products – will cause chlorine gas.
Conditions to avoid	: Heat, flames and sparks. Direct sources of heat. Exposure to sunlight.
Incompatible materials	: Bases Metals Organic materials
Hazardous decomposition products	: In case of fire hazardous decomposition products may be produced such as: Carbon oxides

Section: 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Potential Health Effects

SAFETY DATA SHEET

INSPEXX 150

Eyes	: Causes serious eye damage.
Skin	: Causes severe skin burns.
Ingestion	: Harmful if swallowed. Causes digestive tract burns.
Inhalation	: May cause respiratory tract irritation. May cause nose, throat, and lung irritation.
Chronic Exposure	: Health injuries are not known or expected under normal use.

Experience with human exposure

Eye contact	: Redness, Pain, Corrosion
Skin contact	: Redness, Pain, Corrosion
Ingestion	: Corrosion, Abdominal pain
Inhalation	: Respiratory irritation, Cough

Toxicity

Product

Acute oral toxicity	: Acute toxicity estimate : 1,958 mg/kg
Acute inhalation toxicity	: 4 h Acute toxicity estimate : 34.16 mg/l Test atmosphere: vapour
Acute dermal toxicity	: Acute toxicity estimate : 2,458 mg/kg
Skin corrosion/irritation	: no data available
Serious eye damage/eye irritation	: no data available
Respiratory or skin sensitization	: no data available
Carcinogenicity	: no data available
Reproductive effects	: no data available
Germ cell mutagenicity	: no data available
Teratogenicity	: no data available
STOT - single exposure	: no data available
STOT - repeated exposure	: no data available
Aspiration toxicity	: no data available

Section: 12. ECOLOGICAL INFORMATION

Toxicity

Environmental Effects	: Toxic to aquatic life.
-----------------------	--------------------------

Product

Toxicity to fish	: no data available
Toxicity to daphnia and other aquatic invertebrates	: no data available

SAFETY DATA SHEET

INSPEXX 150

Toxicity to algae : no data available

Components

Toxicity to fish : Acetic acid
96 h LC50 Oncorhynchus mykiss (rainbow trout): > 1,000 mg/l

Peracetic acid
96 h LC50: 0.8 mg/l

Components

Toxicity to daphnia and other aquatic invertebrates : Acetic acid
48 h EC50 Daphnia magna (Water flea): 39.6 mg/l

Peracetic acid
48 h EC50: 0.73 mg/l

Components

Toxicity to algae : Acetic acid
72 h EC50 Skeletonema costatum (marine diatom): > 1,000 mg/l

Hydrogen peroxide
72 h EC50: 1.38 mg/l

Peracetic acid
72 h EC50: 0.7 mg/l

Persistence and degradability

Readily biodegradable.

Bioaccumulative potential

no data available

Mobility in soil

no data available

Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Disposal methods : Do not contaminate ponds, waterways or ditches with chemical or used container. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.

Disposal considerations : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

Section: 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

SAFETY DATA SHEET

INSPEXX 150

UN number : 3098
UN proper shipping name : OXIDIZING LIQUID, CORROSIVE, N.O.S.
(Hydrogen peroxide, Peroxyacetic acid, acetic acid)
Transport hazard class(es) : 5.1 (8)
Packing group : III
Environmental hazards : Yes
Special precautions for user : None

Air transport (IATA)

UN number : 3098
Proper shipping name : Oxidizing liquid, corrosive, n.o.s.
(Hydrogen peroxide, Peroxyacetic acid, acetic acid)
Class : 5.1 (8)
Packing group : III
Environmentally hazardous : Yes

Sea transport (IMDG/IMO)


UN number : 3098
Proper shipping name : OXIDIZING LIQUID, CORROSIVE, N.O.S.
(Hydrogen peroxide, Peroxyacetic acid, acetic acid)
Class : 5.1 (8)
Packing group : III
Marine pollutant : Yes

Section: 15. REGULATORY INFORMATION

For Regulatory information please contact your Ecolab sales representative.

Section: 16. OTHER INFORMATION

NFPA:



HMIS III:

HEALTH	3
FLAMMABILITY	2
PHYSICAL HAZARD	1

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Issuing date : 29.06.2021
Version : 1.0
Prepared by : Regulatory Affairs

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

SAFETY DATA SHEET

INSPEXX 150

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.