

SECTION 1. IDENTIFICATION OF THE CHEMICAL AND COMPANY

Product name : TURBO EMULSION FUTURE
 Other means of identification : Not applicable
 Recommended use : Basis Detergent
 Restrictions on use : Reserved for industrial and professional use.
 Product dilution information : No dilution information provided.
 Company : Chile ECOLAB S.A.
 Avenida Pedro de Valdivia 3801
 Santiago, Santiago Chile
 (2)-22413300, Telephone: (2)-22381603, Telephone: SAC: 600 241 6600
 sac.chile@ecolab.com
 Emergency telephone : (+56-2) 2635-3600 (CITUC) EMERGENCY PHONE
 Toxicological Emergency Phone : CITUC (+56-2) 2635-3800 (24 hours) Toxicological Emergencies

SECTION 2. HAZARDS IDENTIFICATION

Classification according to NCH 382 : Class: Class 8 Corrosives

Distintivo según NCh 2190 :


GHS Classification

Corrosive to Metals : Category 1
 Skin corrosion : Category 1
 Serious eye damage : Category 1
 Short-term (acute) aquatic hazard : Category 2

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : May be corrosive to metals.
 Causes severe skin burns and eye damage.
 Toxic to aquatic life.

Precautionary Statements : **Prevention:**

SAFETY DATA SHEET

TURBO EMULSION FUTURE

Keep only in original container. Wash skin thoroughly after handling. Avoid release to the environment. Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Wash contaminated clothing before reuse. Absorb spillage to prevent material damage.

Other hazards : None known.

SECTION 3. COMPOSITION/INFORMATION OF INGREDIENTS

Pure substance/mixture : Mixture

Chemical name	CAS-No.	Concentration (%)
Sodium hydroxide	1310-73-2	10 - 30
Isotridecanol, ethoxylated	69011-36-5	10 - 30
alanine, n,n-bis(carboxymethyl)-, trisodium salt	164462-16-2	5 - 10
Alcohols, C13-15, branched and linear, ethoxylated	157627-86-6	1 - 5
	Proprietary Ingredient	1 - 5
EDTMPA and Na-EDTMPA	22042-96-2	1 - 5

SECTION 4. FIRST AID MEASURES

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
- If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.
- Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal protective equipment.
- Notes to physician : Treat symptomatically.
- Expected acute effects**
- Eyes : Causes serious eye damage.
- Skin : Causes severe skin burns.
- Ingestion : Causes digestive tract burns.
- Inhalation : May cause nose, throat, and lung irritation.

SAFETY DATA SHEET

TURBO EMULSION FUTURE

Expected chronic effects

Chronic Exposure : Health injuries are not known or expected under normal use.

Most important symptoms / effects

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Pain, Corrosion

Ingestion : Corrosion, Abdominal pain

Inhalation : Respiratory irritation, Cough

SECTION 5. FIREFIGHTING MEASURES

Extinguishing Agents : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing agents : None known.

Specific hazards during fire fighting : Not flammable or combustible.

Products generated in combustion and thermal degradation : Decomposition products may include the following materials:
Carbon oxides
Nitrogen oxides (NO_x)
Sulfur oxides
Oxides of phosphorus

Precautions for Emergency Personnel and / or Firefighters : Use personal protective equipment.

Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

SECTION 6. MEASURES IN CASE OF ACCIDENTAL SPILLAGE

Personal precautions, protective equipment and emergency procedures : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed.

Environmental precautions : Do not allow contact with soil, surface or ground water.

Methods and materials for containment and cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

SECTION 7. HANDLING AND STORAGE

SAFETY DATA SHEET

TURBO EMULSION FUTURE

Handling

Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. Use only with adequate ventilation. Wash hands thoroughly after handling. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).

Storage

Conditions for safe storage : Do not store near acids. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

Recommended and unsuitable packaging by supplier : Use high density plastic containers.

Storage temperature : 5 °C to 40 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
Sodium hydroxide	1310-73-2	CMP-C	2 mg/m ³	AR OEL
sodium hydroxide	1310-73-2	LPA	2 ppm	CL OEL
Sodium hydroxide	1310-73-2	CEIL	2 mg/m ³	PE OEL
Sodium hydroxide	1310-73-2	LB	2 mg/m ³	VE OEL
Sodium hydroxide	1310-73-2	VLE-P	2 mg/m ³	NOM-010-STPS-2014
Sodium hydroxide	1310-73-2	C	2 mg/m ³	ACGIH
		Ceiling	2 mg/m ³	NIOSH REL
		TWA	2 mg/m ³	OSHA Z1

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

Personal protective equipment

Eye protection : Safety goggles
Face-shield

Hand protection : Wear the following personal protective equipment:
Impervious gloves, resistant to chemicals.
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin protection : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing

Wear closed shoes.

Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use.

SAFETY DATA SHEET

TURBO EMULSION FUTURE

Wash face, hands and any exposed skin thoroughly after handling.
Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Emulsion
Color	: opaque, light yellow
Odor	: Perfumes, fragrances
pH	: 13,0 - 14,0, (100 %)
Flash point	: closed cupNot applicable
Odor Threshold	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: > 100 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapor pressure	: No data available
Relative vapor density	: No data available
Relative density	: 1,16 - 1,23
Water solubility	: soluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, kinematic	: 586,829 mm ² /s (40 °C)
Explosive properties	: No data available
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Molecular weight	: No data available
VOC	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reaction known under conditions of normal use.
Conditions to avoid	: None known.
Incompatible materials	: Acids

SAFETY DATA SHEET

TURBO EMULSION FUTURE

Hazardous decomposition products : In case of fire hazardous decomposition products may be produced such as:
Carbon oxides
Nitrogen oxides (NO_x)
Sulfur oxides
Oxides of phosphorus

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Toxicity

Product

Acute oral toxicity : Acute toxicity estimate : > 5.000 mg/kg
Acute inhalation toxicity : No data available
Acute dermal toxicity : Acute toxicity estimate : > 5.000 mg/kg
Skin corrosion/irritation : No data available
Serious eye damage/eye irritation : No data available
Respiratory or skin sensitization : Contains an ingredient that can cause asthmatic-like reactions in sulfite-sensitive individuals.
Carcinogenicity : No data available
Reproductive effects : No data available
Germ cell mutagenicity : No data available
Teratogenicity : No data available
STOT-single exposure : No data available
STOT-repeated exposure : No data available
Aspiration toxicity : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Environmental Effects : Toxic to aquatic life.

Product

Toxicity to fish : No data available
Toxicity to daphnia and other aquatic invertebrates : No data available
Toxicity to algae : No data available

Components

Toxicity to fish : Isotridecanol, ethoxylated
LC50: 5,33 mg/l

alanine, n,n-bis(carboxymethyl)-, trisodium salt
96 h LC50: > 200 mg/l

SAFETY DATA SHEET

TURBO EMULSION FUTURE

EDTMPA and Na-EDTMPA
96 h LC50: > 100 mg/l

Components

Toxicity to daphnia and other : Sodium hydroxide
aquatic invertebrates 48 h EC50: 40 mg/l

Alcohols, C13-15, branched and linear, ethoxylated
48 h EC50 Daphnia magna (Water flea): 0,317 mg/l

48 h EC50 Daphnia magna (Water flea): > 1 mg/l

Components

Toxicity to algae :
72 h EC50 Desmodesmus subspicatus (green algae): > 10 mg/l

Persistence and degradability

Poorly biodegradable

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. INFORMATION OF DISPOSAL

Disposal of contaminated : In accordance with what is described by Supreme Decree No. 148,
packaging the packaging of the product is considered hazardous waste and must
be disposed of through companies authorized to receive and / or treat
such waste, which must be issued and final disposal certificate waste.

SECTION 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport

Official transport classification of the United Nations

UN number	:	1824
Description of the goods	:	SODIUM HYDROXIDE SOLUTION
Class	:	8
Packing group	:	II
Environmentally hazardous	:	no

Air transport (IATA)

Official transport classification of the United Nations

Contact Regulatory for air freight eligibility

SAFETY DATA SHEET

TURBO EMULSION FUTURE

Sea transport (IMDG/IMO)

Official transport classification of the United Nations

UN number	:	1824
Description of the goods	:	SODIUM HYDROXIDE SOLUTION
Class	:	8
Packing group	:	II
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	:	Not applicable
Marine pollutant	:	no

SECTION 15. REGULATORY INFORMATION

Registrations and Certifications

Chile: Our HDS meets Chilean Normative: NCH 2245: 2015 (Safety Data Sheet for chemical products - Content and order of sections)

The receiver should pay attention to the possible existence of local regulations.

NCh 1411: Prevention of risks, IV identification of risks of materials

NCh 2190: Transportation of Hazardous Substances - Pictograms for hazard identification

NCh 382: Dangerous Good - Classification

D.S. No. 594: Minimum basic conditions in the workplace

D.S. No. 148: Hazardous waste disposal


D.S. No. 72: Mining Safety Regulations

D. S. No. 43: reports on the storage of hazardous substances

D. S. No. 40: Reporting on exposure hazards

SECTION 16. OTHER INFORMATION

NFPA:



HMIS III:

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Issuing date : 27.06.2019
Version : 1.1
Prepared by : Regulatory Affairs

While there is no change in the formula or hazard classifications, this SDS remains valid.

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

SAFETY DATA SHEET

TURBO EMULSION FUTURE

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.