

NexGuard™ 22325

Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: **NexGuard™ 22325**
Substance type: CLP Mixture

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Use of the Substance/Mixture : BOILER WATER TREATMENT
Identified uses : Boiler treatment under 1T per day
Recommended restrictions on use : Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet:

COMPANY IDENTIFICATION
NALCO EUROPE B.V.
Postbus 627
2300 AP Leiden, The Netherlands
TEL: 0031 71 5241100

LOCAL COMPANY IDENTIFICATION
Nalco Ltd.
P.O. BOX 11, WINNINGTON AVENUE
NORTHWICH, CHESHIRE, U.K. CW8 4DX
TEL: +44 (0)1606 74488

For Product Safety information please contact: msdseame@nalco.com

1.4 Emergency telephone number:

Emergency telephone number : +32-(0)3-575-5555 Trans-European

Date of Compilation/Revision: 22.06.2018
Version Number: 2.2

Section: 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin corrosion, Category 1B	H314
Serious eye damage, Category 1	H318

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H314 Causes severe skin burns and eye damage.

Precautionary Statements : **Prevention:**
P280 Wear protective gloves/ protective clothing/
eye protection/ face protection.

Response:
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do
NOT induce vomiting.

NexGuard™ 22325

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:
Sodium Hydroxide

2.3 Other hazards

None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS**3.2 Mixtures****Hazardous components**

Chemical Name	CAS-No. EC-No. REACH No.	Classification (REGULATION (EC) No 1272/2008)	Concentration: [%]
Sodium Hydroxide	1310-73-2 215-185-5 01-2119457892-27	Skin corrosion Category 1A; H314 Corrosive to metals Category 1; H290	2.5 - < 5

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section: 4. FIRST AID MEASURES**4.1 Description of first aid measures**

If inhaled : Remove to fresh air.
Treat symptomatically.
Get medical attention if symptoms occur.

In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes.
Use a mild soap if available.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
Get medical attention immediately.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Remove contact lenses, if present and easy to do. Continue

NexGuard™ 22325

rinsing.
Get medical attention immediately.

If swallowed : Rinse mouth with water.
Do NOT induce vomiting.
Never give anything by mouth to an unconscious person.
If conscious, give 2 glasses of water.
Get medical attention immediately.

Protection of first-aiders : In event of emergency assess the danger before taking action.
Do not put yourself at risk of injury. If in doubt, contact emergency responders. Use personal protective equipment as required.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

Section: 5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Not flammable or combustible.

Hazardous combustion products : Depending on combustion properties, decomposition products may include following materials:
Carbon oxides
nitrogen oxides (NO_x)
Sulphur oxides
Oxides of phosphorus

5.3 Advice for firefighters

Special protective equipment for firefighters : Use personal protective equipment.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel : Ensure adequate ventilation.
Keep people away from and upwind of spill/leak.
Avoid inhalation, ingestion and contact with skin and eyes.
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Ensure clean-up is conducted by trained personnel only.

NexGuard™ 22325

Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Stop leak if safe to do so.
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Flush away traces with water.
For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

6.4 Reference to other sections

See Section 1 for emergency contact information.
For personal protection see section 8.
See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Advice on safe handling : Do not ingest. Do not breathe spray, vapour. Do not get in eyes, on skin, or on clothing. Wash hands thoroughly after handling. Use only with adequate ventilation.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Do not store near acids. Keep out of reach of children. Keep container tightly closed. Store in suitable labelled containers.

Suitable material : The following compatibility data is suggested based on similar product data and/or industry experience: Shipping and long term storage compatibility with construction materials can vary; we therefore recommend that compatibility is tested prior to use.

7.3 Specific end uses

Specific use(s) : BOILER WATER TREATMENT

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

NexGuard™ 22325**Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Sodium Hydroxide	1310-73-2	STEL	2 mg/m3	UKCOSSTD

DNEL

Sodium Hydroxide	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 1 mg/m3
	:	End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 1 mg/m3

8.2 Exposure controls**Appropriate engineering controls**

Effective exhaust ventilation system.

Maintain air concentrations below occupational exposure standards.

Individual protection measures

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Eye/face protection (EN 166) : Safety goggles
Face-shield

Hand protection (EN 374) : Recommended preventive skin protection
Gloves
Nitrile rubber
butyl-rubber
Breakthrough time: 1 – 4 hours
Minimum thickness for butyl-rubber 0.7 mm for nitrile rubber 0.4 mm or equivalent (please refer to the gloves manufacturer/distributor for advise).
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin and body protection (EN 14605) : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing including appropriate safety shoes

Respiratory protection (EN 143, 14387) : When respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization, consider the use of certified respiratory protection equipment meeting EU requirements (89/656/EEC, (EU) 2016/425), or equivalent, with filter type:P

Environmental exposure controls

General advice : Consider the provision of containment around storage

NexGuard™ 22325

vessels.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	: Liquid
Colour	: yellow
Odour	: odourless
Flash point	: Will not burn: inorganic or water-based product
pH	: 13.6, 100 %
Odour Threshold	: no data available
Melting point/freezing point	: POUR POINT: -8.3 °C
Initial boiling point and boiling range	: no data available
Evaporation rate	: no data available
Flammability (solid, gas)	: no data available
Upper explosion limit	: no data available
Lower explosion limit	: no data available
Vapour pressure	: no data available
Relative vapour density	: no data available
Relative density	: 1.09 (20.0 °C)
Solubility(ies)	
Water solubility	: completely soluble
Solubility in other solvents	: no data available
Partition coefficient: n-octanol/water	: no data available
Auto-ignition temperature	: no data available
Thermal decomposition	: no data available
Viscosity	
Viscosity, dynamic	: no data available
Viscosity, kinematic	: 1.4 mm ² /s (20 °C)
Explosive properties	: no data available
Oxidizing properties	: no data available

9.2 Other information

no data available

Section: 10. STABILITY AND REACTIVITY

NexGuard™ 22325

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

10.5 Incompatible materials

Materials to avoid : Strong acids

10.6 Hazardous decomposition products

Hazardous decomposition products : Depending on combustion properties, decomposition products may include following materials:
Carbon oxides
nitrogen oxides (NO_x)
Sulphur oxides
Oxides of phosphorus

Section: 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Toxicity

Product

Acute oral toxicity : There is no data available for this product.
Acute inhalation toxicity : There is no data available for this product.
Skin corrosion/irritation : There is no data available for this product.
Serious eye damage/eye irritation : There is no data available for this product.
Respiratory or skin sensitization : There is no data available for this product.
Carcinogenicity : There is no data available for this product.
Reproductive effects : There is no data available for this product.
Germ cell mutagenicity : There is no data available for this product.
Teratogenicity : There is no data available for this product.
STOT - single exposure : There is no data available for this product.

NexGuard™ 22325

STOT - repeated exposure : There is no data available for this product.

Aspiration toxicity : There is no data available for this product.

Potential Health Effects

Eyes : Causes serious eye damage.

Skin : Causes severe skin burns.

Ingestion : Causes digestive tract burns.

Inhalation : May cause nose, throat, and lung irritation.

Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Pain, Corrosion

Ingestion : Corrosion, Abdominal pain

Inhalation : Respiratory irritation, Cough

Further information : no data available

Section: 12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity

Product

Environmental Effects : This product has no known ecotoxicological effects.

Toxicity to fish : no data available

Toxicity to daphnia and other aquatic invertebrates : no data available

Toxicity to algae : no data available

Components

Toxicity to daphnia and other aquatic invertebrates : Sodium Hydroxide
48 h EC50: 40 mg/l

12.2 Persistence and degradability

Product

no data available

Components

Biodegradability : Sodium Hydroxide

NexGuard™ 22325

Result: Not applicable - inorganic

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods

- | | |
|-----------------------------------|---|
| Product | : Where possible recycling is preferred to disposal or incineration.
If recycling is not practicable, dispose of in compliance with local regulations.
Dispose of wastes in an approved waste disposal facility. |
| Contaminated packaging | : Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers. |
| Guidance for Waste Code selection | : Inorganic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations. |

Section: 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

NexGuard™ 22325

Land transport (ADR/ADN/RID)

14.1 UN number:	UN 1824
14.2 UN proper shipping name:	SODIUM HYDROXIDE SOLUTION
14.3 Transport hazard class(es):	8
14.4 Packing group:	III
14.5 Environmental hazards:	No
14.6 Special precautions for user:	Not applicable.

Air transport (IATA)

14.1 UN number:	UN 1824
14.2 UN proper shipping name:	SODIUM HYDROXIDE SOLUTION (Sodium Hydroxide)
14.3 Transport hazard class(es):	8
14.4 Packing group:	III
14.5 Environmental hazards:	No
14.6 Special precautions for user:	Not applicable.

Sea transport (IMDG/IMO)

14.1 UN number:	UN 1824
14.2 UN proper shipping name:	SODIUM HYDROXIDE SOLUTION (Sodium Hydroxide)
14.3 Transport hazard class(es):	8
14.4 Packing group:	III
14.5 Environmental hazards:	No
14.6 Special precautions for user:	Not applicable.
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:	Not applicable.

Section: 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

INTERNATIONAL REGULATIONS

FOOD AND DRUG ADMINISTRATION (FDA) Federal Food, Drug and Cosmetic Act
When use situations necessitate compliance with FDA regulations, this product is acceptable under: 21 CFR 173.310 Boiler Water Additives

The following limitations apply:

Maximum dosage	Limitation
184 PPM (AS PRODUCT)	in the boiler feedwater, As product in the boiler BLOWDOWN

The concentration guidelines are listed for boilers operating up to 50 cycles of concentration. The polymer must not be used at pressures above 1,000 PSIG (6895 kPa). Steam produced may be used in contact with any food type, defined under 21 CFR 170.3, which includes milk or milk products.

KOSHER

This product has been certified as KOSHER/PAREVE for year-round use EXCEPT FOR THE PASSOVER SEASON by the CHICAGO RABBINICAL COUNCIL.

NSF NON-FOOD COMPOUNDS REGISTRATION PROGRAM (former USDA List of Proprietary Substances & Non-Food Compounds):

NSF Registration number for this product is: 141345

This product is acceptable for treating boilers or steam lines where steam produced may contact edible products and/or cooling systems where the treated water may not contact edible products in and around food processing areas (G6).

INTERNATIONAL CHEMICAL CONTROL LAWS

NexGuard™ 22325

CANADA

The substance(s) in this preparation are included in or exempted from the Domestic Substance List (DSL).

United States TSCA Inventory

On the inventory, or in compliance with the inventory

NATIONAL REGULATIONS GERMANY

FEDERAL INSTITUTE FOR RISK ASSESSMENT (BfR) RECOMMENDATION

Acceptable Sections: LFGB compliant

15.2 Chemical Safety Assessment:

A Chemical Safety Assessment has been carried out for some of the substances in this mixture.

Section: 16. OTHER INFORMATION**Procedure used to derive the classification according to REGULATION (EC) No 1272/2008**

Classification	Justification
Skin corrosion 1B, H314	Calculation method
Serious eye damage 1, H318	Calculation method

Full text of H-Statements

H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.

Full text of other abbreviations

ADN – European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR – European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS – Australian Inventory of Chemical Substances; ASTM – American Society for the Testing of Materials; bw – Body weight; CLP – Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR – Carcinogen, Mutagen or Reproductive Toxicant; DIN – Standard of the German Institute for Standardisation; DSL – Domestic Substances List (Canada); ECHA – European Chemicals Agency; EC-Number – European Community number; ECx – Concentration associated with x% response; ELx – Loading rate associated with x% response; EmS – Emergency Schedule; ENCS – Existing and New Chemical Substances (Japan); ErCx – Concentration associated with x% growth rate response; GHS – Globally Harmonized System; GLP – Good Laboratory Practice; IARC – International Agency for Research on Cancer; IATA – International Air Transport Association; IBC – International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 – Half maximal inhibitory concentration; ICAO – International Civil Aviation Organization; IECSC – Inventory of Existing Chemical Substances in China; IMDG – International Maritime Dangerous Goods; IMO – International Maritime Organization; ISHL – Industrial Safety and Health Law (Japan); ISO – International Organisation for Standardization; KECI – Korea Existing Chemicals Inventory; LC50 – Lethal Concentration to 50 % of a test population; LD50 – Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL – International Convention for the Prevention of Pollution from Ships; n.o.s. – Not Otherwise Specified; NO(A)EC – No Observed (Adverse) Effect Concentration; NO(A)EL – No Observed (Adverse) Effect Level; NOELR – No Observable Effect Loading Rate; NZIoC – New Zealand Inventory of Chemicals; OECD – Organization for Economic Co-operation and Development; OPPTS – Office of Chemical Safety and Pollution Prevention; PBT – Persistent, Bioaccumulative and Toxic substance; PICCS – Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR – (Quantitative) Structure Activity Relationship; REACH – Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID – Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT – Self-Accelerating Decomposition Temperature; SDS – Safety Data

NexGuard™ 22325

Sheet; TCSI – Taiwan Chemical Substance Inventory; TRGS – Technical Rule for Hazardous Substances; TSCA – Toxic Substances Control Act (United States); UN – United Nations; vPvB – Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : IARC Monographs on the Evaluation of the Carcinogenic Risk of Chemicals to Man, Geneva: World Health Organization, International Agency for Research on Cancer.

The possible key literature references and data sources which may have been used in conjunction with the consideration of expert judgment to compile this Safety Data Sheet: European regulations/directives (including (EC) No. 1907/2006, (EC) No. 1272/2008), supplier data, inter-net, ESIS, IUCLID, ERICards, Non European official regulatory data and other data sources.

Prepared By : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Annex: Exposure Scenarios

Exposure Scenario: Boiler treatment under 1T per day

Life Cycle Stage : Industrial uses: Uses of substances as such or in preparations at industrial sites

Sector of use : **SU23** Electricity, steam, gas water supply and sewage treatment

Contributing scenario controlling environmental exposure for:

Environmental release category : **ERC4** Industrial use of processing aids in processes and products, not becoming part of articles

Daily amount per site : 1000 kg

Type of Sewage Treatment Plant : none

Contributing scenario controlling worker exposure for:

Process category : **PROC15** Use as laboratory reagent

NexGuard™ 22325

Exposure duration : 60.00 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation with 90% efficiency is required

General ventilation Ventilation rate per hour: 1

Skin Protection : Yes: See Section 8

Respiratory Protection : No

Contributing scenario controlling worker exposure for:

Process category : **PROC1** Use in closed process, no likelihood of exposure

Exposure duration : 60 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour: 1

Skin Protection : Yes: See Section 8

Respiratory Protection : No

Contributing scenario controlling worker exposure for:

Process category : **PROC8a** Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities

Exposure duration : 15 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour: 1

Skin Protection : Yes: See Section 8

Respiratory Protection : No

Contributing scenario controlling worker exposure for:

Process category : **PROC28** Manual maintenance (cleaning and repair) of machinery

Exposure duration : 240 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

NexGuard™ 22325

General ventilation Ventilation rate per hour: 1

Skin Protection : Yes: See Section 8

Respiratory Protection : No