

Section: 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : MOULD-EX

Other means of identification : Not applicable.

Recommended use : Cleaning product

Restrictions on use : Reserved for industrial and professional use.

Product dilution information : No dilution information provided.

Company

Ecolab Gulf FZE
P.O. Box 17063
Jebel Ali Free Zone Area, Near Container Terminal 3 - North Zone
Dubai
UAE
00971 4 8014444 Customer Services, 00971 48146800 00971 4
8014000 Reception phone numbers

Nalco Egypt Trading
5th Settlement, South 90th St.
The Address Building No 67th – 1st floor
New Cairo, Cairo, Egypt11835
0020 2 25 37 1195,

Ecolab Maroc S.A.R.L.
Batiment, Lot. Mounir 1, Parc Industriel
Attawfik
Route 1029
Sidi Maarouf, Casablanca, Morocco
00212 22 58 25 30 - 35,

Emergency telephone number : +32-(0)3-575-5555

Issuing date : 22.05.2019

Section: 2. HAZARDS IDENTIFICATION
GHS Classification

Corrosive to metals : Category 1
Skin corrosion : Category 1
Serious eye damage : Category 1

GHS Label element

Hazard pictograms :



Signal Word : Danger

SAFETY DATA SHEET

MOULD-EX

- Hazard Statements** : May be corrosive to metals.
Causes severe skin burns and eye damage.
- Precautionary Statements** : **Prevention:**
Keep only in original container. Wash skin thoroughly after handling.
Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician. Wash contaminated clothing before reuse. Absorb spillage to prevent material damage.
Storage:
Store locked up. Store in corrosive resistant container with a resistant inner liner.
Disposal:
Dispose of contents/ container to an approved waste disposal plant.
- Other hazards** : Mixing this product with acid or ammonia releases chlorine gas.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

Pure substance/mixture : Mixture

Chemical Name	CAS-No.	Concentration: (%)
sodium hypochlorite	7681-52-9	5 - 10
Amines, C12-14 alkyl dimethyl, N-oxides	308062-28-4	1 - 5
potassium hydroxide	1310-58-3	1 - 5

Section: 4. FIRST AID MEASURES

- In case of eye contact** : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact** : Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
- If swallowed** : Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- If inhaled** : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.
- Protection of first-aiders** : If potential for exposure exists refer to Section 8 for specific personal protective equipment.
- Notes to physician** : Treat symptomatically.
- Most important symptoms and effects, both acute and delayed** : See Section 11 for more detailed information on health effects and symptoms.

SAFETY DATA SHEET

MOULD-EX

Section: 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : None known.
- Specific hazards during firefighting : Not flammable or combustible.
- Hazardous combustion products : Decomposition products may include the following materials:
Carbon oxides
nitrogen oxides (NO_x)
metal oxides
Hydrogen chloride
- Special protective equipment for firefighters : Use personal protective equipment.
- Specific extinguishing methods : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Do not allow contact with soil, surface or ground water.
- Methods and materials for containment and cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

Section: 7. HANDLING AND STORAGE

- Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Do not breathe dust/fume/gas/mist/vapours/spray. Use only with adequate ventilation. Wash hands thoroughly after handling. Mixing this product with acid or ammonia releases chlorine gas. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).
- Conditions for safe storage : Do not store near acids. Keep out of reach of children. Store in suitable labeled containers. Keep only in original packaging. Absorb spillage to prevent material damage.
- Storage temperature : 0 °C to 25 °C

SAFETY DATA SHEET

MOULD-EX

Packaging material : Suitable material: Plastic material
Unsuitable material: Mild steel, Aluminium

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
potassium hydroxide	1310-58-3	CLV	2 mg/m ³	BH OEL
potassium hydroxide	1310-58-3	Ceiling limit	2 mg/m ³	ARE OEL

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

Personal protective equipment

Eye protection : Wear eye protection/face protection.

Hand protection : Wear the following personal protective equipment:
Standard glove type.
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin protection : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing

Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use.
Wash face, hands and any exposed skin thoroughly after handling.
Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid
Colour : clear, light yellow
Odour : Chlorine
pH : 12.5 - 13.5, (100 %)
Flash point : Not applicable.
Odour Threshold : no data available
Melting point/freezing point : no data available
Initial boiling point and boiling range : no data available
Evaporation rate : no data available
Flammability (solid, gas) : no data available
Upper explosion limit : no data available
Lower explosion limit : no data available

SAFETY DATA SHEET

MOULD-EX

Vapour pressure	: no data available
Relative vapour density	: no data available
Relative density	: no data available
Water solubility	: no data available
Solubility in other solvents	: no data available
Partition coefficient: n-octanol/water	: no data available
Auto-ignition temperature	: no data available
Thermal decomposition	: no data available
Viscosity, kinematic	: no data available
Explosive properties	: no data available
Oxidizing properties	: Yes
Molecular weight	: no data available
VOC	: no data available

Section: 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Mixing this product with acid or ammonia releases chlorine gas.
Conditions to avoid	: None known.
Incompatible materials	: Acids Aluminium Mild steel
Hazardous decomposition products	: In case of fire hazardous decomposition products may be produced such as: Carbon oxides nitrogen oxides (NOx) metal oxides Hydrogen chloride

Section: 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Potential Health Effects

Eyes	: Causes serious eye damage.
Skin	: Causes severe skin burns.
Ingestion	: Causes digestive tract burns.
Inhalation	: May cause nose, throat, and lung irritation.

SAFETY DATA SHEET

MOULD-EX

Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Eye contact : Redness, Pain, Corrosion
Skin contact : Redness, Pain, Corrosion
Ingestion : Corrosion, Abdominal pain
Inhalation : Respiratory irritation, Cough

Toxicity

Product

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg
Acute inhalation toxicity : no data available
Acute dermal toxicity : no data available
Skin corrosion/irritation : no data available
Serious eye damage/eye irritation : no data available
Respiratory or skin sensitization : no data available
Carcinogenicity : no data available
Reproductive effects : no data available
Germ cell mutagenicity : no data available
Teratogenicity : no data available
STOT - single exposure : no data available
STOT - repeated exposure : no data available
Aspiration toxicity : no data available

Components

Acute dermal toxicity : sodium hypochlorite
LD50 rabbit: > 10,000 mg/kg

Section: 12. ECOLOGICAL INFORMATION

Ecotoxicity

Environmental Effects : Very toxic to aquatic life.

Product

Toxicity to fish : no data available
Toxicity to daphnia and other aquatic invertebrates : no data available
Toxicity to algae : no data available

Components

Toxicity to fish : sodium hypochlorite
96 h EC50: 0.14 mg/l

SAFETY DATA SHEET

MOULD-EX

Amines, C12-14 alkyldimethyl, N-oxides
LC50: 2.67 mg/l

Components

Toxicity to daphnia and other aquatic invertebrates : sodium hypochlorite
48 h EC50: 0.071 mg/l

Amines, C12-14 alkyldimethyl, N-oxides
EC50 Daphnia magna (Water flea): 3.1 mg/l

Components

Toxicity to algae : Amines, C12-14 alkyldimethyl, N-oxides
LC50: 0.143 mg/l
NOEC: 0.067 mg/l

Persistence and degradability

Readily biodegradable.

Bioaccumulative potential

no data available

Mobility in soil

no data available

Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Disposal methods : Do not contaminate ponds, waterways or ditches with chemical or used container. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.

Disposal considerations : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

Section: 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

UN number : 3266
UN proper shipping name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S.
(sodium hypochlorite, Potassium hydroxide)
Transport hazard class(es) : 8
Packing group : III
Environmental hazards : Yes
Special precautions for user : None

SAFETY DATA SHEET

MOULD-EX

Air transport (IATA)

UN number : 3266
Description of the goods : Corrosive liquid, basic, inorganic, n.o.s.
(sodium hypochlorite, Potassium hydroxide)
Class : 8
Packing group : III
Environmentally hazardous : Yes

Sea transport (IMDG/IMO)


UN number : 3266
Description of the goods : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S.
(sodium hypochlorite, Potassium hydroxide)
Class : 8
Packing group : III
Marine pollutant : Yes

Section: 15. REGULATORY INFORMATION

For Regulatory information please contact your Ecolab sales representative.

Section: 16. OTHER INFORMATION

NFPA:



HMIS III:

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Issuing date : 22.05.2019
Version : 1.1
Prepared by : Regulatory Affairs

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.