

Chameleon® Stellaris LED Fly Trap

Comprehensive Unit Specification

Part No.	125-000529 / 125-000528	125-000536 / 125-000535
Description	White UK / EU	304 ST.ST UK /EU
Unit Class	I	
Guarantee	3 Years	
Area of Coverage	180-220m ²	
Voltage Range	220-240V	
Frequency Range	50-60Hz	
IP Rating	20	
Ambient operating temperatures	0 to +40°C *	
Power Consumption	13.5W	
Glueboard (2 Required)	135-000226 (6 Pieces)	
LED Tube (2 Required)	130-000321 - Quantum® X LED 370nm 550mm T5	
Mains Cable	IEC / HO5RN-F	
Unit Dimensions (mm)	H420 x W590 x D160	
Carton Dimensions (mm)	H560 x W730 x D210	
Unit Weight	5.7kg	
Carton Weight	7.7kg	

* recommended operating temperature range, should they be exceeded in either way it may affect the working of the unit.

The Chameleon® Stellaris is compliant with the essential requirements of the EMC Directive 2014/30/EU and the Low Voltage Directive 2014/35/EU. The unit is CE and UKCA marked.

Additionally, the Chameleon Stellaris is compliant with the following International Standards:

EN 55014-1:2017	Electromagnetic compatibility. Requirements for household appliances, electric tools and similar apparatus. Emission.
EN 55014-2:2015	Electromagnetic compatibility. Requirements for household appliances, electric tools and similar apparatus. Immunity.
IEC 60335-1:2020	Safety of household and similar electrical appliances – Part 1: General requirements.
IEC 60335-2-59:2021	Household and similar electrical appliances – Safety – Part 2-59: Particular requirements for insect killers.

Engineering and Technical Manager Signature:



Dated: 15th November 2023