

NIBOR-D[®]

INSECTICIDE

Active Ingredient:

Disodium Octaborate Tetrahydrate (CAS No. 12280-03-4).....98%
OTHER INGREDIENT*.....2%
TOTAL.....100%

*Contains 2% H₂O – Absorbed Moisture

First Aid

If Swallowed: Immediately call a poison control center or doctor for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything by mouth to an unconscious person. **If Inhaled:** Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice. **If In Eyes:** Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for further treatment advice. Have the product container or label with you when calling a poison control center or doctor or going for treatment.

PRECAUTIONARY STATEMENTS
Hazards to Humans and Domestic Animals

CAUTION: Harmful if swallowed or inhaled. Causes moderate eye irritation. Avoid contact with eyes or clothing. Avoid breathing dust. Thoroughly wash with soap and water after handling. Remove contaminated clothing and wash clothing before reuse.

Personal Protective Equipment (PPE)

Some materials that are chemical-resistant to this product are barrier laminate; butyl, nitrile, neoprene and natural rubbers ≥ 14 mils; polyethylene; polyvinyl chloride; and viton ≥ 14 mils. Applicators, mixers and other handlers must wear long-sleeved shirt, long pants, socks, shoes, chemical-resistant gloves and protective eyewear. When applying this product in confined spaces, provide ventilation or an exhaust system. When using pressurized equipment to load and apply dust products to structural building components and poultry houses, wear a minimum of a NIOSH-approved particulate filtering facepiece respirator with any N, R or P filter; OR a NIOSH-approved elastomeric particulate respirator with any N, R or P filter; OR a NIOSH-approved powered air purifying respirator with HE filters.

Respirator fit testing, medical qualification, and training

Using a program that conforms to OSHA's requirements (see 29 CFR Part 1910.134), employers must verify that any handler who uses a respirator is: Fit-tested and fit-checked, Trained, and Examined by a qualified medical practitioner to ensure physical ability to safely wear the style of respirator to be worn. A qualified medical practitioner is a physician or other licensed health care professional who will evaluate the ability of a worker to wear a respirator. The initial evaluation consists of a questionnaire that asks about medical conditions (such as a heart condition) that would be problematic for respirator use. If concerns are identified, then additional evaluations, such as a physical exam, might be necessary. The initial evaluation must be done before respirator use begins. Handlers must be reexamined by a qualified medical practitioner if their health status or respirator style or use-conditions change. Upon request by local/state/federal/tribal enforcement personnel, employers must provide documentation demonstrating how they have complied with these requirements.

User Safety Requirements

Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry.

User Safety Recommendations

Users should: Wash hands before eating, drinking, chewing gum, using tobacco or using the toilet; Remove clothing immediately if pesticide gets inside, then wash thoroughly and put on clean clothing; Remove PPE immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly and change into clean clothing.

Environmental Hazards

Wood treatment facilities must take steps to prevent runoff of the product into the waterway. Treated material stored outdoors within 100 feet of a pond, lake, stream, or river must be covered, surrounded by a containment berm, or otherwise protected to prevent surface water runoff. The containment berm must be of sufficient height to prevent runoff during heavy rainfall events. This pesticide is toxic to fish and wildlife. Do not apply directly to water, to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment washwaters.

NOTICE

Read and understand the entire label before using. Use only according to label directions. Before buying or using this product, read the **Warranty Disclaimer** and **Limitation of Remedies** statements found elsewhere on this label. If terms are unacceptable, return unopened package to seller for full refund of purchase price. Otherwise, use by the buyer or any other user constitutes acceptance of the terms under the **Warranty Disclaimer** and **Limitation of Remedies**.



NISUS[®]
CORPORATION

100 Nisus Drive
Rockford, TN 37853
(800) 264-0870

Nibor-D, Nisus and Nisus Corporation are registered trademarks of Nisus Corporation.
©2023 Nisus Corporation #NID-1LB-0123-SAL053119

FOR THE CONTROL OF:
CRICKETS • COCKROACHES • SILVERFISH • ANTS • FLEAS
LADY BUGS • DRAIN FLIES • FRUIT FLIES
CLUSTER FLIES • DARKLING BEETLES • EARWIGS

For both interior and exterior use

EPA Reg. No. 64405-8 EPA Est. 64405-TN-1

KEEP OUT OF REACH OF CHILDREN
CAUTION

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Use of this product for the control of bed bugs is prohibited. Applications to carpets are prohibited. **For treatments in poultry houses:** Do not apply with pressurized application methods except for use with crack and crevice, spot, or void treatments. Use hand-operated pump or backpack sprayers. **For treatments in poultry houses/industrial/commercial/structural buildings:** Do not apply with pressurized application methods except for use with crack and crevice, spot, or void treatments. **For applications to tree stumps,** do not apply dust directly to stumps, instead mix dust and water and then spray on to the stumps.

GENERAL INSECT CONTROL
Product Information

Nibor-D is a water soluble inorganic borate salt with insecticidal properties that can be applied as a liquid solution, mop solution or dust. Dry foam applications can be used when better adhesion to treated surfaces and minimal runoff is desired. Residual effects of Nibor-D will last longer in areas protected from weather and elements. It is effective as both a preventative and remedial treatment to kill and control general and nuisance pests such as, but not limited to, those listed below:

General Ants (including Argentine, Thief, Little Black, Pavement, Odorous House, Crazy and Ghost Ants), **Boxelder Bugs, Carpenter Ants, Cluster Flies, Centipedes, Crickets** (including House Crickets, Field Crickets and Camel Crickets), **Darkling Beetles, Dust Mites, Earwigs, Flies, Fleas, Hide Beetles, Lady Bugs, Millipedes, Roaches** (including German, Brown-banded, Smokey Brown, Brown, American, Australian and Oriental Roaches), **Small Flies** (including Fruit and Drain flies) and **Silverfish**.

Use Nibor-D in apartment buildings, bird and poultry production facilities, buses, factories, garages, grocery stores, homes, hospitals, hotels, industrial plants, kennels, libraries, manhole covers, markets, military bases, mobile homes, new construction, nursing homes, offices, public and private institutions, restaurants, sewers, schools, ships, theaters, trains, trucks, utilities, warehouses, yachts and zoos.

Nibor-D may be applied into cracks and crevices on outside areas of structures including cracks and crevices around windows, doorframes and other areas where insect pests may enter or to areas where insects hide, such as behind baseboards, storage shelves and wall studs; between elements of construction, equipment and floors; in attics, attic insulation, block voids, box sills, cracks, crevices, eaves, equipment legs and equipment bases, voids and wall voids; in openings around pipes and sinks and openings leading to voids and hollow spaces in walls; on logs, lumber, moist areas, plywood, railroad ties, soffits and utility poles; under refrigerators; and wood-foam composite structural components. Do not apply Nibor-D liquid solutions in conduits, motor housings, junction boxes, switch boxes or other electrical equipment because of possible shock hazard.

Application for Food Processing and Handling Establishments, including Federally Inspected Poultry and Meat Plants: In food areas, only apply product into cracks, crevices and other inaccessible areas. Avoid introducing any product into the air. Avoid contamination of food and feed stuffs. Do not apply product directly onto a surface where food is prepared, served or stored. Any product left visible on a food surface after treatment should be removed and surface washed.

Food Areas Include: Serving areas, such as dining rooms, food storage areas, receiving areas, processing areas, including enclosed systems such as oil and syrup plants, mills and dairies; packing areas, including canning, bottling, wrapping and boxing; and edible waste storage areas. In these areas, direct product applications into cracks and crevices, such as along baseboards and between elements of construction. Do not allow product on any surfaces that may be contacted by food. Do not apply where food is exposed.

Non-Food Areas Include: Bathrooms, locker rooms, offices, maintenance rooms, mechanical rooms, trash rooms, garages, janitorial closets, storage areas after bottling or canning and floor drains leading to sewer entries. In these areas, apply product as labeled for other non-food areas.

Always test any materials to be treated for color fastness and potential staining. Product may leave a light residue on dark surfaces. This residue may be removed with a warm damp cloth. Apply Nibor-D only in areas inaccessible to children and pets. Allow product to dry completely before allowing pets or children back on treated surfaces.

NET WT: 1.0 LB.



Made in the U.S.A.

Preparation of a 15% Nibor-D Liquid Solution

Measure approximately 80% of the required volume of water to the mixing vessel. While stirring, gradually add Nibor-D powder into water. For liquid sprays or foams, add 1.5 lbs (approximately 7.5 cups) of Nibor-D for each gallon of finished solution required. Or, if mopping, treating furniture, mold or mildew, add only 8 ounces (approximately 2.5 cups) of Nibor-D per gallon of water. Add remaining water to the mixing vessel and stir until Nibor-D has completely dissolved. Use this finished solution as soon as possible. Do not store for an extended length of time. Nibor-D can be used in conjunction with an insect growth regulator (IGR) such as pyriproxyfen, hydroprene or methoprene, a fungicide/mildewcide, an emulsifiable disinfectant or a non-residual knock-down emulsifiable insect adulticide.

Preparation of a Nibor-D Foam Solution

To create a dry consistency foam, add a surfactant/foaming agent and a Nibor-D liquid solution into foaming application equipment. Generally 1-2 ounces of a foaming agent will create dry foam with the desired expansion ratio of 20:1. Refer to the foaming equipment manufacturer's manuals and the surfactant labels for additional instructions. Wash and rinse all equipment after each use.

Dust Application Instructions

No powder should be visible after application. Remove or brush any powder visible after application into cracks and crevices.

General and Nuisance Pests, including Lady Bugs: Apply Nibor-D as a dust into the cracks, crevices and void areas of exterior walls and around windows, doors eaves and soffits. Caulking should be applied after application to seal any available crack.

Refuse Containers: Apply to container at the rate of 12-20 ounces per 250 ft² of area.

Floor Drains: Apply 1-2 ounces of dust into the drain opening followed by at least one quart of mop rinse water to control and prevent fly, including small fly, populations.

Sewers and Manhole Cavities: Apply as a dust at a rate not to exceed 12 oz. per 250 ft² using a blower or air pressure equipment.

New Construction: When treating large areas such as wall voids or soffit and subcabinet voids in new and existing construction, dust liberally using dusting application equipment. Apply dust at 12-20 ounces per 250 ft².

Attic Insulation: Nibor-D can be applied to all insulation materials including cellulose, fiberglass and natural fiber. Make sure the areas around attic soffits and pipe protrusions are properly treated. Do not over-apply or reapply into previously treated attics unless the treated insulation has been removed or additional insulation is installed.

Rolled Insulation: Apply before or after installation at the rate of 1 oz / 8 ft² of insulated area.

Blown Insulation: Apply to existing insulation at the rate of 2 oz / 8 ft² of insulated area. If new insulation is to be installed over any type of existing insulation, apply at the rate of 1 oz / 8 ft² to the existing insulation and then again to the new blown-in insulation. Add to blown-in insulation applicators at a maximum rate of 1-2 oz / 8 ft² of insulation.

Liquid and Foam Application Instructions

Refuse Containers: Apply liquid or foam solution at a gallon per 200-250 ft².

Floor Drains: Pour up to one quart of finished solution into each floor drain to prevent and control fly populations. This solution can also be applied as foam into drains.

Mop Solution: This is to be used as a supplemental treatment in conjunction with other pest management practices and may be reapplied as necessary. Apply only to floors by mopping. Allow the mop solution to penetrate into cracks and crevices in the tile or flooring and into crevice areas under equipment to affect possible hidden food sources and harborage areas that may contain small fly larva, including fruit fly and drain fly species and other insect pests. Remove or brush any powder visible after application into cracks and crevices.

Avoid introducing the material into the air or onto any exposed surfaces other than the floor area. Avoid contaminating food or food processing surfaces. Do not apply when foods are exposed or facility is in operation. Do not contaminate feed and foodstuffs.

Flies, Darkling Beetles and Hide Beetles (adults and larvae) Control in Bird and Poultry Facilities

First, remove birds. Use equipment designed for this type of application. Apply to structural sidewalls, posts, framing, top plates, into cracks and crevices, around insulation and on other structural components that might harbor beetles. Reapply application annually, after each grow-out or if facility is washed, sanitized and disinfected.

Dust Applications: If birds are in contact with floor or litter: Apply dry product with a spreader directly to the floor or old litter surface at the rate of 1-2 lbs/100 ft² of floor area. Apply a band treatment along bird feeder lines. Reapply annually if needed or after each grow-out. If birds are caged and not in contact with the floor or litter: Apply dry product at the rate of 1 1/2-2 lbs/100 ft² of surface area. For fly control, apply the dust to the surface of manure piles at the rate of 1 1/2-2 lbs/100 ft² of surface area.

Supplemental Liquid Applications: Add product at the rate of 1 lb/gallon of water. Apply solution on structural sidewalls, posts, framing, top plates, into cracks and crevices, around insulation and on other structural components that might harbor beetles at the rate of 4 gallons/100 ft² of surface area. For fly control, apply a liquid application to the surface of manure piles at the rate of 1 1/2 lbs of product/gallon of water/150 ft² of surface area.

Wood Treatment Product Information

Nibor-D is a water soluble, inorganic borate salt with insecticidal and fungicidal properties that may be used on wood and applied as a liquid solution or powder. Nibor-D may be used as a preventative treatment

(before signs of infestation) and for remedial treatment of infested wood. This product may also be used for pretreatment of wood before or during the construction process. Nibor-D kills, prevents and controls wood destroying insects and fungi such as, but not limited to, the following organisms:

Subterranean Termites (*Reticulitermes*, *Heterotermes*, *Coptotermes* (Formosan)), **Drywood Termites** (*Kaloterms*, *Incisitermes*), **Dampwood Termites** (*Zootermopsis*), **Powderpost Beetles** (*Lyctinae*, *Bostrichidae*), **Deathwatch and Furniture Beetles** (*Anobiidae*), **Old House Borers**, **Longhorned Beetles** (*Cerambycidae*), **Carpenter Ants** (*Camponotus*), **Bark and Timber Beetles** (*Scolytidae*), and **Decay Fungi** including white rot, brown rot (i.e., *Poria*) and wet rots.

Nibor-D is recommended for wood and cellulose materials in accordance with the specific treatment methods described herein and is effective for all interior and exterior wood (and wood-foam composite structural components) that will be protected from excessive rain and not in direct contact with the soil. Types of treatable materials include, but are not limited to, decks, fences, steps, sheds, barns and other outbuildings, ties, wool insulation, stumps, utility poles, timber, lumber, logs and plywood. Some etching of treated wood may occur from organisms before they die. Do not apply Nibor-D to wood or cellulose material that has been painted, varnished or sealed. For best results, apply Nibor-D to bare wood. Use soap and water to clean application equipment.

Note: Spraying water on some wood species can mobilize natural wood extractives, raise the grain and leave behind calcium or other deposits. Prior to treating large areas, treat a small area with Nibor-D solution to ensure that you are satisfied with the final aesthetics.

Preparation of Treatment Solutions (*In Situ* Treatment)

10% Liquid Solution: To prepare solution, add approximately 80% of the required volume of water to the mixing vessel. While stirring, gradually add 1.0 pound of Nibor-D for each gallon of treating solution required. Add remaining water to the solution and stir until the entire product has dissolved.

15% Liquid Solution: Prepare solution as above, but gradually add 1.5 lbs of Nibor-D for each gallon of treatment solution needed. Use this solution as soon as possible and do not store for an extended length of time.

15% Foam: Prepare a 15% liquid solution as described above and also add a surfactant-foaming agent. Generally 1-2 ounces of a foaming agent, added to the 15% liquid solution, produces a dry foam with the desired expansion ratio of approximately 20 to 1 (20 gallons of foam per 1 gallon of liquid solution). The Nibor-D foam should be of a "dry" consistency that adheres to wood surfaces so that run-off is minimized. A "wet" foam may damage wallboard or other building components. Refer to the individual foam equipment manufacturer's manual and the surfactant's label for specific instructions. Wash and rinse all equipment after each use.

Product Application Instructions

Liquid Application: Use a liquid solution to control wood destroying organisms, and to kill active infestations of termites, powderpost beetles and wood decay fungi. Application may also be made by drilling and then injecting the solution under pressure into sound wood or into the insect galleries of infested wood. For remedial control of wood attacking organisms or for the protection of wood against future infestations, either two applications of a 10% liquid solution or one application of a 15% liquid solution are required. Apply Nibor-D solutions by brush or spray at the rate of 5 gallons of liquid solution per 1000 ft² of wood surface area. Thoroughly wet wood surface area. Application may also be made by drilling and then injecting the liquid solution under pressure into sound wood or until run-off is observed coming from entry/exit holes of infested wood.

Foam Application: Nibor-D may be applied as foam to wood surfaces or injected into wall voids or insect galleries. In wall voids, inject enough dry foam to contact wood surfaces of studs in the wall or the entire desired target area. Apply foam, where possible, to abutting wood surfaces and between wood joints. Apply the foam so that all accessible wood surfaces are covered with foam. Foam can also be injected into insect galleries until run-off is observed.

Dust Application: Apply Nibor-D as a dust to kill and control wood destroying organisms such as termites and carpenter ants by drilling and injecting the powder into galleries, by dusting generously on wood surfaces, or by injecting or dusting into wall voids such as between studs, block voids, box sills, eaves, attics, soffits, etc. Apply to these areas at the rate of 0.5 ounce (12-14 grams) per ft². Dust can be injected or dusted into utility poles at a rate of 0.25 pound per cubic foot of area to be treated.

Wood Treatment During Construction for Prevention of Wood Destroying Organisms: Spray, foam or dust applications of Nibor-D may be made to wood after framing and roofing are in place and before insulation and drywall are installed. Apply Nibor-D liquid solutions to all accessible surfaces of bare wood at a rate of approximately 5 gallons per 1000 ft² of wood surface area. Do not spray electrical components or other non-wood components. Treat end-cuts of wood by application methods listed above, or by dipping end-cuts for 1-5 minutes in a Nibor-D 10% liquid solution. Apply powder at the rate of 0.5 ounce (12-14 grams) per ft² to wall stud areas, box sills, roof eaves, attics and soffits. Protect newly treated wood from excessive rain or moisture.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

Pesticide Storage: Store in a dry place. Do not store where children or animals may gain access.

Pesticide Disposal: Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

Container Handling: Non-refillable container; do not reuse or refill this container. Completely empty container by shaking and tapping sides and bottom to loosen clinging particles. Empty residue into application equipment; then offer for recycling, if available; or dispose of in a sanitary landfill; or, if allowed by state and local authorities, by incineration.

Warranty Disclaimer

To the extent not prohibited by applicable law, Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions, subject to the inherent risks set forth below. To the extent not prohibited by applicable law, **MANUFACTURER MAKES NO OTHER EXPRESS OR IMPLIED**

WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

Inherent Risks of Use

The directions for use of this product are believed to be adequate and must be carefully followed. It is impossible to eliminate all risks associated with use of this product. Lack of performance or other unintended consequences may result because of such factors as use of the product contrary to label instructions, abnormal conditions, the presence of other materials, climatic conditions or the manner of use/application, all of which are beyond the control of the Manufacturer. To the extent not prohibited by applicable law, the buyer/user assumes all such risks.

Limitation of Remedies

To the extent not prohibited by applicable law, the exclusive remedy for losses or damages resulting from this product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's election, one of the following:

1. Refund of purchase price paid by buyer or user for product bought, or
2. Replacement of amount of product used.

To the extent not prohibited by applicable law: a) Manufacturer shall not be liable for losses or damages resulting from handling or use of this product unless Manufacturer is promptly notified of such loss or damage in writing; and b) **TO THE EXTENT NOT PROHIBITED BY APPLICABLE LAW IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES.**

The terms of this **Warranty Disclaimer** and **Limitation of Remedies** cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this **Warranty Disclaimer** or **Limitation of Remedies** in any manner.

It is not intended that this product be used to practice any applicable patent, whether mentioned or not, without procurement of a license, if necessary, from the owner, following investigation by the user.