



SAFETY DATA SHEET

QUIK FILL 32 FLOOR STRIPPER

Section: 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : QUIK FILL 32 FLOOR STRIPPER

Other means of identification : Not applicable.

Recommended use : Floor Stripper

Restrictions on use : Reserved for industrial and professional use.

Product dilution information : 6.25 % - 16.7 %

Company

Ecolab Gulf FZE
P.O. Box 17063
Jebel Ali Free Zone Area, Near Container Terminal 3 - North Zone
Dubai
UAE
00971 4 8014444 Customer Services, 00971 48146800 00971 4
8014000 Reception phone numbers

Nalco Egypt Trading
5th Settlement, South 90th St.
The Address Building No 67th – 1st floor
New Cairo, Cairo, Egypt11835
0020 2 25 37 1195,

Ecolab Maroc S.A.R.L.
Batiment, Lot. Mounir 1, Parc Industriel
Attawfik
Route 1029
Sidi Maarouf, Casablanca, Morocco
00212 22 58 25 30 - 35,

Emergency telephone : +32-(0)3-575-5555 Trans-European
number

Issuing date : 12.10.2019

Section: 2. HAZARDS IDENTIFICATION

GHS Classification

Product AS SOLD

Corrosive to metals : Category 1

Acute toxicity (Inhalation) : Category 4

Skin corrosion : Category 1A

Serious eye damage : Category 1

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

Product AT USE DILUTION

Skin corrosion : Category 1A

Serious eye damage : Category 1

SAFETY DATA SHEET

QUIK FILL 32 FLOOR STRIPPER

GHS Label element

Product AS SOLD

Hazard pictograms



Signal Word

: Danger

Hazard Statements

: May be corrosive to metals.
Causes severe skin burns and eye damage.
Harmful if inhaled.
May cause respiratory irritation.

Precautionary Statements

: **Prevention:**

Keep only in original container. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician. Wash contaminated clothing before reuse. Absorb spillage to prevent material damage.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Store in corrosive resistant container with a resistant inner liner.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Product AT USE DILUTION

Hazard pictograms



Signal Word

: Danger

Hazard Statements

: Causes severe skin burns and eye damage.

Precautionary Statements

: **Prevention:**

Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

SAFETY DATA SHEET

QUIK FILL 32 FLOOR STRIPPER

Wash contaminated clothing before reuse.

Storage:

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Product AS SOLD

Other hazards : None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

Product AS SOLD

Pure substance/mixture : Mixture

Chemical Name	CAS-No.	Concentration: (%)
2-butoxyethanol	111-76-2	10 - 30
monoethanolamine	141-43-5	5 - 10
sodium hydroxide	1310-73-2	5 - 10
Sodium Xylenesulfonate	1300-72-7	1 - 5
alcohols, c12-16, ethoxylated	68551-12-2	1 - 5

Product AT USE DILUTION

Chemical Name	CAS-No.	Concentration: (%)
2-butoxyethanol	111-76-2	1 - 5
monoethanolamine	141-43-5	1 - 5
sodium hydroxide	1310-73-2	0.1 - 1

Section: 4. FIRST AID MEASURES

Product AS SOLD

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
- If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention.
- Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal protective equipment.
- Notes to physician : Treat symptomatically.
- Most important symptoms and effects, both acute and delayed : See Section 11 for more detailed information on health effects and symptoms.

Product AT USE DILUTION

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use

SAFETY DATA SHEET

QUIK FILL 32 FLOOR STRIPPER

	a mild soap if available. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
If swallowed	: Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.
If inhaled	: Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

Section: 5. FIREFIGHTING MEASURES

Product AS SOLD

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	: None known.
Specific hazards during firefighting	: Not flammable or combustible.
Hazardous combustion products	: Decomposition products may include the following materials: Carbon oxides nitrogen oxides (NOx) Sulphur oxides metal oxides
Special protective equipment for firefighters	: Use personal protective equipment.
Specific extinguishing methods	: Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

Product AS SOLD

Personal precautions, protective equipment and emergency procedures	: Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.
Environmental precautions	: Do not allow contact with soil, surface or ground water.
Methods and materials for containment and cleaning up	: Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

Product AT USE DILUTION

Personal precautions, protective equipment and emergency procedures	: Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they
---	---

SAFETY DATA SHEET

QUIK FILL 32 FLOOR STRIPPER

must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Do not allow contact with soil, surface or ground water.

Methods and materials for containment and cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

Section: 7. HANDLING AND STORAGE

Product AS SOLD

Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Do not breathe dust/fume/gas/mist/vapours/spray. Use only with adequate ventilation. Wash hands thoroughly after handling.

Conditions for safe storage : Do not store near acids. Keep out of reach of children. Store in suitable labeled containers.

Storage temperature : 15 °C to 45 °C

Product AT USE DILUTION

Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Do not breathe dust/fume/gas/mist/vapours/spray. Use only with adequate ventilation. Wash hands thoroughly after handling.

Conditions for safe storage : Do not store near acids. Keep out of reach of children. Store in suitable labeled containers.

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Product AS SOLD

Components with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
2-butoxyethanol	111-76-2	TWA OEL-CL	25 ppm 120 mg/m ³	ZA OEL
		TWA OEL-RL	25 ppm 120 mg/m ³	ZA OEL
2-butoxyethanol	111-76-2	TWA	25 ppm 121 mg/m ³	BH OEL
2-butoxyethanol	111-76-2	STEL 15 min	50 ppm 246 mg/m ³	TR OEL
		TWA (8 Hour)	20 ppm 98 mg/m ³	TR OEL
2-butoxyethanol	111-76-2	TWA	20 ppm 97 mg/m ³	ARE OEL
monoethanolamine	141-43-5	TWA OEL-RL	3 ppm 8 mg/m ³	ZA OEL
		STEL OEL-RL	6 ppm 15 mg/m ³	ZA OEL
monoethanolamine	141-43-5	TWA	3 ppm 7.5 mg/m ³	BH OEL

SAFETY DATA SHEET

QUIK FILL 32 FLOOR STRIPPER

		STEL	6 ppm 15 mg/m3	BH OEL
monoethanolamine	141-43-5	STEL 15 min	3 ppm 7.6 mg/m3	TR OEL
		TWA (8 Hour)	1 ppm 2.5 mg/m3	TR OEL
monoethanolamine	141-43-5	TWA	3 ppm 7.5 mg/m3	ARE OEL
		STEL	6 ppm 15 mg/m3	ARE OEL
sodium hydroxide	1310-73-2	STEL OEL-RL	2 mg/m3	ZA OEL
sodium hydroxide	1310-73-2	CLV	2 mg/m3	BH OEL
sodium hydroxide	1310-73-2	Ceiling limit	2 mg/m3	ARE OEL

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

Personal protective equipment

Eye protection : Wear eye protection/face protection.

Hand protection : Wear the following personal protective equipment:
Standard glove type.
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin protection : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing

Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use.
Wash face, hands and any exposed skin thoroughly after handling.
Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Product AT USE DILUTION

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

Personal protective equipment

Eye protection : Wear eye protection/face protection.

Hand protection : Wear the following personal protective equipment:
Standard glove type.
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin protection : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing

Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

SAFETY DATA SHEET

QUIK FILL 32 FLOOR STRIPPER

	Product AS SOLD	Product AT USE DILUTION
Appearance	: liquid	liquid
Colour	: red	light pink
Odour	: pungent	pungent
pH	: 13.25, (100 %)	12.7 - 13.4
Flash point	: Not applicable.	
Odour Threshold	: no data available	
Melting point/freezing point	: no data available	
Initial boiling point and boiling range	: 100 °C	
Evaporation rate	: no data available	
Flammability (solid, gas)	: Not applicable.	
Upper explosion limit	: no data available	
Lower explosion limit	: no data available	
Vapour pressure	: no data available	
Relative vapour density	: no data available	
Relative density	: 1.05	
Water solubility	: no data available	
Solubility in other solvents	: no data available	
Partition coefficient: n-octanol/water	: no data available	
Auto-ignition temperature	: no data available	
Thermal decomposition	: no data available	
Viscosity, kinematic	: no data available	
Explosive properties	: no data available	
Oxidizing properties	: no data available	
Molecular weight	: no data available	
VOC	: no data available	

Section: 10. STABILITY AND REACTIVITY

Product AS SOLD

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reaction known under conditions of normal use.
Conditions to avoid	: None known.
Incompatible materials	: Acids Metals
Hazardous decomposition products	: Decomposition products may include the following materials: Carbon oxides

SAFETY DATA SHEET

QUIK FILL 32 FLOOR STRIPPER

nitrogen oxides (NOx)
Sulphur oxides
metal oxides

Section: 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Potential Health Effects

Product AS SOLD

Eyes : Causes serious eye damage.

Skin : Causes severe skin burns.

Ingestion : Causes digestive tract burns.

Inhalation : May cause respiratory tract irritation. Harmful if inhaled. May cause nose, throat, and lung irritation.

Chronic Exposure : Health injuries are not known or expected under normal use.

Product AT USE DILUTION

Eyes : Causes serious eye damage.

Skin : Causes severe skin burns.

Ingestion : Causes digestive tract burns.

Inhalation : May cause nose, throat, and lung irritation.

Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Product AS SOLD

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Pain, Corrosion

Ingestion : Corrosion, Abdominal pain

Inhalation : Respiratory irritation, Cough

Product AT USE DILUTION

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Pain, Corrosion

Ingestion : Corrosion, Abdominal pain

Inhalation : Respiratory irritation, Cough

Toxicity

Product AS SOLD

Product

Acute oral toxicity : Acute toxicity estimate : 3,695 mg/kg

SAFETY DATA SHEET

QUIK FILL 32 FLOOR STRIPPER

Acute inhalation toxicity	: Acute toxicity estimate : > 1 mg/l Test atmosphere: dust/mist
Acute dermal toxicity	: Acute toxicity estimate : 3,095 mg/kg
Skin corrosion/irritation	: Corrosive
Serious eye damage/eye irritation	: no data available
Respiratory or skin sensitization	: no data available
Carcinogenicity	: no data available
Reproductive effects	: no data available
Germ cell mutagenicity	: no data available
Teratogenicity	: no data available
STOT - single exposure	: no data available
STOT - repeated exposure	: no data available
Aspiration toxicity	: no data available

Section: 12. ECOLOGICAL INFORMATION

Product AS SOLD Ecotoxicity

Environmental Effects : Harmful to aquatic life.

Product

Toxicity to fish : no data available
Toxicity to daphnia and other aquatic invertebrates : no data available
Toxicity to algae : no data available

Components

Toxicity to fish : 2-butoxyethanol
96 h LC50: 1,474 mg/l

alcohols, c12-16, ethoxylated
LC50: 1.5 mg/l

Components

Toxicity to daphnia and other aquatic invertebrates : 2-butoxyethanol
48 h EC50: 690 mg/l

monoethanolamine
48 h LC50: 65 mg/l

sodium hydroxide
48 h EC50: 40 mg/l

Components

Toxicity to algae : 2-butoxyethanol
72 h EC50: 911 mg/l

Sodium Xylenesulfonate

SAFETY DATA SHEET

QUIK FILL 32 FLOOR STRIPPER

96 h EC50: 230 mg/l

Persistence and degradability

Product AS SOLD

Poorly biodegradable

Product AT USE DILUTION

Poorly biodegradable

Bioaccumulative potential

no data available

Mobility in soil

no data available

Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Product AS SOLD

- Disposal methods : Do not contaminate ponds, waterways or ditches with chemical or used container. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.
- Disposal considerations : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

Product AT USE DILUTION

- Disposal methods : Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.
- Disposal considerations : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

Section: 14. TRANSPORT INFORMATION

Product AS SOLD

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

- UN number : 1719
- UN proper shipping name : CAUSTIC ALKALI LIQUID, N.O.S.
(sodium hydroxide, monoethanolamine)
- Transport hazard class(es) : 8
- Packing group : II
- Environmental hazards : No

SAFETY DATA SHEET

QUIK FILL 32 FLOOR STRIPPER

Special precautions for user : None

Air transport (IATA)

UN number : 1719
Description of the goods : Caustic alkali liquid, n.o.s.
(sodium hydroxide, monoethanolamine)
Class : 8
Packing group : II
Environmentally hazardous : No

Sea transport (IMDG/IMO)

UN number : 1719
Description of the goods : CAUSTIC ALKALI LIQUID, N.O.S.
(sodium hydroxide, monoethanolamine)
Class : 8
Packing group : II
Marine pollutant : No


Section: 15. REGULATORY INFORMATION

For Regulatory information please contact your Ecolab sales representative.

Section: 16. OTHER INFORMATION

Product AS SOLD

NFPA:




HMIS III:

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Product AT USE DILUTION

NFPA:



HMIS III:

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Issuing date : 12.10.2019
Version : 1.1

SAFETY DATA SHEET

QUIK FILL 32 FLOOR STRIPPER

Prepared by : Regulatory Affairs

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.