

Section: 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : ECOBRITE POWER PLUS

Other means of identification : Not applicable.

Recommended use : Laundry detergent

Restrictions on use : Reserved for industrial and professional use.

Product dilution information : No dilution information provided.

Company

Ecolab Gulf FZE
P.O. Box 17063
Jebel Ali Free Zone Area, Near Container Terminal 3 - North Zone
Dubai
UAE
00971 4 8014444 Customer Services, 00971 48146800 00971 4
8014000 Reception phone numbers

Nalco Egypt Trading
5th Settlement, South 90th St.
The Address Building No 67th – 1st floor
New Cairo, Cairo, Egypt11835
0020 2 25 37 1195,

Ecolab Maroc S.A.R.L.
Batiment, Lot. Mounir 1, Parc Industriel
Attawfik
Route 1029
Sidi Maarouf, Casablanca, Morocco
00212 22 58 25 30 - 35,

Emergency telephone : +32-(0)3-575-5555 Trans-European
number

Issuing date : 23.01.2022

Section: 2. HAZARDS IDENTIFICATION**GHS Classification**

Acute toxicity (Oral) : Category 4
Skin irritation : Category 2
Serious eye damage : Category 1

GHS Label element

Hazard pictograms :



Signal Word : Danger

SAFETY DATA SHEET

ECOBRITE POWER PLUS

- Hazard Statements : Harmful if swallowed.
Causes skin irritation.
Causes serious eye damage.
- Precautionary Statements : **Prevention:**
Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/ eye protection/ face protection.
Response:
IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
Disposal:
Dispose of contents/ container to an approved waste disposal plant.
- Other hazards : None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

Pure substance/mixture : Mixture

Chemical Name	CAS-No.	Concentration: (%)
Alcohols, C13-15, branched and linear, ethoxylated	157627-86-6	30 - 60
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs	85536-14-7	5 - 10
Dipropylene glycol methyl ether	34590-94-8	5 - 10
triethanolamine	102-71-6	1 - 5
sodium hydroxide	1310-73-2	0.1 - 1

Section: 4. FIRST AID MEASURES

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
- If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.
- Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal protective equipment.
- Notes to physician : Treat symptomatically.
- Most important symptoms and effects, both acute and delayed : See Section 11 for more detailed information on health effects and symptoms.

SAFETY DATA SHEET

ECOBRITE POWER PLUS

Section: 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : None known.
- Specific hazards during firefighting : Not flammable or combustible.
- Hazardous combustion products : Decomposition products may include the following materials:
Carbon oxides
Sulphur oxides
nitrogen oxides (NOx)
- Special protective equipment for firefighters : Use personal protective equipment.
- Specific extinguishing methods : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Do not allow contact with soil, surface or ground water.
- Methods and materials for containment and cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

Section: 7. HANDLING AND STORAGE

- Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Do not breathe dust/fume/gas/mist/vapours/spray. Use only with adequate ventilation. Wash hands thoroughly after handling. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).
- Conditions for safe storage : Keep out of reach of children. Store in suitable labeled containers.
- Storage temperature : 5 °C to 40 °C

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

SAFETY DATA SHEET

ECOBRITE POWER PLUS

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
Dipropylene glycol methyl ether	34590-94-8	STEL	150 ppm 909 mg/m ³	BH OEL
		TWA	100 ppm 606 mg/m ³	BH OEL
Dipropylene glycol methyl ether	34590-94-8	TWA	100 ppm 606 mg/m ³	ARE OEL
		STEL	150 ppm 909 mg/m ³	ARE OEL
Dipropylene glycol methyl ether	34590-94-8	STEL	150 ppm 900 mg/m ³	NIOSH REL
		TWA	100 ppm 600 mg/m ³	NIOSH REL
		TWA	100 ppm 600 mg/m ³	OSHA Z1
triethanolamine	102-71-6	TWA	5 mg/m ³	BH OEL
triethanolamine	102-71-6	TWA	5 mg/m ³	ARE OEL
triethanolamine	102-71-6	TWA	5 mg/m ³	ACGIH
sodium hydroxide	1310-73-2	CLV	2 mg/m ³	BH OEL
sodium hydroxide	1310-73-2	Ceiling limit	2 mg/m ³	ARE OEL
sodium hydroxide	1310-73-2	Ceiling	2 mg/m ³	ACGIH
		Ceiling	2 mg/m ³	NIOSH REL
		TWA	2 mg/m ³	OSHA Z1

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

Personal protective equipment

Eye protection : Wear eye protection/face protection.

Hand protection : Recommended preventive skin protection
Gloves
Nitrile rubber
butyl-rubber
Breakthrough time: 1 – 4 hours
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin protection : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing

Respiratory protection : None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

SAFETY DATA SHEET

ECOBRITE POWER PLUS

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: light yellow
Odour	: slight
pH	: 7.8, (100 %)
Flash point	: Not applicable.
Odour Threshold	: no data available
Melting point/freezing point	: no data available
Initial boiling point and boiling range	: no data available
Evaporation rate	: no data available
Flammability (solid, gas)	: Not applicable.
Upper explosion limit	: no data available
Lower explosion limit	: no data available
Vapour pressure	: no data available
Relative vapour density	: no data available
Relative density	: 1.03
Water solubility	: soluble
Solubility in other solvents	: no data available
Partition coefficient: n-octanol/water	: no data available
Auto-ignition temperature	: no data available
Thermal decomposition	: no data available
Viscosity, kinematic	: no data available
Explosive properties	: no data available
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Molecular weight	: no data available
VOC	: no data available

Section: 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reaction known under conditions of normal use.
Conditions to avoid	: None known.
Incompatible materials	: None known.
Hazardous decomposition products	: In case of fire hazardous decomposition products may be produced such as: Carbon oxides

SAFETY DATA SHEET

ECOBRITE POWER PLUS

Sulphur oxides
metal oxides
nitrogen oxides (NOx)

Section: 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Potential Health Effects

Eyes : Causes serious eye damage.

Skin : Causes severe skin burns. Causes skin irritation.

Ingestion : Harmful if swallowed. Causes digestive tract burns.

Inhalation : May cause nose, throat, and lung irritation.

Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Pain, Irritation, Corrosion

Ingestion : Corrosion, Abdominal pain

Inhalation : Respiratory irritation, Cough

Toxicity

Product

Acute oral toxicity : Acute toxicity estimate : 1,411 mg/kg

Acute inhalation toxicity : no data available

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Skin corrosion/irritation : no data available

Serious eye damage/eye irritation : no data available

Respiratory or skin sensitization : no data available

Carcinogenicity : no data available

Reproductive effects : no data available

Germ cell mutagenicity : no data available

Teratogenicity : no data available

STOT - single exposure : no data available

STOT - repeated exposure : no data available

Aspiration toxicity : no data available

Section: 12. ECOLOGICAL INFORMATION

Toxicity

SAFETY DATA SHEET

ECOBRITE POWER PLUS

Environmental Effects : Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Product

Toxicity to fish : no data available

Toxicity to daphnia and other aquatic invertebrates : no data available

Toxicity to algae : no data available

Components

Toxicity to fish : Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs
96 h LC50 Fish: 1.67 mg/l

Dipropylene glycol methyl ether
96 h LC50 Poecilia reticulata (guppy): > 100 mg/l

triethanolamine
96 h LC50: 11,800 mg/l

Components

Toxicity to daphnia and other aquatic invertebrates : Dipropylene glycol methyl ether
48 h LC50 Daphnia magna (Water flea): 1,919 mg/l

triethanolamine
48 h EC50: 609.88 mg/l

sodium hydroxide
48 h EC50: 40 mg/l

Components

Toxicity to algae : Dipropylene glycol methyl ether
72 h EC50 Pseudokirchneriella subcapitata (green algae): > 969 mg/l

triethanolamine
72 h EC50: > 100 mg/l

Persistence and degradability

Biodegradable

Bioaccumulative potential

no data available

Mobility in soil

no data available

Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Disposal methods : Do not contaminate ponds, waterways or ditches with chemical or used container. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of contents/container in accordance with local regulations Dispose of wastes in an approved waste disposal facility.

Disposal considerations : Dispose of as unused product. Empty containers should be taken to

SAFETY DATA SHEET

ECOBRITE POWER PLUS

an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

Section: 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

UN number : Not dangerous goods
UN proper shipping name : Not dangerous goods
Transport hazard class(es) : Not dangerous goods
Packing group : Not dangerous goods
Environmental hazards : Not dangerous goods
Special precautions for user : Not dangerous goods

Air transport (IATA)

Not dangerous goods

Sea transport (IMDG/IMO)


Not dangerous goods

Section: 15. REGULATORY INFORMATION

For Regulatory information please contact your Ecolab sales representative.

Section: 16. OTHER INFORMATION

NFPA:



HMIS III:

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Issuing date : 23.01.2022
version : 1.0
Prepared by : Regulatory Affairs

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

SAFETY DATA SHEET

ECOBRITE POWER PLUS

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.