

Section: 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : P3-LUBODRIVE TK

Other means of identification : Not applicable.

Recommended use : Lubricant

Restrictions on use : Reserved for industrial and professional use.

Product dilution information : No dilution information provided.

Company

Ecolab Gulf FZE
P.O. Box 17063
Jebel Ali Free Zone Area, Near Container Terminal 3 - North Zone
Dubai
UAE
00971 4 8014444 Customer Services, 00971 48146800 00971 4
8014000 Reception phone numbers

Nalco Egypt Trading
5th Settlement, South 90th St.
The Address Building No 67th – 1st floor
New Cairo, Cairo, Egypt11835
0020 2 25 37 1195,

Ecolab Maroc S.A.R.L.
Batiment, Lot. Mounir 1, Parc Industriel
Attawfik
Route 1029
Sidi Maarouf, Casablanca, Morocco
00212 22 58 25 30 - 35,

Emergency telephone number : +32-(0)3-575-5555

Issuing date : 01.08.2019

Section: 2. HAZARDS IDENTIFICATION
GHS Classification

Skin irritation : Category 2
Serious eye damage : Category 1

GHS Label element

Hazard pictograms :



Signal Word : Danger

Hazard Statements : Causes skin irritation.

SAFETY DATA SHEET

P3-LUBODRIVE TK

Causes serious eye damage.

- Precautionary Statements : **Prevention:**
Wash skin thoroughly after handling. Wear protective gloves/ eye protection/ face protection.
Response:
IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
- Other hazards** : Do not mix with bleach or other chlorinated products – will cause chlorine gas.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

Pure substance/mixture : Mixture

Chemical Name	CAS-No.	Concentration: (%)
Alkylamine acetate	7173-67-3	5 - 10
Isotridecanol, ethoxylated	69011-36-5	5 - 10
Alkylamine acetate	61791-64-8	1 - 5
Alkylamine ethoxylates	61791-14-8	1 - 5
Acetic acid	64-19-7	1 - 5

Section: 4. FIRST AID MEASURES

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Get medical attention if irritation develops and persists.
- If swallowed : Rinse mouth. Get medical attention if symptoms occur.
- If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.
- Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal protective equipment.
- Notes to physician : Treat symptomatically.
- Most important symptoms and effects, both acute and delayed : See Section 11 for more detailed information on health effects and symptoms.

Section: 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : None known.

SAFETY DATA SHEET

P3-LUBODRIVE TK

- Specific hazards during firefighting : Not flammable or combustible.
- Hazardous combustion products : Decomposition products may include the following materials:
Carbon oxides
nitrogen oxides (NOx)
- Special protective equipment for firefighters : Use personal protective equipment.
- Specific extinguishing methods : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Do not allow contact with soil, surface or ground water.
- Methods and materials for containment and cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

Section: 7. HANDLING AND STORAGE

- Advice on safe handling : Do not get in eyes, on skin, or on clothing. Wash hands thoroughly after handling. Do not mix with bleach or other chlorinated products – will cause chlorine gas. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).
- Conditions for safe storage : Keep out of reach of children. Store in suitable labeled containers.
- Storage temperature : 5 °C to 40 °C

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
Acetic acid	64-19-7	TWA OEL-RL	10 ppm 25 mg/m ³	ZA OEL
		STEL OEL-RL	15 ppm 37 mg/m ³	ZA OEL
Acetic acid	64-19-7	TWA	10 ppm 25 mg/m ³	BH OEL

SAFETY DATA SHEET

P3-LUBODRIVE TK

		STEL	15 ppm 37 mg/m ³	BH OEL
Acetic acid	64-19-7	TWA (8 Hour)	10 ppm 25 mg/m ³	TR OEL
		TWA	10 ppm 25 mg/m ³	2017/164/EU
		STEL	20 ppm 50 mg/m ³	2017/164/EU
Acetic acid	64-19-7	TWA	10 ppm 25 mg/m ³	ARE OEL
		STEL	15 ppm 37 mg/m ³	ARE OEL

Engineering measures : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal protective equipment

Eye protection : Wear eye protection/face protection.

Hand protection : Wear the following personal protective equipment:
Standard glove type.
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin protection : No special protective equipment required.

Respiratory protection : No personal respiratory protective equipment normally required.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : light yellow

Odour : amine-like

pH : 6.4 - 6.8, (100 %)

Flash point : Not applicable.

Odour Threshold : no data available

Melting point/freezing point : no data available

Initial boiling point and boiling range : > 100 °C

Evaporation rate : no data available

Flammability (solid, gas) : no data available

Upper explosion limit : no data available

Lower explosion limit : no data available

Vapour pressure : no data available

Relative vapour density : no data available

SAFETY DATA SHEET

P3-LUBODRIVE TK

Relative density	: 0.99 - 1.01
Water solubility	: soluble
Solubility in other solvents	: no data available
Partition coefficient: n-octanol/water	: no data available
Auto-ignition temperature	: no data available
Thermal decomposition	: no data available
Viscosity, kinematic	: no data available
Explosive properties	: no data available
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Molecular weight	: no data available
VOC	: no data available

Section: 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Do not mix with bleach or other chlorinated products – will cause chlorine gas.
Conditions to avoid	: None known.
Incompatible materials	: None known.
Hazardous decomposition products	: In case of fire hazardous decomposition products may be produced such as: Carbon oxides nitrogen oxides (NOx)

Section: 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Potential Health Effects

Eyes	: Causes serious eye damage.
Skin	: Causes skin irritation.
Ingestion	: Health injuries are not known or expected under normal use.
Inhalation	: Health injuries are not known or expected under normal use.
Chronic Exposure	: Health injuries are not known or expected under normal use.

Experience with human exposure

Eye contact	: Redness, Pain, Corrosion
Skin contact	: Redness, Irritation

SAFETY DATA SHEET

P3-LUBODRIVE TK

Ingestion : No symptoms known or expected.

Inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled.

No symptoms known or expected.

Toxicity

Product

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Acute inhalation toxicity : 4 h Acute toxicity estimate : > 200 mg/l
Test atmosphere: dust/mist

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Skin corrosion/irritation : no data available

Serious eye damage/eye irritation : no data available

Respiratory or skin sensitization : no data available

Carcinogenicity : no data available

Reproductive effects : no data available

Germ cell mutagenicity : no data available

Teratogenicity : no data available

STOT - single exposure : no data available

STOT - repeated exposure : no data available

Aspiration toxicity : no data available

Section: 12. ECOLOGICAL INFORMATION

Ecotoxicity

Environmental Effects : Toxic to aquatic life.

Product

Toxicity to fish : no data available

Toxicity to daphnia and other aquatic invertebrates : no data available

Toxicity to algae : no data available

Components

Toxicity to fish : Isotridecanol, ethoxylated
LC50: 5.33 mg/l

Alkylamine ethoxylates
96 h LC50 Leuciscus idus (Golden orfe): > 1 mg/l

Acetic acid
96 h LC50 Oncorhynchus mykiss (rainbow trout): > 1,000 mg/l

Components

Toxicity to daphnia and other : Alkylamine acetate

SAFETY DATA SHEET

P3-LUBODRIVE TK

aquatic invertebrates

48 h EC50: 0.16 mg/l

Alkylamine ethoxylates

LC50 Daphnia magna (Water flea): > 10 mg/l

Acetic acid

48 h EC50 Daphnia magna (Water flea): 39.6 mg/l

Components

Toxicity to algae

: Acetic acid

72 h EC50 Skeletonema costatum (marine diatom): > 1,000 mg/l

Persistence and degradability

Poorly biodegradable

Bioaccumulative potential

no data available

Mobility in soil

no data available

Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Disposal methods

: Do not contaminate ponds, waterways or ditches with chemical or used container. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.

Disposal considerations

: Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

Section: 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

UN number : Not dangerous goods

UN proper shipping name : Not dangerous goods

Transport hazard class(es) : Not dangerous goods

Packing group : Not dangerous goods

Environmental hazards : Not dangerous goods

Special precautions for user : Not dangerous goods

Air transport (IATA)

Not dangerous goods

SAFETY DATA SHEET

P3-LUBODRIVE TK

Sea transport (IMDG/IMO)


Not dangerous goods

Section: 15. REGULATORY INFORMATION

For Regulatory information please contact your Ecolab sales representative.

Section: 16. OTHER INFORMATION

NFPA:



HMIS III:

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Issuing date : 01.08.2019
Version : 1.1
Prepared by : Regulatory Affairs

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.