

Material Safety Data Sheet

MAXX FLOOR FINISH REMOVER



1. Product and company identification

Trade name of product : MAXX FLOOR FINISH REMOVER

Product use : Floor Cleaner

Product dilution information : Up to 16 oz/gal or 125 mL/L in water

Supplier's information : Ecolab Inc. Institutional Division
370 N. Wabasha Street
St. Paul, MN 55102
1-800-352-5326

Code : 912544-05

Date of issue : 19-February-2013

EMERGENCY HEALTH INFORMATION: 1-800-328-0026

Outside United States and Canada CALL 1-651-222-5352 (in USA)

2. Hazards identification

Product AS SOLD

Physical state : Liquid.

Emergency overview : DANGER !

CAUSES DIGESTIVE TRACT, EYE AND SKIN BURNS.

CAUSES RESPIRATORY TRACT IRRITATION.

Do not ingest. Do not get in eyes, on skin or on clothing. Avoid breathing vapors, spray or mists. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

Product AT USE DILUTION

Liquid.

WARNING !

CAUSES EYE AND SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION.

Avoid contact with eyes, skin and clothing. Avoid breathing vapors, spray or mists. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

Potential acute health effects

Product AS SOLD

Eyes : Corrosive to eyes.

Skin : Corrosive to the skin.

Inhalation : Severely irritating to the respiratory system.

Ingestion : Causes burns to mouth, throat and stomach.

Product AT USE DILUTION

Severely irritating to eyes.

Severely irritating to the skin.

Moderately irritating to the respiratory system.

No known significant effects or critical hazards.

See toxicological information (Section 11)

3. Composition/information on ingredients

Product AS SOLD

Name

2-hexyloxyethanol
POTASSIUM HYDROXIDE
BENZYL ALCOHOL
ETHANOLAMINE
POTASSIUM OLEATE

CAS number

112-25-4
1310-58-3
100-51-6
141-43-5
143-18-0

% by weight

11
4
20 - 50
5 - 20
5 - 20

3. Composition/information on ingredients

Product AT USE DILUTION

<u>Name</u>	<u>CAS number</u>	<u>% by weight</u>
2-hexyloxyethanol	112-25-4	1
POTASSIUM HYDROXIDE	1310-58-3	<1
BENZYL ALCOHOL	100-51-6	1 - 5
ETHANOLAMINE	141-43-5	1 - 5
POTASSIUM OLEATE	143-18-0	1 - 5

4. First aid measures

	Product AS SOLD	Product AT USE DILUTION
Eye contact	: In case of contact, immediately flush eyes with cool running water. Remove contact lenses and continue flushing with plenty of water for at least 15 minutes. Get medical attention immediately.	In case of contact, immediately flush eyes with cool running water. Remove contact lenses and continue flushing with plenty of water for at least 15 minutes. Get medical attention.
Skin contact	: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Clean shoes thoroughly before reuse.	In case of contact, immediately flush skin with plenty of water. Continue to rinse for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Inhalation	: If inhaled, remove to fresh air. If exposed person is not breathing, give artificial respiration or oxygen applied by trained personnel. Get medical attention.	If inhaled, remove to fresh air.
Ingestion	: If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.	Get medical attention if symptoms occur.

5. Fire-fighting measures

Product AS SOLD

Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides
Fire-fighting media and instructions	: Use an extinguishing agent suitable for the surrounding fire. Dike area of fire to prevent runoff. In a fire or if heated, a pressure increase will occur and the container may burst.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

6. Accidental release measures

	Product AS SOLD	Product AT USE DILUTION
Personal precautions	: Initiate company's spill response procedures immediately. Keep people out of area. Put on appropriate personal protective equipment (see section 8). Do not touch or walk through spilled material.	Use personal protective equipment as required.
Environmental precautions	: Avoid contact of spilled material and runoff with soil and surface waterways.	Avoid contact of large amounts of spilled material and runoff with soil and surface waterways.
Methods for cleaning up	: Follow company's spill procedures. Keep people away from spill. Put on appropriate personal protective equipment (see section 8). Absorb/neutralize liquid material. Use a tool to scoop up solid or absorbed material and put into appropriate labeled container. Use a water rinse for final clean-up.	Use a water rinse for final clean-up.

7. Handling and storage

	Product AS SOLD	Product AT USE DILUTION
Handling	: Do not ingest. Do not get in eyes, on skin, or on clothing. Do not breathe vapor or spray. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.	Avoid contact with eyes, skin and clothing. Avoid breathing vapors, spray or mists. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.
Storage	: Keep out of reach of children. Store in a closed container. Keep container tightly closed. Store between the following temperatures: 0 and 50°C	Keep out of reach of children. Store in a closed container.

8. Exposure controls/personal protection

	Product AS SOLD	Product AT USE DILUTION
Engineering measures	: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Personal protection		
Eyes	: Use chemical splash goggles. For continued or severe exposure wear a face shield over the goggles.	Wear eye protection.
Hands	: Use chemical-resistant, impervious gloves.	Use chemical-resistant, impervious gloves.
Skin	: Use synthetic apron, other protective equipment as necessary to prevent skin contact.	No protective equipment is needed under normal use conditions.
Respiratory	: Wear appropriate respirator when ventilation is inadequate and occupational exposure limits are exceeded.	Avoid breathing vapors, spray or mists.

8. Exposure controls/personal protection

Ingredient	Exposure limits
BENZYL ALCOHOL	AIHA WEEL (United States, 10/2011). TWA: 10 ppm 8 hours.
ETHANOLAMINE	ACGIH TLV (United States, 3/2012). STEL: 15 mg/m ³ 15 minutes. STEL: 6 ppm 15 minutes. TWA: 7.5 mg/m ³ 8 hours. TWA: 3 ppm 8 hours. OSHA PEL (United States, 6/2010). TWA: 6 mg/m ³ 8 hours. TWA: 3 ppm 8 hours. NIOSH REL (United States, 6/2009). TWA: 3 ppm 10 hours. TWA: 8 mg/m ³ 10 hours. STEL: 6 ppm 15 minutes. STEL: 15 mg/m ³ 15 minutes.
POTASSIUM HYDROXIDE	ACGIH TLV (United States, 3/2012). C: 2 mg/m ³ NIOSH REL (United States, 6/2009). TWA: 2 mg/m ³ 10 hours.

9. Physical and chemical properties

Product AS SOLD		Product AT USE DILUTION
Physical state	: Liquid.	Liquid.
Flash point	: 93 °C (Closed cup)	> 100°C
Color	: Amber [Light]	Hazy liquid [Light]
Odor	: Amine-like	Amine-like
pH	: 14 [Conc. (% w/w): 100%]	12 to 13
Boiling/condensation point	: >100°C (>212°F)	
Relative density	: 1.046	
Dispersibility properties	: Easily dispersible in the following materials: cold water and hot water.	
Solubility	: Easily soluble in the following materials: cold water and hot water.	

10. Stability and reactivity

Product AS SOLD

Stability	: The product is stable. Under normal conditions of storage and use, hazardous polymerization will not occur.
Reactivity	: Highly reactive or incompatible with the following materials: acids. Reactive or incompatible with the following materials: metals.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hazardous polymerization	: Under normal conditions of storage and use, hazardous polymerization will not occur.

11. Toxicological information

Potential acute health effects

Product AS SOLD

Eyes	: Corrosive to eyes.
Skin	: Corrosive to the skin.
Inhalation	: Severely irritating to the respiratory system.
Ingestion	: Causes burns to mouth, throat and stomach.

Product AT USE DILUTION

Severely irritating to eyes.
Severely irritating to the skin.
Moderately irritating to the respiratory system.
No known significant effects or critical hazards.

Product AS SOLD

Other adverse effects

Target organs	: Contains material which may cause damage to the following organs: kidneys, the nervous system, liver, gastrointestinal tract, upper respiratory tract, central nervous system (CNS), testes.
----------------------	--

12. Ecological information

Ecotoxicity	: Not reported
--------------------	----------------

13. Disposal considerations

Product AS SOLD

Waste disposal	: Avoid disposal. Attempt to use product completely in accordance with intended use. Disposal should be in accordance with applicable regional, national and local laws and regulations.
-----------------------	--

Product AT USE DILUTION

Diluted product can be flushed to sanitary sewer. Discard empty container in trash.

14. Transport information

Certain shipping modes or package sizes may have exceptions from the transport regulations. The classification provided may not reflect those exceptions and may not apply to all shipping modes or package sizes.

Product AS SOLD

DOT

DOT Classification	UN1719
DOT Proper shipping name	Caustic alkali liquids, n.o.s. (2-aminoethanol)
Class	8
Packing group	II

IMO/IMDG

IMO/IMDG Classification	UN1719
IMO/IMDG Proper shipping name	CAUSTIC ALKALI LIQUID, N.O.S. (2-aminoethanol)
Class	8
Packing group	II

For transport in bulk, see shipping documents for specific transportation information.

Product AT USE DILUTION

Not intended for transport.

15. Regulatory information

Product AS SOLD

United States

HCS : Corrosive material
 Classification Target organ effects

Product AT USE DILUTION

Irritating material
 Target organ effects

16. Other information

Product AS SOLD

Hazardous Material :
 Information System (U.S.A.)


Health	*	3
Flammability		1
Physical hazards		0

National Fire Protection :
 Association (U.S.A.)



Product AT USE DILUTION

Health	*	2
Flammability		0
Physical hazards		0



Date of issue : 19-February-2013
 Responsible name : Regulatory Affairs
 1-800-352-5326

▣ Indicates information that has changed from previously issued version.

Notice to reader

The above information is believed to be correct with respect to the formula used to manufacture the product in the country of origin. As data, standards, and regulations change, and conditions of use and handling are beyond our control, NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.