

Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
1.1 Product identifier

Product name : DP 2019

Product code : 117764E

Use of the Substance/Mixture : Laundry product

Substance type: : Mixture

For professional users only.

Product dilution information : No dilution information provided.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laundry aid (non-gasing). Automatic process
Laundry aid (non-gasing). Semi automatic process

Recommended restrictions on use : Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : Ecolab Ltd.
PO Box 11; Winnington Avenue
Northwich, Cheshire, United Kingdom CW8 4DX
+ 44 (0)1606 74488
ccs@ecolab.com

1.4 Emergency telephone number

Emergency telephone number : +441618841235
+32-(0)3-575-5555 Trans-European

Date of Compilation/Revision : 15.04.2020
Version : 1.0

Section: 2. HAZARDS IDENTIFICATION
2.1 Classification of the substance or mixture
Classification (REGULATION (EC) No 1272/2008)

Serious eye damage, Category 1 H318

2.2 Label elements
Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



DP 2019

Signal Word : Danger

Hazard Statements : H318 Causes serious eye damage.

Precautionary Statements : **Prevention:**
P280e Wear eye protection/face protection.
Response:
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label:

Alcohols, C13-15, branched and linear, ethoxylated

Additional Labelling:

Special labelling of certain mixtures : Contains: subtilisin, May produce an allergic reaction.

2.3 Other hazards

None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Hazardous components

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration: [%]
Alcohols, C13-15, branched and linear, ethoxylated	157627-86-6 POLYMER	Acute toxicity Category 4; H302 Serious eye damage Category 1; H318 Chronic aquatic toxicity Category 3; H412	>= 10 - < 20
subtilisin	9014-01-1 232-752-2 01-2119480434-38	Acute toxicity Category 4; H302 Skin irritation Category 2; H315 Serious eye damage Category 1; H318 Respiratory sensitization Category 1; H334 Specific target organ toxicity - single exposure Category 3; H335	>= 0.25 - < 0.5
Substances with a workplace exposure limit :			
Propylene glycol	57-55-6 200-338-0 01-2119456809-23	Not Classified;	>= 10 - < 20
glycerin	56-81-5 200-289-5 01-2119471987-18	Not Classified;	>= 0.1 - < 0.25

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section: 4. FIRST AID MEASURES

4.1 Description of first aid measures

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

DP 2019

- | | |
|-------------------------|--|
| In case of skin contact | : Rinse with plenty of water. |
| If swallowed | : Rinse mouth. Get medical attention if symptoms occur. |
| If inhaled | : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur. |

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

- | | |
|-----------|--------------------------|
| Treatment | : Treat symptomatically. |
|-----------|--------------------------|

Section: 5. FIREFIGHTING MEASURES

5.1 Extinguishing media

- | | |
|--------------------------------|---|
| Suitable extinguishing media | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Unsuitable extinguishing media | : None known. |

5.2 Special hazards arising from the substance or mixture

- | | |
|--------------------------------------|---|
| Specific hazards during firefighting | : Not flammable or combustible. |
| Hazardous combustion products | : Depending on combustion properties, decomposition products may include following materials:
Carbon oxides
nitrogen oxides (NOx) |

5.3 Advice for firefighters

- | | |
|---|---|
| Special protective equipment for firefighters | : Use personal protective equipment. |
| Further information | : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes. |

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

- | | |
|------------------------------------|--|
| Advice for non-emergency personnel | : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8. |
| Advice for emergency responders | : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable |

DP 2019

materials.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

6.4 Reference to other sections

See Section 1 for emergency contact information.
For personal protection see section 8.
See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE**7.1 Precautions for safe handling**

Advice on safe handling : Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation. Wash hands thoroughly after handling. Do not breathe spray, vapour. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

Storage temperature : -5 °C to 40 °C

7.3 Specific end uses

Specific use(s) : Laundry aid (non-gasing). Automatic process
Laundry aid (non-gasing). Semi automatic process

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1 Control parameters****Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
------------	---------	-------------------------------	--------------------	-------

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

DP 2019

Propylene glycol	57-55-6	TWA (particles)	10 mg/m3	UKCOSSTD
Further information	16	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.		
		TWA (Total vapour and particles)	150 ppm 474 mg/m3	UKCOSSTD
Further information	16	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.		
subtilisin	9014-01-1	TWA	0.00004 mg/m3	UKCOSSTD
Further information	39	One of the suitable measurement methods is the fluorescence polarisation technique developed by the Health and Safety Laboratory (HSL). The previous limit for subtilisin was based on high-volume static sampling to achieve sufficient sensitivity. However, improvements in the analytical methodology have improved the sensitivity and the WEL for subtilisin reflects this. The limit is based on standard personal sampling (MDHS14/4). Short-term reference period (15 minute) sampling is not appropriate.		
	52+5 3	Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even in tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not include the disease themselves. The latter substances are not classified as asthmagens or respiratory sensitisers. Further information can be found in the HSE publication Asthmagen? Critical assessments of the evidence for agents implicated in occupational asthma.		
	54	Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced to as low as is reasonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance.		
	38	Subtilisins are proteolytic enzymes derived from <i>Bacillus subtilis</i> . They are used in biological washing powders, animal feedstuffs etc. The enzyme preparation contains active enzyme, inactive enzyme and protein residues.		
	Sen	Capable of causing occupational asthma.		
	16	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.		
	55	The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma in the categories shown in Table 1. It should be remembered that other substances not in these tables may cause occupational asthma. HSE's asthma web pages (www.hse.gov.uk/asthma) provide further information.		
glycerin	56-81-5	TWA (Mist)	10 mg/m3	UKCOSSTD
Further information	16	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.		

DNEL

Propylene glycol	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 168 mg/m3 End Use: Workers Exposure routes: Inhalation
------------------	---	--

DP 2019

	Potential health effects: Long-term local effects Value: 10 mg/m³ End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 50 mg/m³ End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 10 mg/m³ End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 213 mg/cm² End Use: Consumers Exposure routes: Ingestion Potential health effects: Long-term systemic effects Value: 85 ppm
--	--

PNEC

Propylene glycol	: Fresh water Value: 260 mg/l Marine water Value: 26 mg/l Intermittent use/release Value: 183 mg/l Fresh water sediment Value: 572 mg/kg Marine sediment Value: 57.2 mg/kg Sewage treatment plant Value: 20000 mg/l Soil Value: 50 mg/kg
------------------	---

8.2 Exposure controls

Appropriate engineering controls

Engineering measures : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Eye/face protection (EN 166) : Safety goggles
Face-shield

Hand protection (EN 374) : No special protective equipment required.

Skin and body protection (EN 14605) : No special protective equipment required.

Respiratory protection (EN 143, 14387) : None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

Environmental exposure controls

General advice : Consider the provision of containment around storage vessels.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: clear, colourless
Odour	: odourless
pH	: 5.0 - 6.0, 100 %
Flash point	: closed cupNot applicable., Does not sustain combustion.
Odour Threshold	: Not applicable and/or not determined for the mixture
Melting point/freezing point	: Not applicable and/or not determined for the mixture
Initial boiling point and boiling range	: > 100 °C
Evaporation rate	: Not applicable and/or not determined for the mixture
Flammability (solid, gas)	: Not applicable and/or not determined for the mixture
Upper explosion limit	: Not applicable and/or not determined for the mixture
Lower explosion limit	: Not applicable and/or not determined for the mixture
Vapour pressure	: Not applicable and/or not determined for the mixture
Relative vapour density	: Not applicable and/or not determined for the mixture
Relative density	: 1.0 - 1.04
Water solubility	: soluble
Solubility in other solvents	: Not applicable and/or not determined for the mixture
Partition coefficient: n-	: Not applicable and/or not determined for the mixture

DP 2019

octanol/water

Auto-ignition temperature : Not applicable and/or not determined for the mixture

Thermal decomposition : Not applicable and/or not determined for the mixture

Viscosity, kinematic : Not applicable and/or not determined for the mixture

Explosive properties : Not applicable and/or not determined for the mixture

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Not applicable and/or not determined for the mixture

Section: 10. STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Depending on combustion properties, decomposition products may include following materials:

Carbon oxides

nitrogen oxides (NO_x)

Section: 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Product

Acute oral toxicity : Acute toxicity estimate : > 2,000 mg/kg

Acute inhalation toxicity : There is no data available for this product.

Acute dermal toxicity : There is no data available for this product.

DP 2019

Skin corrosion/irritation	: There is no data available for this product.
Serious eye damage/eye irritation	: There is no data available for this product.
Respiratory or skin sensitization	: There is no data available for this product.
Carcinogenicity	: There is no data available for this product.
Reproductive effects	: There is no data available for this product.
Germ cell mutagenicity	: There is no data available for this product.
Teratogenicity	: There is no data available for this product.
STOT - single exposure	: There is no data available for this product.
STOT - repeated exposure	: There is no data available for this product.
Aspiration toxicity	: There is no data available for this product.

Components

Acute oral toxicity	: subtilisin LD50 rat: 1,800 mg/kg
	Propylene glycol LD50 rat: 22,000 mg/kg
	glycerin LD50 rat: 18,300 mg/kg

Components

Acute inhalation toxicity	: Propylene glycol 4 h LC50 rat: > 158.5 mg/l Test atmosphere: dust/mist
---------------------------	--

Components

Acute dermal toxicity	: glycerin LD50 rabbit: 23,000 mg/kg
-----------------------	---

Potential Health Effects

Eyes	: Causes serious eye damage.
Skin	: Health injuries are not known or expected under normal use.
Ingestion	: Health injuries are not known or expected under normal use.
Inhalation	: Health injuries are not known or expected under normal use.
Chronic Exposure	: Health injuries are not known or expected under normal use.

Experience with human exposure

Eye contact	: Redness, Pain, Corrosion
-------------	----------------------------

DP 2019

Skin contact : No symptoms known or expected.
Ingestion : No symptoms known or expected.
Inhalation : No symptoms known or expected.

Section: 12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity

Environmental Effects : This product has no known ecotoxicological effects.

Product

Toxicity to fish : no data available
Toxicity to daphnia and other aquatic invertebrates : no data available
Toxicity to algae : no data available

Components

Toxicity to fish : Propylene glycol
96 h LC50: > 10,000 mg/l

glycerin
96 h LC50 Fish: 855 mg/l

Components

Toxicity to daphnia and other aquatic invertebrates : subtilisin
48 h EC50: 1.4 mg/l

Propylene glycol
48 h EC50: 18,340 mg/l

Components

Toxicity to algae : Propylene glycol
96 h EC50: 19,000 mg/l

12.2 Persistence and degradability

Product

Biodegradability : The surfactants contained in the product are biodegradable according to the requirements of the detergent regulation 648/2004/EC

Components

Biodegradability : Alcohols, C13-15, branched and linear, ethoxylated
Result: Readily biodegradable.

subtilisin
Result: Readily biodegradable.

Propylene glycol
Result: Readily biodegradable.

DP 2019

glycerin
Result: Readily biodegradable.

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods

- | | |
|-----------------------------------|---|
| Product | : Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility. |
| Contaminated packaging | : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations. |
| Guidance for Waste Code selection | : Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations. |

Section: 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

DP 2019

14.1 UN number : Not dangerous goods
14.2 UN proper shipping name : Not dangerous goods
14.3 Transport hazard class(es) : Not dangerous goods
14.4 Packing group : Not dangerous goods
14.5 Environmental hazards : Not dangerous goods
14.6 Special precautions for user : Not dangerous goods

Air transport (IATA)

14.1 UN number : Not dangerous goods
14.2 UN proper shipping name : Not dangerous goods
14.3 Transport hazard class(es) : Not dangerous goods
14.4 Packing group : Not dangerous goods
14.5 Environmental hazards : Not dangerous goods
14.6 Special precautions for user : Not dangerous goods

Sea transport (IMDG/IMO)

14.1 UN number : Not dangerous goods
14.2 UN proper shipping name : Not dangerous goods
14.3 Transport hazard class(es) : Not dangerous goods
14.4 Packing group : Not dangerous goods
14.5 Environmental hazards : Not dangerous goods
14.6 Special precautions for user : Not dangerous goods
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not dangerous goods

Section: 15. REGULATORY INFORMATION**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

according to Detergents Regulation EC 648/2004 : 15 % or over but less than 30 %: Non-ionic surfactants
Other constituents: Enzymes
Preservation agents:
2-phenoxyethanol

National Regulations

Take note of Dir 94/33/EC on the protection of young people at work.

Other regulations : The Chemicals (Hazard Information and Packaging for Supply) Regulations.
The Control of Substances Hazardous to Health Regulations.
Health and Safety at Work Act.

15.2 Chemical Safety Assessment

DP 2019

No Chemical Safety Assessment has been carried out on the product.

Section: 16. OTHER INFORMATION**Procedure used to derive the classification according to REGULATION (EC) No 1272/2008**

Classification	Justification
Serious eye damage 1, H318	Calculation method

Full text of H-Statements

H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

ADN – European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR – European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS – Australian Inventory of Chemical Substances; ASTM – American Society for the Testing of Materials; bw – Body weight; CLP – Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR – Carcinogen, Mutagen or Reproductive Toxicant; DIN – Standard of the German Institute for Standardisation; DSL – Domestic Substances List (Canada); ECHA – European Chemicals Agency; EC-Number – European Community number; ECx – Concentration associated with x% response; ELx – Loading rate associated with x% response; EmS – Emergency Schedule; ENCS – Existing and New Chemical Substances (Japan); ErCx – Concentration associated with x% growth rate response; GHS – Globally Harmonized System; GLP – Good Laboratory Practice; IARC – International Agency for Research on Cancer; IATA – International Air Transport Association; IBC – International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 – Half maximal inhibitory concentration; ICAO – International Civil Aviation Organization; IECSC – Inventory of Existing Chemical Substances in China; IMDG – International Maritime Dangerous Goods; IMO – International Maritime Organization; ISHL – Industrial Safety and Health Law (Japan); ISO – International Organisation for Standardization; KECI – Korea Existing Chemicals Inventory; LC50 – Lethal Concentration to 50 % of a test population; LD50 – Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL – International Convention for the Prevention of Pollution from Ships; n.o.s. – Not Otherwise Specified; NO(A)EC – No Observed (Adverse) Effect Concentration; NO(A)EL – No Observed (Adverse) Effect Level; NOELR – No Observable Effect Loading Rate; NZIoC – New Zealand Inventory of Chemicals; OECD – Organization for Economic Co-operation and Development; OPPTS – Office of Chemical Safety and Pollution Prevention; PBT – Persistent, Bioaccumulative and Toxic substance; PICCS – Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR – (Quantitative) Structure Activity Relationship; REACH – Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID – Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT – Self-Accelerating Decomposition Temperature; SDS – Safety Data Sheet; TCSI – Taiwan Chemical Substance Inventory; TRGS – Technical Rule for Hazardous Substances; TSCA – Toxic Substances Control Act (United States); UN – United Nations; vPvB – Very Persistent and Very Bioaccumulative

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1

DP 2019

thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Annex: Exposure Scenarios**Exposure Scenario: Laundry aid (non-gasing). Automatic process**

Life Cycle Stage : Use at industrial sites

Product category : **PC35** Washing and cleaning products (including solvent based products)

Contributing scenario controlling environmental exposure for:

Environmental release category : **ERC4** Industrial use of processing aids in processes and products, not becoming part of articles

Daily amount per site : 50 kg

Type of Sewage Treatment Plant : Municipal sewage treatment plant

Contributing scenario controlling worker exposure for:

Process category : **PROC8b** Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities

Exposure duration : 60 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : Yes: See Section 8

Respiratory Protection : No

Contributing scenario controlling worker exposure for:

Process category : **PROC2** Use in closed, continuous process with occasional controlled exposure

DP 2019

Exposure duration : 480 min

Operational conditions and
risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : No

Respiratory Protection : No

Exposure Scenario: Laundry aid (non-gasing). Semi automatic processProduct category : **PC35** Washing and cleaning products (including solvent based products)**Contributing scenario controlling worker exposure for:**Process category : **PROC8a** Transfer of substance or preparation (charging/
discharging) from/ to vessels/ large containers at non-
dedicated facilities

Exposure duration : 60 min

Operational conditions and
risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : Yes: See Section 8

Respiratory Protection : No

Contributing scenario controlling worker exposure for:Process category : **PROC1** Use in closed process, no likelihood of exposure

Exposure duration : 480 min

Operational conditions and
risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : No

Respiratory Protection : No