

Section: 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : SERVICE PRODUCT 50-ETD

Other means of identification : Not applicable.

Product code : GOT-0103

Recommended use : Cleaning product

Restrictions on use : Reserved for industrial and professional use.

Product dilution information : No dilution information provided.

Company Olympus MEA FZ-LLC
Dubai Science Park 310-316
3rd Floor, Laboratory Complex
33607 Dubai

+9714 363 1500,

Manufacturer: Ecolab Deutschland GmbH
Ecolab-Allee 1
40789 Monheim am Rhein
Germany
+49 (0)2173 599 0, OfficeService.DEDUS@ecolab.com

Emergency telephone : +32-(0)3-575-5555
number

Issuing date : 29.08.2018

Section: 2. HAZARDS IDENTIFICATION
GHS Classification

Corrosive to metals : Category 1

Acute toxicity (Oral) : Category 4

Skin corrosion : Category 1

Serious eye damage : Category 1

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

GHS Label element

Hazard pictograms :




Signal Word : Danger

Hazard Statements : May be corrosive to metals.
Harmful if swallowed.

SAFETY DATA SHEET

SERVICE PRODUCT 50-ETD

Causes severe skin burns and eye damage.
May cause respiratory irritation.

Precautionary Statements

: **Prevention:**

Keep only in original container. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

Wash contaminated clothing before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. Absorb spillage to prevent material damage.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Store in corrosive resistant container with a resistant inner liner.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

: Do not mix with bleach or other chlorinated products – will cause chlorine gas.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

Pure substance/mixture

: Mixture

Chemical Name

CAS-No.

Concentration: (%)

Hydrogen peroxide

7722-84-1

10 - 30

Acetic acid

64-19-7

5 - 10

Peroxyacetic acid

79-21-0

1 - 5

Section: 4. FIRST AID MEASURES

In case of eye contact

: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

In case of skin contact

: Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.

If swallowed

: Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.

If inhaled

: Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

Protection of first-aiders

: If potential for exposure exists refer to Section 8 for specific personal

SAFETY DATA SHEET

SERVICE PRODUCT 50-ETD

protective equipment.

Notes to physician : Treat symptomatically.

Most important symptoms and effects, both acute and delayed : See Section 11 for more detailed information on health effects and symptoms.

Section: 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : None known.

Specific hazards during firefighting : Special protective equipment for firefighters
Oxidizer; material is an oxidizer which may readily react with other materials, especially upon heating.

Hazardous combustion products : Decomposition products may include the following materials:
Carbon oxides
nitrogen oxides (NOx)
Sulphur oxides
Oxides of phosphorus

Special protective equipment for firefighters : In case of fire, wear a full face positive-pressure self contained breathing apparatus and protective suit.

Specific extinguishing methods : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Do not allow contact with soil, surface or ground water.

Methods and materials for containment and cleaning up : Stop leak if safe to do so. Isolate the waste do not allow it to come into contact with incompatible materials. For small spills contain with sand or vermiculite and dilute the contained product at least 10 times with water. Transfer to an open topped container and remove to a safe place for neutralization* / disposal. For large spills contain spill and evacuate the area, leave until the reaction subsides, then collect up for disposal. Obtain consent from the local water company / authority if considering discharge to sewer. *NEUTRALIZATION : once diluted, neutralize with a suitable alkali such as sodium bicarbonate. Combustible materials exposed to this product should be rinsed immediately with large amounts of water to ensure that all product is removed. Residual product which is allowed to dry on organic materials such as rags, cloths, paper, fabrics, cotton, leather, wood, or other combustibles may spontaneously ignite and result in a fire.

SAFETY DATA SHEET

SERVICE PRODUCT 50-ETD

Section: 7. HANDLING AND STORAGE

- Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Do not breathe dust/fume/gas/mist/vapours/spray. Use only with adequate ventilation. Wash hands thoroughly after handling. Do not mix with bleach or other chlorinated products – will cause chlorine gas.
- Conditions for safe storage : Keep away from strong bases. Keep out of reach of children. Store in suitable labeled containers. Pressure bursts may occur due to gas evolution if the container is not adequately vented.
- Storage temperature : 0 °C to 25 °C
- Packaging material : Suitable material: Plastic material
Unsuitable material: Mild steel, Aluminium

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
Hydrogen peroxide	7722-84-1	TWA OEL-RL	1 ppm 1.5 mg/m ³	ZA OEL
		STEL OEL-RL	2 ppm 3 mg/m ³	ZA OEL
Hydrogen peroxide	7722-84-1	TWA	1 ppm 1.4 mg/m ³	BH OEL
Hydrogen peroxide	7722-84-1	TWA	1 ppm 1.4 mg/m ³	ARE OEL
Acetic acid	64-19-7	TWA OEL-RL	10 ppm 25 mg/m ³	ZA OEL
		STEL OEL-RL	15 ppm 37 mg/m ³	ZA OEL
Acetic acid	64-19-7	TWA	10 ppm 25 mg/m ³	BH OEL
		STEL	15 ppm 37 mg/m ³	BH OEL
Acetic acid	64-19-7	TWA (8 Hour)	10 ppm 25 mg/m ³	TR OEL
		TWA	10 ppm 25 mg/m ³	2017/164/EU
		STEL	20 ppm 50 mg/m ³	2017/164/EU
Acetic acid	64-19-7	TWA	10 ppm 25 mg/m ³	ARE OEL
		STEL	15 ppm 37 mg/m ³	ARE OEL

- Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

Personal protective equipment

- Eye protection : Wear eye protection/face protection.

SAFETY DATA SHEET

SERVICE PRODUCT 50-ETD

Hand protection	: Wear the following personal protective equipment: Standard glove type. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
Skin protection	: Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing
Respiratory protection	: When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: light yellow
Odour	: vinegar-like
pH	: 1.0, (100 %)
Flash point	: Not applicable., Does not sustain combustion.
Odour Threshold	: no data available
Melting point/freezing point	: no data available
Initial boiling point and boiling range	: no data available
Evaporation rate	: no data available
Flammability (solid, gas)	: no data available
Upper explosion limit	: no data available
Lower explosion limit	: no data available
Vapour pressure	: no data available
Relative vapour density	: no data available
Relative density	: 1.12
Water solubility	: soluble
Solubility in other solvents	: no data available
Partition coefficient: n-octanol/water	: no data available
Auto-ignition temperature	: no data available
Thermal decomposition	: no data available
Viscosity, kinematic	: no data available
Explosive properties	: no data available
Oxidizing properties	: no data available
Molecular weight	: no data available
VOC	: no data available

SAFETY DATA SHEET

SERVICE PRODUCT 50-ETD

Section: 10. STABILITY AND REACTIVITY

Chemical stability	: Contamination may result in dangerous pressure increases - closed containers may rupture.
Possibility of hazardous reactions	: Do not mix with bleach or other chlorinated products – will cause chlorine gas.
Conditions to avoid	: Direct sources of heat. Exposure to sunlight.
Incompatible materials	: Mild steel Aluminium
Hazardous decomposition products	: In case of fire hazardous decomposition products may be produced such as: Carbon oxides nitrogen oxides (NOx) Sulphur oxides Oxides of phosphorus

Section: 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Potential Health Effects

Eyes	: Causes serious eye damage.
Skin	: Causes severe skin burns.
Ingestion	: Harmful if swallowed. Causes digestive tract burns.
Inhalation	: May cause respiratory tract irritation. May cause nose, throat, and lung irritation.
Chronic Exposure	: Health injuries are not known or expected under normal use.

Experience with human exposure

Eye contact	: Redness, Pain, Corrosion
Skin contact	: Redness, Pain, Corrosion
Ingestion	: Corrosion, Abdominal pain
Inhalation	: Respiratory irritation, Cough

Toxicity

Product

Acute oral toxicity	: Acute toxicity estimate : 1,678 mg/kg
Acute inhalation toxicity	: 4 h Acute toxicity estimate : 5.3 mg/l Test atmosphere: dust/mist
Acute dermal toxicity	: Acute toxicity estimate : > 5,000 mg/kg

SAFETY DATA SHEET

SERVICE PRODUCT 50-ETD

Skin corrosion/irritation	: no data available
Serious eye damage/eye irritation	: no data available
Respiratory or skin sensitization	: no data available
Carcinogenicity	: no data available
Reproductive effects	: no data available
Germ cell mutagenicity	: no data available
Teratogenicity	: no data available
STOT - single exposure	: no data available
STOT - repeated exposure	: no data available
Aspiration toxicity	: no data available

Section: 12. ECOLOGICAL INFORMATION

Ecotoxicity

Environmental Effects	: Toxic to aquatic life.
-----------------------	--------------------------

Product

Toxicity to fish	: no data available
Toxicity to daphnia and other aquatic invertebrates	: no data available
Toxicity to algae	: no data available

Components

Toxicity to fish	: Acetic acid 96 h LC50 Oncorhynchus mykiss (rainbow trout): > 1,000 mg/l Peroxyacetic acid 96 h LC50: 0.8 mg/l
------------------	--

Components

Toxicity to daphnia and other aquatic invertebrates	: Acetic acid 48 h EC50 Daphnia magna (Water flea): 39.6 mg/l Peroxyacetic acid 48 h EC50: 0.73 mg/l
---	---

Components

Toxicity to algae	: Hydrogen peroxide 72 h EC50: 1.38 mg/l Acetic acid 72 h EC50 Skeletonema costatum (marine diatom): > 1,000 mg/l Peroxyacetic acid 72 h EC50: 0.7 mg/l
-------------------	--

Persistence and degradability

Readily biodegradable.

SAFETY DATA SHEET

SERVICE PRODUCT 50-ETD

Bioaccumulative potential

no data available

Mobility in soil

no data available

Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

- Disposal methods : Do not contaminate ponds, waterways or ditches with chemical or used container. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.
- Disposal considerations : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

Section: 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

- UN number : 3149
- UN proper shipping name : HYDROGEN PEROXIDE AND PEROXYACETIC ACID MIXTURE, STABILIZED
- Transport hazard class(es) : 5.1 (8)
- Packing group : II
- Environmental hazards : Yes
- Special precautions for user : None

Air transport (IATA)

- UN number : 3149
- Description of the goods : Hydrogen peroxide and peroxyacetic acid mixture stabilized
- Class : 5.1 (8)
- Packing group : II
- Environmentally hazardous : Yes

Sea transport (IMDG/IMO)

- UN number : 3149
- Description of the goods : HYDROGEN PEROXIDE AND PEROXYACETIC ACID MIXTURE, STABILIZED
- Class : 5.1 (8)
- Packing group : II
- Marine pollutant : Yes

SAFETY DATA SHEET


SERVICE PRODUCT 50-ETD

Section: 15. REGULATORY INFORMATION

For Regulatory information please contact your Ecolab sales representative.

Section: 16. OTHER INFORMATION

NFPA:



HMIS III:

HEALTH	
FLAMMABILITY	
PHYSICAL HAZARD	

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Issuing date : 29.08.2018
Version : 1.0
Prepared by : Regulatory Affairs

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.