

1. Identification of the product and company

Identification of the substance or preparation

Product name : SPITADERM
Product use : Hand and skin disinfectant
Company : Ecolab Food Safety & Hygiene Solutions Pvt. Ltd
 Unit No. 808, "215-Atrium", 8th floor,
 Next to Courtyard by Marriott Hotel,
 Andheri Kurla Road, Andheri (East),
 Mumbai - 400 059, India
 Toll free number: 1800 209 2530

EMERGENCY HEALTH INFORMATION: +1-800-656608
Outside United States and Canada CALL: +1 651-222-5352

2. Composition/information on ingredients

Ingredient name	CAS number	% by weight
Isopropyl alcohol	67-63-0	60-100%
Chlorhexidine digluconate	18472-51-0	<1%

3. Hazards identification

Potential acute health effects

Eyes : Irritating to eyes.
Skin : Slightly irritating to the skin.
Inhalation : High vapor concentrations can cause drowsiness and dizziness.
Ingestion : No known significant effects or critical hazards.

4. First aid measures

Eye contact : Immediately flush with plenty of cool running water. Remove contact lenses. Continue flushing for at least 15 minutes, holding eyelid apart to ensure rinsing of the entire eye. Seek medical attention immediately.
Skin contact : Immediately flush skin with plenty of cool running water for at least 15 minutes. If irritation persists, seek medical attention.
Inhalation : If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Ingestion : DO NOT induce vomiting. NEVER give anything by mouth to any unconscious person. Seek medical attention immediately.

5. Fire-fighting measures

Flash point : > 20°C
Fire fighting media and Instructions : Use water spray, foam, dry chemical or CO₂. Dike area of fire to prevent runoff.
Fire hazards : Flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.
Special protective equipment for fire-fighters : Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face piece operated in

positive pressure mode.

6. Accidental release measures

- Personal Precautions** : Ventilate area of leak or spill. Do not touch damaged containers or spilled material unless wearing appropriate protective equipment (Section 8). Stop leak if without risk. Prevent entry into sewers, water courses, basements or confined areas.
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- Methods for cleaning up** : If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) scoop up material and place in a sealed, liquid-proof container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

7. Handling and storage

- Handling** : Do not ingest. Avoid contact with eyes. Keep away from heat, sparks and flame. Eliminate ignition sources. Avoid breathing vapor or mist. Wash thoroughly after handling.
- Storage** : Keep out of the reach of children. Keep container tightly closed. Keep container in a cool, well-ventilated area. Avoid all possible sources of ignition.
Do not store at temperatures above 25°C.

8. Exposure controls/personal protection

- Engineering Controls** : Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are proximal to the work-station location.
- Personal protection**
- Eyes** : Use chemical splash goggles. For continued or severe exposure wear a face shield over the goggles.
- Hands** : Use chemical resistant, impervious gloves.
- Skin** : Use synthetic apron, other protective equipment as necessary to prevent skin contact.
- Respiratory** : Wear appropriate respirator when ventilation is inadequate and occupational exposure limits are exceeded.

Consult local authorities for acceptable exposure limits.

Name	Exposure limits
Isopropyl alcohol	ACGIH STEL: 400 ppm (15 minutes).
	ACGIH TWA: 200 ppm (8 hours).
	OSHA TWA: 980 mg/m ³ (8 hours)
	OSHA TWA: 400 ppm (8 hours).

9. Physical and chemical properties

- Physical state** : Liquid

Color : Colorless
 Odor : Pleasantly fresh
 pH : 6.5 – 7.5 (20°C) (undiluted)
 Relative density : 0.86 g/cm³ (20°C)
 Solubility : Miscible in water

10. Stability and reactivity

Stability : The product is stable.
 Reactivity : None known.

11. Toxicological information

Potential acute health effects

Eyes : Irritating to eyes.
 Skin : Slightly irritating to the skin.
 Inhalation : High vapor concentrations can cause drowsiness and dizziness.
 Ingestion : No known significant effects or critical hazards..

12. Ecological information

Ecological data : Not available

13. Disposal considerations

Waste disposal : Do not reuse product container. The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

14. Transport information

Regulation Information	UN number	Proper shipping name	Class	Packing Group
IMDG Classification	UN1219	Flammable liquid (Isopropyl alcohol)	3	II

15. Regulatory information

THE MANUFACTURE, STORAGE AND IMPORT OF HAZARDOUS CHEMICALS RULES, 1989

Hazard Classification : Flammable material
 Risk phrase : R11 Highly flammable.
 R36 Irritating to eyes.
 R67 Vapors may cause drowsiness and dizziness.
 Safety phrase : S2 Keep out of reach of children
 S16 Keep away from sources of ignition
 S25 Avoid contact with eyes
 S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

16. Other information

Date of issue : 26 August 2013
Responsible name : Regulatory Affairs
Version : 1

Disclaimer

To the best of our knowledge, the information contains herein is accurate. However, neither the above names supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.