

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : MAXX FLOOR FINISH REMOVER

Other means of identification : Not applicable

Recommended use : Floor Cleaner

Product dilution information : 12,5 %

Company : ECOLAB S. DE R.L. DE C.V.
 EDIFICIO CORPORATIVO CENTURY PLAZA.
 AVENIDA SANTA FE N°. 440 PISO 6 Y 7
 COLONIA SANTA FE
 DELEGACIÓN CUAJIMALPA, CIUDAD DE MEXICO, Mexico
 C.P. 05349
 (55) 1253 1900

Emergency telephone : 01 800 837 2998 Please request assistance in Spanish language

Issuing date : 20.03.2018

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Product AS SOLD

Acute toxicity (Oral), Category 4	H302
Acute toxicity (Dermal), Category 5	H313
Skin corrosion, Sub-category 1A	H314
Serious eye damage, Category 1	H318
Specific target organ systemic toxicity - single exposure, Category 3, Respiratory system	H335

Product AT USE DILUTION

Skin corrosion, Sub-category 1A	H314
Serious eye damage, Category 1	H318

GHS label elements

Product AS SOLD

Hazard pictograms :



Signal Word : Danger

Hazard Statements :	H302	Harmful if swallowed.
	H313	May be harmful in contact with skin.
	H314	Causes severe skin burns and eye damage.
	H335	May cause respiratory irritation.

Precautionary Statements :	Prevention:	
	P261	Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
	P264	Wash skin thoroughly after handling.
	P270	Do not eat, drink or smoke when using this product.

SAFETY DATA SHEET

MAXX FLOOR FINISH REMOVER

P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth.

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P310 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

P312 Call a POISON CENTER or doctor/ physician if you feel unwell.

P363 Wash contaminated clothing before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Product AT USE DILUTION

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H314 Causes severe skin burns and eye damage.

Precautionary Statements : **Prevention:**

P264 Wash skin thoroughly after handling.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P310 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

P363 Wash contaminated clothing before reuse.

SAFETY DATA SHEET

MAXX FLOOR FINISH REMOVER

Storage:

P405

Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Product AS SOLD**Other hazards** : None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Product AS SOLD

Pure substance/mixture : Mixture

Chemical name	CAS-No.	Concentration (%)
Benzyl alcohol	100-51-6	20 - 30
monoethanolamine	141-43-5	10 - 20
2-hexyloxyethanol	112-25-4	10 - 20
potassium hydroxide	1310-58-3	1 - 5

Product AT USE DILUTION

Chemical name	CAS-No.	Concentration (%)
Benzyl alcohol	100-51-6	1 - 5
monoethanolamine	141-43-5	1 - 5
2-hexyloxyethanol	112-25-4	1 - 5

SECTION 4. FIRST AID MEASURES

Product AS SOLD

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
- If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.
- Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal protective equipment.
- Notes to physician : Treat symptomatically.
- Most important symptoms and effects, both acute and delayed : See Section 11 for more detailed information on health effects and symptoms.

Product AT USE DILUTION

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use

SAFETY DATA SHEET

MAXX FLOOR FINISH REMOVER

	a mild soap if available. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
If swallowed	: Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.
If inhaled	: Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

SECTION 5. FIRE-FIGHTING MEASURES

Product AS SOLD

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	: None known.
Specific hazards during fire fighting	: Not flammable or combustible.
Hazardous combustion products	: Decomposition products may include the following materials: Carbon oxides Nitrogen oxides (NOx) Sulfur oxides Oxides of phosphorus
Special protective equipment for fire-fighters	: Use personal protective equipment.
Specific extinguishing methods	: Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Product AS SOLD

Personal precautions, protective equipment and emergency procedures	: Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed.
Environmental precautions	: Do not allow contact with soil, surface or ground water.
Methods and materials for containment and cleaning up	: Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

Product AT USE DILUTION

Personal precautions, protective equipment and emergency procedures	: Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is
---	--

SAFETY DATA SHEET

MAXX FLOOR FINISH REMOVER

conducted by trained personnel only. Refer to protective measures listed.

Environmental precautions : Do not allow contact with soil, surface or ground water.

Methods and materials for containment and cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

SECTION 7. HANDLING AND STORAGE

Product AS SOLD

Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. Use only with adequate ventilation. Wash hands thoroughly after handling.

Conditions for safe storage : Do not store near acids. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

Storage temperature : 0 °C to 50 °C

Product AT USE DILUTION

Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. Use only with adequate ventilation. Wash hands thoroughly after handling.

Conditions for safe storage : Do not store near acids. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Product AS SOLD

Ingredients with workplace control parameters

Ingredients	CAS-No.	Form of exposure	Permissible concentration	Basis
monoethanolamine	141-43-5	VLE-PPT	3 ppm	NOM-010-STPS-2014
		VLE-CT	6 ppm	NOM-010-STPS-2014
monoethanolamine	141-43-5	TWA	3 ppm	ACGIH
		STEL	6 ppm	ACGIH
		TWA	3 ppm 8 mg/m3	NIOSH REL
		STEL	6 ppm 15 mg/m3	NIOSH REL
		TWA	3 ppm 6 mg/m3	OSHA Z1
potassium hydroxide	1310-58-3	VLE-P	2 mg/m3	NOM-010-STPS-2014
potassium hydroxide	1310-58-3	C	2 mg/m3	ACGIH
		Ceiling	2 mg/m3	NIOSH REL

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

SAFETY DATA SHEET

MAXX FLOOR FINISH REMOVER

Personal protective equipment

Eye protection	: Safety goggles Face-shield
Hand protection	: Wear the following personal protective equipment: Standard glove type. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
Skin protection	: Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing
Respiratory protection	: When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Product AT USE DILUTION

Engineering measures	: Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.
----------------------	--

Personal protective equipment

Eye protection	: Safety goggles Face-shield
Hand protection	: Wear the following personal protective equipment: Standard glove type. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
Skin protection	: Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing
Respiratory protection	: When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

	Product AS SOLD	Product AT USE DILUTION
Appearance	: liquid	liquid
Color	: amber	amber
Odor	: amine-like	amine-like
pH	: 14,0, (100 %)	12,0 - 13,0
Flash point	: closed cupNot applicable	
Odor Threshold	: No data available	
Melting point/freezing point	: No data available	
Initial boiling point and boiling range	: > 100 °C	

SAFETY DATA SHEET

MAXX FLOOR FINISH REMOVER

Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapor pressure	: No data available
Relative vapor density	: No data available
Relative density	: 1,046
Water solubility	: soluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, kinematic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Molecular weight	: No data available
VOC	: No data available

SECTION 10. STABILITY AND REACTIVITY

Product AS SOLD

Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reaction known under conditions of normal use.
Conditions to avoid	: None known.
Incompatible materials	: Acids Metals
Hazardous decomposition products	: Decomposition products may include the following materials: Carbon oxides Nitrogen oxides (NOx) Sulfur oxides Oxides of phosphorus

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Potential Health Effects

Product AS SOLD

Eyes	: Causes serious eye damage.
Skin	: May be harmful in contact with skin. Causes severe skin burns.
Ingestion	: Harmful if swallowed. Causes digestive tract burns.

SAFETY DATA SHEET

MAXX FLOOR FINISH REMOVER

Inhalation : May cause respiratory tract irritation. May cause nose, throat, and lung irritation.

Chronic Exposure : Health injuries are not known or expected under normal use.

Product AT USE DILUTION

Eyes : Causes serious eye damage.

Skin : Causes severe skin burns.

Ingestion : Causes digestive tract burns.

Inhalation : May cause nose, throat, and lung irritation.

Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Product AS SOLD

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Pain, Corrosion

Ingestion : Corrosion, Abdominal pain

Inhalation : Respiratory irritation, Cough

Product AT USE DILUTION

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Pain, Corrosion

Ingestion : Corrosion, Abdominal pain

Inhalation : Respiratory irritation, Cough

Toxicity

Product AS SOLD

Product

Acute oral toxicity : Acute toxicity estimate : 1.751 mg/kg

Acute dermal toxicity : Acute toxicity estimate : 2.157 mg/kg

Skin corrosion/irritation : No data available

Serious eye damage/eye irritation : No data available

Respiratory or skin sensitization : No data available

Carcinogenicity : No data available

Reproductive effects : No data available

Germ cell mutagenicity : No data available

Teratogenicity : No data available

STOT-single exposure : No data available

STOT-repeated exposure : No data available

SAFETY DATA SHEET

MAXX FLOOR FINISH REMOVER

Aspiration toxicity : No data available

SECTION 12. ECOLOGICAL INFORMATION

Product AS SOLD

Ecotoxicity

Environmental Effects : This product has no known ecotoxicological effects.

Product

Toxicity to fish : 96 h LC50: > 120 mg/l

Toxicity to daphnia and other aquatic invertebrates : No data available

Toxicity to algae : No data available

Ingredients

Toxicity to daphnia and other aquatic invertebrates : monoethanolamine
48 h EC50 Daphnia: 65 mg/l

2-hexyloxyethanol
48 h EC50 Daphnia: 145 mg/l

Persistence and degradability

Product AS SOLD

Readily biodegradable.

Product AT USE DILUTION

Readily biodegradable.

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Product AS SOLD

Disposal methods : Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.

Disposal considerations : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

Product AT USE DILUTION

Disposal methods : Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.

SAFETY DATA SHEET

MAXX FLOOR FINISH REMOVER

Disposal considerations : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

SECTION 14. TRANSPORT INFORMATION

Product AS SOLD

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport: generally applicable for transport in Mexico.

UN number : 1719
Description of the goods : CAUSTIC ALKALI LIQUID, N.O.S.
(Potassium hydroxide, monoethanolamine)
Class : 8
Packing group : II
Environmentally hazardous : no

Air transport (IATA)

Contact Regulatory for air freight eligibility

Sea transport (IMDG/IMO)

UN number : 1719
Description of the goods : CAUSTIC ALKALI LIQUID, N.O.S.
(Potassium hydroxide, monoethanolamine)
Class : 8
Packing group : II
Marine pollutant : no


SECTION 15. REGULATORY INFORMATION

Mexico: Our SDS meets the requirements established by the Official Mexican Regulation NOM-018-STPS-2015, Harmonized System for the identification and communication of hazards and risks by dangerous chemical substances in work centers.

SECTION 16. OTHER INFORMATION

Product AS SOLD

NFPA:



HMIS III:

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	0


0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Product AT USE DILUTION

SAFETY DATA SHEET

MAXX FLOOR FINISH REMOVER

NFPA:



HMIS III:

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Revision Date : 20.03.2018
Version : 1.0
Prepared by : Regulatory Affairs

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the MSDS.

The information provided in this Material Safety Data Sheet is considered correct but is not thorough and is intended for guidance only, which is based on current knowledge of the substance or mixture and is applicable to the appropriate safety precautions for the product.