

TALON WAX BLOCKS

Version	Revision Date:	SDS Number:	This version replaces all previous versions.
2.1	08.04.2021	S1490615202	

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : TALON WAX BLOCKS

Design code : A12720B

Product Registration Number : UK-2015-0907-0001

Unique Formula Identifier (UFI) : 3KG3-K0TP-900V-U307

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Rodenticide

Recommended restrictions on use : professional use

1.3 Details of the supplier of the safety data sheet

Company : Syngenta UK Limited
CPC4, Capital Park
Fulbourn, Cambridge CB21 5XE
United Kingdom

Telephone : +44 (0) 1223 883400

Telefax : +44 (0) 1223 882195

E-mail address of person responsible for the SDS : customer.services@syngenta.com

1.4 Emergency telephone number

Emergency telephone number : +44 1484 538444

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Reproductive toxicity, Category 1A	H360D: May damage the unborn child.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs (blood) through prolonged or repeated exposure .

TALON WAX BLOCKS

Version 2.1 Revision Date: 08.04.2021 SDS Number: S1490615202

This version replaces all previous versions.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H360D May damage the unborn child.
H373 May cause damage to organs (blood) through prolonged or repeated exposure .

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
Response:
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
Storage:
P405 Store locked up.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

brodifacoum (ISO)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

May form combustible dust concentrations in air.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TALON WAX BLOCKS

Version
2.1

Revision Date:
08.04.2021

SDS Number:
S1490615202

This version replaces all previous versions.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
brodifacoum (ISO)	56073-10-0 259-980-5 607-172-00-1	Acute Tox. 1; H300 Acute Tox. 1; H330 Acute Tox. 1; H310 Skin Sens. 1B; H317 Repr. 1A; H360D STOT RE 1; H372 (Blood) Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 10 specific concentration limit Repr. 1A; H360D ≥ 0,003 % STOT RE 1; H372 ≥ 0,02 % STOT RE 2; H373 ≥ 0,002 - < 0,02 %	≥ 0.003 - < 0.02

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Have the product container, label or Safety Data Sheet with you when calling the emergency number, a poison control center or physician, or going for treatment.

If inhaled : Move the victim to fresh air.
If breathing is irregular or stopped, administer artificial respiration.
Keep patient warm and at rest.
Call a physician or poison control centre immediately.

TALON WAX BLOCKS

Version	Revision Date:	SDS Number:	This version replaces all previous versions.
2.1	08.04.2021	S1490615202	

- | | | |
|-------------------------|---|--|
| In case of skin contact | : | Take off all contaminated clothing immediately.
Wash off immediately with plenty of water.
If skin irritation persists, call a physician.
Wash contaminated clothing before re-use. |
| In case of eye contact | : | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Remove contact lenses.
Immediate medical attention is required. |
| If swallowed | : | Take victim immediately to hospital.
Do NOT induce vomiting. |

4.2 Most important symptoms and effects, both acute and delayed

- | | | |
|----------|---|---|
| Symptoms | : | Symptoms of poisoning are typical of anticoagulants. In severe cases there may be bruising, haematomas of the joints, blood in the faeces and urine |
|----------|---|---|

4.3 Indication of any immediate medical attention and special treatment needed

- | | | |
|-----------|---|--|
| Treatment | : | <p>This product contains anticoagulants with an effect similar to warfarin in that they act by interfering with the synthesis of prothrombin.</p> <p>The specific measure of effect is the prothrombin time. Note this may not become prolonged until 12-18 hours after ingestion.</p> <p>The specific antidote is vitamin K1 (Phytomenandione). Initially, antidote should be given by injection (10-20mg, or 0.25mg/kg for children), by slow intravenous infusion at a rate not exceeding 1mg/minute. In severe cases the use of fresh frozen plasma may be required.</p> <p>Maintenance treatment is given orally (40mg/day in divided doses for adults; up to 20mg/day in divided doses for children).</p> <p>The prothrombin time and the haemoglobin should be monitored. Patients should be kept under medical supervision until the prothrombin time has been normal for 3 consecutive days.</p> <p>Oral treatment may need continuing for several months (20mg/day in divided doses for adults and up to 20mg/day in divided doses for children). (For animal cases the dose is 2-5mg/kg).</p> |
|-----------|---|--|

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | | |
|------------------------------|---|-----------------------------------|
| Suitable extinguishing media | : | Extinguishing media - small fires |
|------------------------------|---|-----------------------------------|

TALON WAX BLOCKS

Version	Revision Date:	SDS Number:	This version replaces all previous versions.
2.1	08.04.2021	S1490615202	

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Extinguishing media - large fires

Alcohol-resistant foam

or

Water spray

Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10). Exposure to decomposition products may be a hazard to health.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear full protective clothing and self-contained breathing apparatus.

Further information : Do not allow run-off from fire fighting to enter drains or water courses.
Cool closed containers exposed to fire with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Refer to protective measures listed in sections 7 and 8.
Avoid dust formation.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, pick up with an electrically protected vacuum cleaner or by wet-brushing and transfer to a container for disposal according to local regulations (see section 13).
Do not create a powder cloud by using a brush or compressed air.
Clean contaminated surface thoroughly.
Clean with detergents. Avoid solvents.
Retain and dispose of contaminated wash water.

6.4 Reference to other sections

For disposal considerations see section 13., Refer to protective measures listed in sections 7 and 8.

TALON WAX BLOCKS

Version 2.1 Revision Date: 08.04.2021 SDS Number: S1490615202 This version replaces all previous versions.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : This material is capable of forming flammable dust clouds in air, which, if ignited, can produce a dust cloud explosion. Flames, hot surfaces, mechanical sparks and electrostatic discharges can serve as ignition sources for this material. Electrical equipment should be compatible with the flammability characteristics of this material. The flammability characteristics will be made worse if the material contains traces of flammable solvents or is handled in the presence of flammable solvents.

This material can become readily charged in most operations.

Avoid contact with skin and eyes.

When using do not eat, drink or smoke.

For personal protection see section 8.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Keep away from food, drink and animal feedingstuffs.

Further information on storage stability : Physically and chemically stable for at least 2 years when stored in the original unopened sales container at ambient temperatures.

7.3 Specific end use(s)

Specific use(s) : For proper and safe use of this product, please refer to the approval conditions laid down on the product label.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
paraffin waxes and hydrocarbon waxes	8002-74-2	TWA (Fumes)	2 mg/m ³	GB EH40
		STEL (Fumes)	6 mg/m ³	GB EH40
sucrose, pure	57-50-1	TWA	10 mg/m ³	GB EH40
		STEL	20 mg/m ³	GB EH40
brodifacoum (ISO)	56073-10-0	TWA	0.002 mg/m ³	Syngenta

8.2 Exposure controls

Engineering measures

Containment and/or segregation is the most reliable technical protection measure if exposure cannot be eliminated.

TALON WAX BLOCKS

Version	Revision Date:	SDS Number:	This version replaces all previous versions.
2.1	08.04.2021	S1490615202	

The extent of these protection measures depends on the actual risks in use.

Maintain air concentrations below occupational exposure standards.
Where necessary, seek additional occupational hygiene advice.

Personal protective equipment

Eye protection : No special protective equipment required.
Hand protection

Material	: Nitrile rubber
Break through time	: > 480 min
Glove thickness	: 0.5 mm

Remarks : Wear protective gloves. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Remove and wash contaminated clothing before re-use.
Wear as appropriate:

Respiratory protection : Dust impervious protective suit
No personal respiratory protective equipment normally required.
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Protective measures : The use of technical measures should always have priority over the use of personal protective equipment.
When selecting personal protective equipment, seek appropriate professional advice.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : solid

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TALON WAX BLOCKS

Version
2.1

Revision Date:
08.04.2021

SDS Number:
S1490615202

This version replaces all previous versions.

Colour	:	dark blue
Odour	:	No data available
Odour Threshold	:	No data available
Melting point/range	:	No data available
Boiling point/boiling range	:	No data available
Flammability	:	May form combustible dust concentrations in air.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Decomposition temperature	:	No data available
pH	:	No data available
Viscosity	:	No data available
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Solubility(ies)	:	No data available
Water solubility	:	Not soluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Vapour pressure	:	No data available
Density	:	1.2 g/cm ³
Relative vapour density	:	No data available
Particle characteristics	:	No data available
Particle size	:	No data available

9.2 Other information

Explosives	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Flammable solids	:	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TALON WAX BLOCKS

Version 2.1 Revision Date: 08.04.2021 SDS Number: S1490615202 This version replaces all previous versions.

Burning number : 2 (20 °C)
Minimum ignition temperature : 350 °C
Evaporation rate : No data available
Minimum ignition energy : 300 - 1,000 mJ

SECTION 10: Stability and reactivity

10.1 Reactivity

None reasonably foreseeable.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : No decomposition if used as directed.

10.5 Incompatible materials

Materials to avoid : None known.

10.6 Hazardous decomposition products

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Ingestion
Inhalation
Skin contact
Eye contact

Acute toxicity

Components:

brodifacoum (ISO):

Acute oral toxicity : LD50 (Rat, female): 0.561 mg/kg

LD50 (Rat, male): 0.418 mg/kg

Acute inhalation toxicity : LC50 (Rat, female): 0.00305 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

LC50 (Rat, male): 0.00486 mg/l

TALON WAX BLOCKS

Version 2.1 Revision Date: 08.04.2021 SDS Number: S1490615202 This version replaces all previous versions.

Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat, male): 5.21 mg/kg
LD50 (Rat, female): 3.16 mg/kg

Skin corrosion/irritation

Components:

brodifacoum (ISO):

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Components:

brodifacoum (ISO):

Species : Rabbit
Result : No eye irritation

Respiratory or skin sensitisation

Components:

brodifacoum (ISO):

Test Type : Buehler Test
Species : Guinea pig
Result : The product is a skin sensitiser, sub-category 1B.

Germ cell mutagenicity

Components:

brodifacoum (ISO):

Germ cell mutagenicity-
Assessment : Animal testing did not show any mutagenic effects.

Carcinogenicity

Components:

brodifacoum (ISO):

Carcinogenicity -
Assessment : No evidence of carcinogenicity in animal studies.

Reproductive toxicity

Components:

brodifacoum (ISO):

Reproductive toxicity - : Some evidence of adverse effects on development, based on

TALON WAX BLOCKS

Version 2.1 Revision Date: 08.04.2021 SDS Number: S1490615202 This version replaces all previous versions.

Assessment animal experiments.

STOT - repeated exposure

Components:

brodifacoum (ISO):

Target Organs : Blood
Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Components:

brodifacoum (ISO):

Remarks : Excessive exposure slows blood clotting time and can cause bleeding, shock and death.

SECTION 12: Ecological information

12.1 Toxicity

Components:

brodifacoum (ISO):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.04 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.45 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Raphidocelis subcapitata (freshwater green alga)): 0.27 mg/l
Exposure time: 72 h

NOEC (Raphidocelis subcapitata (freshwater green alga)): 0.01 mg/l
End point: Growth rate
Exposure time: 72 h

TALON WAX BLOCKS

Version 2.1 Revision Date: 08.04.2021 SDS Number: S1490615202 This version replaces all previous versions.

M-Factor (Acute aquatic toxicity) : 10

Toxicity to microorganisms : EC50 (activated sludge): > 100 mg/l
Exposure time: 30 min

M-Factor (Chronic aquatic toxicity) : 10

12.2 Persistence and degradability

Components:

brodifacoum (ISO):

Biodegradability : Result: Not rapidly biodegradable

Stability in water : Degradation half life: ca. 300 d
Remarks: Persistent in water.

12.3 Bioaccumulative potential

Components:

brodifacoum (ISO):

Bioaccumulation : Remarks: bioaccumulative

12.4 Mobility in soil

Components:

brodifacoum (ISO):

Distribution among environmental compartments : Remarks: Low mobility in soil.

Stability in soil : Dissipation time: 157 d
Percentage dissipation: 50 % (DT50)
Remarks: Product is not persistent.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

Components:

brodifacoum (ISO):

Assessment : PBT substance.

TALON WAX BLOCKS

Version Revision Date: SDS Number: This version replaces all previous versions.
2.1 08.04.2021 S1490615202

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not contaminate ponds, waterways or ditches with chemical or used container.
Do not dispose of waste into sewer.
Where possible recycling is preferred to disposal or incineration.
If recycling is not practicable, dispose of in compliance with local regulations.

Contaminated packaging : Empty remaining contents.
Triple rinse containers.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

Waste Code : uncleaned packagings
15 01 10, packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TALON WAX BLOCKS

Version	Revision Date:	SDS Number:	This version replaces all previous versions.
2.1	08.04.2021	S1490615202	

regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: brodifacoum (ISO) (Number on list 30)
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	Not applicable
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	:	Not applicable
Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals	:	Not applicable
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.	:	Not applicable

Other regulations:

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance when it is used in the specified applications.

SECTION 16: Other information

Full text of H-Statements

H300	:	Fatal if swallowed.
H310	:	Fatal in contact with skin.
H317	:	May cause an allergic skin reaction.
H330	:	Fatal if inhaled.
H360D	:	May damage the unborn child.
H372	:	Causes damage to organs through prolonged or repeated exposure.
H400	:	Very toxic to aquatic life.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TALON WAX BLOCKS

Version	Revision Date:	SDS Number:	This version replaces all previous versions.
2.1	08.04.2021	S1490615202	

H410 : Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Repr.	: Reproductive toxicity
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Repr. 1A	H360D
STOT RE 2	H373

Classification procedure:

Calculation method
Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



TALON WAX BLOCKS

Version
2.1

Revision Date:
08.04.2021

SDS Number:
S1490615202

This version replaces all previous versions.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN