

P3-TOPAX 17

Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name : P3-TOPAX 17

Product code : 116891E

Use of the Substance/Mixture : Cleaning product

Substance type: : Mixture

For professional users only.

Product dilution information : No dilution information provided.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Foam cleaner. Semi-Automatic with venting process

Recommended restrictions on use : Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : Ecolab Temizleme Sistemleri Ltd. Şti
Esentepe Mahallesi, Cevizli - Esentepe E-5 Yanyol Caddesi
Vizyon Bulvarı No: 13, Kat 1 No: 65 Turkey TR 34870 KARTAL / İSTANBUL
+90 (216) 458 69 00, Fax: +90 (216) 458 69 07

1.4 Emergency telephone number

Emergency telephone number : +32-(0)3-575-5555 Trans- European

Poison Information Centre telephone number : 114 Ulusal Zehir Danışma Merkezi (UZEM)

Date of Compilation/Revision : 09.07.2020
Version : 2.0

Section: 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (T.R. SEA No 28848)

Corrosive to metals, Category 1	H290
Skin corrosion, Category 1	H314
Serious eye damage, Category 1	H318

P3-TOPAX 17

2.2 Label elements

Labelling (T.R. SEA No 28848)

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.

Precautionary Statements : **Prevention:**
P280 Wear protective gloves/ eye protection/ face protection.

Response:
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label:
benzenesulfonic acid, C10-13- alkyl derivs., sodium salt
disodium metasilicate

2.3 Other hazards

None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Hazardous components

Chemical Name	CAS-No. EC-No.	Classification (T.R. SEA No 28848)	Concentration: [%]
2-(2-butoxyethoxy)ethanol	112-34-5 203-961-6	Eye irritation Category 2; H319	>= 3 - < 5
benzenesulfonic acid, C10-13- alkyl derivs., sodium salt	68411-30-3 270-115-0	Acute toxicity Category 4; H302 Skin irritation Category 2; H315 Serious eye damage Category 1; H318 Chronic aquatic toxicity Category 3; H412	>= 3 - < 5
Sodium silicate	1344-09-8 215-687-4	Skin corrosion Category 1B; H314 Serious eye damage Category 1; H318 Specific target organ toxicity - single exposure Category 3; H335	>= 1 - < 2.5

P3-TOPAX 17

sodium hydroxide	1310-73-2 215-185-5	Skin corrosion Category 1A; H314 Corrosive to metals Category 1; H290	$\geq 0.5 - < 1$
------------------	------------------------	--	------------------

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section: 4. FIRST AID MEASURES

4.1 Description of first aid measures

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
- If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If conscious, give 2 glasses of water. Get medical attention immediately.
- If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

Section: 5. FIREFIGHTING MEASURES

5.1 Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Not flammable or combustible.
- Hazardous combustion products : Depending on combustion properties, decomposition products may include following materials:
Carbon oxides
nitrogen oxides (NO_x)
Sulphur oxides
metal oxides

P3-TOPAX 17

5.3 Advice for firefighters

Special protective equipment for firefighters : Use personal protective equipment.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

6.4 Reference to other sections

See Section 1 for emergency contact information.
For personal protection see section 8.
See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation. Wash hands thoroughly after handling. Do not breathe spray, vapour. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).

Hygiene measures : Handle in accordance with good industrial hygiene and safety

P3-TOPAX 17

practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Do not store near acids. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers. Keep only in original packaging. Absorb spillage to prevent material damage.

Storage temperature : 0 °C to 40 °C

Packaging material : Suitable material: Plastic material
Unsuitable material: Aluminium, Mild steel

7.3 Specific end uses

Specific use(s) : Foam cleaner. Semi-Automatic with venting process

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-(2-butoxyethoxy)ethanol	112-34-5	STEL 15 min	15 ppm 101.2 mg/m3	TR OEL
Further information		EU - I / C (1991 / 322 / EC) list of indicative limit values (updated with 2006 / 15 / EC)		
		TWA (8 Hour)	10 ppm 67.5 mg/m3	TR OEL
Further information		EU - I / C (1991 / 322 / EC) list of indicative limit values (updated with 2006 / 15 / EC)		

DNEL

2-(2-butoxyethoxy)ethanol	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Short-term - local Value: 101.2 mg/m3 End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 20 mg/kg End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 67.5 mg/m3 End Use: Workers Exposure routes: Inhalation
---------------------------	---	---

P3-TOPAX 17

		Potential health effects: Short-term - local Value: 67.5 mg/m3
benzenesulfonic acid, C10-13- alkyl derivs., sodium salt	:	End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 85 mg/cm2 End Use: Workers Exposure routes: Dermal Potential health effects: Long-term local effects Value: 85 mg/cm2 End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 6 mg/m3 End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 6 mg/m3
Sodium silicate	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 5.61 mg/m3 End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 1.59 mg/cm2 End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 1.38 mg/m3 End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 0.8 mg/cm2 End Use: Consumers Exposure routes: Ingestion Potential health effects: Long-term systemic effects Value: 0.8 ppm
sodium hydroxide	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 1 mg/m3

P3-TOPAX 17

		End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 1 mg/m3
Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt	:	End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 175 mg/m3

PNEC

2-(2-butoxyethoxy)ethanol	:	Fresh water Value: 1 mg/l Marine water Value: 0.1 mg/l Intermittent use/release Value: 3.9 mg/l Sewage treatment plant Value: 200 mg/l Sediment Value: 4 mg/kg Soil Value: 0.4 mg/kg Oral Value: 56 mg/kg
benzenesulfonic acid, C10-13- alkyl derivs., sodium salt	:	Fresh water Value: 0.268 mg/l Marine water Value: 0.0268 mg/l Intermittent use/release Value: 0.0167 mg/l Fresh water sediment Value: 8.1 mg/kg Marine sediment Value: 8.1 mg/kg Sewage treatment plant

P3-TOPAX 17

		Value: 3.43 mg/l
Sodium silicate	:	Fresh water Value: 7.5 mg/l Marine water Value: 1 mg/l Intermittent use/release Value: 7.5 mg/l Sewage treatment plant Value: 348 mg/l
Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt	:	Fresh water Value: 0.24 mg/l Marine water Value: 0.024 mg/l Intermittent use/release Value: 0.071 mg/l Sewage treatment plant Value: 10000 mg/l Fresh water sediment Value: 5.45 mg/kg Marine sediment Value: 0.545 mg/kg Soil Value: 0.946 mg/kg

8.2 Exposure controls

Appropriate engineering controls

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

Individual protection measures

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Eye/face protection (EN 166) : Safety goggles
Face-shield

P3-TOPAX 17

- Hand protection (EN 374) : Recommended preventive skin protection
Gloves
Nitrile rubber
butyl-rubber
Breakthrough time: 1 – 4 hours
Minimum thickness for butyl-rubber 0.7 mm for nitrile rubber 0.4 mm or equivalent (please refer to the gloves manufacturer/distributor for advise).
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Skin and body protection (EN 14605) : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing including appropriate safety shoes
- Respiratory protection (EN 143, 14387) : None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

Environmental exposure controls

- General advice : Consider the provision of containment around storage vessels.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

- Appearance : liquid
- Colour : light yellow
- Odour : odourless
- pH : 12.9 - 13.2, 100 %
- Flash point : Not applicable.
- Odour Threshold : Not applicable and/or not determined for the mixture
- Melting point/freezing point : Not applicable and/or not determined for the mixture
- Initial boiling point and boiling range : Not applicable and/or not determined for the mixture
- Evaporation rate : Not applicable and/or not determined for the mixture
- Flammability (solid, gas) : Not applicable and/or not determined for the mixture
- Upper explosion limit : Not applicable and/or not determined for the mixture
- Lower explosion limit : Not applicable and/or not determined for the mixture
- Vapour pressure : Not applicable and/or not determined for the mixture
- Relative vapour density : Not applicable and/or not determined for the mixture

P3-TOPAX 17

Relative density	: 1.03 - 1.07
Water solubility	: soluble
Solubility in other solvents	: Not applicable and/or not determined for the mixture
Partition coefficient: n-octanol/water	: Not applicable and/or not determined for the mixture
Auto-ignition temperature	: Not applicable and/or not determined for the mixture
Thermal decomposition	: Not applicable and/or not determined for the mixture
Viscosity, kinematic	: Not applicable and/or not determined for the mixture
Explosive properties	: Not applicable and/or not determined for the mixture
Oxidizing properties	: The substance or mixture is not classified as oxidizing.

9.2 Other information

Not applicable and/or not determined for the mixture

Section: 10. STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Acids

Aluminium
Mild steel

10.6 Hazardous decomposition products

Depending on combustion properties, decomposition products may include following materials:
Carbon oxides
nitrogen oxides (NO_x)
Sulphur oxides
metal oxides

Section: 11. TOXICOLOGICAL INFORMATION

P3-TOPAX 17

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Product

Acute oral toxicity : Acute toxicity estimate : > 2,000 mg/kg

Acute inhalation toxicity : There is no data available for this product.

Acute dermal toxicity : There is no data available for this product.

Skin corrosion/irritation : There is no data available for this product.

Serious eye damage/eye irritation : There is no data available for this product.

Respiratory or skin sensitization : There is no data available for this product.

Carcinogenicity : There is no data available for this product.

Reproductive effects : There is no data available for this product.

Germ cell mutagenicity : There is no data available for this product.

Teratogenicity : There is no data available for this product.

STOT - single exposure : There is no data available for this product.

STOT - repeated exposure : There is no data available for this product.

Aspiration toxicity : There is no data available for this product.

Components

Acute oral toxicity : 2-(2-butoxyethoxy)ethanol
LD50 rat: 3,306 mg/kg

benzenesulfonic acid, C10-13- alkyl derivs., sodium salt
LD50 rat: 1,080 mg/kg

Sodium silicate
LD50 rat: 3,400 mg/kg

Components

Acute dermal toxicity : 2-(2-butoxyethoxy)ethanol
LD50 rabbit: 2,764 mg/kg

Sodium silicate
LD50 rat: > 5,000 mg/kg
Test substance: Information given is based on data obtained from similar substances.

P3-TOPAX 17

Potential Health Effects

Eyes : Causes serious eye damage.

Skin : Causes severe skin burns.

Ingestion : Causes digestive tract burns.

Inhalation : May cause nose, throat, and lung irritation.

Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Pain, Corrosion

Ingestion : Corrosion, Abdominal pain

Inhalation : Respiratory irritation, Cough

Section: 12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity

Environmental Effects : This product has no known ecotoxicological effects.

Product

Toxicity to fish : no data available

Toxicity to daphnia and other aquatic invertebrates : no data available

Toxicity to algae : no data available

Components

Toxicity to fish : 2-(2-butoxyethoxy)ethanol
96 h LC50 Fish: 1,300 mg/l

benzenesulfonic acid, C10-13- alkyl derivs., sodium salt
96 h LC50 Lepomis macrochirus (Bluegill sunfish): 1.67 mg/l

Sodium silicate
96 h LC50 Oncorhynchus mykiss (rainbow trout): 260 mg/l

Components

Toxicity to daphnia and other aquatic invertebrates : benzenesulfonic acid, C10-13- alkyl derivs., sodium salt
48 h LC50 Daphnia magna (Water flea): 2.4 mg/l

Sodium silicate
48 h EC50 Daphnia magna (Water flea): 1,700 mg/l

sodium hydroxide

P3-TOPAX 17

48 h EC50: 40 mg/l

Components

Toxicity to algae : benzenesulfonic acid, C10-13- alkyl derivs., sodium salt
96 h EC50 *Pseudokirchneriella subcapitata* (green algae): 29 mg/l

Sodium silicate
72 h EC50 *Desmodesmus subspicatus* (green algae): 207 mg/l

12.2 Persistence and degradability

Product

Biodegradability : The surfactants contained in the product are biodegradable according to the requirements of the detergent regulation 648/2004/EC

Components

Biodegradability : 2-(2-butoxyethoxy)ethanol
Result: Readily biodegradable.

benzenesulfonic acid, C10-13- alkyl derivs., sodium salt
Result: Readily biodegradable.

Sodium silicate
Result: Not applicable - inorganic

sodium hydroxide
Result: Not applicable - inorganic

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste

P3-TOPAX 17

codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods

- | | |
|-----------------------------------|---|
| Product | : Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility. |
| Contaminated packaging | : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations. |
| Guidance for Waste Code selection | : Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations. |

Section: 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

- | | |
|-----------------------------------|---|
| 14.1 UN number | : 3266 |
| 14.2 UN proper shipping name | : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S.
(silicic acid, sodium salt, sodium hydroxide) |
| 14.3 Transport hazard class(es) | : 8 |
| 14.4 Packing group | : III |
| 14.5 Environmental hazards | : No |
| 14.6 Special precautions for user | : None |

Air transport (IATA)

- | | |
|-----------------------------------|---|
| 14.1 UN number | : 3266 |
| 14.2 UN proper shipping name | : Corrosive liquid, basic, inorganic, n.o.s.
(silicic acid, sodium salt, sodium hydroxide) |
| 14.3 Transport hazard class(es) | : 8 |
| 14.4 Packing group | : III |
| 14.5 Environmental hazards | : No |
| 14.6 Special precautions for user | : None |

Sea transport (IMDG/IMO)

- | | |
|----------------|--------|
| 14.1 UN number | : 3266 |
|----------------|--------|

P3-TOPAX 17

14.2 UN proper shipping name : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S.
(silicic acid, sodium salt, sodium hydroxide)
14.3 Transport hazard class(es) : 8
14.4 Packing group : III
14.5 Environmental hazards : No
14.6 Special precautions for user : None
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not applicable.

Section: 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Detergents Regulation EC 648/2004 : less than 5 %: Anionic surfactants

National Regulations

Take note of Dir 94/33/EC on the protection of young people at work.

Other regulations : According to 11 December 2013, Numbered 28848 (Bis), "Ministry of Environment and Forestry"; Regulation on Classification, Labelling and Packaging of Substances and Mixtures.
According to 13 Dec 2014, Numbered 29204, "Ministry of Environment and Urbanization"; Regulation on Safety Data Sheets regarding Dangerous Substances and Mixtures.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out on the product.

Section: 16. OTHER INFORMATION

Procedure used to derive the classification according to REGULATION (EC) No 1272/2008 and Regulation T.R. SEA No 28848

Classification	Justification
Corrosive to metals 1, H290	Based on product data or assessment
Skin corrosion 1, H314	Based on product data or assessment
Serious eye damage 1, H318	Based on product data or assessment

Full text of H-Statements

H290 May be corrosive to metals.
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H412 Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

ADN – European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR – European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS – Australian Inventory of Chemical Substances; ASTM – American Society for the Testing of Materials; bw – Body weight; CLP – Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR – Carcinogen, Mutagen or Reproductive Toxicant; DIN – Standard of the German Institute for Standardisation; DSL – Domestic Substances List (Canada); ECHA – European Chemicals Agency; EC-Number – European Community number; ECx – Concentration associated with x% response; ELx – Loading rate associated with x% response; EmS – Emergency Schedule; ENCS – Existing and New Chemical Substances (Japan); ErCx – Concentration associated with x% growth rate response; GHS – Globally Harmonized System; GLP – Good Laboratory Practice; IARC – International Agency for Research on Cancer; IATA – International Air Transport Association; IBC – International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 – Half maximal inhibitory concentration; ICAO – International Civil Aviation Organization; IECSC – Inventory of Existing Chemical Substances in China; IMDG – International Maritime Dangerous Goods; IMO – International Maritime Organization; ISHL – Industrial Safety and Health Law (Japan); ISO – International Organisation for Standardization; KECI – Korea Existing Chemicals Inventory; LC50 – Lethal Concentration to 50 % of a test population; LD50 – Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL – International Convention for the Prevention of Pollution from Ships; n.o.s. – Not Otherwise Specified; NO(A)EC – No Observed (Adverse) Effect Concentration; NO(A)EL – No Observed (Adverse) Effect Level; NOELR – No Observable Effect Loading Rate; NZIoC – New Zealand Inventory of Chemicals; OECD – Organization for Economic Co-operation and Development; OPPTS – Office of Chemical Safety and Pollution Prevention; PBT – Persistent, Bioaccumulative and Toxic substance; PICCS – Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR – (Quantitative) Structure Activity Relationship; REACH – Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID – Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT – Self-Accelerating Decomposition Temperature; SDS – Safety Data Sheet; TCSI – Taiwan Chemical Substance Inventory; TRGS – Technical Rule for Hazardous Substances; TSCA – Toxic Substances Control Act (United States); UN – United Nations; vPvB – Very Persistent and Very Bioaccumulative

Prepared by : Name, Surname: Nuryıl Subaşı
Certificate number: GBF-A-0-2776
Certificate date: 09.05.2018
Certificate expiry date: 09.05.2021
Contact: +902164586983

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

P3-TOPAX 17