

X-TRA PROFESSIONAL**Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier**

Product name : X-TRA PROFESSIONAL

UFI : U3YG-79ME-K00J-Y1G1

Product code : 108978E

Use of the
Substance/Mixture : Laundry detergent

Substance type: : Mixture

For professional users only.

Product dilution information : No dilution information provided.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laundry detergent. Semi automatic process

Recommended restrictions
on use : Reserved for industrial and professional use.**1.3 Details of the supplier of the safety data sheet**Company : Ecolab Deutschland GmbH
Ecolab-Allee 1
40789 Monheim am Rhein, Germany +49 (0)2173 599 0
OfficeService.DEDUS@ecolab.com**1.4 Emergency telephone number**Emergency telephone
number : +4932221096286
+32-(0)3-575-5555 Trans-EuropeanPoison Information Centre
telephone number : +49 (0)551 38318854Date of Compilation/Revision : 28.07.2020
Version : 2.0**Section: 2. HAZARDS IDENTIFICATION****2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)****||**Serious eye damage, Category 1

H318

2.2 Label elements**Labelling (REGULATION (EC) No 1272/2008)**

X-TRA PROFESSIONAL

Hazard pictograms



Signal Word

: Danger

Hazard Statements

: H318

Causes serious eye damage.

Precautionary Statements

: **Prevention:**

P280e

Wear eye protection/face protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310

Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label:

Sodium carbonate peroxyhydrate

benzenesulfonic acid, C10-13- alkyl derivs., sodium salt

Sodium silicate

2.3 Other hazards

None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS**3.2 Mixtures****Hazardous components**

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration: [%]
Sodium Carbonate	497-19-8 207-838-8 01-2119485498-19	Eye irritation Category 2; H319	>= 10 - < 20
Sodium carbonate peroxyhydrate	15630-89-4 239-707-6 01-2119457268-30	Oxidizing solids Category 3; H272 Acute toxicity Category 4; H302 Serious eye damage Category 1; H318	>= 5 - < 10
benzenesulfonic acid, C10-13- alkyl derivs., sodium salt	68411-30-3 270-115-0 01-2119489428-22	Acute toxicity Category 4; H302 Skin irritation Category 2; H315 Serious eye damage Category 1; H318 Chronic aquatic toxicity Category 3; H412	>= 5 - < 10
Sodium silicate	1344-09-8 215-687-4 01-2119448725-31	Skin corrosion Category 1B; H314 Serious eye damage Category 1; H318 Specific target organ toxicity - single exposure Category 3; H335	>= 3 - < 5
Alcohols, C13-15, branched and linear, ethoxylated	157627-86-6 POLYMER	Acute toxicity Category 4; H302 Eye irritation Category 2; H319 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 3; H412	>= 1 - < 2.5

For the full text of the H-Statements mentioned in this Section, see Section 16.

X-TRA PROFESSIONAL

Section: 4. FIRST AID MEASURES

4.1 Description of first aid measures

- | | |
|-------------------------|---|
| In case of eye contact | : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately. |
| In case of skin contact | : Rinse with plenty of water. |
| If swallowed | : Rinse mouth. Get medical attention if symptoms occur. |
| If inhaled | : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur. |

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

- | | |
|-----------|--------------------------|
| Treatment | : Treat symptomatically. |
|-----------|--------------------------|

Section: 5. FIREFIGHTING MEASURES

5.1 Extinguishing media

- | | |
|--------------------------------|---|
| Suitable extinguishing media | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Unsuitable extinguishing media | : None known. |

5.2 Special hazards arising from the substance or mixture

- | | |
|--------------------------------------|---|
| Specific hazards during firefighting | : Not flammable or combustible. |
| Hazardous combustion products | : Depending on combustion properties, decomposition products may include following materials:
Carbon oxides
nitrogen oxides (NOx)
Sulphur oxides
metal oxides |

5.3 Advice for firefighters

- | | |
|---|---|
| Special protective equipment for firefighters | : Use personal protective equipment. |
| Further information | : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes. |

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

X-TRA PROFESSIONAL

- Advice for non-emergency personnel : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.
- Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

6.2 Environmental precautions

- Environmental precautions : Do not allow contact with soil, surface or ground water.

6.3 Methods and materials for containment and cleaning up

- Methods for cleaning up : Sweep up and shovel into suitable containers for disposal.

6.4 Reference to other sections

See Section 1 for emergency contact information.
For personal protection see section 8.
See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

- Advice on safe handling : Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation. Wash hands thoroughly after handling. Do not breathe dust. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.
- Storage temperature : 0 °C to 40 °C

7.3 Specific end uses

- Specific use(s) : Laundry detergent. Semi automatic process

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Contains no substances with occupational exposure limit values.

X-TRA PROFESSIONAL

DNEL

Sodium Carbonate	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 10 mg/m³ End Use: Consumers Exposure routes: Inhalation Potential health effects: Acute local effects Value: 10 mg/m³
benzenesulfonic acid, C10-13- alkyl derivs., sodium salt	:	End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 85 mg/cm² End Use: Workers Exposure routes: Dermal Potential health effects: Long-term local effects Value: 85 mg/cm² End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 6 mg/m³ End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 6 mg/m³
Sodium silicate	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 5.61 mg/m³ End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 1.59 mg/cm² End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 1.38 mg/m³ End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 0.8 mg/cm² End Use: Consumers Exposure routes: Ingestion Potential health effects: Long-term systemic effects Value: 0.8 ppm

X-TRA PROFESSIONAL

sodium hydroxide	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 1 mg/m ³ End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 1 mg/m ³
------------------	---	--

PNEC

benzenesulfonic acid, C10-13- alkyl derivs., sodium salt	:	Fresh water Value: 0.268 mg/l Marine water Value: 0.0268 mg/l Intermittent use/release Value: 0.0167 mg/l Fresh water sediment Value: 8.1 mg/kg Marine sediment Value: 8.1 mg/kg Sewage treatment plant Value: 3.43 mg/l
Sodium silicate	:	Fresh water Value: 7.5 mg/l Marine water Value: 1 mg/l Intermittent use/release Value: 7.5 mg/l Sewage treatment plant Value: 348 mg/l

8.2 Exposure controls**Appropriate engineering controls**

Engineering measures : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing

X-TRA PROFESSIONAL

of the eyes and body in case of contact or splash hazard.

Eye/face protection (EN 166)	: Safety goggles Face-shield
Hand protection (EN 374)	: No special protective equipment required.
Skin and body protection (EN 14605)	: No special protective equipment required.
Respiratory protection (EN 143, 14387)	: When respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization, consider the use of certified respiratory protection equipment meeting EU requirements (89/656/EEC, (EU) 2016/425), or equivalent, with filter type:P

Environmental exposure controls

General advice	: Consider the provision of containment around storage vessels.
----------------	---

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES**9.1 Information on basic physical and chemical properties**

Appearance	: powder
Colour	: white with coloured particles
Odour	: Perfumes, fragrances
pH	: 10.4 - 10.6, 1 %
Flash point	: Not applicable.
Odour Threshold	: Not applicable and/or not determined for the mixture
Melting point/freezing point	: Not applicable and/or not determined for the mixture
Initial boiling point and boiling range	: Not applicable and/or not determined for the mixture
Evaporation rate	: Not applicable and/or not determined for the mixture
Flammability (solid, gas)	: Not applicable and/or not determined for the mixture
Upper explosion limit	: Not applicable and/or not determined for the mixture
Lower explosion limit	: Not applicable and/or not determined for the mixture
Vapour pressure	: Not applicable and/or not determined for the mixture
Relative vapour density	: Not applicable and/or not determined for the mixture
Relative density	: 0.64 - 0.72
Water solubility	: soluble
Solubility in other solvents	: Not applicable and/or not determined for the mixture
Partition coefficient: n-octanol/water	: Not applicable and/or not determined for the mixture
Auto-ignition temperature	: Not applicable and/or not determined for the mixture
Thermal decomposition	: Not applicable and/or not determined for the mixture
Viscosity, kinematic	: Not applicable and/or not determined for the mixture

X-TRA PROFESSIONAL

Explosive properties : Not applicable and/or not determined for the mixture
Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Not applicable and/or not determined for the mixture

Section: 10. STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Acids

10.6 Hazardous decomposition products

Depending on combustion properties, decomposition products may include following materials:

Carbon oxides
nitrogen oxides (NO_x)
Sulphur oxides
metal oxides

Section: 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Product

Acute oral toxicity : Acute toxicity estimate : > 2,000 mg/kg
Acute inhalation toxicity : There is no data available for this product.
Acute dermal toxicity : There is no data available for this product.
Skin corrosion/irritation : There is no data available for this product.
Serious eye damage/eye : There is no data available for this product.

X-TRA PROFESSIONAL

irritation

Respiratory or skin sensitization : There is no data available for this product.

Carcinogenicity : There is no data available for this product.

Reproductive effects : There is no data available for this product.

Germ cell mutagenicity : There is no data available for this product.

Teratogenicity : There is no data available for this product.

STOT - single exposure : There is no data available for this product.

STOT - repeated exposure : There is no data available for this product.

Aspiration toxicity : There is no data available for this product.

Components

Acute oral toxicity : Sodium Carbonate
LD50 rat: 2,800 mg/kg

Sodium carbonate peroxyhydrate
LD50 rat: 1,034 mg/kg

benzenesulfonic acid, C10-13- alkyl derivs., sodium salt
LD50 rat: 1,080 mg/kg

Sodium silicate
LD50 rat: 3,400 mg/kg

Alcohols, C13-15, branched and linear, ethoxylated
LD50 rat: 1,250 mg/kg

Components

Acute dermal toxicity : Sodium silicate
LD50 rat: > 5,000 mg/kg
Test substance: Information given is based on data obtained from similar substances.

Alcohols, C13-15, branched and linear, ethoxylated
LD50 rat: > 2,000 mg/kg

Potential Health Effects

Eyes : Causes serious eye damage.

Skin : Health injuries are not known or expected under normal use.

Ingestion : Health injuries are not known or expected under normal use.

Inhalation : Health injuries are not known or expected under normal use.

Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

X-TRA PROFESSIONAL

Eye contact : Redness, Pain, Corrosion

Skin contact : No symptoms known or expected.

Ingestion : No symptoms known or expected.

Inhalation : No symptoms known or expected.

Section: 12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity

Environmental Effects : This product has no known ecotoxicological effects.

Product

Toxicity to fish : no data available

Toxicity to daphnia and other aquatic invertebrates : no data available

Toxicity to algae : no data available

Components

Toxicity to fish : Sodium Carbonate
96 h LC50 *Lepomis macrochirus* (Bluegill sunfish): 300 mg/l

benzenesulfonic acid, C10-13- alkyl derivs., sodium salt
96 h LC50 *Lepomis macrochirus* (Bluegill sunfish): 1.67 mg/l

Sodium silicate
96 h LC50 *Oncorhynchus mykiss* (rainbow trout): 260 mg/l

Components

Toxicity to daphnia and other aquatic invertebrates : Sodium Carbonate
48 h EC50 *Ceriodaphnia* (water flea): 213.5 mg/l

Sodium carbonate peroxyhydrate
48 h EC50 *Daphnia*: 4.9 mg/l

benzenesulfonic acid, C10-13- alkyl derivs., sodium salt
48 h LC50 *Daphnia magna* (Water flea): 2.4 mg/l

Sodium silicate
48 h EC50 *Daphnia magna* (Water flea): 1,700 mg/l

Alcohols, C13-15, branched and linear, ethoxylated
48 h EC50 *Daphnia magna* (Water flea): 0.317 mg/l

Components

Toxicity to algae : benzenesulfonic acid, C10-13- alkyl derivs., sodium salt
96 h EC50 *Pseudokirchneriella subcapitata* (green algae): 29 mg/l

Sodium silicate
72 h EC50 *Desmodesmus subspicatus* (green algae): 207 mg/l

12.2 Persistence and degradability

X-TRA PROFESSIONAL

Product

Biodegradability : The surfactants contained in the product are biodegradable according to the requirements of the detergent regulation 648/2004/EC

Components

Biodegradability : Sodium Carbonate
Result: Not applicable - inorganic

Sodium carbonate peroxyhydrate
Result: Not applicable - inorganic

benzenesulfonic acid, C10-13- alkyl derivs., sodium salt
Result: Readily biodegradable.

Sodium silicate
Result: Not applicable - inorganic

Alcohols, C13-15, branched and linear, ethoxylated
Result: Readily biodegradable.

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods

Product : Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.

Contaminated packaging : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local,

X-TRA PROFESSIONAL

state, and federal regulations.

Guidance for Waste Code selection : Inorganic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations.

Section: 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

14.1 UN number : Not dangerous goods
14.2 UN proper shipping name : Not dangerous goods
14.3 Transport hazard class(es) : Not dangerous goods
14.4 Packing group : Not dangerous goods
14.5 Environmental hazards : Not dangerous goods
14.6 Special precautions for user : Not dangerous goods

Air transport (IATA)

14.1 UN number : Not dangerous goods
14.2 UN proper shipping name : Not dangerous goods
14.3 Transport hazard class(es) : Not dangerous goods
14.4 Packing group : Not dangerous goods
14.5 Environmental hazards : Not dangerous goods
14.6 Special precautions for user : Not dangerous goods

Sea transport (IMDG/IMO)

14.1 UN number : Not dangerous goods
14.2 UN proper shipping name : Not dangerous goods
14.3 Transport hazard class(es) : Not dangerous goods
14.4 Packing group : Not dangerous goods
14.5 Environmental hazards : Not dangerous goods
14.6 Special precautions for user : Not dangerous goods
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not dangerous goods

Section: 15. REGULATORY INFORMATION

X-TRA PROFESSIONAL**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

according to Detergents : 15 % or over but less than 30 %: Zeolites
 Regulation EC 648/2004 5 % or over but less than 15 %: Anionic surfactants, Oxygen-based bleaching agents
 less than 5 %: Phosphonates, Non-ionic surfactants, Soap, Polycarboxylates
 Other constituents: Enzymes, Optical brighteners, Perfumes

National Regulations

Take note of Dir 94/33/EC on the protection of young people at work.

Hazard class for water : WGK 2
 Classification according to AwSV, Annex 1

German storage class : 13

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out on the product.

Section: 16. OTHER INFORMATION**Procedure used to derive the classification according to REGULATION (EC) No 1272/2008**

Classification	Justification
Serious eye damage 1, H318	Calculation method

Full text of H-Statements

H272 May intensify fire; oxidiser.
 H302 Harmful if swallowed.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H400 Very toxic to aquatic life.
 H412 Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

ADN – European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR – European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS – Australian Inventory of Chemical Substances; ASTM – American Society for the Testing of Materials; bw – Body weight; CLP – Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR – Carcinogen, Mutagen or Reproductive Toxicant; DIN – Standard of the German Institute for Standardisation; DSL – Domestic Substances List (Canada); ECHA – European Chemicals Agency; EC-Number – European Community number; ECx – Concentration associated with x% response; ELx – Loading rate associated with x% response; EmS – Emergency Schedule; ENCS – Existing and New Chemical Substances (Japan); ErCx – Concentration associated with x% growth rate response; GHS – Globally Harmonized System; GLP – Good Laboratory Practice; IARC – International Agency for Research on Cancer; IATA – International Air Transport Association; IBC – International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in

X-TRA PROFESSIONAL

Bulk; IC50 – Half maximal inhibitory concentration; ICAO – International Civil Aviation Organization; IECSC – Inventory of Existing Chemical Substances in China; IMDG – International Maritime Dangerous Goods; IMO – International Maritime Organization; ISHL – Industrial Safety and Health Law (Japan); ISO – International Organisation for Standardization; KECI – Korea Existing Chemicals Inventory; LC50 – Lethal Concentration to 50 % of a test population; LD50 – Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL – International Convention for the Prevention of Pollution from Ships; n.o.s. – Not Otherwise Specified; NO(A)EC – No Observed (Adverse) Effect Concentration; NO(A)EL – No Observed (Adverse) Effect Level; NOELR – No Observable Effect Loading Rate; NZIoC – New Zealand Inventory of Chemicals; OECD – Organization for Economic Co-operation and Development; OPPTS – Office of Chemical Safety and Pollution Prevention; PBT – Persistent, Bioaccumulative and Toxic substance; PICCS – Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR – (Quantitative) Structure Activity Relationship; REACH – Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID – Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT – Self-Accelerating Decomposition Temperature; SDS – Safety Data Sheet; TCSI – Taiwan Chemical Substance Inventory; TRGS – Technical Rule for Hazardous Substances; TSCA – Toxic Substances Control Act (United States); UN – United Nations; vPvB – Very Persistent and Very Bioaccumulative

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Annex: Exposure Scenarios**Exposure Scenario: Laundry detergent. Semi automatic process**

Life Cycle Stage : Widespread use by professional workers

Product category : **PC35** Washing and cleaning products (including solvent based products)

Contributing scenario controlling environmental exposure for:

Environmental release category : **ERC8a** Wide dispersive indoor use of processing aids in open systems

Daily amount per site : 7.5 kg

Type of Sewage Treatment Plant : Municipal sewage treatment plant

X-TRA PROFESSIONAL

Contributing scenario controlling worker exposure for:

Process category : **PROC8a** Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities

Exposure duration : 60 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC1** Use in closed process, no likelihood of exposure

Exposure duration : 480 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8