

Section: 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : ECOBRITE POWER PLUS

Other means of identification : Not applicable.

Recommended use : Laundry product

Restrictions on use : Reserved for industrial and professional use.

Product dilution information : No dilution information provided.

Company

Ecolab Gulf FZE
P.O. Box 17063
Jebel Ali Free Zone Area, Near Container Terminal 3 - North Zone
Dubai
UAE
00971 4 8014444 Customer Services, 00971 48146800 00971 4
8014000 Reception phone numbers

Nalco Egypt Trading
5th Settlement, South 90th St.
The Address Building No 67th – 1st floor
New Cairo, Cairo, Egypt11835
0020 2 25 37 1195,

Ecolab Maroc S.A.R.L.
Batiment, Lot. Mounir 1, Parc Industriel
Attawfik
Route 1029
Sidi Maarouf, Casablanca, Morocco
00212 22 58 25 30 - 35,

Emergency telephone number : +32-(0)3-575-5555 Trans-European

Issuing date : 29.10.2019

Section: 2. HAZARDS IDENTIFICATION
GHS Classification

Flammable liquids : Category 4

Serious eye damage : Category 1

Skin irritation : Category 2

GHS Label element

Hazard pictograms :



Signal Word : Danger

SAFETY DATA SHEET

ECOBRITE POWER PLUS

- Hazard Statements : Combustible liquid
Causes skin irritation.
Causes serious eye damage.
- Precautionary Statements : **Prevention:**
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Wash skin thoroughly after handling. Wear protective gloves/ eye protection/ face protection.
Response:
IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:
Store in a well-ventilated place. Keep cool.
Disposal:
Dispose of contents/ container to an approved waste disposal plant.
- Other hazards : None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

Pure substance/mixture : Mixture

Chemical Name	CAS-No.	Concentration: (%)
Alcohols, C13-15, branched and linear, ethoxylated	157627-86-6	30 - 60
Dipropylene glycol methyl ether	34590-94-8	10 - 30
Isopropyl Alcohol	67-63-0	1 - 5

Section: 4. FIRST AID MEASURES

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Get medical attention if irritation develops and persists.
- If swallowed : Rinse mouth. Get medical attention if symptoms occur.
- If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.
- Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal protective equipment.
- Notes to physician : Treat symptomatically.
- Most important symptoms and effects, both acute and delayed : See Section 11 for more detailed information on health effects and symptoms.

Section: 5. FIREFIGHTING MEASURES

SAFETY DATA SHEET

ECOBRITE POWER PLUS

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Fire Hazard
Keep away from heat and sources of ignition.
Flash back possible over considerable distance.
- Hazardous combustion products : Decomposition products may include the following materials:
Carbon oxides
- Special protective equipment for firefighters : Use personal protective equipment.
- Specific extinguishing methods : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Ensure adequate ventilation. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Do not allow contact with soil, surface or ground water.
- Methods and materials for containment and cleaning up : Eliminate all ignition sources if safe to do so. Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

Section: 7. HANDLING AND STORAGE

- Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Keep away from fire, sparks and heated surfaces. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Wash hands thoroughly after handling. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).
- Conditions for safe storage : Keep away from heat and sources of ignition. Keep away from oxidizing agents. Keep out of reach of children. Store in suitable labeled containers.
- Storage temperature : 5 °C to 40 °C

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

SAFETY DATA SHEET

ECOBRITE POWER PLUS

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
Dipropylene glycol methyl ether	34590-94-8	STEL	150 ppm 909 mg/m ³	BH OEL
		TWA	100 ppm 606 mg/m ³	BH OEL
Dipropylene glycol methyl ether	34590-94-8	TWA (8 Hour)	50 ppm 308 mg/m ³	TR OEL
Dipropylene glycol methyl ether	34590-94-8	TWA	100 ppm 606 mg/m ³	ARE OEL
		STEL	150 ppm 909 mg/m ³	ARE OEL
Isopropyl Alcohol	67-63-0	STEL OEL-RL	500 ppm 1,225 mg/m ³	ZA OEL
		TWA OEL-RL	400 ppm 960 mg/m ³	ZA OEL
Isopropyl Alcohol	67-63-0	TWA	400 ppm 983 mg/m ³	BH OEL
		STEL	500 ppm 1,230 mg/m ³	BH OEL
Isopropyl Alcohol	67-63-0	TWA	200 ppm 492 mg/m ³	ARE OEL
		STEL	400 ppm 984 mg/m ³	ARE OEL

Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
-----------	---------	--------------------	---------------------	---------------	---------------------------	-------

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

Personal protective equipment

Eye protection : Wear eye protection/face protection.

Hand protection : Wear the following personal protective equipment:
Standard glove type.
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin protection : No special protective equipment required.

Respiratory protection : No personal respiratory protective equipment normally required.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid
Colour : light yellow
Odour : odourless

SAFETY DATA SHEET

ECOBRITE POWER PLUS

pH	: 8.0 - 9.0, (100 %)
Flash point	: 66 °C closed cup, Does not sustain combustion.
Odour Threshold	: no data available
Melting point/freezing point	: no data available
Initial boiling point and boiling range	: no data available
Evaporation rate	: no data available
Flammability (solid, gas)	: Not applicable.
Upper explosion limit	: no data available
Lower explosion limit	: no data available
Vapour pressure	: no data available
Relative vapour density	: no data available
Relative density	: 0.975
Water solubility	: soluble
Solubility in other solvents	: no data available
Partition coefficient: n-octanol/water	: no data available
Auto-ignition temperature	: no data available
Thermal decomposition	: no data available
Viscosity, kinematic	: 51.374 mm ² /s (40 °C)
Explosive properties	: no data available
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Molecular weight	: no data available
VOC	: no data available

Section: 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reaction known under conditions of normal use.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: None known.
Hazardous decomposition products	: In case of fire hazardous decomposition products may be produced such as: Carbon oxides

Section: 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure	: Inhalation, Eye contact, Skin contact
--	---

SAFETY DATA SHEET

ECOBRITE POWER PLUS

Potential Health Effects

Eyes	: Causes serious eye damage.
Skin	: Causes skin irritation.
Ingestion	: Health injuries are not known or expected under normal use.
Inhalation	: Health injuries are not known or expected under normal use.
Chronic Exposure	: Health injuries are not known or expected under normal use.

Experience with human exposure

Eye contact	: Redness, Pain, Corrosion
Skin contact	: Redness, Irritation
Ingestion	: No information available.
Inhalation	: No symptoms known or expected.

Toxicity

Product

Acute oral toxicity	: no data available
Acute inhalation toxicity	: 4 h Acute toxicity estimate : > 200 mg/l Test atmosphere: vapour
Acute dermal toxicity	: no data available
Skin corrosion/irritation	: no data available
Serious eye damage/eye irritation	: no data available
Respiratory or skin sensitization	: no data available
Carcinogenicity	: no data available
Reproductive effects	: no data available
Germ cell mutagenicity	: no data available
Teratogenicity	: no data available
STOT - single exposure	: no data available
STOT - repeated exposure	: no data available
Aspiration toxicity	: no data available

Components

Acute oral toxicity	: Alcohols, C13-15, branched and linear, ethoxylated LD50 rat: 1,250 mg/kg
	Dipropylene glycol methyl ether LD50 rat: 5,135 mg/kg
	Isopropyl Alcohol LD50 rat: 5,840 mg/kg

Components

SAFETY DATA SHEET

ECOBRITE POWER PLUS

Acute dermal toxicity : Alcohols, C13-15, branched and linear, ethoxylated
LD50 rat: > 2,000 mg/kg

Dipropylene glycol methyl ether
LD50 rabbit: 9,510 mg/kg

Isopropyl Alcohol
LD50 rabbit: 12,870 mg/kg

Section: 12. ECOLOGICAL INFORMATION

Ecotoxicity

Environmental Effects : Harmful to aquatic life with long lasting effects.

Product

Toxicity to fish : no data available

Toxicity to daphnia and other aquatic invertebrates : no data available

Toxicity to algae : no data available

Components

Toxicity to fish : Dipropylene glycol methyl ether
96 h LC50 Fish: > 1,000 mg/l

Isopropyl Alcohol
96 h LC50 Pimephales promelas (fathead minnow): 9,640 mg/l

Components

Toxicity to daphnia and other aquatic invertebrates : Alcohols, C13-15, branched and linear, ethoxylated
48 h EC50 Daphnia magna (Water flea): 0.317 mg/l

Isopropyl Alcohol
LC50 Daphnia magna (Water flea): > 10,000 mg/l

Persistence and degradability

Readily biodegradable.

Bioaccumulative potential

no data available

Mobility in soil

no data available

Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Disposal methods : Do not contaminate ponds, waterways or ditches with chemical or used container. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.

SAFETY DATA SHEET

ECOBRITE POWER PLUS

Disposal considerations : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

Section: 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

UN number : 3082
UN proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Alcohol ethoxylate)
Transport hazard class(es) : 9
Packing group : III
Environmental hazards : Yes
Special precautions for user : None

Air transport (IATA)

UN number : 3082
Description of the goods : Environmentally hazardous substance, liquid, n.o.s. (Alcohol ethoxylate)
Class : 9
Packing group : III
Environmentally hazardous : Yes

Sea transport (IMDG/IMO)

UN number : 3082
Description of the goods : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Alcohol ethoxylate)
Class : 9
Packing group : III
Marine pollutant : Yes

Section: 15. REGULATORY INFORMATION


For Regulatory information please contact your Ecolab sales representative.

Section: 16. OTHER INFORMATION

SAFETY DATA SHEET

ECOBRITE POWER PLUS

NFPA:



HMIS III:

HEALTH	3
FLAMMABILITY	2
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Issuing date : 29.10.2019
Version : 1.6
Prepared by : Regulatory Affairs

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.