

SECTION 1. IDENTIFICATION OF THE CHEMICAL AND COMPANY

Product name : SKINMAN SOFT
 Other means of identification : Not applicable
 Recommended use : Skin-care
 Restrictions on use : Reserved for industrial and professional use.
 Product dilution information : Product is sold ready to use.
 Company : Chile ECOLAB S.A.
 Avenida Pedro de Valdivia 3801
 Santiago, Santiago Chile
 (2)-22413300, Telephone: (2)-22381603, Telephone: SAC: 600 241 6600
 sac.chile@ecolab.com
 Emergency telephone : (+56-2) 2247-3600 (CITUC)
 Toxicological Emergency Phone : CITUC (+56-2) 2635-3800 (24 hours)

SECTION 2. HAZARDS IDENTIFICATION

Classification according to NCH 382 : Class: Class 3 Flammable liquids

Distintivo según NCh 2190 :


GHS Classification

Flammable liquids : Category 2
 Eye irritation : Category 2A
 Specific target organ systemic toxicity - single exposure : Category 3 (Central nervous system)
 Acute aquatic toxicity : Category 3
 Chronic aquatic toxicity : Category 3

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : Highly flammable liquid and vapor.
 Causes serious eye irritation.
 May cause drowsiness or dizziness.

SAFETY DATA SHEET

SKINMAN SOFT

Harmful to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**
Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. Avoid release to the environment.
Response:
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. If eye irritation persists: Get medical advice/ attention. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:
Store in a well-ventilated place. Keep container tightly closed.

Other hazards : None known.

SECTION 3. COMPOSITION/INFORMATION OF INGREDIENTS

Pure substance/mixture : Mixture

Chemical name	CAS-No.	Concentration (%)
Isopropyl Alcohol	67-63-0	30 - 60

SECTION 4. FIRST AID MEASURES

In case of eye contact : Rinse with water.
In case of skin contact : Rinse with water.
If swallowed : Rinse mouth. Get medical attention if symptoms occur.
If inhaled : Get medical attention if symptoms occur.
Protection of first-aiders : No special precautions are necessary for first aid responders.
Notes to physician : Treat symptomatically.

Expected acute effects

Eyes : Causes serious eye irritation.
Skin : Health injuries are not known or expected under normal use.
Ingestion : Health injuries are not known or expected under normal use.
Inhalation : Inhalation may cause central nervous system effects.

Expected chronic effects

Chronic Exposure : Health injuries are not known or expected under normal use.

Most important symptoms / effects

Eye contact : Redness, Pain, Irritation
Skin contact : No symptoms known or expected.
Ingestion : No symptoms known or expected.
Inhalation : Dizziness, Drowsiness

SAFETY DATA SHEET

SKINMAN SOFT

SECTION 5. FIREFIGHTING MEASURES

- Extinguishing Agents : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing agents : High volume water jet
- Specific hazards during fire fighting : Fire Hazard
Keep away from heat and sources of ignition.
Flash back possible over considerable distance.
Beware of vapors accumulating to form explosive concentrations.
Vapors can accumulate in low areas.
- Products generated in combustion and thermal degradation : Decomposition products may include the following materials:
Carbon oxides
Nitrogen oxides (NO_x)
Sulfur oxides
Oxides of phosphorus
- Precautions for Emergency Personnel and / or Firefighters : Use personal protective equipment.
- Specific extinguishing methods : Use water spray to cool unopened containers. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6. MEASURES IN CASE OF ACCIDENTAL SPILLAGE

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed.
- Environmental precautions : Do not allow contact with soil, surface or ground water.
- Methods and materials for containment and cleaning up : Eliminate all ignition sources if safe to do so. Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

SECTION 7. HANDLING AND STORAGE

Handling

- Advice on safe handling : Keep away from fire, sparks and heated surfaces. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Open drum carefully as content may be under pressure.

Storage

- Conditions for safe storage : Keep away from heat and sources of ignition. Keep in a cool, well-ventilated place. Keep away from oxidizing agents. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.
- Recommended and : Use high density plastic containers.

SAFETY DATA SHEET

SKINMAN SOFT

unsuitable packaging by
supplier

Storage temperature : 0 °C to 25 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Ingredients	CAS-No.	Form of exposure	Permissible concentration	Basis
Isopropyl Alcohol	67-63-0	CMP	400 ppm	AR OEL
		CMP - CPT	500 ppm	AR OEL
Isopropyl Alcohol	67-63-0	LT	310 ppm 765 mg/m3	BR OEL
Isopropanol	67-63-0	LPP	350 ppm 858 mg/m3	CL OEL
		LPT	500 ppm 1.230 mg/m3	CL OEL
Isopropyl Alcohol	67-63-0	TWA	200 ppm 491 mg/m3	PE OEL
		STEL	400 ppm 983 mg/m3	PE OEL
Isopropyl Alcohol	67-63-0	L-8/40	200 ppm	VE OEL
		LB	400 ppm	VE OEL
Isopropyl Alcohol	67-63-0	VLE-PPT	200 ppm	NOM-010-STPS-2014
		VLE-CT	400 ppm	NOM-010-STPS-2014
Isopropyl Alcohol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		STEL	500 ppm 1.225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z1

Engineering measures : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal protective equipment

Eye protection : No special protective equipment required.

Hand protection : No special protective equipment required.

Skin protection : No special protective equipment required.

Respiratory protection : No personal respiratory protective equipment normally required.

Hygiene measures : No specific measures identified.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

SAFETY DATA SHEET

SKINMAN SOFT

Color	: blue
Odor	: Perfumes, fragrances
pH	: 5,0, (100 %)
Flash point	: 22 °C closed cup
Odor Threshold	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: No data available
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapor pressure	: No data available
Relative vapor density	: No data available
Relative density	: 0,88
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, kinematic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Molecular weight	: No data available
VOC	: No data available

SECTION 10. STABILITY AND REACTIVITY

Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reaction known under conditions of normal use.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Bases
Hazardous decomposition products	: Decomposition products may include the following materials: Carbon oxides Nitrogen oxides (NOx) Sulfur oxides Oxides of phosphorus

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of	: Inhalation, Eye contact, Skin contact
---------------------------------	---

SAFETY DATA SHEET

SKINMAN SOFT

exposure

Toxicity

Product

Acute oral toxicity	: No data available
Acute inhalation toxicity	: 4 h Acute toxicity estimate : > 40 mg/l Test atmosphere: vapor
Acute dermal toxicity	: No data available
Skin corrosion/irritation	: No data available
Serious eye damage/eye irritation	: No data available
Respiratory or skin sensitization	: No data available
Carcinogenicity	: No data available
Reproductive effects	: No data available
Germ cell mutagenicity	: No data available
Teratogenicity	: No data available
STOT-single exposure	: No data available
STOT-repeated exposure	: No data available
Aspiration toxicity	: No data available

Ingredients

Acute oral toxicity	: Isopropyl Alcohol LD50 Rat: 5.840 mg/kg
---------------------	--

Ingredients

Acute dermal toxicity	: Isopropyl Alcohol LD50 Rabbit: 12.870 mg/kg
-----------------------	--

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Environmental Effects	: Harmful to aquatic life with long lasting effects.
-----------------------	--

Product

Toxicity to fish	: No data available
Toxicity to daphnia and other aquatic invertebrates	: No data available
Toxicity to algae	: No data available

Ingredients

Toxicity to fish	: Isopropyl Alcohol 96 h LC50 Pimephales promelas: 9.640 mg/l
------------------	--

Ingredients

Toxicity to daphnia and other aquatic invertebrates	: Isopropyl Alcohol LC50 Daphnia magna (Water flea): > 10.000 mg/l
---	---

SAFETY DATA SHEET

SKINMAN SOFT

Persistence and degradability

Readily biodegradable.

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. INFORMATION OF DISPOSAL

- Disposal methods : The product should not be allowed to enter drains, water courses or the soil. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.
- Disposal considerations : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.
- Disposal of contaminated packaging : In accordance with what is described by Supreme Decree No. 148, the packaging of the product is considered hazardous waste and must be disposed of through companies authorized to receive and / or treat such waste, which must be issued and final disposal certificate waste.

SECTION 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport

Official transport classification of the United Nations

UN number	:	1219
Description of the goods	:	ISOPROPANOL
Class	:	3
Packing group	:	II
Environmentally hazardous	:	no

Air transport (IATA)

Official transport classification of the United Nations

Contact Regulatory for air freight eligibility

Sea transport (IMDG/IMO)

Official transport classification of the United Nations

UN number	:	1219
Description of the goods	:	ISOPROPANOL
Class	:	3
Packing group	:	II
Transport in bulk according to Annex II of MARPOL	:	Not applicable

SAFETY DATA SHEET

SKINMAN SOFT

73/78 and the IBC Code		
Marine pollutant	:	no

SECTION 15. REGULATORY INFORMATION

Registrations and Certifications

Chile: Our HDS meets Chilean Normative: NCH 2245: 2015 (Safety Data Sheet for chemical products - Content and order of sections)

The receiver should pay attention to the possible existence of local regulations.

NCh 1411: Prevention of risks, IV identification of risks of materials

NCh 2190: Transportation of Hazardous Substances - Pictograms for hazard identification

NCh 382: Dangerous Good - Classification

D.S. No. 594: Minimum basic conditions in the workplace

D.S. No. 148: Hazardous waste disposal


D.S. No. 72: Mining Safety Regulations

D. S. No. 43: reports on the storage of hazardous substances

D. S. No. 40: Reporting on exposure hazards

SECTION 16. OTHER INFORMATION

NFPA:



HMIS III:

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Issuing date : 27.12.2017
Version : 1.0
Prepared by : Regulatory Affairs

While there is no change in the formula or hazard classifications, this SDS remains valid

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.