

SECTION 1. IDENTIFICATION OF THE CHEMICAL AND COMPANY

Product name	: RADIANCE
Other means of identification	: Not applicable
Recommended use	: Furniture Polish
Restrictions on use	: Reserved for industrial and professional use.
Product dilution information	: Product is sold ready to use.
Company	: Chile ECOLAB S.A. Avenida Pedro de Valdivia 3801 Santiago, Santiago Chile (2)-22413300, Telephone: (2)-22381603, Telephone: SAC: 600 241 6600 sac.chile@ecolab.com
Emergency telephone	: (+56-2) 2635-3600 (CITUC) EMERGENCY PHONE
Toxicological Emergency Phone	: CITUC (+56-2) 2635-3800 (24 hours) Toxicological Emergencies

SECTION 2. HAZARDS IDENTIFICATION

Classification according to NCh 382 : Class: Class 2.1 Flammable gases
Class Secondary: Class 8 Corrosives

Distintivo según NCh 2190 :


GHS Classification

Aerosols : Category 2
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : Flammable aerosol.
Pressurised container: May burst if heated.
May cause drowsiness or dizziness.

Precautionary Statements : **Prevention:**
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other

SAFETY DATA SHEET

RADIANCE

ignition source. Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. Use only outdoors or in a well-ventilated area. Intentional misuse by deliberate inhalation may be harmful or fatal.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards : None known.

SECTION 3. COMPOSITION/INFORMATION OF INGREDIENTS

Pure substance/mixture : Mixture

Chemical name	CAS-No.	Concentration (%)
distillates (petroleum), hydrotreated light	64742-47-8	10 - 30
Butane	106-97-8	5 - 10
propane	74-98-6	5 - 10

SECTION 4. FIRST AID MEASURES

In case of eye contact : Rinse with plenty of water.

In case of skin contact : Rinse with plenty of water.

If swallowed : Rinse mouth. Get medical attention if symptoms occur.

If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Notes to physician : Treat symptomatically.

Expected acute effects

Eyes : Health injuries are not known or expected under normal use.

Skin : Health injuries are not known or expected under normal use.

Ingestion : Health injuries are not known or expected under normal use.

Inhalation : Inhalation may cause central nervous system effects. Intentional misuse by deliberate inhalation may be harmful or fatal.

Expected chronic effects

Chronic Exposure : Health injuries are not known or expected under normal use.

Most important symptoms / effects

Eye contact : No symptoms known or expected.

Skin contact : No symptoms known or expected.

SAFETY DATA SHEET

RADIANCE

Ingestion : No symptoms known or expected.

Inhalation : Dizziness, Drowsiness

SECTION 5. FIREFIGHTING MEASURES

Extinguishing Agents : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing agents : High volume water jet

Specific hazards during fire fighting : Pressurised container: May burst if heated.
Flammable aerosols

Products generated in combustion and thermal degradation : Decomposition products may include the following materials:
Carbon oxides

Precautions for Emergency Personnel and / or Firefighters : Use personal protective equipment.

Specific extinguishing methods : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6. MEASURES IN CASE OF ACCIDENTAL SPILLAGE

Personal precautions, protective equipment and emergency procedures : Refer to protective measures listed.

Environmental precautions : Do not allow contact with soil, surface or ground water.

Methods and materials for containment and cleaning up : Stop leak if safe to do so.

SECTION 7. HANDLING AND STORAGE

Handling

Advice on safe handling : Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. Use only with adequate ventilation. Contents under pressure. Do not puncture. Wash hands thoroughly after handling. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).

Storage

Conditions for safe storage : Keep in a cool, well-ventilated place. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

Recommended and unsuitable packaging by supplier : Use high density plastic containers.

Storage temperature : 0 °C to 50 °C

SAFETY DATA SHEET

RADIANCE

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
distillates (petroleum), hydrotreated light	64742-47-8	CMP (Mist)	5 mg/m ³	AR OEL
		CMP - CPT (Mist)	10 mg/m ³	AR OEL
distillates (petroleum), hydrotreated light	64742-47-8	TWA (Mist)	5 mg/m ³	PE OEL
		STEL (Mist)	10 mg/m ³	PE OEL
distillates (petroleum), hydrotreated light	64742-47-8	L-8/40 (Mist)	5 mg/m ³	VE OEL
		LB (Mist)	10 mg/m ³	VE OEL
distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2.000 mg/m ³	OSHA Z1
		TWA	200 mg/m ³ (total hydrocarbon vapor)	ACGIH
		TWA (Mist)	5 mg/m ³	OSHA Z1
		TWA (Mist)	5 mg/m ³	NIOSH REL
		STEL (Mist)	10 mg/m ³	NIOSH REL
Butane	106-97-8	CMP	800 ppm	AR OEL
Butane	106-97-8	LT	470 ppm 1.090 mg/m ³	BR OEL
Butane	106-97-8	TWA	800 ppm 1.902 mg/m ³	PE OEL
Butane	106-97-8	L-8/40 (gas)	1.000 ppm	VE OEL
Butane	106-97-8	VLE-PPT	1.000 ppm	NOM-010-STPS-2014
Butane	106-97-8	TWA	800 ppm 1.900 mg/m ³	NIOSH REL
		STEL	1.000 ppm	ACGIH

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

Personal protective equipment

Eye protection : No special protective equipment required.

Hand protection : No special protective equipment required.

Skin protection : No special protective equipment required.

Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Wash face, hands and any exposed skin thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

SAFETY DATA SHEET

RADIANCE

Appearance	: aerosol
Color	: clear, off-white
Odor	: citrus
pH	: 7,0, (100 %)
Flash point	: Not applicable, Sustains combustion
Odor Threshold	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: > 100 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: Not applicable
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapor pressure	: No data available
Relative vapor density	: No data available
Relative density	: 0,8714 - 0,8716
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, kinematic	: 3900,000 mm ² /s (40 °C)
Explosive properties	: No data available
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Molecular weight	: No data available
VOC	: No data available
Heat of combustion	: 10,49 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reaction known under conditions of normal use.
Conditions to avoid	: None known.
Incompatible materials	: None known.
Hazardous decomposition products	: In case of fire hazardous decomposition products may be produced such as:

SAFETY DATA SHEET

RADIANCE

Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Eye contact

Skin contact

Toxicity

Product

Acute oral toxicity : No data available
Acute inhalation toxicity : No data available
Acute dermal toxicity : No data available
Skin corrosion/irritation : No data available
Serious eye damage/eye irritation : No data available
Respiratory or skin sensitization : No data available
Carcinogenicity : No data available
Reproductive effects : No data available
Germ cell mutagenicity : No data available
Teratogenicity : No data available
STOT-single exposure : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects. May cause drowsiness or dizziness.
STOT-repeated exposure : No data available
Aspiration toxicity : No data available

Components

Acute oral toxicity : distillates (petroleum), hydrotreated light
LD50 Rat: > 5.000 mg/kg

Components

Acute inhalation toxicity : Butane
4 h LC50 Rat: 280000 ppm
Test atmosphere: gas

Components

Acute dermal toxicity : distillates (petroleum), hydrotreated light
LD50 Rabbit: > 5.000 mg/kg

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Environmental Effects : This product has no known ecotoxicological effects.

Product

Toxicity to fish : No data available

SAFETY DATA SHEET

RADIANCE

Toxicity to daphnia and other aquatic invertebrates : No data available

Toxicity to algae : No data available

Components

Toxicity to fish : distillates (petroleum), hydrotreated light
96 h LC50 Oncorhynchus mykiss (rainbow trout): > 1.000 mg/l

Butane
96 h LC50 Fish: 22,03 mg/l

Components

Toxicity to daphnia and other aquatic invertebrates : distillates (petroleum), hydrotreated light
48 h EC50 Daphnia magna (Water flea): > 1.000 mg/l

Components

Toxicity to algae : distillates (petroleum), hydrotreated light
72 h EC50 Pseudokirchneriella subcapitata (green algae): > 1.000 mg/l

Persistence and degradability

Readily biodegradable.

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. INFORMATION OF DISPOSAL

Disposal methods : Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.

Disposal of contaminated packaging : In accordance with what is described by Supreme Decree No. 148, the packaging of the product is considered hazardous waste and must be disposed of through companies authorized to receive and / or treat such waste, which must be issued and final disposal certificate waste.

Disposal of contaminated packaging : In accordance with what is described by Supreme Decree No. 148, the packaging of the product is considered hazardous waste and must be disposed of through companies authorized to receive and / or treat such waste, which must be issued and final disposal certificate waste.

SECTION 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport

Official transport classification of the United Nations

UN number	:	1950
-----------	---	------

SAFETY DATA SHEET

RADIANCE

Description of the goods	:	AEROSOLS
Class	:	2.1 (8)
Environmentally hazardous	:	no

Air transport (IATA)

Official transport classification of the United Nations

Contact Regulatory for air freight eligibility

Sea transport (IMDG/IMO)

Official transport classification of the United Nations

UN number	:	1950
Description of the goods	:	AEROSOLS
Class	:	2.1
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	:	Not applicable
Marine pollutant	:	no

SECTION 15. REGULATORY INFORMATION

Registrations and Certifications

Chile: Our HDS meets Chilean Normative: NCH 2245: 2015 (Safety Data Sheet for chemical products - Content and order of sections)

The receiver should pay attention to the possible existence of local regulations.

NCh 1411: Prevention of risks, IV identification of risks of materials

NCh 2190: Transportation of Hazardous Substances - Pictograms for hazard identification

NCh 382: Dangerous Good - Classification

D.S. No. 594: Minimum basic conditions in the workplace

D.S. No. 148: Hazardous waste disposal


D.S. No. 72: Mining Safety Regulations

D. S. No. 43: reports on the storage of hazardous substances

D. S. No. 40: Reporting on exposure hazards

SECTION 16. OTHER INFORMATION

NFPA:



HMIS III:

HEALTH	0
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Issuing date : 14.12.2021
Version : 1.1
Prepared by : Regulatory Affairs

While there is no change in the formula or hazard classifications, this SDS remains valid.

SAFETY DATA SHEET

RADIANCE

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.