

Section: 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : SIRAFAN SPEED

Other means of identification : Not applicable.

Recommended use : Disinfectant

Restrictions on use : Reserved for industrial and professional use.

Product dilution information : No dilution information provided.

Company

Ecolab Gulf FZE
P.O. Box 17063
Jebel Ali Free Zone Area, Near Container Terminal 3 - North Zone
Dubai
UAE
00971 4 8014444 Customer Services, 00971 48146800 00971 4
8014000 Reception phone numbers

Nalco Egypt Trading
5th Settlement, South 90th St.
The Address Building No 67th – 1st floor
New Cairo, Cairo, Egypt11835
0020 2 25 37 1195,

Ecolab Maroc S.A.R.L.
Batiment, Lot. Mounir 1, Parc Industriel
Attawfik
Route 1029
Sidi Maarouf, Casablanca, Morocco
00212 22 58 25 30 - 35,

Emergency telephone : +32-(0)3-575-5555 Trans-European
number

Issuing date : 13.08.2021

Section: 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 3

Skin irritation : Category 2

Eye irritation : Category 2A

Specific target organ toxicity - single exposure : Category 3 (Central Nervous System)

GHS Label element

Hazard pictograms :



SAFETY DATA SHEET

SIRAFAN SPEED

Signal Word : Warning

Hazard Statements : Flammable liquid and vapour.
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.

Precautionary Statements : **Prevention:**
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapours. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/ eye protection/ face protection.
Response:
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:
Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal:
Dispose of contents/ container to an approved waste disposal plant.

Other hazards : None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

Pure substance/mixture : Mixture

Chemical Name	CAS-No.	Concentration: (%)
Isopropyl Alcohol	67-63-0	30 - 60
propan-1-ol	71-23-8	10 - 30
Propylene glycol	57-55-6	1 - 5

Section: 4. FIRST AID MEASURES

In case of eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.

In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Get medical attention if irritation develops and persists.

If swallowed : Rinse mouth. Get medical attention if symptoms occur.

If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

SAFETY DATA SHEET

SIRAFAN SPEED

Protection of first-aiders	: If potential for exposure exists refer to Section 8 for specific personal protective equipment.
Notes to physician	: Treat symptomatically.
Most important symptoms and effects, both acute and delayed	: See Section 11 for more detailed information on health effects and symptoms.

Section: 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Fire Hazard Keep away from heat and sources of ignition. Flash back possible over considerable distance. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Hazardous combustion products	: Decomposition products may include the following materials: Carbon oxides
Special protective equipment for firefighters	: Use personal protective equipment.
Specific extinguishing methods	: Use water spray to cool unopened containers. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Remove all sources of ignition. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.
Environmental precautions	: Do not allow contact with soil, surface or ground water.
Methods and materials for containment and cleaning up	: Eliminate all ignition sources if safe to do so. Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

Section: 7. HANDLING AND STORAGE

Advice on safe handling	: Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray. Use only with adequate ventilation. Keep away from fire, sparks and heated surfaces. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Wash hands thoroughly after handling. Open drum carefully as content may be under pressure. In case of
-------------------------	---

SAFETY DATA SHEET

SIRAFAN SPEED

mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).

Conditions for safe storage : Keep away from heat and sources of ignition. Keep in a cool, well-ventilated place. Keep away from oxidizing agents. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

Storage temperature : 0 °C to 25 °C

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
Isopropyl Alcohol	67-63-0	TWA	400 ppm 983 mg/m ³	BH OEL
		STEL	500 ppm 1,230 mg/m ³	BH OEL
Isopropyl Alcohol	67-63-0	TWA	200 ppm 492 mg/m ³	ARE OEL
		STEL	400 ppm 984 mg/m ³	ARE OEL
Isopropyl Alcohol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m ³	NIOSH REL
		STEL	500 ppm 1,225 mg/m ³	NIOSH REL
		TWA	400 ppm 980 mg/m ³	OSHA Z1
propan-1-ol	71-23-8	TWA	200 ppm 592 mg/m ³	BH OEL
		STEL	250 ppm 614 mg/m ³	BH OEL
propan-1-ol	71-23-8	STEL	250 ppm 614 mg/m ³	ARE OEL
		TWA	100 ppm 246 mg/m ³	ARE OEL
propan-1-ol	71-23-8	TWA	100 ppm	ACGIH
		TWA	200 ppm 500 mg/m ³	NIOSH REL
		STEL	250 ppm 625 mg/m ³	NIOSH REL
		TWA	200 ppm 500 mg/m ³	OSHA Z1
Propylene glycol	57-55-6	TWA	10 mg/m ³	AIHA WEEL

Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
-----------	---------	--------------------	---------------------	---------------	---------------------------	-------

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

SAFETY DATA SHEET

SIRAFAN SPEED

Personal protective equipment

Eye protection	: Wear eye protection/face protection.
Hand protection	: Recommended preventive skin protection Gloves Nitrile rubber butyl-rubber Breakthrough time: 1 – 4 hours Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
Skin protection	: No special protective equipment required.
Respiratory protection	: None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety practice. Wash face, hands and any exposed skin thoroughly after handling.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: clear, colourless
Odour	: alcohol-like
pH	: 7.5 - 8.5, (100 %)
Flash point	: 25 °C closed cup
Odour Threshold	: no data available
Melting point/freezing point	: no data available
Initial boiling point and boiling range	: no data available
Evaporation rate	: no data available
Flammability (solid, gas)	: Not applicable.
Upper explosion limit	: no data available
Lower explosion limit	: no data available
Vapour pressure	: no data available
Relative vapour density	: no data available
Relative density	: 0.876 - 0.896
Water solubility	: soluble
Solubility in other solvents	: no data available
Partition coefficient: n-octanol/water	: no data available
Auto-ignition temperature	: no data available

SAFETY DATA SHEET

SIRAFAN SPEED

Thermal decomposition	: no data available
Viscosity, kinematic	: no data available
Explosive properties	: no data available
Oxidizing properties	: no data available
Molecular weight	: no data available
VOC	: no data available

Section: 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reaction known under conditions of normal use.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: None known.
Hazardous decomposition products	: In case of fire hazardous decomposition products may be produced such as: Carbon oxides

Section: 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure	: Inhalation, Eye contact, Skin contact
--	---

Potential Health Effects

Eyes	: Causes serious eye irritation.
Skin	: Causes skin irritation.
Ingestion	: Health injuries are not known or expected under normal use.
Inhalation	: May cause respiratory tract irritation. May cause nose, throat, and lung irritation. Inhalation may cause central nervous system effects.
Chronic Exposure	: Health injuries are not known or expected under normal use.

Experience with human exposure

Eye contact	: Redness, Pain, Irritation
Skin contact	: Redness, Irritation
Ingestion	: No symptoms known or expected.
Inhalation	: Respiratory irritation, Cough, Dizziness, Drowsiness

Toxicity

Product

Acute oral toxicity	: no data available
---------------------	---------------------

SAFETY DATA SHEET

SIRAFAN SPEED

Acute inhalation toxicity	: 4 h Acute toxicity estimate : 86.58 mg/l Test atmosphere: vapour
Acute dermal toxicity	: Acute toxicity estimate : > 5,000 mg/kg
Skin corrosion/irritation	: No skin irritation
Serious eye damage/eye irritation	: Eye irritation Method: OECD Test Guideline 405 Test substance: Similar Product
Respiratory or skin sensitization	: no data available
Carcinogenicity	: no data available
Reproductive effects	: no data available
Germ cell mutagenicity	: no data available
Teratogenicity	: no data available
STOT - single exposure	: May cause drowsiness or dizziness.
STOT - repeated exposure	: no data available
Aspiration toxicity	: no data available

Components

Acute oral toxicity	: Isopropyl Alcohol LD50 rat: 5,840 mg/kg
	propan-1-ol LD50 : 1,870 mg/kg
	Propylene glycol LD50 rat: 22,000 mg/kg

Section: 12. ECOLOGICAL INFORMATION

Toxicity

Environmental Effects	: This product has no known ecotoxicological effects.
-----------------------	---

Product

Toxicity to fish	: no data available
Toxicity to daphnia and other aquatic invertebrates	: no data available
Toxicity to algae	: no data available

Components

Toxicity to fish	: Isopropyl Alcohol 96 h LC50 Pimephales promelas (fathead minnow): 9,640 mg/l
	propan-1-ol 96 h EC50: 3,800 mg/l
	Propylene glycol 96 h LC50 Fish: > 10,000 mg/l

Components

Toxicity to daphnia and other	: Isopropyl Alcohol
-------------------------------	---------------------

SAFETY DATA SHEET

SIRAFAN SPEED

aquatic invertebrates LC50 Daphnia magna (Water flea): > 10,000 mg/l

propan-1-ol
48 h LC50: 1,000 mg/l

Propylene glycol
48 h EC50 Aquatic Invertebrate: 18,340 mg/l

Components

Toxicity to algae : propan-1-ol
48 h EC50: 9,170 mg/l

Persistence and degradability

Readily biodegradable.

Bioaccumulative potential

no data available

Mobility in soil

no data available

Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Disposal methods : Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.

Disposal considerations : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

Section: 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

UN number : 1987
UN proper shipping name : ALCOHOLS, N.O.S.
(Isopropanol, Propanol)
Transport hazard class(es) : 3
Packing group : III
Environmental hazards : No
Special precautions for user : None

Air transport (IATA)

UN number : 1987
Proper shipping name : Alcohols, n.o.s.
(Isopropanol, Propanol)
Class : 3
Packing group : III

SAFETY DATA SHEET

SIRAFAN SPEED

Environmentally hazardous : No

Sea transport (IMDG/IMO)


UN number : 1987
Proper shipping name : ALCOHOLS, N.O.S.
(Isopropanol, Propanol)
Class : 3
Packing group : III
Marine pollutant : No

Section: 15. REGULATORY INFORMATION

For Regulatory information please contact your Ecolab sales representative.

Section: 16. OTHER INFORMATION

NFPA:



HMIS III:

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Issuing date : 13.08.2021
version : 1.1
Prepared by : Regulatory Affairs

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.