

480mm

OXYSAN ZS**ACTIVE INGREDIENTS:** Contains 450 g/L Acetic acid, 89 g/L Hydrogen peroxide, 59 g/L Peroxyacetic acid.

Oxysan® ZS is an effective cold sanitiser of pre-cleaned surfaces such as processing equipment, floors, walls and drains. The unique Dual Peroxid chemistry and highly concentrated formula make this product highly efficient and economical for all CIP and spray sanitising applications in the dairy, beverage and food processing industries. Oxysan ZS is also suitable for use with most membrane types.

DIRECTIONS FOR USE

Before use, all edible product and packaging material must be removed from the room or carefully protected. Prior to sanitising, wash all surfaces with a detergent solution, followed by a potable water rinse.

Use Oxysan ZS at concentrations of 0.08% - 0.25% v/v (0.8 to 2.5mL per litre). Use immersion, coarse spray or circulation techniques as appropriate to the equipment. All surfaces should be exposed to the sanitising solution for at least one minute unless otherwise specified by governing sanitation code. After using Oxysan ZS food contact surfaces must be thoroughly rinsed with potable water before production starts.

Fish processors may be exempt, see NZFSA requirements.

Consult your Ecolab Representative for specific use instructions and recommended dispensing equipment.

FIRST AID:

Immediately call the NATIONAL POISONS CENTRE 0800 764 766 or a doctor/physician, have product container or label at hand.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

PRECAUTIONS: Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep only in original container. Take any precaution to avoid mixing with combustibles and other incompatible materials. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Do not breathe vapour. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

STORAGE: Store locked up. Store away from combustibles. Store in corrosive resistant container with a resistant inliner. Keep container tightly closed. Keep container in a cool well ventilated area. Keep away from incompatibles, such as reducing materials, alkalis, metals and organic materials.

DISPOSAL: Prevent spillage entering water drains. For small spills, add compatible absorbent (soil may be used in the absence of other suitable material), scoop up material and place in a sealable, liquid proof container for disposal. For large spills, dyke spill material or otherwise contain material to ensure runoff does not reach a waterway. Place spill material in an appropriate container for disposal.

READ MATERIAL SAFETY DATA SHEET BEFORE USING THIS PRODUCT

EMERGENCY HEALTH INFORMATION:

AUSTRALIA 1800 022 002 NEW ZEALAND 0800 243 622

EMERGENCY RESPONSE INFORMATION SERVICE 0800 243 622 (0800CHEMCALL)

May intensify fire; oxidiser.

May be corrosive to metals.

Harmful if swallowed.

Harmful if inhaled.

May be harmful in contact with skin.

Causes severe skin burns and eye damage.

Causes damage to organs if inhaled.

Very toxic to aquatic life.

Harmful to terrestrial vertebrates.

MPI APPROVED C 43 (ALL ANIMAL PRODUCTS EXCEPT DAIRY)

MPI RECOGNISED FOR USE IN DAIRY PROCESSING



Registered To:

ECOLAB®

AUSTRALIA Ecolab 2 Drake Avenue Macquarie Park NSW 2113 tel: 1800 022 002
NEW ZEALAND Ecolab 2 Daniel Place Te Rapa Hamilton 3241 tel: 0508 732 733

DANGER

KEEP OUT OF REACH OF CHILDREN

ECOLAB®***Oxysan ZS****Sanitiser*

READ LABEL BEFORE USE

To: Adam

Company: Ecolab

Description: Oxysam 25

Please Read: This is your artwork for approval. Please check carefully, pay particular attention to phone, fax and code numbers, internet and mailing addresses, barcode numbers etc. CLEARLY indicate any alterations, tick appropriate box, and return the signed proof to us at your earliest convenience.

Check thoroughly as responsibility passes to the client once this work is signed and Approved. Thank you.

NOTE: Any delay in response or corrections to the artwork may affect delivery date. Changes to the original may incur additional cost. Colour proofs are intended as a guide and are not representative of final results. Colour matching to a computer screen is not possible.



Phone: 07 849 5295

Fax: 07 849 3902

Size: 480mm x 165mm

Stock: White Gloss Vinyl

Quantity: 1 total

Finishing: Face Slit, Guillotined

Ref #: 95963

PROOF #: 2

Printed Colours:

Black

PMS 109

Ecolab Grey

PMS 185

DATE: 12-12-2013

LPI: #85?

Operator: AP

ensure PMS numbers are supplied.

☐ OK to proceed

NAME: _____

☐ Revised Proof required

DATE: / /

SIGNED: _____