

SECTION 1. IDENTIFICATION OF THE CHEMICAL AND COMPANY

Product name : WOOD SHIELD
 Other means of identification : Not applicable
 Recommended use : Furniture Polish
 Restrictions on use : Reserved for industrial and professional use.
 Product dilution information : No dilution information provided.
 Company : Chile ECOLAB S.A.
 Avenida Pedro de Valdivia 3801
 Santiago, Santiago Chile
 (2)-22413300, Telephone: (2)-22381603, Telephone: SAC: 600 241 6600
 sac.chile@ecolab.com
 Emergency telephone : (+56-2) 2247-3600 (CITUC)
 Toxicological Emergency Phone : CITUC (+56-2) 2635-3800 (24 hours)

SECTION 2. HAZARDS IDENTIFICATION

Classification according to NCH 382 : Not classified according to NCh 382

Distintivo según NCh 2190 : Not classified according to NCh 382

GHS Classification

Flammable liquids : Category 3
 Skin irritation : Category 3
 Carcinogenicity : Category 2
 Aspiration hazard : Category 1
 Acute aquatic toxicity : Category 3

GHS label elements

Hazard pictograms :  

Signal Word : Danger

Hazard Statements : Flammable liquid and vapor.
 May be fatal if swallowed and enters airways.
 Causes mild skin irritation.
 Suspected of causing cancer.
 Harmful to aquatic life.

Precautionary Statements : **Prevention:**
 Obtain special instructions before use. Keep away from

SAFETY DATA SHEET

WOOD SHIELD

heat/sparks/open flames/hot surfaces. No smoking. Avoid release to the environment. Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF exposed or concerned: Get medical advice/ attention. Do NOT induce vomiting. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

Store in a well-ventilated place. Keep cool.

Other hazards : None known.

SECTION 3. COMPOSITION/INFORMATION OF INGREDIENTS

Pure substance/mixture : Mixture

Chemical name	CAS-No.	Concentration (%)
Stoddard Solvent	8052-41-3	30 - 60
Siloxane, dimethyl	63148-62-9	1 - 5
amides, tall-oil fatty, n,n-bis(hydroxyethyl)	68155-20-4	1 - 5
smectite-group minerals	12199-37-0	1 - 5
2,2'-iminodiethanol	111-42-2	0,1 - 1

SECTION 4. FIRST AID MEASURES

In case of eye contact : Rinse with plenty of water.

In case of skin contact : Rinse with plenty of water.

If swallowed : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Aspiration hazard if swallowed - can enter lungs and cause damage. Get medical attention immediately.

If inhaled : Get medical attention if symptoms occur.

Protection of first-aiders : No special precautions are necessary for first aid responders.

Notes to physician : Treat symptomatically.

Expected acute effects

Eyes : Health injuries are not known or expected under normal use.

Skin : Causes mild skin irritation.

Ingestion : May be fatal if swallowed and enters airways.

Inhalation : Health injuries are not known or expected under normal use.

Expected chronic effects

Chronic Exposure : Suspected of causing cancer.

Most important symptoms / effects

Eye contact : No symptoms known or expected.

Skin contact : slight irritation

SAFETY DATA SHEET

WOOD SHIELD

Ingestion : Vomiting

Inhalation : No symptoms known or expected.

SECTION 5. FIREFIGHTING MEASURES

Extinguishing Agents : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing agents : High volume water jet

Specific hazards during fire fighting : Fire Hazard
Keep away from heat and sources of ignition.
Flash back possible over considerable distance.
Beware of vapors accumulating to form explosive concentrations.
Vapors can accumulate in low areas.

Products generated in combustion and thermal degradation : Decomposition products may include the following materials:
Carbon oxides
Nitrogen oxides (NOx)
Sulfur oxides
Oxides of phosphorus

Precautions for Emergency Personnel and / or Firefighters : Use personal protective equipment.

Specific extinguishing methods : Use water spray to cool unopened containers. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6. MEASURES IN CASE OF ACCIDENTAL SPILLAGE

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed.

Environmental precautions : Do not allow contact with soil, surface or ground water.

Methods and materials for containment and cleaning up : Eliminate all ignition sources if safe to do so. Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

SECTION 7. HANDLING AND STORAGE

Handling

Advice on safe handling : Keep away from fire, sparks and heated surfaces. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Wash hands thoroughly after handling.

Storage

Conditions for safe storage : Keep away from heat and sources of ignition. Keep in a cool, well-ventilated place. Keep away from oxidizing agents. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled

SAFETY DATA SHEET

WOOD SHIELD

containers.

Recommended and unsuitable packaging by supplier : Use high density plastic containers.

Storage temperature : 50 °C to -25 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Ingredients	CAS-No.	Form of exposure	Permissible concentration	Basis
Stoddard Solvent	8052-41-3	CMP	100 ppm	AR OEL
Stoddard Solvent	8052-41-3	L-8/40	100 ppm	VE OEL
Stoddard Solvent	8052-41-3	LMPE-PPT	100 ppm 523 mg/m ³	MX OEL
		LMPE-CT	200 ppm 1.050 mg/m ³	MX OEL
		VLE-PPT	100 ppm	NOM-010-STPS-2014
Stoddard Solvent	8052-41-3	TWA	100 ppm	ACGIH
		TWA	350 mg/m ³	NIOSH REL
		Ceiling	1.800 mg/m ³	NIOSH REL
		TWA	500 ppm 2.900 mg/m ³	OSHA Z1
2,2'-iminodiethanol	111-42-2	CMP	2 mg/m ³	AR OEL
2,2'-iminodiethanol	111-42-2	TWA	0,46 ppm 2 mg/m ³	PE OEL
2,2'-iminodiethanol	111-42-2	L-8/40	1 mg/m ³	VE OEL
2,2'-iminodiethanol	111-42-2	VLE-PPT	2 mg/m ³	NOM-010-STPS-2014
2,2'-iminodiethanol	111-42-2	TWA (Inhalable fraction and vapor)	1 mg/m ³	ACGIH
		TWA	3 ppm 15 mg/m ³	NIOSH REL

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

Personal protective equipment

Eye protection : Safety goggles
Face-shield

Hand protection : Wear the following personal protective equipment:
Impervious gloves, resistant to chemicals.
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin protection : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing

Respiratory protection : No personal respiratory protective equipment normally required.

SAFETY DATA SHEET

WOOD SHIELD

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Wash face, hands and any exposed skin thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Color	: opaque, light yellow
Odor	: citrus
pH	: 8,0 - 9,2, (100 %)
Flash point	: 52 °C closed cup, Sustains combustion
Odor Threshold	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: > 100 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapor pressure	: No data available
Relative vapor density	: No data available
Relative density	: 1,1 - 1,12
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, kinematic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Molecular weight	: No data available
VOC	: No data available

SECTION 10. STABILITY AND REACTIVITY

Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reaction known under conditions of normal use.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: None known.
Hazardous decomposition	: Decomposition products may include the following materials:

SAFETY DATA SHEET

WOOD SHIELD

products	Carbon oxides Nitrogen oxides (NOx) Sulfur oxides Oxides of phosphorus
----------	---

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Toxicity

Product

Acute oral toxicity	: Acute toxicity estimate : > 5.000 mg/kg
Acute inhalation toxicity	: No data available
Acute dermal toxicity	: Acute toxicity estimate : > 5.000 mg/kg
Skin corrosion/irritation	: No data available
Serious eye damage/eye irritation	: No data available
Respiratory or skin sensitization	: No data available
Carcinogenicity	: No data available
Reproductive effects	: No data available
Germ cell mutagenicity	: No data available
Teratogenicity	: No data available
STOT-single exposure	: No data available
STOT-repeated exposure	: No data available
Aspiration toxicity	: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Environmental Effects : Harmful to aquatic life.

Product

Toxicity to fish	: No data available
Toxicity to daphnia and other aquatic invertebrates	: No data available
Toxicity to algae	: No data available

Ingredients

Toxicity to fish	: Siloxane, dimethyl 96 h LC50 Fish: 38 mg/l
------------------	---

Ingredients

Toxicity to daphnia and other aquatic invertebrates	: 2,2'-iminodiethanol 48 h EC50 Daphnia: 65,5 mg/l
---	---

Ingredients

SAFETY DATA SHEET

WOOD SHIELD

Toxicity to algae : amides, tall-oil fatty, n,n-bis(hydroxyethyl)
72 h EC50: 1,1 mg/l

Persistence and degradability

Poorly biodegradable

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. INFORMATION OF DISPOSAL

- Disposal methods : The product should not be allowed to enter drains, water courses or the soil. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.
- Disposal considerations : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.
- Disposal of contaminated packaging : In accordance with what is described by Supreme Decree No. 148, the packaging of the product is considered hazardous waste and must be disposed of through companies authorized to receive and / or treat such waste, which must be issued and final disposal certificate waste.

SECTION 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport

Official transport classification of the United Nations

Not dangerous goods

Air transport (IATA)

Official transport classification of the United Nations

Contact Regulatory for air freight eligibility

Sea transport (IMDG/IMO)

Official transport classification of the United Nations

Not dangerous goods

SECTION 15. REGULATORY INFORMATION

Registrations and Certifications

SAFETY DATA SHEET

WOOD SHIELD

Chile: Our HDS meets Chilean Normative: NCH 2245: 2015 (Safety Data Sheet for chemical products - Content and order of sections)

The receiver should pay attention to the possible existence of local regulations.

NCh 1411: Prevention of risks, IV identification of risks of materials

NCh 2190: Transportation of Hazardous Substances - Pictograms for hazard identification

NCh 382: Dangerous Good - Classification

D.S. No. 594: Minimum basic conditions in the workplace

D.S. No. 148: Hazardous waste disposal


D.S. No. 72: Mining Safety Regulations

D. S. No. 43: reports on the storage of hazardous substances

D. S. No. 40: Reporting on exposure hazards

SECTION 16. OTHER INFORMATION

NFPA:



HMIS III:

HEALTH	2*
FLAMMABILITY	2
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Issuing date : 08.12.2017
Version : 1.0
Prepared by : Regulatory Affairs

While there is no change in the formula or hazard classifications, this SDS remains valid

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.