

P3-stabilon WT**Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier**

Product name : P3-stabilon WT

UFI : AJRC-C614-M00N-2A6F

Product code : 104797E

Use of the Substance/Mixture : Booster

Substance type: : Mixture

For professional users only.

Product dilution information : No dilution information provided.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Process cleaner. Semi closed cleaning process

Recommended restrictions on use : Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : Ecolab Deutschland GmbH
Ecolab-Allee 1
40789 Monheim am Rhein, Germany +49 (0)2173 599 0
OfficeService.DEDUS@ecolab.com

1.4 Emergency telephone number

Emergency telephone number : +4932221096286
+32-(0)3-575-5555 Trans-European

Poison Information Centre telephone number : +49 (0)551 38318854

Date of Compilation/Revision : 24.09.2020
Version : 1.2

Section: 2. HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)**

Skin corrosion, Category 1 H314
Serious eye damage, Category 1 H318
The classification of this product is based only on its extreme pH value (in accordance with current European legislation).

2.2 Label elements

P3-stabilon WT**Labelling (REGULATION (EC) No 1272/2008)**

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H314 Causes severe skin burns and eye damage.

Precautionary Statements : **Prevention:**
 P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label:
 Lactic acid

2.3 Other hazards

Do not mix with bleach or other chlorinated products – will cause chlorine gas.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS**3.2 Mixtures****Hazardous components**

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration: [%]
citric acid, monohydrate	5949-29-1 201-069-1 01-2119457026-42	Eye irritation Category 2; H319	>= 5 - < 10
gluconic acid, d-	526-95-4 208-401-4 01-2119454394-36	Eye irritation Category 2; H319	>= 5 - < 10
Lactic acid	79-33-4 201-196-2 01-2119474164-39	Skin irritation Category 2; H315 Serious eye damage Category 1; H318	>= 3 - < 5
2-Phosphono-1,2,4-Butanetricarboxylic Acid	37971-36-1 253-733-5 01-2119436643-39	Corrosive to metals Category 1; H290 Eye irritation Category 2; H319	>= 3 - < 5

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section: 4. FIRST AID MEASURES**4.1 Description of first aid measures**

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy

P3-stabilon WT

to do. Continue rinsing. Get medical attention immediately.

- | | | |
|-------------------------|---|--|
| In case of skin contact | : | Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately. |
| If swallowed | : | Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately. |
| If inhaled | : | Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur. |

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

- | | | |
|-----------|---|------------------------|
| Treatment | : | Treat symptomatically. |
|-----------|---|------------------------|

Section: 5. FIREFIGHTING MEASURES

5.1 Extinguishing media

- | | | |
|--------------------------------|---|---|
| Suitable extinguishing media | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Unsuitable extinguishing media | : | None known. |

5.2 Special hazards arising from the substance or mixture

- | | | |
|--------------------------------------|---|--|
| Specific hazards during firefighting | : | Not flammable or combustible. |
| Hazardous combustion products | : | Depending on combustion properties, decomposition products may include following materials:
Carbon oxides
Oxides of phosphorus |

5.3 Advice for firefighters

- | | | |
|---|---|---|
| Special protective equipment for firefighters | : | Use personal protective equipment. |
| Further information | : | Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes. |

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

- | | | |
|------------------------------------|---|---|
| Advice for non-emergency personnel | : | Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the |
|------------------------------------|---|---|

P3-stabilon WT

exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

6.4 Reference to other sections

See Section 1 for emergency contact information.
For personal protection see section 8.
See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation. Wash hands thoroughly after handling. Do not breathe spray, vapour. Do not mix with bleach or other chlorinated products – will cause chlorine gas. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep away from strong bases. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

Storage temperature : 0 °C to 45 °C

7.3 Specific end uses

Specific use(s) : Process cleaner. Semi closed cleaning process

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

P3-stabilon WT**8.1 Control parameters****Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
citric acid, monohydrate	5949-29-1	AGW (Inhalable fraction)	2 mg/m ³	TRGS 900
Further information	Y	When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		

8.2 Exposure controls**Appropriate engineering controls**

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

Individual protection measures

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Eye/face protection (EN 166) : Safety goggles
Face-shield

Hand protection (EN 374) : Recommended preventive skin protection
Gloves
Nitrile rubber
butyl-rubber
Breakthrough time: 1 – 4 hours
Minimum thickness for butyl-rubber 0.7 mm for nitrile rubber 0.4 mm or equivalent (please refer to the gloves manufacturer/distributor for advice).
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin and body protection (EN 14605) : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing including appropriate safety shoes

Respiratory protection (EN 143, 14387) : None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements (89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

Environmental exposure controls

General advice : Consider the provision of containment around storage vessels.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

P3-stabilon WT

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: dark yellow
Odour	: odourless
pH	: 1.0 - 2.0, 100 %
Flash point	: Not applicable.
Odour Threshold	: Not applicable and/or not determined for the mixture
Melting point/freezing point	: Not applicable and/or not determined for the mixture
Initial boiling point and boiling range	: Not applicable and/or not determined for the mixture
Evaporation rate	: Not applicable and/or not determined for the mixture
Flammability (solid, gas)	: Not applicable and/or not determined for the mixture
Upper explosion limit	: Not applicable and/or not determined for the mixture
Lower explosion limit	: Not applicable and/or not determined for the mixture
Vapour pressure	: Not applicable and/or not determined for the mixture
Relative vapour density	: Not applicable and/or not determined for the mixture
Relative density	: 1.05 - 1.09
Water solubility	: soluble
Solubility in other solvents	: Not applicable and/or not determined for the mixture
Partition coefficient: n-octanol/water	: Not applicable and/or not determined for the mixture
Auto-ignition temperature	: Not applicable and/or not determined for the mixture
Thermal decomposition	: Not applicable and/or not determined for the mixture
Viscosity, kinematic	: Not applicable and/or not determined for the mixture
Explosive properties	: Not applicable and/or not determined for the mixture
Oxidizing properties	: The substance or mixture is not classified as oxidizing.

9.2 Other information

Not applicable and/or not determined for the mixture

Section: 10. STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Do not mix with bleach or other chlorinated products – will cause chlorine gas.

10.4 Conditions to avoid

P3-stabilon WT

None known.

10.5 Incompatible materials

Bases

10.6 Hazardous decomposition products

Depending on combustion properties, decomposition products may include following materials:

Carbon oxides

Oxides of phosphorus

Section: 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Product

Acute oral toxicity : There is no data available for this product.

Acute inhalation toxicity : There is no data available for this product.

Acute dermal toxicity : There is no data available for this product.

Skin corrosion/irritation : There is no data available for this product.

Serious eye damage/eye irritation : There is no data available for this product.

Respiratory or skin sensitization : There is no data available for this product.

Carcinogenicity : There is no data available for this product.

Reproductive effects : There is no data available for this product.

Germ cell mutagenicity : There is no data available for this product.

Teratogenicity : There is no data available for this product.

STOT - single exposure : There is no data available for this product.

STOT - repeated exposure : There is no data available for this product.

Aspiration toxicity : There is no data available for this product.

Components

Acute oral toxicity : citric acid, monohydrate
LD50 rat: 11,700 mg/kg

gluconic acid, d-
LD50 rat: 6,060 mg/kg

P3-stabilon WT

Lactic acid
LD50 rat: 3,543 mg/kg

2-Phosphono-1,2,4-Butanetricarboxylic Acid
LD50 rat: > 6,500 mg/kg

Components

Acute inhalation toxicity : Lactic acid
4 h LC50 rat: > 7.94 mg/l
Test atmosphere: dust/mist

Components

Acute dermal toxicity : citric acid, monohydrate
LD50 rat: > 2,000 mg/kg

gluconic acid, d-
LD50 rat: > 2,000 mg/kg

Lactic acid
LD50 rabbit: > 2,000 mg/kg

Potential Health Effects

Eyes : Causes serious eye damage.
Skin : Causes severe skin burns.
Ingestion : Causes digestive tract burns.
Inhalation : May cause nose, throat, and lung irritation.
Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Eye contact : Redness, Pain, Corrosion
Skin contact : Redness, Pain, Corrosion
Ingestion : Corrosion, Abdominal pain
Inhalation : Respiratory irritation, Cough

Section: 12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity

Environmental Effects : This product has no known ecotoxicological effects.

Product

Toxicity to fish : no data available
Toxicity to daphnia and other aquatic invertebrates : no data available
Toxicity to algae : no data available

P3-stabilon WT

Components

Toxicity to fish : citric acid, monohydrate
96 h LC50 Fish: > 100 mg/l

Lactic acid
96 h LC50 Fish: 130 mg/l

2-Phosphono-1,2,4-Butanetricarboxylic Acid
96 h LC50 Brachydanio rerio (zebrafish): > 1,042 mg/l

Components

Toxicity to daphnia and other aquatic invertebrates : gluconic acid, d-
48 h EC50 Daphnia: > 1,000 mg/l

2-Phosphono-1,2,4-Butanetricarboxylic Acid
48 h EC50 Daphnia magna (Water flea): > 1,071 mg/l

Components

Toxicity to algae : 2-Phosphono-1,2,4-Butanetricarboxylic Acid
72 h EC50 Desmodesmus subspicatus (green algae): 140 mg/l

12.2 Persistence and degradability

Product

no data available

Components

Biodegradability : citric acid, monohydrate
Result: Readily biodegradable.

gluconic acid, d-
Result: Readily biodegradable.

Lactic acid
Result: Readily biodegradable.

2-Phosphono-1,2,4-Butanetricarboxylic Acid
Result: Poorly biodegradable

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

P3-stabilon WT**12.6 Other adverse effects**

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods

- | | | |
|-----------------------------------|---|---|
| Product | : | Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility. |
| Contaminated packaging | : | Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations. |
| Guidance for Waste Code selection | : | Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations. |

Section: 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

- | | | |
|-----------------------------------|---|---|
| 14.1 UN number | : | 3265 |
| 14.2 UN proper shipping name | : | CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.
(Citric acid, Lactic acid) |
| 14.3 Transport hazard class(es) | : | 8 |
| 14.4 Packing group | : | III |
| 14.5 Environmental hazards | : | No |
| 14.6 Special precautions for user | : | None |

Air transport (IATA)

- | | | |
|---------------------------------|---|---|
| 14.1 UN number | : | 3265 |
| 14.2 UN proper shipping name | : | Corrosive liquid, acidic, organic, n.o.s.
(Citric acid, Lactic acid) |
| 14.3 Transport hazard class(es) | : | 8 |
| 14.4 Packing group | : | III |
| 14.5 Environmental hazards | : | No |

P3-stabilon WT

14.6 Special precautions for user : None

Sea transport (IMDG/IMO)

14.1 UN number : 3265
14.2 UN proper shipping name : CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.
(Citric acid, Lactic acid)
14.3 Transport hazard class(es) : 8
14.4 Packing group : III
14.5 Environmental hazards : No
14.6 Special precautions for user : None
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not applicable.

Section: 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Detergents Regulation EC 648/2004 : less than 5 %: Phosphonates
Preservation agents:
Lactic acid

National Regulations

Take note of Dir 94/33/EC on the protection of young people at work.

Hazard class for water : WGK 2
Classification according to AwSV, Annex 1

German storage class : 8B

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out on the product.

Section: 16. OTHER INFORMATION

Procedure used to derive the classification according to REGULATION (EC) No 1272/2008

Classification	Justification
Skin corrosion 1, H314	Based on product data or assessment
Serious eye damage 1, H318	Based on product data or assessment

Full text of H-Statements

H290 : May be corrosive to metals.
H315 : Causes skin irritation.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

Full text of other abbreviations

P3-stabilon WT

ADN – European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR – European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS – Australian Inventory of Chemical Substances; ASTM – American Society for the Testing of Materials; bw – Body weight; CLP – Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR – Carcinogen, Mutagen or Reproductive Toxicant; DIN – Standard of the German Institute for Standardisation; DSL – Domestic Substances List (Canada); ECHA – European Chemicals Agency; EC-Number – European Community number; ECx – Concentration associated with x% response; ELx – Loading rate associated with x% response; EmS – Emergency Schedule; ENCS – Existing and New Chemical Substances (Japan); ErCx – Concentration associated with x% growth rate response; GHS – Globally Harmonized System; GLP – Good Laboratory Practice; IARC – International Agency for Research on Cancer; IATA – International Air Transport Association; IBC – International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 – Half maximal inhibitory concentration; ICAO – International Civil Aviation Organization; IECSC – Inventory of Existing Chemical Substances in China; IMDG – International Maritime Dangerous Goods; IMO – International Maritime Organization; ISHL – Industrial Safety and Health Law (Japan); ISO – International Organisation for Standardization; KECI – Korea Existing Chemicals Inventory; LC50 – Lethal Concentration to 50 % of a test population; LD50 – Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL – International Convention for the Prevention of Pollution from Ships; n.o.s. – Not Otherwise Specified; NO(A)EC – No Observed (Adverse) Effect Concentration; NO(A)EL – No Observed (Adverse) Effect Level; NOELR – No Observable Effect Loading Rate; NZIoC – New Zealand Inventory of Chemicals; OECD – Organization for Economic Co-operation and Development; OPPTS – Office of Chemical Safety and Pollution Prevention; PBT – Persistent, Bioaccumulative and Toxic substance; PICCS – Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR – (Quantitative) Structure Activity Relationship; REACH – Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID – Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT – Self-Accelerating Decomposition Temperature; SDS – Safety Data Sheet; TCSI – Taiwan Chemical Substance Inventory; TRGS – Technical Rule for Hazardous Substances; TSCA – Toxic Substances Control Act (United States); UN – United Nations; vPvB – Very Persistent and Very Bioaccumulative

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Annex: Exposure Scenarios**Exposure Scenario: Process cleaner. Semi closed cleaning process**

Life Cycle Stage : Use at industrial sites

P3-stabilon WT

Product category : **PC35** Washing and cleaning products (including solvent based products)

Contributing scenario controlling environmental exposure for:

Environmental release category : **ERC4** Industrial use of processing aids in processes and products, not becoming part of articles

Daily amount per site : 50 kg

Type of Sewage Treatment Plant : Municipal sewage treatment plant

Contributing scenario controlling worker exposure for:

Process category : **PROC8b** Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities

Exposure duration : 60 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC4** Use in batch and other process (synthesis) where opportunity for exposure arises

Exposure duration : 480 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8