

CHAMELEON® EXG FLY TRAP

Comprehensive unit specification

Part No.	CHAEXG287
Description	Chameleon® EXG Explosion proof
Unit Class	I
Guarantee	3 Years
Area of Coverage	120 m ²
Voltage Range	110-240V
Frequency Range	50-60Hz
IP Rating	66
Ambient operating temperatures	0 to +40°C *
Power Consumption	45W
Glueboard (Quantity/Reference)	2 / BOAEXG883
Lamp (Quantity/Reference/Description)	2 / TUB18W492 / 18 watt 60cm long T8 Quantum® shatterproof
Mains Cable	Hard Wired / No cable
Unit Dimensions mm	H800 x W900 x D300
Carton Dimensions	H900 x W795 x D265
Unit Weight	14,5 kg
Carton Weight	17,0 kg

* recommended operating temperature range, should they be exceeded in either way it may affect the working of the unit.

The Chameleon® EXG is compliant with the essential requirements of the EMC Directive 2014/30/EU and the Low Voltage Directive 2006/95/EC and the ATEX Directive 94/9/EX. The unit is CE marked.

Additionally, the Chameleon® EXG unit is compliant with the following International Standards:

EN60079-0:2009	Explosive atmospheres - Part 0: Equipment - General requirements
EN60079-1:2007	Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d"
EN60079-7:2007	Explosive atmospheres - Part 7: Equipment protection by increased safety "
EN60079-31:2009	Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure 't'.

Engineering and Technical Manager Signature:



Dated: December 2017

PestWest Electronics Limited
Wakefield Road
Ossett
West Yorkshire
WF5 9AJ United Kingdom
Email: info@pestwest.com
Website: www.pestwest.com