

CHAMELEON® QUALIS FLY TRAP

Comprehensive unit specification

Part No.	125-000474 (EU) White / 125-000500 (EU) Stainless
Description	Chameleon® Qualis White / Stainless Steel (304 Grade)
Unit Class	I
Guarantee	3 years
Area of Coverage	90-120 m ²
Voltage Range	220-240V
Frequency Range	50-60Hz
IP Rating	20
Ambient operating temperatures	0 to +40°C *
Power Consumption	13W
Glueboard (Quantity/Reference)	1 / 135-000226 (LED 21" Glue Board)
Tube (Quantity/Reference/Description)	2 / 130-000321 / Quantum X LED 370nm 550mm T5 Shatter Resistant
Mains Cable	IEC / HO5RN-F
Unit Dimensions mm	H300 x W575 x D40
Carton Dimensions	H410 x W725 X D70
Unit Weight	3.6 kg (White) / 3.5kg (Stainless)
Carton Weight	4.4 kg (White) / 4.3kg (Stainless)

* recommended operating temperature range, should they be exceeded in either way it may affect the working of the unit.

The Chameleon® Qualis is compliant with the essential requirements of the EMC Directive 2014/30/EU and the Low Voltage Directive 2014/35/EU. The unit is CE and UKCA marked.

Additionally, the Chameleon Qualis unit is compliant with the following International Standards:

EN 55014-1:2017	Electromagnetic compatibility. Requirements for household appliances, electric tools and similar apparatus. Emission.
EN 55014-2:2015	Electromagnetic compatibility. Requirements for household appliances, electric tools and similar apparatus. Immunity.
IEC 60335-1:2010	Safety of household and similar electrical appliances – Part 1: General requirements.
IEC 60335-2-59:2002	Household and similar electrical appliances – Safety – Part 2-59: Particular requirements for insect killers.

Engineering and Technical Manager Signature:



Dated: 27th October 2021