

SAFETY DATA SHEET

INSPEXX 150

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : INSPEXX 150

Other means of identification : Not applicable

Recommended use : Food additive

Restrictions on use : Reserved for industrial and professional use.

Product dilution information : 0.059 % - 1.18 %

Company :

Chile ECOLAB S.A., Avenida Pedro de Valdivia 3801, Santiago, Chile, (2)-22413300, Telephone: (2)-22381603, Telephone: SAC: 600 241 6600, sac.chile@ecolab.com

Ecolab Argentina S.R.L., Street 11 N° 978, Industrial Park Pilar - Pilar, Buenos Aires, Zip Code: B1629MXA, Telephone: 0230 467 1000

Ecolab Colombia S.A., Avenida Carrera 60 No. 22 – 75 Interior 7., Bogotá, Colômbia, Telephone: 01 8000-120020

ECOLAB Costa Rica SRL, BES Free Zone, El Coyoil 7 km west Juan Santamaria Airport, Alajuela, Costa Rica, ZIP Code: Apdo109-4003

Ecolab Mexico, Avenida Industriales 28, Fraccionamiento Industrial - Cuamatla, Cuautitlán Izcalli, Mexico State, Zip Code: 54730, Telephone: (0155) 5864-1800

Quimiproduktos S. de R.L. de C.V., Carretera Miguel Alemán, 990, Colonia La Encarnación - Apodaca, Nuevo León, Mexico, Zip Code: 66633, Telephone: (0181) 47395900

Peru, Calle Santa Isabel # 326 Miraflores. Lima - Perú, Telephone: 511 7176200

Emergency telephone :

Argentina: Ciquime: 0800-222-2933/ 011 4613-1100, National Poison Control Center: 0800 333 0160

Chile: Poison Information Centre CITUC: (+56-2) 2635-3800

Colômbia: CISPROMQUIM® (24 hour service) Phone: 2886012 (Bogotá), Telephone: 018000916012 (Colombia), Telephone: 08001005012 (Venezuela), Telephone: 1800-59-3005 (Ecuador: solo Quito, La sierra, Centro and norte), Telephone: Ecolab USA and Canadá 1-651-222-5352

Costa Rica: For medical emergency information, call 911 and (506) 2436-3900 in Costa Rica. National Poison Control Center in Costa Rica: (506)2223-1028

Mexico: Telephone: 01 800 837 2998 Please request assistance in spanish language

Mexico State: Telephone: 01 800 837 2998

Peru: Telephone: 1-651-222-5352 Please request assistance in spanish language

Issuing date : 24.10.2019

SECTION 2. HAZARDS IDENTIFICATION

Product AS SOLD

Physical and chemical hazards : Heating may cause a fire. May intensify fire; oxidizer.

Potential Health Effects

Eyes : Causes serious eye damage.

Skin : Causes severe skin burns.

Ingestion : Harmful if swallowed. Causes digestive tract burns.

Inhalation : May be harmful if inhaled. May cause respiratory tract irritation.

SAFETY DATA SHEET

INSPEXX 150

Chronic Exposure : Health injuries are not known or expected under normal use.

Product AT USE DILUTION

Physical and chemical hazards : Not flammable or combustible.

Potential Health Effects

Eyes : Health injuries are not known or expected under normal use.

Skin : Health injuries are not known or expected under normal use.

Ingestion : Health injuries are not known or expected under normal use.

Inhalation : Health injuries are not known or expected under normal use.

Chronic Exposure : Health injuries are not known or expected under normal use.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Product AS SOLD

Pure substance/mixture : Mixture

Chemical name	CAS-No.	Concentration (%)
Acetic acid	64-19-7	30 - 60
Peroxyacetic acid	79-21-0	10 - 30
Hydrogen peroxide	7722-84-1	10 - 30

Product AT USE DILUTION

Chemical name	CAS-No.	Concentration (%)
Peroxyacetic acid	79-21-0	0.1 - 1

SECTION 4. FIRST AID MEASURES

Product AS SOLD

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
- If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.
- Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal protective equipment.
- Notes to physician : Treat symptomatically.
- Most important symptoms and effects, both acute and delayed : See Section 11 for more detailed information on health effects and symptoms.

SAFETY DATA SHEET

INSPEXX 150

Product AT USE DILUTION

In case of eye contact	: Rinse with plenty of water.
In case of skin contact	: Rinse with plenty of water.
If swallowed	: Rinse mouth. Get medical attention if symptoms occur.
If inhaled	: Get medical attention if symptoms occur.

SECTION 5. FIRE-FIGHTING MEASURES

Product AS SOLD

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	: None known.
Specific hazards during fire fighting	: Special protective equipment for fire-fighters Oxidizer. Contact with other material may cause fire. Oxidizer; material is an oxidizer which may readily react with other materials, especially upon heating.
Hazardous combustion products	: Decomposition products may include the following materials: Carbon oxides Nitrogen oxides (NOx) Sulfur oxides Oxides of phosphorus
Special protective equipment for fire-fighters	: In case of fire, wear a full face positive-pressure self contained breathing apparatus and protective suit.
Specific extinguishing methods	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Product AS SOLD

Personal precautions, protective equipment and emergency procedures	: Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed.
Environmental precautions	: Do not allow contact with soil, surface or ground water.
Methods and materials for containment and cleaning up	: Stop leak if safe to do so. Isolate the waste do not allow it to come into contact with incompatible materials. For small spills contain with sand or vermiculite and dilute the contained product at least 10 times with water. Transfer to an open topped container and remove to a safe place for neutralization* / disposal. For large spills contain spill and evacuate the area, leave until the reaction subsides, then collect up for disposal. Obtain consent from the local water company / authority if

SAFETY DATA SHEET

INSPEXX 150

considering discharge to sewer. *NEUTRALIZATION : once diluted, neutralize with a suitable alkali such as sodium bicarbonate. Combustible materials exposed to this product should be rinsed immediately with large amounts of water to ensure that all product is removed. Residual product which is allowed to dry on organic materials such as rags, cloths, paper, fabrics, cotton, leather, wood, or other combustibles may spontaneously ignite and result in a fire.

Product AT USE DILUTION

- Personal precautions, protective equipment and emergency procedures : Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed.
- Environmental precautions : Do not allow contact with soil, surface or ground water.
- Methods and materials for containment and cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

SECTION 7. HANDLING AND STORAGE

Product AS SOLD

- Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. Use only with adequate ventilation. Wash hands thoroughly after handling. Do not mix with bleach or other chlorinated products – will cause chlorine gas. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).
- Conditions for safe storage : Keep in a cool, well-ventilated place. Keep away from reducing agents. Keep away from strong bases. Keep away from combustible material. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers. Pressure bursts may occur due to gas evolution if the container is not adequately vented.
- Storage temperature : -10 °C to 50 °C

Product AT USE DILUTION

- Advice on safe handling : Wash hands thoroughly after handling. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).
- Conditions for safe storage : Keep out of reach of children. Store in suitable labeled containers.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Product AS SOLD

Ingredients with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
Acetic acid	64-19-7	CMP	10 ppm	AR OEL
		CMP - CPT	15 ppm	AR OEL
Acetic acid	64-19-7	LT	8 ppm 20 mg/m ³	BR OEL

SAFETY DATA SHEET

INSPEXX 150

Acetic acid	64-19-7	LPP	8.8 ppm 21.9 mg/m3	CL OEL
		LPT	15 ppm 37 mg/m3	CL OEL
Acetic acid	64-19-7	TWA	10 ppm 24.5 mg/m3	PE OEL
		STEL	15 ppm 37 mg/m3	PE OEL
Acetic acid	64-19-7	L-8/40	10 ppm	VE OEL
		LB	15 ppm	VE OEL
Acetic acid	64-19-7	CPT	10 ppm 25 mg/m3	PA OEL
		CCT	15 ppm 37 mg/m3	PA OEL
Acetic acid	64-19-7	VLE-PPT	10 ppm	NOM-010-STPS-2014
		VLE-CT	15 ppm	NOM-010-STPS-2014
Acetic acid	64-19-7	TWA	10 ppm	ACGIH
		STEL	15 ppm	ACGIH
		STEL	15 ppm 37 mg/m3	NIOSH REL
		TWA	10 ppm 25 mg/m3	NIOSH REL
		TWA	10 ppm 25 mg/m3	OSHA Z1
Peroxyacetic acid	79-21-0	STEL	0.4 ppm	ACGIH
Hydrogen peroxide	7722-84-1	CMP	1 ppm	AR OEL
Hydrogen peroxide	7722-84-1	LPP	0.9 ppm 1.23 mg/m3	CL OEL
Hydrogen peroxide	7722-84-1	TWA	1 ppm 1.4 mg/m3	PE OEL
Hydrogen peroxide	7722-84-1	L-8/40	1 ppm	VE OEL
Hydrogen peroxide	7722-84-1	CCT	2 ppm 3 mg/m3	PA OEL
		CPT	1 ppm 1.5 mg/m3	PA OEL
Hydrogen peroxide	7722-84-1	VLE-PPT	1 ppm	NOM-010-STPS-2014
Hydrogen peroxide	7722-84-1	TWA	1 ppm	ACGIH
		TWA	1 ppm 1.4 mg/m3	NIOSH REL
		TWA	1 ppm 1.4 mg/m3	OSHA Z1

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

Personal protective equipment

Eye protection : Chemical resistant goggles must be worn.
Face-shield

Hand protection : Wear the following personal protective equipment:
Polyvinyl alcohol or nitrile- butyl-rubber gloves
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

SAFETY DATA SHEET

INSPEXX 150

Skin protection	: Chemical resistant apron Footwear protecting against chemicals
Respiratory protection	: When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with a full face mask.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Product AT USE DILUTION

Engineering measures	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
----------------------	--

Personal protective equipment

Eye protection	: No special protective equipment required.
Hand protection	: No special protective equipment required.
Skin protection	: No special protective equipment required.
Respiratory protection	: No personal respiratory protective equipment normally required.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

	Product AS SOLD	Product AT USE DILUTION
Appearance	: liquid	liquid
Color	: colorless	colorless
Odor	: vinegar-like	slight
pH	: 1.8, (100 %)	2.9 - 7.5
Flash point	: 96 °C closed cup, Does not sustain combustion.	
Odor Threshold	: No data available	
Melting point/freezing point	: No data available	
Initial boiling point and boiling range	: > 100 °C	
Evaporation rate	: No data available	
Flammability (solid, gas)	: Not applicable	
Upper explosion limit	: No data available	
Lower explosion limit	: No data available	
Vapor pressure	: No data available	
Relative vapor density	: No data available	
Relative density	: 1.114	
Water solubility	: soluble	
Solubility in other solvents	: No data available	
Partition coefficient: n-octanol/water	: No data available	

SAFETY DATA SHEET

INSPEXX 150

Autoignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, kinematic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Molecular weight	: No data available
VOC	: No data available

SECTION 10. STABILITY AND REACTIVITY

Product AS SOLD

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: pressure build-up Contamination may result in dangerous pressure increases - closed containers may rupture.
Possibility of hazardous reactions	: Do not mix with bleach or other chlorinated products – will cause chlorine gas.
Conditions to avoid	: Direct sources of heat. Exposure to sunlight.
Incompatible materials	: Metals Bases Organic materials
Hazardous decomposition products	: In case of fire hazardous decomposition products may be produced such as: Carbon oxides Nitrogen oxides (NOx) Sulfur oxides Oxides of phosphorus

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Potential Health Effects

Product AS SOLD

Eyes	: Causes serious eye damage.
Skin	: Causes severe skin burns.
Ingestion	: Harmful if swallowed. Causes digestive tract burns.
Inhalation	: May be harmful if inhaled. May cause respiratory tract irritation.
Chronic Exposure	: Health injuries are not known or expected under normal use.

Product AT USE DILUTION

Eyes	: Health injuries are not known or expected under normal use.
Skin	: Health injuries are not known or expected under normal use.

SAFETY DATA SHEET

INSPEXX 150

Ingestion	: Health injuries are not known or expected under normal use.
Inhalation	: Health injuries are not known or expected under normal use.
Chronic Exposure	: Health injuries are not known or expected under normal use.

Experience with human exposure

Product AS SOLD

Eye contact	: Redness, Pain, Corrosion
Skin contact	: Redness, Pain, Corrosion
Ingestion	: Corrosion, Abdominal pain
Inhalation	: Respiratory irritation, Cough

Product AT USE DILUTION

Eye contact	: No symptoms known or expected.
Skin contact	: No symptoms known or expected.
Ingestion	: No symptoms known or expected.
Inhalation	: No symptoms known or expected.

Toxicity

Product AS SOLD

Product

Acute oral toxicity	: Acute toxicity estimate : 1,500 mg/kg
Acute inhalation toxicity	: No data available
Acute dermal toxicity	: LD50 : 6,000 mg/kg
Skin corrosion/irritation	: No data available
Serious eye damage/eye irritation	: No data available
Respiratory or skin sensitization	: No data available
Carcinogenicity	: No data available
Reproductive effects	: No data available
Germ cell mutagenicity	: No data available
Teratogenicity	: No data available
STOT-single exposure	: No data available
STOT-repeated exposure	: No data available
Aspiration toxicity	: No data available

Components

Acute inhalation toxicity	: Peroxyacetic acid 4 h LC50 Rat: 4.080 mg/l Test atmosphere: dust/mist
---------------------------	---

SAFETY DATA SHEET

INSPEXX 150

Hydrogen peroxide
4 h LC50 Rat: 11 mg/l
Test atmosphere: vapor

SECTION 12. ECOLOGICAL INFORMATION

Product AS SOLD

Ecotoxicity

Environmental Effects : Toxic to aquatic life.

Product

Toxicity to fish : 96 h LC50: 10.3 mg/l

Toxicity to daphnia and other aquatic invertebrates : 48 h LC50 Daphnia magna (Water flea): 4.36 mg/l

Toxicity to algae : No data available

Components

Toxicity to algae : Acetic acid
72 h EC50 Skeletonema costatum (marine diatom): > 1,000 mg/l

Peroxyacetic acid
72 h EC50: 0.7 mg/l

Hydrogen peroxide
72 h EC50: 1.38 mg/l

Persistence and degradability

Product AS SOLD

Readily biodegradable.

Product AT USE DILUTION

Not applicable - Biocide

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Product AS SOLD

Disposal methods : The product should not be allowed to enter drains, water courses or the soil. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.

Disposal considerations : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and

SAFETY DATA SHEET

INSPEXX 150

federal regulations.

Product AT USE DILUTION

Disposal methods	: The product should not be allowed to enter drains, water courses or the soil. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.
Disposal considerations	: Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

SECTION 14. TRANSPORT INFORMATION

Product AS SOLD

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport

UN number	: 3109
Description of the goods	: ORGANIC PEROXIDE TYPE F, LIQUID (Peroxyacetic acid)
Class	: 5.2 (8)
Environmentally hazardous	: yes

Air transport (IATA)

Contact Regulatory for air freight eligibility

Sea transport (IMDG/IMO)

UN number	: 3109
Description of the goods	: ORGANIC PEROXIDE TYPE F, LIQUID (Peroxyacetic acid)
Class	: 5.2 (8)
Marine pollutant	: no

SECTION 15. REGULATORY INFORMATION

For Regulatory information please contact your Ecolab sales representative.


SECTION 16. OTHER INFORMATION

Product AS SOLD

SAFETY DATA SHEET

INSPEXX 150

NFPA:




HMIS III:

HEALTH	3
FLAMMABILITY	1
PHYSICAL HAZARD	1

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Product AT USE DILUTION

NFPA:



HMIS III:

HEALTH	0
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Issuing date : 24.10.2019
Version : 1.4
Prepared by : Regulatory Affairs

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the MSDS.

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.