

SECTION 1. IDENTIFICATION OF THE CHEMICAL AND COMPANY

Product name : QUIK FILL 35 MAXX DUAL ACTION FLOOR CLEANER

Other means of identification : Not applicable

Recommended use : Cleaning product

Product dilution information : 0,19 % - 0,78 %

Company : Chile ECOLAB S.A.
 Avenida Pedro de Valdivia 3801
 Santiago, Santiago Chile
 (2)-22413300, Telephone: (2)-22381603, Telephone: SAC: 600 241 6600
 sac.chile@ecolab.com

Emergency telephone : (+56-2) 2247-3600 (CITUC)

Toxicological Emergency Phone : CITUC (+56-2) 2635-3800 (24 hours)

SECTION 2. HAZARDS IDENTIFICATION

Classification according to NCH 382 : Class: Class 8 Corrosives

Distintivo según NCh 2190 :


GHS Classification
Product AS SOLD

Acute toxicity (Oral) : Category 5
 Acute toxicity (Inhalation) : Category 5
 Skin corrosion : Category 1A
 Serious eye damage : Category 1
 Specific target organ systemic toxicity - single exposure : Category 3 (Respiratory system)
 Acute aquatic toxicity : Category 3

Product AT USE DILUTION

Skin corrosion : Category 1A
 Serious eye damage : Category 1

GHS label elements
Product AS SOLD

Hazard pictograms :



SAFETY DATA SHEET

QUIK FILL 35 MAXX DUAL ACTION FLOOR CLEANER

Signal Word	: Danger
Hazard Statements	: May be harmful if swallowed or if inhaled. Causes severe skin burns and eye damage. May cause respiratory irritation. Harmful to aquatic life.
Precautionary Statements	: Prevention: Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. Wash skin thoroughly after handling. Avoid release to the environment. Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Wash contaminated clothing before reuse. Storage: Store in a well-ventilated place. Keep container tightly closed.

Product AT USE DILUTION

Hazard pictograms



Signal Word	: Danger
Hazard Statements	: Causes severe skin burns and eye damage.
Precautionary Statements	: Prevention: Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Wash contaminated clothing before reuse. Storage: Store locked up. Disposal: Dispose of contents/ container to an approved waste disposal plant.

Product AS SOLD

Other hazards : None known.

SECTION 3. COMPOSITION/INFORMATION OF INGREDIENTS

Product AS SOLD

Pure substance/mixture : Mixture

SAFETY DATA SHEET

QUIK FILL 35 MAXX DUAL ACTION FLOOR CLEANER

Chemical name	CAS-No.	Concentration (%)
monoethanolamine	141-43-5	10 - 30
Sodium Xylenesulfonate	1300-72-7	1 - 5
sodium metasilicate	6834-92-0	1 - 5
poly(oxy-1,2-ethanediyl), α-(2-propylheptyl)-w-hydroxy-	160875-66-1	1 - 5
ethylenediamine tetraacetate	64-02-8	1 - 5

Product AT USE DILUTION

No hazardous ingredients

SECTION 4. FIRST AID MEASURES

Product AS SOLD

In case of eye contact	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
In case of skin contact	: Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
If swallowed	: Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.
If inhaled	: Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.
Protection of first-aiders	: If potential for exposure exists refer to Section 8 for specific personal protective equipment.
Notes to physician	: Treat symptomatically.

Product AT USE DILUTION

In case of eye contact	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
In case of skin contact	: Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
If swallowed	: Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.
If inhaled	: Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

Product AS SOLD

Expected acute effects

Eyes	: Causes serious eye damage.
Skin	: Causes severe skin burns.
Ingestion	: Causes digestive tract burns.

SAFETY DATA SHEET

QUIK FILL 35 MAXX DUAL ACTION FLOOR CLEANER

Inhalation : May cause respiratory tract irritation. May cause nose, throat, and lung irritation.

Expected chronic effects

Chronic Exposure : Health injuries are not known or expected under normal use.

Product AT USE DILUTION

Expected acute effects

Eyes : Causes serious eye damage.

Skin : Causes severe skin burns.

Ingestion : Causes digestive tract burns.

Inhalation : May cause nose, throat, and lung irritation.

Expected chronic effects

Chronic Exposure : Health injuries are not known or expected under normal use.

Most important symptoms / effects

Product AS SOLD

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Pain, Corrosion

Ingestion : Corrosion, Abdominal pain

Inhalation : Respiratory irritation, Cough

Product AT USE DILUTION

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Pain, Corrosion

Ingestion : Corrosion, Abdominal pain

Inhalation : Respiratory irritation, Cough

SECTION 5. FIREFIGHTING MEASURES

Product AS SOLD

Extinguishing Agents : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing agents : None known.

Specific hazards during fire fighting : Not flammable or combustible.

Products generated in combustion and thermal degradation : Decomposition products may include the following materials:
Carbon oxides
Nitrogen oxides (NOx)
Sulfur oxides
Oxides of phosphorus

Precautions for Emergency : Use personal protective equipment.

SAFETY DATA SHEET

QUIK FILL 35 MAXX DUAL ACTION FLOOR CLEANER

Personnel and / or
Firefighters

Specific extinguishing methods : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

SECTION 6. MEASURES IN CASE OF ACCIDENTAL SPILLAGE

Product AS SOLD

Personal precautions, protective equipment and emergency procedures : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed.

Environmental precautions : Do not allow contact with soil, surface or ground water.

Methods and materials for containment and cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

Product AT USE DILUTION

Personal precautions, protective equipment and emergency procedures : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed.

Environmental precautions : Do not allow contact with soil, surface or ground water.

Methods and materials for containment and cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

SECTION 7. HANDLING AND STORAGE

Product AS SOLD

Handling

Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. Use only with adequate ventilation. Wash hands thoroughly after handling.

Storage

Conditions for safe storage : Do not store near acids. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

Recommended and unsuitable packaging by supplier : Use high density plastic containers.

SAFETY DATA SHEET

QUIK FILL 35 MAXX DUAL ACTION FLOOR CLEANER

Storage temperature : 10 °C to 45 °C

Product AT USE DILUTION

Handling

Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. Use only with adequate ventilation. Wash hands thoroughly after handling.

Storage

Conditions for safe storage : Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

Recommended and unsuitable packaging by supplier : Use high density plastic containers.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Product AS SOLD

Ingredients with workplace control parameters

Ingredients	CAS-No.	Form of exposure	Permissible concentration	Basis
monoethanolamine	141-43-5	CMP	3 ppm	AR OEL
		CMP - CPT	6 ppm	AR OEL
monoethanolamine	141-43-5	TWA	3 ppm 7,5 mg/m ³	PE OEL
		STEL	6 ppm 15 mg/m ³	PE OEL
monoethanolamine	141-43-5	L-8/40	3 ppm	VE OEL
		LB	6 ppm	VE OEL
monoethanolamine	141-43-5	VLE-PPT	3 ppm	NOM-010-STPS-2014
		VLE-CT	6 ppm	NOM-010-STPS-2014
monoethanolamine	141-43-5	TWA	3 ppm	ACGIH
		STEL	6 ppm	ACGIH
		TWA	3 ppm 8 mg/m ³	NIOSH REL
		STEL	6 ppm 15 mg/m ³	NIOSH REL
		TWA	3 ppm 6 mg/m ³	OSHA Z1

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

Personal protective equipment

Eye protection : Safety goggles
Face-shield

Hand protection : Wear the following personal protective equipment:
Impervious gloves, resistant to chemicals.
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin protection : Personal protective equipment comprising: suitable protective gloves,

SAFETY DATA SHEET

QUIK FILL 35 MAXX DUAL ACTION FLOOR CLEANER

safety goggles and protective clothing

Wear closed shoes.

Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Product AT USE DILUTION

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

Personal protective equipment

Eye protection : Safety goggles
Face-shield

Hand protection : Wear the following personal protective equipment:
Impervious gloves, resistant to chemicals.
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin protection : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing

Wear closed shoes.

Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

	Product AS SOLD	Product AT USE DILUTION
Appearance	: liquid	liquid
Color	: dark green	light green
Odor	: Perfumes, fragrances	Perfumes, fragrances
pH	: 12,5 - 14,0, (100 %)	10,0 - 13,0
Flash point	: Not applicable	
Odor Threshold	: No data available	
Melting point/freezing point	: No data available	
Initial boiling point and boiling range	: No data available	
Evaporation rate	: No data available	
Flammability (solid, gas)	: No data available	
Upper explosion limit	: No data available	
Lower explosion limit	: No data available	
Vapor pressure	: No data available	

SAFETY DATA SHEET

QUIK FILL 35 MAXX DUAL ACTION FLOOR CLEANER

Relative vapor density	: No data available
Relative density	: 1,073
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, kinematic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Molecular weight	: No data available
VOC	: No data available

SECTION 10. STABILITY AND REACTIVITY

Product AS SOLD

Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reaction known under conditions of normal use.
Conditions to avoid	: None known.
Incompatible materials	: Acids Metals
Hazardous decomposition products	: Decomposition products may include the following materials: Carbon oxides Nitrogen oxides (NOx) Sulfur oxides Oxides of phosphorus

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Toxicity

Product AS SOLD Product

Acute oral toxicity	: Acute toxicity estimate : 4.301 mg/kg
Acute inhalation toxicity	: 4 h Acute toxicity estimate : 9,98 mg/l Test atmosphere: dust/mist
Acute dermal toxicity	: Acute toxicity estimate : > 5.000 mg/kg
Skin corrosion/irritation	: Corrosive

SAFETY DATA SHEET

QUIK FILL 35 MAXX DUAL ACTION FLOOR CLEANER

Serious eye damage/eye irritation : No data available

Respiratory or skin sensitization : No data available

Carcinogenicity : No data available

Reproductive effects : No data available

Germ cell mutagenicity : No data available

Teratogenicity : No data available

STOT-single exposure : No data available

STOT-repeated exposure : No data available

Aspiration toxicity : No data available

SECTION 12. ECOLOGICAL INFORMATION

Product AS SOLD Ecotoxicity

Environmental Effects : Harmful to aquatic life.

Product

Toxicity to fish : No data available

Toxicity to daphnia and other aquatic invertebrates : No data available

Toxicity to algae : No data available

Ingredients

Toxicity to fish : sodium metasilicate
96 h LC50 Fish: 210 mg/l

ethylenediamine tetraacetate
96 h LC50 Fish: 121 mg/l

Ingredients

Toxicity to daphnia and other aquatic invertebrates : monoethanolamine
48 h EC50 Daphnia: 65 mg/l

poly(oxy-1,2-ethanediyl), a-(2-propylheptyl)-w-hydroxy-
48 h Daphnia magna (Water flea): 1 mg/l

Ingredients

Toxicity to algae : Sodium Xylenesulfonate
96 h EC50: 230 mg/l

Persistence and degradability

Product AS SOLD
Poorly biodegradable

Product AT USE DILUTION
Poorly biodegradable

Bioaccumulative potential

No data available

SAFETY DATA SHEET

QUIK FILL 35 MAXX DUAL ACTION FLOOR CLEANER

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. INFORMATION OF DISPOSAL

Product AS SOLD

- Disposal methods : The product should not be allowed to enter drains, water courses or the soil. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.
- Disposal considerations : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.
- Disposal of contaminated packaging : In accordance with what is described by Supreme Decree No. 148, the packaging of the product is considered hazardous waste and must be disposed of through companies authorized to receive and / or treat such waste, which must be issued and final disposal certificate waste.

Product AT USE DILUTION

- Disposal methods : Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.
- Disposal considerations : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.
- Disposal of contaminated packaging : In accordance with what is described by Supreme Decree No. 148, the packaging of the product is considered hazardous waste and must be disposed of through companies authorized to receive and / or treat such waste, which must be issued and final disposal certificate waste.

SECTION 14. TRANSPORT INFORMATION

Product AS SOLD

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport

Official transport classification of the United Nations

UN number	:	2491
Description of the goods	:	ETHANOLAMINE SOLUTION
Class	:	8
Packing group	:	III
Environmentally hazardous	:	yes

SAFETY DATA SHEET

QUIK FILL 35 MAXX DUAL ACTION FLOOR CLEANER

Air transport (IATA)

Official transport classification of the United Nations

Contact Regulatory for air freight eligibility

Sea transport (IMDG/IMO)

Official transport classification of the United Nations

UN number	:	2491
Description of the goods	:	ETHANOLAMINE SOLUTION
Class	:	8
Packing group	:	III
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	:	Not applicable
Marine pollutant	:	no

SECTION 15. REGULATORY INFORMATION

Registrations and Certifications

Chile: Our HDS meets Chilean Normative: NCH 2245: 2015 (Safety Data Sheet for chemical products - Content and order of sections)

The receiver should pay attention to the possible existence of local regulations.

NCh 1411: Prevention of risks, IV identification of risks of materials

NCh 2190: Transportation of Hazardous Substances - Pictograms for hazard identification

NCh 382: Dangerous Good - Classification

D.S. No. 594: Minimum basic conditions in the workplace

D.S. No. 148: Hazardous waste disposal

D.S. No. 72: Mining Safety Regulations


D. S. No. 43: reports on the storage of hazardous substances

D. S. No. 40: Reporting on exposure hazards

SECTION 16. OTHER INFORMATION

Product AS SOLD

NFPA:



HMIS III:

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	0


0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Product AT USE DILUTION

SAFETY DATA SHEET

QUIK FILL 35 MAXX DUAL ACTION FLOOR CLEANER

NFPA:



HMIS III:

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Issuing date : 06.02.2018
Version : 1.0
Prepared by : Regulatory Affairs

While there is no change in the formula or hazard classifications, this SDS remains valid

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.