

Safety Data Sheet



1. Identification Of The Product

Material Type:	FER 3638F	Application:	Friction Material
Company:	Federal-Mogul Friction Products Limited Hayfield Road Chapel-en-le-Frith High Peak SK23 0JP		
Telephone:	01298 811300		

2. Composition/Information On Ingredients

Wollastonite	Approx 16%	MEL: 5 mg/m ³ 8 hour TWA, 2 fibre/ml 8 hour TWA.
Barium Sulphate	Approx 14%	OES: Resp Dust 2 mg/m ³ 8 hour TWA.
Kaolin contains crystalline silica (<0.5%)	Approx 9%	MEL Silica Respirable Dust 0.3 mg/m ³ 8 hour TWA
Brass	Approx 2%	OES: 1 mg/m ³ 8 hour TWA, 2 mg/m ³ 15 min ref period.

3. Hazards Identification

Human Health Effects: Dust can be created by the machining of finished products; the dust concentration in the atmosphere should be kept as low as is reasonably practicable and the occupational exposure limits for dust detailed in Section 8 observed. Handling for long periods may cause some skin irritation in susceptible persons.

Environmental Effects: No known environmental effects.

4. First Aid Measures

Skin Contact: Maintain good industrial hygiene standards, use suitable barrier creams and gloves if skin irritation is apparent.

Eye Contact: In the event of contact with eyes, irrigate copiously with water for at least ten minutes; obtain medical advice immediately if irritation persists or there is any tissue damage.

Inhalation: In the event of excessive inhalation remove the individual to fresh air and keep at rest; obtain medical advice immediately.