## 8. Exposure controls/personal protection

## Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Antimony sulfide (CAS 1345-04-6)	PEL	0.5 mg/m3	
Barium sulphate (CAS 7727-43-7)	PEL	5 mg/m3	Respirable fraction.
,		15 mg/m3	Total dust.
Calcium dihydroxide (CAS 1305-62-0)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Calcium silicate (CAS 1344-95-2)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Graphite (CAS 7782-42-5)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Magnesium oxide (CAS 1309-48-4)	PEL	15 mg/m3	Total particulate.
Zirconium oxide (CAS 1314-23-4)	PEL	5 mg/m3	
US. OSHA Table Z-3 (29 CFR	•		
Components	Туре	Value	
Graphite (CAS 7782-42-5)	TWA	15 mppcf	
US. ACGIH Threshold Limit	Values		
Components	Туре	Value	Form
Antimony sulfide (CAS 1345-04-6)	TWA	0.5 mg/m3	
Barium sulphate (CAS 7727-43-7)	TWA	5 mg/m3	Inhalable fraction.
Calcium dihydroxide (CAS 1305-62-0)	TWA	5 mg/m3	
Calcium silicate (CAS 1344-95-2)	TWA	10 mg/m3	
Graphite (CAS 7782-42-5)	TWA	2 mg/m3	Respirable fraction.
Magnesium oxide (CAS 1309-48-4)	TWA	10 mg/m3	Inhalable fraction.
Zirconium oxide (CAS 1314-23-4)	STEL	10 mg/m3	
	TWA	5 mg/m3	
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	Form
Antimony sulfide (CAS 1345-04-6)	TWA	0.5 mg/m3	
Barium sulphate (CAS 7727-43-7)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Calcium dihydroxide (CAS 1305-62-0)	TWA	5 mg/m3	
Calcium silicate (CAS 1344-95-2)	TWA	5 mg/m3	Respirable.
•		10 mg/m3	Total
		2.5 mg/m3	Respirable.
Graphite (CAS 7782-42-5)	TWA		
Graphite (CAS 7782-42-5) Zirconium oxide (CAS 1314-23-4)	STEL	10 mg/m3	
Zirconium oxide (CAS			

SDS US FER9213 3/8