

SAFETY DATA SHEET

US



WOLFRAKOTE TOP PASTE

Version 1.0 Revision Date: 05/14/2021 Date of last issue: - Date of first issue: 05/14/2021 Print Date: 05/14/2021

		(Form of exposure)	ters / Permissible concentration	
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		TWA (Mist)	5 mg/m3	OSHA Z-1
Titanium dioxide	13463-67-7	TWA	10 mg/m3	ACGIH
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
graphite (synthetic)	7782-42-5	TWA (Respirable)	2.5 mg/m3	NIOSH REL
		TWA (Dust)	15 Million particles per cubic foot	OSHA Z-3
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable particulate matter)	2 mg/m3	ACGIH
molybdenum disulphide	1317-33-5	TWA (total dust)	15 mg/m3 (Molybdenum)	OSHA Z-1
		TWA (Inhalable particulate matter)	10 mg/m3 (Molybdenum)	ACGIH
		TWA (Respirable particulate matter)	3 mg/m3 (Molybdenum)	ACGIH
		TWA (Total dust)	10 mg/m3 (Molybdenum)	OSHA P0

Engineering measures : none

Personal protective equipment

Respiratory protection : Not required; except in case of aerosol formation.

Filter type : Filter type P