Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressureNot available.Vapor densityNot available.Relative density0.98 (Water=1)

Solubility(ies)

Solubility (water) Soluble

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Similar to water

Other information

VOC 4.4

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular

weight hydrocarbons.

11. Toxicological information

Information on likely routes of exposure

Inhalation Based on available data, the classification criteria are not met. Prolonged inhalation may be

harmful.

Skin contact Based on available data, the classification criteria are not met.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

May be irritating to the skin.

Eye contactBased on available data, the classification criteria are not met. Can cause severe eye irritation.

Ingestion Based on available data, the classification criteria are not met. May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Can cause severe eye irritation. Mild skin irritation.

Information on toxicological effects

Acute toxicity

Components Species Calculated/Test Results

2-BUTOXYETHANOL (CAS 111-76-2)

<u>Acute</u>

Dermal

LD50 Rabbit 400 mg/kg

Inhalation

LC50 Mouse 700 ppm, 7 Hours

Rat 486 ppm, 4 Hours

450 ppm, 4 Hours

FIR No.: 510572 SDS US Version: 01 5 / 8

Issue Date: 09-08-2023