Appropriate engineering

controls

Provide adequate ventilation. Provide easy access to water supply and eye wash facilities.

Individual protection measures, such as personal protective equipment

Eye/face protection None under normal conditions. Leak from a damaged or opened battery: Wear safety glasses with

side shields (or goggles) and a face shield.

Skin protection

Hand protection None under normal conditions. Leak from a damaged or opened battery: Wear appropriate

chemical resistant gloves. Glove material: Nitrile rubber Layer thickness: 0.152 or 0.381 mm Breakthrough time: 240 or 480 min. Suitable gloves can be recommended by the glove supplier.

Skin protection

None under normal conditions. Leak from a damaged or opened battery: Wear appropriate Other

chemical resistant clothing. Use of an impervious apron is recommended.

None under normal conditions. Respiratory protection

Thermal hazards When material is heated, wear gloves to protect against thermal burns.

**General hygiene** considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

## 9. Physical and chemical properties

**Appearance** 

Solid. Physical state

**Form** Sulfuric acid, gelatinous. Lead, solid.

Not available. Color Odorless. Odor Odor threshold Not available.

< 1 pН

Melting point/freezing point Not available.

Initial boiling point and boiling

range

235 - 240 °F (112.8 - 115.6 °C) (Sulfuric acid)

Flash point

Below room temperature (as hydrogen gas).

**Evaporation rate** < 1 (n-BuAc=1)

Flammability (solid, gas)

Upper/lower flammability or explosive limits

Flammability limit - lower 4 % (Hydrogen)

(%)

Flammability limit - upper

(%)

74 % (Hydrogen)

10 mm Hg Vapor pressure Vapor density > 1 (Air=1)Relative density 1.27 - 1.33

Solubility(ies)

100 % (Sulfuric acid) Solubility (water)

Partition coefficient Not available.

(n-octanol/water)

**Auto-ignition temperature** Not available. **Decomposition temperature** Not available. Not available.

Other information

**Viscosity** 

**Explosive properties** Not explosive. Oxidizing properties Not oxidizing.

10. Stability and reactivity

Reactivity The product is non-reactive under normal conditions of use, storage and transport.

Stable at normal conditions. Chemical stability

Valve Regulated Lead Acid Battery SDS US 4/9 923336 Version #: 03 Revision date: 31-August-2020 Issue date: 19-September-2017