

## SAFETY DATA SHEET

## 1. Identification

**Product identifier** Silicone Gasket Remover

Other means of identification

FIR No. 197247

Recommended use Silicone gasket remover

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

**Company Name** Ford Motor Company

**Address** Attention: SDS Information, P.O. Box 1899

Dearborn, Michigan 48121

USA

1-800-392-3673 **Telephone** 

**SDS Information** 1-800-448-2063 (USA and Canada)

fordsds.com

**Emergency telephone** 

numbers

Poison Control Center: USA and Canada: 1-800-959-3673 INFOTRAC (Transportation): USA and Canada 1-800-535-5053

## 2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1 **Health hazards** Skin corrosion/irritation Category 2 Sensitization, skin Category 1B Aspiration hazard Category 1

**Environmental hazards** Hazardous to the aquatic environment, acute Category 1

hazard

Hazardous to the aquatic environment,

Category 2

long-term hazard

**OSHA** defined hazards Not classified.

Label elements



Signal word Danger

**Hazard statement** Extremely flammable aerosol. Pressurized container: May burst if heated. May be fatal if

swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Very

toxic to aquatic life. Toxic to aquatic life with long lasting effects.

**Precautionary statement** 

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing mist/vapors. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves.

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash Response

with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off

contaminated clothing and wash it before reuse. Collect spillage.

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Storage

Dispose of contents/container in accordance with local/regional/national/international regulations. **Disposal** 

Hazard(s) not otherwise classified (HNOC)

None known.

FIR No.: 197247 SDS US Version: 02 1/10

Issue Date: 02-21-2025