

## Biological limit values

### ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
------------	-------	-------------	----------	---------------

METHANOL (CAS 67-56-1)	15 mg/l	Methanol	Urine	*
------------------------	---------	----------	-------	---

\* - For sampling details, please see the source document.

## Exposure guidelines

### US - California OELs: Skin designation

METHANOL (CAS 67-56-1)	Can be absorbed through the skin.
------------------------	-----------------------------------

### US - Minnesota Haz Subs: Skin designation applies

METHANOL (CAS 67-56-1)	Skin designation applies.
------------------------	---------------------------

### US - Tennessee OELs: Skin designation

METHANOL (CAS 67-56-1)	Can be absorbed through the skin.
------------------------	-----------------------------------

### US ACGIH Threshold Limit Values: Skin designation

METHANOL (CAS 67-56-1)	Danger of cutaneous absorption
------------------------	--------------------------------

### US NIOSH Pocket Guide to Chemical Hazards: Skin designation

METHANOL (CAS 67-56-1)	Can be absorbed through the skin.
------------------------	-----------------------------------

## Appropriate engineering controls

Provide eyewash station and safety shower. Use adequate ventilation to control airborne concentrations below the exposure limits/guidelines. If user operations generate a vapor, dust and/or mist, use process enclosure, appropriate local exhaust ventilation, or other engineering controls to control airborne levels below the recommended exposure limits/guidelines.

## Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
---------------------	---

### Skin protection

Hand protection	Suitable chemical protective gloves should be worn when the potential exists for skin exposure. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Nitrile or butyl rubber gloves are recommended.
-----------------	---

### Other

Wear appropriate chemical resistant clothing if applicable.

### Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of OSHA Respiratory Protection Standard 29 CFR 1910.134 and/or Canadian Standard CSA Z94.4.

### Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

## General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

### Appearance

Physical state	Liquid.
----------------	---------

Form	Liquid.
------	---------

Color	Blue
-------	------

Odor	Alcoholic.
------	------------

Odor threshold	Not available.
----------------	----------------

pH	Not available.
----	----------------

Melting point/freezing point	-144.4 °F (-98 °C)
------------------------------	--------------------

Initial boiling point and boiling range	148.46 °F (64.7 °C)
---	---------------------

Flash point	52.0 °F (11.1 °C) Closed Cup
-------------	------------------------------

Evaporation rate	> 1 (BuAc=1)
------------------	--------------

Flammability (solid, gas)	Not applicable.
---------------------------	-----------------

### Upper/lower flammability or explosive limits

Explosive limit - lower (%)	6 % v/v
-----------------------------	---------

Explosive limit - upper (%)	36 % v/v
-----------------------------	----------