



SLIPKOTE® Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • FAX (330) 425-9637
(800) 238-5823 • www.speclubes.com

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • FAX (951) 340-4011
(800) 4-HUSKEY • www.huskey.com

MATERIAL SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: SLIPKOTE Liquid Assembly Lube
PRODUCT CODE: 57000
REVISION DATE: 01/01/11

MANUFACTURER: SPECIALTY LUBRICANTS CORPORATION
 8300 Corporate Park Drive
 Macedonia, OH 44056 USA
 (P): 1-800-238-5823
 (F): 1-330-425-9637

EMERGENCY PHONE: 800-424-9300 (24HR)
CHEMTREC PHONE: 800-424-9300 (24HR)

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

If present, IARL, NTP and OSHA carcinogens and chemical subjects to this reporting requirement of the SARA Title 111, Section 313 are identified in this section.

	CAS NUMBER	TLV	PEL	%
(NON HAZARDOUS) COMPONENTS				
PETROLEUM OILS	64742-62-7			85 to 95
RED DYE	71819-51-7			0.1 to 0.5
PROPRIETARY COMPONENTS				
	N.J.T.S.R.N.			
	80100362-5009P			1 to 5
	80100362-5050P			1 to 5
	80100362-5051P			1 to 5
	80100362-5057P			0.5 to 1.0

SECTION 3: PHYSICAL DATA

WATER SOLUBILITY:	NIL	BOILING POINT, F°:	N/A
SPECIFIC GRAVITY:	0.92	MELTING POINT, F°:	N/A
APPEARANCE & COLOR:	Red Liquid	VOLATILE BY VOLUME, %:	None
ODOR:	Mild Petroleum Odor	VAPOR PRESSURE:	N/A
EVAPORATION RATE:	N/A	VAPOR DENSITY:	N/A