

**Conditions for safe storage, including any incompatibilities** Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

#### US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
2-BUTOXYETHANOL (CAS 111-76-2)	PEL	240 mg/m3	
		50 ppm	
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	PEL	5 mg/m3	Mist.
PROPAN-2-OL (CAS 67-63-0)	PEL	980 mg/m3	
		400 ppm	

#### US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value	Form
2-BUTOXYETHANOL (CAS 111-76-2)	TWA	20 ppm	
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	TWA	5 mg/m3	Inhalable fraction.
PROPAN-2-OL (CAS 67-63-0)	STEL	400 ppm	
	TWA	200 ppm	

#### NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Components	Type	Value
2-BUTOXYETHANOL (CAS 111-76-2)	IDLH	1.1 %
		700 ppm
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	IDLH	2500 mg/m3
PROPAN-2-OL (CAS 67-63-0)	IDLH	2 %
		2000 ppm

#### US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL)

Components	Type	Value	Form
2-BUTOXYETHANOL (CAS 111-76-2)	TWA	24 mg/m3	
		5 ppm	
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
PROPAN-2-OL (CAS 67-63-0)	STEL	1225 mg/m3	
		500 ppm	
	TWA	980 mg/m3	
		400 ppm	