

# Safety Data Sheet

According to HAZARD COMMUNICATION STANDARD (HCS-2012) (29 CFR 1910.1200(G))

Version: 1.0/EN  
Product name: Tyre Sealant

Revision date: 01/06/2012  
Printing date: 01/06/2012

Eye/face protection:

Skin protection:

combination filters for organic vapours and particles are to be worn. Higher exposure: Self-contained breathing apparatus.

In case of risk of splashing, wear protective glasses/face-shield.

Repeated or prolonged exposure: Chemical resistant apron.

Protective gloves, chemical-resistant. The manufacturer recommends the following glove materials: nitrile rubber. Safety gloves should be selected for the actual conditions of use and in accordance with the instructions for use provided by the manufacturer.

## SECTION 9: Physical and chemical properties

(a) Appearance;	White liquid
(b) Odor;	Ammoniacal
(c) Odor threshold;	Not available.
(d) pH;	8-10
(e) Melting point/freezing point;	Not available.
(f) Initial boiling point and boiling range;	104°C
(g) Flash point;	> 100 °C, COC - Cleveland Open Cup
(h) Evaporation rate;	Not available.
(i) Flammability;	Not available.
(j) Upper/lower flammability or explosive limits;	Not available.
(k) Vapor pressure;	Not available.
(l) Vapor density;	Not available.
(m) Relative density;	Not available.
(n) Solubility(ies);	Emulsifiable in water.
(o) Partition coefficient: n-octanol/water;	Not available.
(p) Auto-ignition temperature;	Not available.
(q) Decomposition temperature;	Not available.
(r) Viscosity.	20-100 Cps at 25°C

## SECTION 10: Stability and reactivity

### (a) Reactivity

Stable under recommended storage and handling conditions (see section 7, handling and storage).

### (b) Chemical stability;

Stable under normal conditions.

### (c) Possibility of hazardous reactions;

None hazardous reactions known.

### (d) Conditions to avoid

To avoid thermal decomposition, do not overheat. Keep away from open flames, hot surfaces, and sources of ignition. Avoid contact with Incompatible materials.

### (e) Incompatible materials

Strong oxidizing materials.