

| | |
|--|---|
| Appropriate engineering controls | Use adequate ventilation to control airborne concentrations below the exposure limits/guidelines. If user operations generate a vapor, dust and/or mist, use process enclosure, appropriate local exhaust ventilation, or other engineering controls to control airborne levels below the recommended exposure limits/guidelines. |
| Individual protection measures, such as personal protective equipment | |
| Eye/face protection | Wear safety glasses with side shields (or goggles). |
| Skin protection | |
| Hand protection | Suitable chemical protective gloves should be worn when the potential exists for skin exposure. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Nitrile, butyl rubber or neoprene gloves are recommended. |
| Other | Wear appropriate chemical resistant clothing if applicable. |
| Respiratory protection | If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of OSHA Respiratory Protection Standard 29 CFR 1910.134 and/or Canadian Standard CSA Z94.4. |
| Thermal hazards | Wear appropriate thermal protective clothing, when necessary. |
| General hygiene considerations | Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. |

9. Physical and chemical properties

| | |
|---|---------------------|
| Appearance | |
| Physical state | Liquid. |
| Form | Liquid. |
| Color | Yellow |
| Odor | Characteristic. |
| Odor threshold | Not available. |
| pH | 7 - 8.5 |
| Melting point/freezing point | < -58 °F (< -50 °C) |
| Initial boiling point and boiling range | 509 °F (265 °C) |
| Flash point | 275.9 °F (135.5 °C) |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Not applicable. |
| Upper/lower flammability or explosive limits | |
| Explosive limit - lower (%) | Not available. |
| Explosive limit - upper (%) | Not available. |
| Vapor pressure | 0.1 kPa |
| Vapor pressure temp. | 68 °F (20 °C) |
| Vapor density | > 1 (Air=1) |
| Relative density | Not available. |
| Solubility(ies) | |
| Solubility (water) | Soluble |
| Partition coefficient (n-octanol/water) | Not available. |
| Auto-ignition temperature | > 392 °F (> 200 °C) |
| Decomposition temperature | Not available. |
| Viscosity | > 1.5 mm²/s |
| Viscosity temperature | 212 °F (100 °C) |
| Other information | |
| Density | 1.06 g/cm³ |

10. Stability and reactivity

| | |
|---------------------------|---|
| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| Chemical stability | Material is stable under normal conditions. |