Vapor density	Not available.
Relative density	0.803 - 0.823
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	<1 cSt
Viscosity temperature	104 °F (40 °C)
Other information	
Flame projection	105 cm
Heat of combustion	24.78 kJ/g
VOC	9.94 %

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Aluminum. Nitrates.
Hazardous decomposition products	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Ingestion	May be harmful if swallowed.
Symptoms related to the physical, chemical and toxicological characteristics	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity

Components	Species	Calculated/Test Results
ACETONE (CAS 67-64-1)		
Acute		
Dermal		
LD50	Rabbit	20000 mg/kg
		20 ml/kg
Inhalation		
LC50	Rat	76 mg/l, 4 Hours
		50.1 mg/l, 8 Hours
Oral		
LD50	Mouse	3000 mg/kg
		5.2 g/kg
	Rabbit	5340 mg/kg
	Rat	9800 mg/kg